



# Standard Specification for *sec*-Butyl Alcohol<sup>1,2</sup>

This standard is issued under the fixed designation D1007; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reappraisal.

## 1. Scope\*

1.1 This specification covers *sec*-butyl alcohol for use in paint, varnish, lacquer, and related products.

1.2 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.3 The following applies to all specified limits in this standard; for purposes of determining conformance with this standard, an observed value or a calculated value shall be rounded off “to the nearest unit” in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E29.

1.4 For hazard information and guidance, see the supplier’s Material Safety Data Sheet.

## 2. Referenced Documents

2.1 *ASTM Standards*:<sup>3</sup>

D268 Guide for Sampling and Testing Volatile Solvents and Chemical Intermediates for Use in Paint and Related Coatings and Material

D1078 Test Method for Distillation Range of Volatile Organic Liquids

D1209 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)

D1353 Test Method for Nonvolatile Matter in Volatile Solvents for Use in Paint, Varnish, Lacquer, and Related Products

D1364 Test Method for Water in Volatile Solvents (Karl Fischer Reagent Titration Method)

D1613 Test Method for Acidity in Volatile Solvents and Chemical Intermediates Used in Paint, Varnish, Lacquer,

and Related Products

D4052 Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter

D5386 Test Method for Color of Liquids Using Tristimulus Colorimetry

E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

E300 Practice for Sampling Industrial Chemicals

2.2 *U.S. Federal Specification*:

PPP-C-2020 Chemicals, Liquid, Dry, and Paste: Packaging of<sup>4</sup>

## 3. Properties

3.1 *sec*-Butyl alcohol shall conform to the following requirements:

Apparent specific gravity:	
20/20°C	0.807 to 0.809
or	
25/25°C	0.804 to 0.806
Color, Pt-Co scale, max <sup>A</sup>	10
Distillation range, 760 mmHg, °C as:	
Initial boiling point, min	98.0
Dry point, max	101.0
Nonvolatile matter, max, mg/100 mL	5
Water, max, weight %	0.5
Acidity, as acetic acid, max, weight %	0.002 <sup>B</sup>

<sup>A</sup> Instrumental Pt-Co color determined by Test Method D5386 have been shown to have no statistically significant difference from Pt-Co color determined by Test Method D1209. However, it is not known whether *sec*-butyl alcohol was part of the sample set included in the interlaboratory study.

<sup>B</sup> Equivalent to 0.019 mg of KOH per gram of sample.

## 4. Sampling

4.1 The material shall be sampled in accordance with Practice E300.

## 5. Test Methods

5.1 The properties enumerated in this specification shall be determined in accordance with the following ASTM methods:

5.1.1 *Apparent Specific Gravity*—Determine the apparent specific gravity at 20 or 25°C by a convenient method that is accurate to the third decimal place. See Guide D268 or Test Method D4052.

<sup>4</sup> Available from Standardization Documents Order Desk, DODSSP, Bldg. 4, Section D, 700 Robbins Ave., Philadelphia, PA 19111-5098, <http://dodssp.daps.dla.mil>.

\*A Summary of Changes section appears at the end of this standard

5.1.2 *Color*—Test Method **D1209** (see Note A in 3.1).

5.1.3 *Distillation Range*—Test Method **D1078** using a temperature measuring device having a range of 72 to 126°C and a resolution of 0.1°C.

5.1.4 *Nonvolatile Matter*—Test Method **D1353**.

5.1.5 *Water*—Test Methods **D1364**.

5.1.6 *Acidity*—Test Method **D1613**.

## 6. Packaging and Package Marking

6.1 Package size shall be agreed upon between the purchaser and the supplier.

6.2 Packaging shall conform to applicable carrier rules and regulations or when specified shall conform to Fed. Spec. PPP-C-2020.

## 7. Keywords

7.1 methyl ethyl carbinol; *sec*-butyl alcohol; 2-hydroxybutane

## SUMMARY OF CHANGES

Committee D01 has identified the location of selected changes to this standard since the last issue (D1007 - 05) that may impact the use of this standard. (Approved November 1, 2011.)

(1) Revised 5.1.3.

(2) Removed Specification E1 from 2.1.

*ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.*

*This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the ASTM website (www.astm.org/COPYRIGHT/).*