



Standard Test Method for Direct Tensile Strength of Intact Rock Core Specimens¹

This standard is issued under the fixed designation D2936; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This test method covers the determination of the direct tensile strength of intact cylindrical rock specimens.

1.2 The values stated in SI units are to be regarded as standard. The values provided in parenthesis are for information only.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*²

[D2216 Test Methods for Laboratory Determination of Water \(Moisture\) Content of Soil and Rock by Mass](#)

[D3740 Practice for Minimum Requirements for Agencies Engaged in Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction](#)

[D4543 Practices for Preparing Rock Core as Cylindrical Test Specimens and Verifying Conformance to Dimensional and Shape Tolerances](#)

[E4 Practices for Force Verification of Testing Machines](#)

[E122 Practice for Calculating Sample Size to Estimate, With Specified Precision, the Average for a Characteristic of a Lot or Process](#)

3. Summary of Test Method

3.1 A rock core sample is cut to length and its ends are cemented to metal caps. The metal caps are attached to a testing machine and the specimen is loaded in tension until it fails.

¹ This test method is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.12 on Rock Mechanics.

Current edition approved July 1, 2008. Published July 2008. Originally approved in 1971. Last previous edition approved in 2004 as D2936 – 95 (2004) ^{ϵ 1}. DOI: 10.1520/D2936-08.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

4. Significance and Use

4.1 Rock is much weaker in tension than in compression. Thus, in determining the failure condition for a rock structure, many investigators employ tensile strength of the component rock as the failure strength for the structure. Direct tensile stressing of rock is the most basic test for determining the tensile strength of rock.

5. Apparatus

5.1 *Loading Device*, to apply and measure axial load on the specimen, of sufficient capacity to apply the load at a rate conforming to the requirements of 8.2. The device shall be verified at suitable time intervals in accordance with the procedures given in Practices E4 and shall comply with the requirements prescribed therein.

5.2 *Caps*—Cylindrical metal caps that, when cemented to the specimen ends, provide a means through which the direct tensile load can be applied. The diameter of the metal caps shall not be less than that of the test specimen, nor shall it exceed the test specimen diameter by more than 1.10 times. Caps shall have a thickness of at least 30 mm (1¼ in.). Caps shall be provided with a suitable linkage system for load transfer from the loading device to the test specimen. The linkage system shall be so designed that the load will be transmitted through the axis of the test specimen without the application of bending or torsional stresses. The length of the linkages at each end shall be at least two times the diameter of the metal end caps. One such system is shown in Fig. 1.

NOTE 1—Roller of link chain of suitable capacity has been found to perform quite well in this application. Because roller chain flexes in one plane only, the upper and lower segments should be positioned at right angles to each other to effectively reduce bending in the specimen. Ball-and-socket, cable, or similar arrangements have been found to be generally unsuitable as their tendency for bending and twisting makes the assembly unable to transmit a purely direct tensile stress to the test specimen.

6. Sampling

6.1 Select the specimen from the cores to represent a valid average of the type of rock under consideration. This can be achieved by visual observations of mineral constituents, grain sizes and shape, partings, and defects such as pores and fissures, or by other methods such as ultrasonic velocity measurements.

*A Summary of Changes section appears at the end of this standard




FIG. 1 Direct Tensile-Strength Test Assembly

7. Test Specimens

7.1 *Preparation*—Prepare test specimens in accordance with Practice **D4543**, except that the degree of flatness and smoothness of the specimen ends is not critical. End surfaces, such as result from sawing with a diamond cutoff wheel, are entirely adequate. Grinding, lapping, or polishing beyond this point serves no useful purpose, and in fact, may adversely affect the adhesion of the cementing medium.

7.2 Water content of the specimen at the time of test can have a significant effect upon the deformation of the rock. Good practice generally dictates that laboratory tests be made upon specimens representative of field conditions. Thus, it follows that the field water content of the specimen should be preserved until the time of test. On the other hand, there may be reasons for testing specimens at other water contents, including zero. In any case, the water content of the test specimen should be tailored to the problem at hand and reported in accordance with **10.1.6**. If the water content of the specimen is to be determined, follow the procedures given in Test Method **D2216**.

7.3 If water content is to be maintained, and the elevated temperature enclosure is not equipped with humidity control, seal the specimen using a flexible membrane or apply a plastic or silicone rubber coating to the specimen sides.

8. Procedure

8.1 Cement the metal caps to the test specimen to ensure alignment of the cap axes with the longitudinal axis of the

specimen (see **Note 2**). The thickness of the cement layer should not exceed 1.5 mm ($\frac{1}{16}$ in.) at each end. The cement layer must be of uniform thickness to ensure parallelism between the top surfaces of the metal caps attached to both ends of the specimens. This should be checked before the cement is hardened (see **Note 1**) by measuring the length of the end-cap assembly at three locations 120° apart and near the edge. The maximum difference between these measurements should be less than 0.10 mm (0.005 in.) for each 25.0 mm (1.0 in.) of specimen diameter. After the cement has hardened sufficiently to exceed the tensile strength of the rock, place the specimen in the testing machine, making certain that the load transfer system is properly aligned.

NOTE 2—In cementing the metal caps to the test specimens, use jigs and fixtures of suitable design to hold the caps and specimens in proper alignment until the cement has hardened. The chucking arrangement of a machine lathe or drill press is also suitable. Epoxy resin formulations of rather stiff consistency and similar to those used as a patching and filling compound in automobile body repair work have been found to be a suitable cementing medium.

8.2 Apply the tensile load continuously and without shock to failure. Apply the load or deformation at an approximately constant rate such that failure will occur in not less than five nor more than 15 min. Note and record the maximum load carried by the specimen during the test.

NOTE 3—In this test arrangement failure often occurs near one of the capped ends. Discard the results for those tests in which failure occurs either partly or wholly within the cementing medium.

9. Calculation

9.1 Calculate the tensile strength of the rock by dividing the maximum load carried by the specimen during the test by the cross-sectional area; express the result to the nearest 35.0 kPa (5 psi).

10. Report

10.1 Report the following information:

10.1.1 Source of sample including project name and location, and if known, storage environment (often location is frequently specified in terms of the borehole number and depth of specimen from the collar of the hole),

10.1.2 Physical description of the sample including: rock type, location and orientation of apparent planes, bedding planes, and schistosity; and large inclusions or inhomogeneities, if any,

10.1.3 Date of sampling and testing,

10.1.4 Specimen length and diameter, also conformance with dimensional requirements,

10.1.5 Rate of loading or deformation rate,

10.1.6 General indication of water condition of sample at time of test, such as, as-received, saturated, laboratory air dry, or oven dry (it is recommended that the moisture condition be more precisely determined when possible and reported as either water content or degree of saturation,

10.1.7 Direct tensile strength for each specimen as calculated, average direct tensile strength of all specimens, standard deviation, or coefficient of variation,

10.1.8 Type and location of failure (a sketch of the fractured specimen is recommended), and

10.1.9 Other available physical data.

NOTE 4—The number of specimens tested may depend upon the availability of specimens, but normally a minimum of ten is preferred. The number of specimens tested should be indicated. The statistical basis for relating the number of specimens to the variability of measurements is given in Practice E122.

11. Precision and Bias

11.1 *Precision*—Due to the nature of the rock materials tested by this test method, it is, at this time, either not feasible or too costly at this time to produce multiple specimens which have uniform mechanical properties. Therefore, since specimens which would yield the same test results cannot be tested, Subcommittee D18.12 cannot determine the variation between tests since any variation observed is just as likely to be due to specimen variation as to operator or laboratory testing varia-

tion. Subcommittee D18.12 welcomes proposals to resolve this problem that would allow for development of a valid precision statement.

11.2 *Bias*—There is no accepted reference value for this test method; therefore, bias cannot be determined.

NOTE 5—The quality of the result produced by this standard is dependent on the competence of the personnel performing it, and the suitability of the equipment and facilities used. Agencies that meet the criteria of Practice D3740 are generally considered capable of competent and objective testing and sampling. Users of this standard are cautioned that compliance with Practice D3740 does not in itself assure reliable results. Reliable results depend on many factors; Practice D3740 provides a means of evaluating some of those factors.

12. Keywords

12.1 loading tests; rock; tension (tensile) properties/tests; tensile strength

SUMMARY OF CHANGES

Committee D18 has identified the location of selected changes to this standard since the last issue (D2936 – 95 (2004)^{E1}) that may impact the use of this standard. (Approved July 1, 2008.)

- (1) Changed units statement in 1.2.
- (2) Inserted reference to Practice D3740.
- (3) Changed jugs to jigs in Note 2.

- (4) Inserted Note 5.
- (5) Inserted Fig. 1.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the ASTM website (www.astm.org/COPYRIGHT/).