



Standard Specification for Labeled Length per Holder of Sewing Thread¹

This standard is issued under the fixed designation D3693; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers requirements for the labeled lengths of sewing threads of all materials.

1.2 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

2. Referenced Documents

2.1 *ASTM Standards*:²

D123 Terminology Relating to Textiles

D204 Test Methods for Sewing Threads

D3888 Terminology for Yarn Spinning Systems

D3990 Terminology Relating to Fabric Defects

D4849 Terminology Related to Yarns and Fibers

3. Terminology

3.1 *Definitions*:

3.1.1 For definitions of textile terms used in this specification, thread holder and sewing thread, refer to Terminology D4849.

3.1.2 For other textile terms used in this specification, refer to Terminology standards D123, D3888, D3990, And D4849.

4. Requirements

4.1 The average for all holders shall equal or exceed the labeled length.

4.2 For home sewing spools, the observed length of individual holders shall equal or exceed the percent of labeled length shown in Table 1.

4.3 For ready-made bobbins, the observed length of individual holders shall equal or exceed 97 % of the labeled length.

4.4 For all other holders, when the sample size is nine or fewer, the observed length of individual holders shall equal or

¹ This specification is under the jurisdiction of ASTM Committee D13 on Textiles and is the direct responsibility of Subcommittee D13.58 on Yarns and Fibers.

Current edition approved Jan. 1, 2016. Published February 2016. Originally approved in 1978. Last previous edition approved in 2010 as D3693 – 02(2010). DOI: 10.1520/D3693-02R16.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

exceed 95 % of the labeled length. For a sample size of ten or more the observed length of one holder may be less than 95 % of the labeled length.

4.5 If the initial sample consists of fewer than ten holders and the average length measured fails to conform to the requirements of 4.1 but meets those of 4.2, 4.3, or 4.4, as appropriate, take additional specimens from the lot and test until a total of ten have been measured. Reevaluate the results of these ten specimens against the requirements of 4.1, 4.2, 4.3, or 4.4, as appropriate. If the new average conforms with the requirements of 4.1 and the individual holders with the requirements of 4.2, 4.3, or 4.4, as appropriate, consider the lot acceptable.

4.5.1 If the original lot consists of fewer than ten holders, the supplementary sample will be one half of the holders remaining in the lot following the initial sampling.

5. Sampling

5.1 *Lot*—Unless otherwise agreed upon between the purchaser and supplier, a lot shall be a discrete manufacturing unit or a billed quantity of a specific color, ticket size, and length put-up of thread. A billed quantity can consist of a single unit, a carton, box, or multiple units of either, containing a number of holders of thread.

NOTE 1—An adequate specification or other agreement between the purchaser and the supplier requires taking into account variability between shipping units, between packages, or ends within shipping unit, and between specimens from a single package so as to provide a sampling plan with a meaningful producer's risk, user's risk, acceptable quality level, and limiting quality level.

5.2 *Sample*—Unless otherwise agreed upon between the purchaser and supplier, and except for ready-made bobbins, the sample, chosen at random, shall be 10 % of the holders in the lot, with a minimum of one holder, up to a maximum of ten holders. The lot sample and laboratory sample are synonymous.

5.2.1 For ready-made bobbins the sample shall be as shown in Table 2.

5.3 *Specimen*—The test specimen is a holder of thread whether a cone, tube, spool, ready-made bobbin, or other.

6. Test Method

6.1 Determine the length of each holder of thread as directed in the length per thread holder procedure of Test

TABLE 1 Minimum Length for Individual Home Sewing Spools

Labeled Length, m	Minimum % Allowed
0 to 40	98.5
Over 40 to 85	98
Over 85 to 140	97.5
Over 140 to 300	97
Over 300 to 1000	96
Over 1000	95

TABLE 2 Sampling Plan for Ready-Made Bobbins

Lot Size, gross	Sample Size
10 or less	10 bobbins
11 through 99	1 bobbin per gross
100 or more	100 bobbins

Method **D204**. Use the sampling directions in this specification in place of those in Methods **D204**.

7. Conformance

7.1 Material that fails to conform to the requirements of this specification may be rejected. Rejection shall be reported to the supplier promptly and in writing. In case of dissatisfaction with the results of the test, the supplier may make claim for a rehearing. The terms of the rehearing shall be as agreed upon between the supplier and the purchaser.

8. Keywords

8.1 length; sewing thread

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; <http://www.copyright.com/>