



Standard Practice for Collecting Benthic Macroinvertebrates With Orange Peel Grab Sampler¹

This standard is issued under the fixed designation D 4407; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This practice covers the procedures for obtaining qualitative bottom samples of macroinvertebrates inhabiting sand, cobble, rubble stone, and similar substrates.

1.2 The sampler should not be used in critical quantitative work that is to be compared with results of other areas and is recommended as a reconnaissance sampler only.

1.3 This device is used primarily in marine waters and deep lakes.

1.4 For the advantages and limitations of selecting grab sampling devices, see Guide D 4387.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* For specific hazards, see Section 5.

2. Referenced Documents

2.1 ASTM Standards:

D 4387 Guide for Selecting Grab Sampling Devices for Collecting Benthic Macroinvertebrates²

3. Summary of Practice

3.1 The Orange-Peel grab sampler has four curved jaws that close to encircle a hemisphere of sediment and must penetrate the intended substrate without disturbing the water surface boundary of the substrate, close when positioned properly on the bottom, and retain discrete samples of sediment while it is brought to the surface for processing.

3.2 A recent modification of the Orange Peel, described by Reish (1959)³ has a new trigger mechanism and more efficient closing jaws, and the volume of sample to surface-area

sampled relationship has been worked out.

3.3 The surface area of this device also varies with penetration depth or volume sampled.

3.4 The device penetrates to a maximum depth of 18 cm, but this depth will vary.

4. Significance and Use

4.1 The Orange-Peel grab sampler is used to collect qualitative samples from different aquatic habitats containing benthic macroinvertebrates living on or in various types of substrates.

4.2 The organisms in the sample are used to define macroinvertebrate community characteristics in water quality studies and ecological assessments.

5. Hazards

5.1 This sampler cannot be used under adverse weather conditions.

5.2 The Orange Peel should be inspected for mechanical defects prior to use.

5.3 When taking samples, a stationary boat or platform should be used.

6. Procedure

6.1 Lower the sampler to the bottom by a powered winch and cable.

6.2 Lower the sampler at a slow but steady rate.

6.3 Once the sampler reaches the bottom, the jaws are operated by a large wheel and sprocket mechanism within the upper frame work, and may be operated by a second cable or by a slack release mechanism activated by a messenger.

6.4 The sampler is retrieved slowly, but to prevent sample loss a loosely fitted canvas sleeve can be placed on the upper works to prevent washing out of the sample.

6.5 Once the sample is on board, empty it either into a suitable container or a sieving device directly for processing.

6.6 Thoroughly wash or hose the device with water, so that all sediment material is included in the sample processing before a replicate sample is taken.

¹ This practice is under the jurisdiction of ASTM Committee E47 on Biological Effects and Environmental Fate and is the direct responsibility of Subcommittee E47.03 on Terrestrial Assessment and Toxicology.

Current edition approved Sept. 28, 1984. Published November 1984.

² *Annual Book of ASTM Standards*, Vol 11.05.

³ Reish, D. J., "Modification of the Hayward Orange Peel Bucket for Bottom Sampling," *Ecology* 40, 1959, pp. 502-503.



D 4407

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).