

Designation: D4967 - 99 (Reapproved 2013)

Standard Guide for Selecting Materials to Be Used for Insulation, Jacketing and Strength Components in Fiber-Optic Cables¹

This standard is issued under the fixed designation D4967; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

- 1.1 This guide is intended to provide a list of materials commonly used in components that provide insulation, jacketing and strength in fiber-optic cables. Where these materials are covered by ASTM standards, an appropriate reference is made. Due to changing technology, not all materials being used are necessarily listed here.
- 1.2 This guide does not include materials used in components for optical purposes (optical fiber and its coating) or external metallic armoring (such as for a barrier to rodents).
 - 1.3 This guide offers two general lists of materials:
- 1.3.1 A subdivision of fiber-optic cable construction into components that are used for insulation, jacketing, or strength, with a generic material classification for specific applications in each component (see Section 5); and
- 1.3.2 An alphabetical list of the generic material classifications, showing ASTM standards where they exist (see Table 1).

2. Referenced Documents

- 2.1 ASTM Standards:²
- D1248 Specification for Polyethylene Plastics Extrusion Materials for Wire and Cable
- D1457 Specification for Polytetrafluoroethylene (Ptfe) Molding and Extrusion Materials (Withdrawn 1996)³
- D1711 Terminology Relating to Electrical Insulation
- D2116 Specification for FEP-Fluorocarbon Molding and Extrusion Materials
- D2287 Specification for Nonrigid Vinyl Chloride Polymer and Copolymer Molding and Extrusion Compounds

- D2526 Specification for Ozone-Resisting Silicone Rubber Insulation for Wire and Cable (Withdrawn 2006)³
- D3159 Specification for Modified ETFE-Fluoropolymer Molding and Extrusion Materials
- D3222 Specification for Unmodified Poly(Vinylidene Fluoride) (PVDF) Molding Extrusion and Coating Materials
- D3275 Classification System for E-CTFE-Fluoroplastic Molding, Extrusion, and Coating Materials
- D3307 Specification for Perfluoroalkoxy (PFA) Fluorocarbon Resin Molding and Extrusion Materials
- D3317 Specification for High Modulus, Organix Yarn and Roving (Withdrawn 1985)³
- D3664 Specification for Biaxially Oriented Polymeric Resin Film for Capacitors in Electrical Equipment
- D3935 Specification for Polycarbonate (PC) Unfilled and Reinforced Material
- D4066 Classification System for Nylon Injection and Extrusion Materials (PA)
- D4101 Specification for Polypropylene Injection and Extrusion Materials
- D4246 Specification for Ozone-Resistant Thermoplastic Elastomer Insulation For Wire and Cable, 90 °C Operation
- D4507 Specification for Thermoplastic Polyester (TPES) Materials (Withdrawn 1999)³
- D4730 Specification for Flooding Compounds for Telecommunications Wire and Cable
- D4731 Specification for Hot-Application Filling Compounds for Telecommunications Wire and Cable
- D4732 Specification for Cool-Application Filling Compounds for Telecommunications Wire and Cable

3. Terminology

- 3.1 *Definitions*—For definitions of terms used in this guide, refer to Terminology D1711.
 - 3.2 Definitions of Terms Specific to This Standard:
- 3.2.1 *buffer*, *n*—a material that is applied over an optical fiber's protective coating to further protect the fiber from physical damage and provide mechanical protection.
- 3.2.2 *composite buffer*; *n*—polymeric material(s) surrounding the optical fiber so that the inner layer is in intimate contact with the fiber cladding or coating with a tightly extruded buffer material overall.

¹ This guide is under the jurisdiction of ASTM Committee D09 on Electrical and Electronic Insulating Materials and is the direct responsibility of Subcommittee D09.18 on Solid Insulations, Non-Metallic Shieldings and Coverings for Electrical and Telecommunication Wires and Cables.

Current edition approved Nov. 1, 2013. Published December 2013. Originally approved in 1989. Last previous edition approved in 2009 as D4967 – 99(2009). DOI: 10.1520/D4967-99R13.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website

³ The last approved version of this historical standard is referenced on www.astm.org.

TABLE 1 Materials in Current Use

Material	ASTM Specification
Acrylates	
Aramids:	
fibers	D3317
tape	
Fluoroplastics:	
ECTFE	D3275
ETFE	D3159
FEP	D2116
PFA	D3307
PTFE	D1457
PVDF	D3222
Glass fibers	
Glass-fiber reinforced plastics	
Grease and similar materials	D4730, D4731, D4732
Nylon	D4066
Polybutylene	D4730, D4731, D4732
Polycarbonate	D3935
Polyester tape	D3664
Polyethylene	D1248
Polyimide tape	
Polypropylene	D4101
Polyurethane	
Poly(vinyl chloride)	D2287
Rubber	D4730, D4731, D4732
Silicone rubber	D2526
Steel	
Thermoplastic elastomer	D4246
Thermoplastic polyester	D4507

- 3.2.3 *loose tube(s)*, *n*—a buffer material that surrounds the optical fiber(s) so that it forms a tube or channel whose inside dimension is greater than the fiber's outside diameter (or combined diameters).
- 3.2.3.1 *Discussion*—When required, the space between the fiber(s) and the inside of the tube may be filled with a suitable filling compound or with strength or cushioning elements, or both.
- 3.2.4 *slotted core*, *n*—an element(s) with helical grooves assembled around a central strength member, in which optical fibers, optical fiber ribbons or copper conductors can be placed.
- 3.2.5 *strength member(s)*, *n*—material(s) used in fiber optic cable construction which provide mechanical integrity and stability.
- 3.2.6 *tight buffer*, *n*—a material surrounding the optical fiber so that it is in intimate contact with the coating on the fiber.

4. Significance and Use

- 4.1 The lists of components and materials are useful in enhancing the user's understanding of the technology and construction of fiber-optics cables and the development of performance standards for cables.
- 4.2 This guide is intended for use by all parties involved with fiber optics: materials suppliers, cable manufacturers, and end-users.

5. Construction Terminology and Material Selection Options

- 5.1 Fiber-optic cable components and materials that have been used for each:
 - 5.1.1 Buffers/Tubes:
 - 5.1.1.1 Tight Buffers:

- (a) Fluoroplastic.
- (b) Nylon.
- (c) Thermoplastic Polyester.
- (d) Poly(vinyl chloride).
- 5.1.1.2 Loose Tubes:
 - (a) Fluoroplastic.
- (b) Nylon.
- (c) Thermoplastic Polyester.
- (d) Polycarbonate.
- (e) Polyethylene.
- 5.1.1.3 Composite Buffers—Silicone rubber.
- 5.1.1.4 Slotted Cores:
 - (a) Polyethylene.
 - (b) Polypropylene.
- 5.1.1.5 Pipes—Polyethylene.
- 5.1.1.6 *Sheaths:*
- (a) Fluoroplastic.
- (b) Nylon.
- (c) Silicone rubber.
- (d) Thermoplastic elastomer.
- (e) Polyethylene.
- 5.1.1.7 *Ribbons:*
 - (a) Acrylates.
 - (b) Silicone Rubber.
- 5.1.2 Jackets:
- 5.1.2.1 Outside Jackets:
- (a) Fluoroplastics: Ethylene Tetrafluoroethylene (ETFE), Ethylene-chlorotrifluoroethylene (ECTFE), Perfluoroalkoxy (PFA), Polytetrafluoroethylene (PTFE), Polyvinylidene Fluoride (PVDF).
 - (b) Polyethylene.
 - (c) Poly(vinyl chloride).
 - (d) Thermoplastic elastomer.
 - 5.1.2.2 Inner Jackets:
 - (a) Fluoroplastics (ECTFE, PVDF).
 - (b) Polyethylene.
 - (c) Polyurethane.
 - (d) Poly(vinyl chloride).
 - (e) Thermoplastic elastomer.
 - 5.1.3 Strength Members:
 - 5.1.3.1 Aramid fibers.
 - 5.1.3.2 Glass-fiber reinforced plastic.
 - 5.1.3.3 Glass fibers.
 - 5.1.3.4 Steel.
 - 5.1.4 Wrapping Tapes:
 - 5.1.4.1 Aramid.
 - 5.1.4.2 Polyester.
 - 5.1.4.3 Polyimide.
 - 5.1.5 Filling and Flooding Compounds:
 - 5.1.5.1 Grease and similar materials.
 - 5.1.5.2 Polybutylene.
 - 5.1.5.3 Rubber.

6. Materials in Current Use

6.1 Table 1 lists materials in current use as defined in the applicable ASTM specification. It is intended only as a guide

and does not include all possible classifications. It is not a function of this guide to provide specific engineering data for design purposes.

7. Keywords

7.1 acrylates; aramids; fluoroplastics; glass fibers; glass-fibers reinforced plastics; grease and similar materials; nylon;

polybutylene; polycarbonate; polyester tape; polyethylene; polyimide tape; polypropylene; polyurethane; poly(vinyl chloride); rubber; silicone rubber; steel; thermoplastic elastomer; thermoplastic polyester

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; http://www.copyright.com/