



Standard Test Method for Screening of Oxidizers in Waste¹

This standard is issued under the fixed designation D4981; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method is intended for use prior to preparation of waste samples for organic analysis. Waste samples that have oxidizing compounds may react with certain reagents in the laboratory (for example, organic solvents).

1.2 This test method is applicable to the analysis of waste liquids, sludges, and solids.

1.3 This test method can neither identify specific oxidizing compounds nor measure concentrations. Since no acid or base is added in this test method, potential oxidizers that require the presence of acid or base will not be detected by this test method.

1.4 It is recommended that, prior to this test, waste samples be screened for water compatibility; see Test Methods [D5058](#).

1.5 This test method is designed and intended as a preliminary test to complement quantitative analytical techniques that may be used to determine the presence of oxidizers in wastes. This test method offers the ability to screen waste for potentially hazardous reactions due to oxidizer content when the more sophisticated techniques are not available or the total waste composition is unknown.

1.6 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.7 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 *ASTM Standards*:²

[D1193 Specification for Reagent Water](#)

¹ This test method is under the jurisdiction of ASTM Committee [D34](#) on Waste Management and is the direct responsibility of Subcommittee [D34.01.05](#) on Screening Methods.

Current edition approved Sept. 1, 2012. Published December 2012. Originally approved in 1989. Last previous edition approved in 2008 as D4981 – 08. DOI: 10.1520/D4981-128.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

[D5058 Practices for Compatibility of Screening Analysis of Waste](#)

[D5681 Terminology for Waste and Waste Management](#)

3. Terminology

3.1 For definitions of terms used in this screening method, refer to Terminology [D5681](#).

3.2 *Definitions of Terms Specific to This Standard:*

3.2.1 *screening analysis*—A preliminary qualitative or semi-quantitative test that is designed to efficiently give the user specific information about a waste that will aid in determining waste identification, process compatibility, and safety in handling.

4. Summary of Test Method

4.1 A small portion of the sample is placed onto a strip of potassium iodide (KI) starch paper. The blue color which is the result of oxidizing the potassium iodide to iodine (I_2) in the presence of starch, indicates a positive test for oxidizers.

5. Significance and Use

5.1 This test method is intended for use by those in waste management industries to avoid potentially harmful reactions due to oxidizing compounds in wastes.

6. Interferences

6.1 Materials that mask the KI starch paper, (for example, oils, syrups, etc.) prevent reaction with the test paper or visual detection of a color change.

6.2 Samples or slurries of samples that are already dark colored prior to applying a test portion to the KI starch paper can give false results.

6.3 Oxidizers such as ferric salts may not oxidize organics; however, they may show positive reactions with KI.

6.4 Oxidizers that require the presence of acid or base will give a false negative result. To overcome this problem, run the oxidizer test at acid, base, and neutral pH conditions.

7. Reagents and Materials

7.1 *Purity of Reagents*—Reagent-grade chemicals shall be used in all tests. Unless otherwise indicated, it is intended that all reagents conform to specifications of the Committee on

Analytical Reagents of the American Chemical Society where such specifications are available.³ Other grades may be used, provided it is first ascertained that the reagent is of sufficiently high purity to permit its use without lessening the accuracy of the determination.

7.2 *Purity of Water*—Unless otherwise indicated, references to water shall be understood to mean reagent water as defined by Type III of Specification **D1193**.

7.3 *Potassium Iodide (KI) Starch Paper Strips*.

7.4 *Beakers*.

7.5 *Pipet or Droppers*.

7.6 *Hydrogen Peroxide Solution (3 % H₂O₂)*, commercial grade.

7.7 *Nitric Acid (1 + 9)*—Add 1 volume of nitric acid (HNO₃, sp. gr 1.42) to 9 volumes of water.

8. Sampling

8.1 Collect a representative sample of the waste in a container with a sealed lid.

8.2 The sample should be analyzed as soon as possible.

8.3 Allow the samples to stabilize to room temperature.

9. Procedure

9.1 *Aqueous Samples*—Using a clean pipet or dropper, place a drop sample on a strip of KI starch paper and note color change.

³ *Reagent Chemicals, American Chemical Society Specifications*, American Chemical Society, Washington, DC. For suggestions on the testing of reagents not listed by the American Chemical Society, see *Analar Standards for Laboratory Chemicals*, BDH Ltd., Poole, Dorset, U.K., and the *United States Pharmacopeia and National Formulary*, U.S. Pharmacopeial Convention, Inc. (USPC), Rockville, MD.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the ASTM website (www.astm.org/COPYRIGHT/).

9.2 *Non-Aqueous Samples (for example, solid, oil, or solvents)*:

9.2.1 In a beaker, prepare a slurry by adding 1 to 5 g of sample to an equal amount of reagent water.

9.2.2 Using a clean pipet or dropper, place a drop of slurry on a strip of KI starch paper.

9.2.3 Note any color change.

9.3 All sample results shall be checked against the quality control and blank test strips to verify positive/negative readings (see Section 10).

9.4 All positive results (a blue color) shall be reported immediately to prevent potential hazardous reactions that may occur.

NOTE 1—Analyst should be aware that the blue color on the reference strip and any positive sample test strip will slowly fade with time.

10. Quality Control

10.1 Quality control check samples, reference blanks and duplicates should be performed at an action level specified by the laboratory and at an appropriate frequency.

10.1.1 Place a drop of reagent water on a KI starch test strip to serve as a reference blank.

10.1.2 Place a drop of 3 % H₂O₂ solution (or 10 % HNO₃) on a KI starch test strip to obtain a dark blue reference color.

10.2 Method detection limits should be determined by each laboratory by using a test oxidizer (7.6 or 7.7).

11. Precision and Bias

11.1 *Precision and Bias*—No information is presented about either the precision or bias of Test Method D4981 for measuring oxidizers since the test result is nonquantitative.

12. Keywords

12.1 oxidizers; screening analysis; starch-iodide paper