



Standard Specification for Cyclohexane 999¹

This standard is issued under the fixed designation D5309; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This specification covers a grade of cyclohexane identified as “cyclohexane 999.”

1.2 The following applies to all specified limits in this standard: for purposes of determining conformance with this standard, an observed value or a calculated value shall be rounded off “to the nearest unit” in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E29.

1.3 Consult current OSHA regulations, supplier’s Safety Data Sheets, and local regulations for all materials used in this specification.

2. Referenced Documents

2.1 ASTM Standards:²

D850 Test Method for Distillation of Industrial Aromatic Hydrocarbons and Related Materials

D3437 Practice for Sampling and Handling Liquid Cyclic Products

D5386 Test Method for Color of Liquids Using Tristimulus Colorimetry

D7183 Test Method for Determination of Total Sulfur in Aromatic Hydrocarbons and Related Chemicals by Ultra-violet Fluorescence

D7266 Test Method for Analysis of Cyclohexane by Gas

¹ This specification is under the jurisdiction of ASTM Committee D16 on Aromatic Hydrocarbons and Related Chemicals and is the direct responsibility of Subcommittee D16.01 on Benzene, Toluene, Xylenes, Cyclohexane and Their Derivatives.

Current edition approved June 1, 2016. Published June 2016. Originally approved in 1992. Last previous edition approved in 2013 as D5309 – 08 (2013)^ε. DOI: 10.1520/D5309-16.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard’s Document Summary page on the ASTM website.

Chromatography (External Standard)

D8005 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)

E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

2.2 Other Documents:

OSHA Regulations, 29 CFR Paragraphs 1910.1000 and 1910.1200³

3. Properties

3.1 Cyclohexane 999 shall conform to the following requirements:

Property	Specification	ASTM Test Method
Purity, min, weight %	99.90	D7266
Benzene, max, mg/kg	50	D7266
n-Hexane, max, mg/kg	200	D7266
Methylcyclohexane, max, mg/kg	200	D7266
Methylcyclopentane, max, mg/kg	150	D7266
Sulfur, max, mg/kg ^A	1	D7183
Appearance ^A	—	
Color, max, Platinum/Cobalt scale ^B	10	D5386 or D8005
Distillation range, including the temperature 80.7°C, at 101.3 kPa (760 mmHg) pressure, max, °C	1.0	D850

^A Clear liquid free of sediment and haze at 18.3 to 25.6°C (65 to 78°F).

^B If more than one method is listed for a property and there is a dispute, the referee method will be agreed upon between the buyer and the seller.

4. Sampling

4.1 Sample the material in accordance with Practice D3437.

5. Keywords

5.1 cyclohexane 999

³ Available from U.S. Government Printing Office Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401, http://www.access.gpo.gov.

*A Summary of Changes section appears at the end of this standard

SUMMARY OF CHANGES

Committee D16 has identified the location of selected changes to this standard since the last issue (D5309–08(2013)^{e1}) that may impact the use of this standard. (Approved June 1, 2016.)

(1) Removed D1209 and added D8005 in Section 2.

(2) Modified table in 3.1 to replace D1209 with D8005.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; <http://www.copyright.com/>