



Standard Specification for Technical Grade Ethylene Dichloride¹

This standard is issued under the fixed designation D5960; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the Department of Defense.

1. Scope

1.1 This specification covers technical grade ethylene dichloride.

1.2 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

2. Referenced Documents

2.1 ASTM Standards:²

[D2108 Test Method for Color of Halogenated Organic Solvents and Their Admixtures \(Platinum-Cobalt Scale\)](#)

[D2111 Test Methods for Specific Gravity and Density of Halogenated Organic Solvents and Their Admixtures](#)

[D2989 Test Method for Acidity-Alkalinity of Halogenated Organic Solvents and Their Admixtures](#)

[D3401 Test Methods for Water in Halogenated Organic Solvents and Their Admixtures](#)

[D6806 Practice for Analysis of Halogenated Organic Solvents and Their Admixtures by Gas Chromatography](#)

2.2 U. S. Government Documents:

[49 CFR 100 to 199 Department of Transportation Hazardous Materials Regulations³](#)

[29 CFR 1910.1200 Department of Labor, OSHA Regulations on Hazard Communications³](#)

3. Chemical Composition

3.1 Technical grade ethylene dichloride shall conform to the requirements prescribed in [Table 1](#).

4. Packaging and Package Marking

4.1 Package and label industrial or commercial quantities in accordance with DOT regulations 49 CFR 100 to 199, and in accordance with state and local regulations, and with OSHA regulations found in 29 CFR 1910.1200.

5. Keywords

5.1 ethylene dichloride; 1,2-dichloroethane

¹ This specification is under the jurisdiction of ASTM Committee D26 on Halogenated Organic Solvents and Fire Extinguishing Agents and is the direct responsibility of Subcommittee D26.02 on Vapor Degreasing.

Current edition approved Feb. 1, 2013. Published March 2013. Originally approved in 1996. Last previous edition approved in 2008 as D5960-03 (2008). DOI: 10.1520/D5960-03R13.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The Code of Federal Regulations may be obtained from the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.

TABLE 1 Technical Grade Ethylene Dichloride Requirements

Property	Specification	Test Method
Color, Pt-Co, max	10	D2108
Ethylene Dichloride, Weight %, min	99.8	D6806
Specific Gravity, 25/25°C	1.248–1.252	D2111
Acidity (as HCl), ppm, max	10	D2989
Water, ppm, max	200	D3401

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the ASTM website (www.astm.org/COPYRIGHT/).