

Designation: D7509 - 09 (Reapproved 2015)

Standard Specification for Fluorocarbon Feedstock Grade Chloroform¹

This standard is issued under the fixed designation D7509; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

- 1.1 This specification specifies chloroform (trichloromethane) that is suitable for use as feedstock for fluorocarbons.
- 1.2 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

2. Referenced Documents

2.1 ASTM Standards:²

D2108 Test Method for Color of Halogenated Organic Solvents and Their Admixtures (Platinum-Cobalt Scale)

D2109 Test Methods for Nonvolatile Matter in Halogenated Organic Solvents and Their Admixtures

D2989 Test Method for Acidity-Alkalinity of Halogenated Organic Solvents and Their Admixtures

- D3401 Test Methods for Water in Halogenated Organic Solvents and Their Admixtures
- D3741 Test Methods for Appearance of Admixtures Containing Halogenated Organic Solvents
- D4755 Test Method for Free Halogens in Halogenated Organic Solvents and Their Admixtures
- D6806 Practice for Analysis of Halogenated Organic Solvents and Their Admixtures by Gas Chromatography
- 2.2 Federal Documents:³
- 29 CFR 1910.1200 Department of Labor, OSHA Regulations on Hazard Communication
- 49 CFR 100 to 199 Department of Transportation Hazardous Materials Regulations

3. Properties

3.1 Fluorocarbon feedstock grade chloroform shall conform to the requirements prescribed in Table 1.

4. Packaging

4.1 Package and label industrial or commercial quantities in accordance with DOT regulations in 49 CFR 100 to 199, in accordance with state and local regulations, and in accordance with OSHA regulations found in 29 CFR 1910.1200.

5. Keywords

5.1 chloroform; feedstock; fluorocarbon; trichloromethane

¹ This specification is under the jurisdiction of ASTM Committee D26 on Halogenated Organic Solvents and Fire Extinguishing Agents and is the direct responsibility of Subcommittee D26.08 on Halogenated Organics Used as Feed Stocks.

Current edition approved June 1, 2015. Published June 2015. Originally approved in 2009. Last previous edition approved in 2009 as D7509–09. DOI: 10.1520/D7509-09R15.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Code of Federal Regulations, available from U.S. Government Publishing Office, 732 N. Capitol St., NW, Washington, DC 20401-0001, http://www.gpo.gov.

TABLE 1 Properties

| Property | Specification | ASTM |
|--------------------------------|------------------|-------------|
| | | Test Method |
| Appearance | Clear, free of | D3741 |
| | sediment and | |
| | suspended matter | |
| Water, ppm, max | 50 | D3401 |
| Non-volatile residue, ppm, max | 10 | D2109 |
| Color, PtCo, Max | 10 | D2108 |
| Free halogens, ppm, max | 1 | D4755 |
| Acidity as HCl, ppm, max | 5 | D2989 |
| 1,1-Dichloroethane, ppm, max | 80 | D6806 |
| Carbon Tetrachloride, ppm, max | 50 | D6806 |
| Methylene Chloride, ppm, max | 50 | D6806 |
| 1,2-Dichloroethylene, ppm, max | 100 | D6806 |
| Assay, wt, %, min | 99.95 | D6806 |

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; http://www.copyright.com/