



# Standard Guide for the Preparation of a Binary Chemical Compatibility Chart<sup>1</sup>

This standard is issued under the fixed designation E2012; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## INTRODUCTION

The purpose of this standard is to provide expert guidance to those interested in the task of compiling chemical compatibility (inter-reactivity) charts for the purposes of process safety and reactive chemicals hazard evaluation. This standard does not provide specific answers regarding the inter-reactivity of specific materials. However, it does provide a detailed framework for developing charts based on the current best practices of the chemical industry and it directs the user to sources of reactivity information. It is the E27 Committee's belief that inter-reactivity charts will be increasingly used in industry for day-to-day operations, process hazard reviews, employee education, and emergency response. It is our hope that this standard guide can be useful in that effort.

## 1. Scope

1.1 A binary chemical compatibility chart also called inter-reactivity chart, documents the hazards associated with the mixing of pairs of materials. This guide provides an aid for the preparation these charts. It reviews a number of issues that are critical in the preparation of such charts: accurate assessment of chemical compatibility, suitable experimental techniques for gathering compatibility information, incorporation of user-friendliness, and provision for revisions.

1.2 The uses of chemical compatibility charts are summarized in this standard.

1.3 This guide also reviews existing public domain compatibility charts, the differences therein, and their advantages and disadvantages.

1.4 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

## 2. Referenced Documents

2.1 *ASTM Standards*:<sup>2</sup>

[E537 Test Method for The Thermal Stability of Chemicals by Differential Scanning Calorimetry](#)

<sup>1</sup> This guide is under the jurisdiction of ASTM Committee E27 on Hazard Potential of Chemicals, and is the direct responsibility of Subcommittee E27.02 on Thermal Stability and Condensed Phases.

Current edition approved Dec. 1, 2012. Published December 2012. Originally approved in 1999. Last previous edition approved in 2006 as E2012 – 06. DOI: 10.1520/E2012-06R12.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

[E698 Test Method for Arrhenius Kinetic Constants for Thermally Unstable Materials Using Differential Scanning Calorimetry and the Flynn/Wall/Ozawa Method](#)

[E1231 Practice for Calculation of Hazard Potential Figures-of-Merit for Thermally Unstable Materials](#)

[PS168 Proposed Guide for Estimating the Incompatibility of Selected Hazardous Wastes Based on Binary Chemical Reactions](#)<sup>3</sup>

2.2 *NFPA Standard*:<sup>4</sup>

[NFPA 491 Guide to Hazardous Chemical Reactions](#)

## 3. Terminology

3.1 *Definitions*:

3.1.1 *compatibility, adj*—the ability of materials to exist in contact without specified (usually hazardous) consequences under a defined scenario.

3.1.2 *scenario, n*—a detailed physical description of the process whereby a potential inadvertent combination of materials may occur.

## 4. Summary of Guide

4.1 A binary chemical compatibility chart indicates whether, under a given set of conditions (the scenario) the combination of two materials does or does not yield a specified undesired consequence.

4.2 A summary of the guide follows. Determine the scenario for the determination of compatibility and the degree of

<sup>3</sup> Withdrawn. This chart was subsequently adopted by the U.S. EPA and is widely available by way of the Internet.

<sup>4</sup> Available from National Fire Protection Association (NFPA), 1 Batterymarch Park, Quincy, MA 02169-7471, <http://www.nfpa.org>.

reaction that constitutes incompatibility. Both should be identified in the documentation for the chart. Define the materials within the scope of the chart. Define the test, calculation or judgment that is used to make a decision. List the materials as both columns and rows of a grid. At the intersections of the grid note whether the materials are compatible. To avoid duplicate entries, a triangular chart is required. If a decision on compatibility was not by the standard means (as defined by the user) or the scenario differs, indicate by footnote the basis for the decision or the change in scenario. The chart should be dated and the author identified. See Fig. 1 for an example of a binary compatibility chart.

## 5. Significance and Use

5.1 Various United States governmental regulations forbid incompatible materials to be transported together and require that chemical reactivity be considered in process hazard and risk analysis. A chemical compatibility chart is one tool to be used to satisfy these regulations. Binary compatibility charts are useful teaching tools in general education, in the chemical plant or laboratory, and for areas and operations where commonly performed tasks might lead to chemical mixtures such as might occur during co-shipment in compartmentalized containers, storage in a common area or compositing waste. Compatibility information is essential during process hazard

REACTIVITY GROUP							
1	Hydrochloric Acid					1	
2	Sulfuric Acid	X <sup>1</sup>				2	
3	Acetic Acid	U <sup>8</sup>	X <sup>2</sup>			3	
4	Ethanol	U <sup>3</sup>	X <sup>4</sup>	X <sup>4</sup>		4	
5	Ethylene Diamine	X <sup>5</sup>	X <sup>6</sup>	X <sup>7</sup>	C <sup>12</sup>	5	
6	Water	X <sup>9</sup>	X <sup>10</sup>	C <sup>11</sup>	C <sup>13</sup>	C <sup>13</sup>	6

Legend:

X	incompatible
C	lab compatibility testing revealed no hazard
U	unknown - further evaluation needed

NOTE 1—Footnotes/Information Sources:

- (1) Unlikely to be compatible—USCG chart NVC-475 indicates a hazard with non-oxidizing acids plus sulfuric acid.
- (2) Unlikely to be compatible—the Proposed Guide PS168 chart indicates that gas and heat are formed; USCG chart NV 4–75 indicates a hazard when combining sulfuric and organic acids.
- (3) The Proposed Guide PS168 chart indicates that heat is formed; USCG chart NV 4–75 only indicates a hazard with furfuryl alcohol plus non-oxidizing mineral acids; testing should be conducted on this combination.
- (4) Unlikely to be compatible — see Proposed Guide PS168 chart.
- (5) Lab experiment 980001 resulted in a XXX°C adiabatic temperature rise.
- (6) Lab experiment 980002 resulted in a XXX°C adiabatic temperature rise.
- (7) Organic acids and amines are generally incompatible.
- (8) The Proposed Guide PS168 and USCG charts indicate no hazard; most likely compatible, but lab testing should be performed.
- (9) Heat of mixing may be a concern in some circumstances. The maximum adiabatic temperature rise is XX°C (see XYZ Encyclopedia of Chemical Technology).
- (10) Heat of mixing may be a concern in some circumstances. The maximum adiabatic temperature rise is XX°C (see XYZ Encyclopedia of Chemical Technology).
- (11) Lab experiment 98005 showed that mixing acetic acid and water is endothermic at room temperature.
- (12) Lab experiments 98003 and 98008 indicate that the materials do not generate heat or gases when mixed nor when heated to 100°C. Although the USCG chart NVC 4–75 indicates that some alcohols and amines are incompatible, ethylene diamine has been found to be compatible with many alcohols; see Appendix of USCG Guide.
- (13) Plant experience has shown that these materials do not generate heat or gases when mixed. In addition, no condition is known that would cause the materials to be combined at elevated temperature.

**FIG. 1 Hypothetical Compatibility Chart**

reviews (for example, HAZOP). These charts may provide guidance to terminal operators on DOT HM-183 that requires that materials on adjacent compartments of multicompartment tank trucks are compatible. They provide documentation that the potential for inadvertent mixing as a potential source of heat and gas evolution from chemical reactions has been considered in sizing relief devices. Compatibility charts serve as check lists for use during process hazard reviews, and the preparation of the chart itself often brings attention to potential hazards that were previously unknown.

5.2 A binary chart only considers pairs of materials and therefore does not cover all possible combinations of materials in an operation. A common third component, for example, acidic or basic catalysts, may be covered by footnoting the potential for catalysis of a reaction between otherwise compatible materials, but the form of the chart does not ensure this. There may be reactive ternary systems that will escape detection in a binary chart.

5.3 The AIChE organization Center for Chemical Process Safety (CCPS) has recommended the use of this standard in one of their recent monographs (1)<sup>5</sup>. This work is currently available for free download from: <http://www.osha.gov/SLTC/reactivechemicals/index.html>

## 6. Procedure

6.1 *Define the Scenario*—Chemical compatibility depends heavily on the mixing scenario (see Appendix X1). Consider including the following factors in the specification of the mixing scenario, as they, and other factors, may contribute to the assignment of compatibility.

- 6.1.1 Specific quantities of materials,
- 6.1.2 Storage temperatures,
- 6.1.3 Confinement (closed or open system),
- 6.1.4 Atmosphere (air, nitrogen inerted), and
- 6.1.5 The maximum time the materials may be in contact.

6.2 *Define Incompatibility Within the Scenario Framework*—An effective chart should clearly convey the criteria for defining two materials as incompatible. In a general sense, chemical incompatibility implies that there may be undesirable consequences of mixing these materials at a macroscopic scale. These consequences might be, in a worst case, a fast chemical reaction or an explosion, a release of toxic gas, or, in a less severe case, an undesirable temperature rise that might take the mixture above its flash point or cause an unacceptable pressure increase in the system. If, however, the tank where the mixing will occur is inerted with nitrogen, and the material has an acceptably low vapor pressure increase, then even this temperature rise might not pose a practical problem. Consequently, a working definition of incompatibility needs to be formulated before compatibility judgments can be effectively and accurately made.

6.2.1 Some examples of mixing scenarios and incompatibility definitions include:

6.2.1.1 Ambient temperature in summer, northern climate (approximately 25°C); (5000 gal) scale; insulated, vented

storage tank; storage time 7 days maximum, nitrogen padded headspace (chemical transport scenario). Materials considered incompatible if temperature rise greater than 25°C, or grassy reaction.

6.2.1.2 Ambient temperature in a hotter, subtropical climate (approximately 40°C), drum (55 gal) storage of mixed waste for 3 months maximum. Materials considered incompatible if there could be a release from the drum.

6.2.1.3 Room temperature, 4L (1 gal) bottles, loosely capped, 1 month maximum storage time (typical lab waste scenario). Materials considered incompatible if there is an evolution of flammable vapor, toxic gas, or a temperature rise greater than 10°C.

6.3 *Compile Compatibility Chart*—The following steps may be followed for constructing the compatibility chart (see Appendix X2).

6.3.1 *State the Scenario*—In the preparation of a compatibility chart, consider stating both the scenario and the scenario-based definition of incompatibility explicitly on the chart.

6.3.2 *Decide on a Hazard Rating Scheme*—Formulate the reference scale for the individual degree of mixing hazard. It may be desirable to have a simple “yes/no” (that is, compatible/incompatible) scale. In some instances, ratings that convey more information may be advantageous. For example, a numerical score of 1, 2, and 3 might be appropriate with 1 indicating a compatible mixture, 2 indicating a moderate hazard (for example, a temperature increase of 10°C or less), and 3 indicating a severe hazard, such as polymerization or spontaneous combustion. Another example of a hazard rating scheme is given in Table 1. Note that in the Table 1 example, the hazard rating scheme also conveys information about procedures for emergency response, but this information need not be included in the chart. The use of color (if available in the charting tool) may also aid in understanding the chart. For example, green could indicate safe, compatible mixtures, red could indicate reactive, incompatible mixtures. It is important to avoid making the chart too complicated.

6.3.3 *Define the Categories*—Defining categories for the chart is an important part of chart construction. For small plants and operations, each chemical may be included in the chart and the resulting chart may still be of manageable size. For more general compatibility charts, for example, for a large manufacturing site, the chart may group chemicals into natural

**TABLE 1 An Example of Hazard Levels and Typical Associated Emergency Response Actions**

Hazard Rating	Hazard Level	Suggested Emergency Response
0	Minimal	Report inadvertent mixing event to supervision; no further action necessary.
1	Caution	Report event to supervision; implement plan(s) to manage the situation; no emergency procedures to be initiated.
2	Danger	Report event to supervision; prepare to initiate unit emergency plan if needed; notify personnel in immediate area; consider halting normal activities until extent of situation is fully assessed.

<sup>5</sup> The boldface numbers in parentheses refer to the list of references at the end of this standard.

classifications based on their chemical structure. Examples of these groupings are: mineral acids, aliphatic amines, monomers, water-based formulations, halogenated hydrocarbons, and so forth. One limitation with this manner of chart construction is that for a number of classes, certain binary combinations might be known to be compatible whereas other combinations within the same two groups may not be. It may be best to provide the worst case compatibility rating in the actual chart with a separate list of compatible exceptions. It may be prudent to include additional useful compatibility information, such as compatibility of chemicals with materials of construction, water (from process streams or from rain in diked areas), cleaning agents, sealants, and adsorbents. “Heat” might be considered as an entry to flag particularly heat sensitive materials such as polymerizable monomers. Consultation with a wide variety of personnel (management, engineers, operators, and so forth) may aid in the determination of what materials are present at a site and which ones should be included in the chart.

**6.3.4 Consider the Hazards for all Binary Combinations—**The potential hazard for each and every binary mixture needs to be carefully considered. Avoid using blanks (empty cells) in compatibility charts since blanks may indicate that there is no hazard, or, simply that the hazard is unknown. Clearly distinguishing between a non-hazard and an unknown hazard is an important consideration. See [Appendix X2](#) for sources of compatibility information.

**6.3.5 Document How the Decisions Are Made—**Backup and supporting data should be easily accessible for chart users and to allow for easier chart updates. If testing was performed to make a decision about a particular binary combination in a chart, then a reference to this test should be included in the chart.

**6.3.6 Label the Chart—**Date the chart and ensure that title clearly states the purpose of the chart such as “Chemical Compatibility Chart for the Styrene Polymerization Plant A-104, last updated 9/2004.” Scenarios may differ from process to process and if the chart is not specifically labeled with the intended use, the chart may be used in a process for which it was not intended, with possible undesired consequences. Since a large plant often has distinct areas, consider including only those materials in each area in the chart, to avoid making the chart needlessly large and complicated. Consider adding a Revisions Log which documents changes to the chart including additions/removal of materials, general chart reviews by subject matter experts, etc. If the chart is made in the EXCEL format, this may be accomplished easily with a new workbook tab

## 7. Experimental Tools for the Determination of Compatibility

7.1 In certain cases, an experimental determination of the compatibility is the most prudent approach. This may be necessary if the compounds or molecular types cannot be found in one of the published charts, if the data are not provided by the manufacturer, or if the scale and scenario of mixing warrant an actual verification of the hazards involved. It is beyond the scope of this guide to provide standard test methods and details

for the experimental determination of chemical compatibility. However, some general considerations are given that may assist in the design of an appropriate experiment.

7.2 Scale is one key consideration in the accurate design of an experimental compatibility test. Start the testing at small enough scale to minimize the potential dangers to the test operator. Also, in order to apply the results of compatibility tests to various scenarios, quantitative data suitable for scaleup are needed. One such quantitative testing scheme using 2 to 200-mg quantities is described. This experimental technique involves differential scanning calorimetry (DSC) testing of the individual components and the mixture and also mixing calorimetry. A summary of this approach is as follows:

7.2.1 Determine some measure of the inherent thermal stability of the individual components using DSC.

7.2.2 Determine the instantaneous energy release (heat and gas evolution) upon mixing of the two components using heat-of-mixing calorimetry. (Use an appropriate mixing ratio that adequately quantifies the hazard; see 7.4).

7.2.3 Determine the relative thermal stability of the mixture (as compared and contrasted to the individual components) by DSC.

7.3 This experimental formalism allows an evaluation of materials that might react very quickly upon mixing and also materials that require more elevated temperature or an induction period to react. Neither mixing calorimetry nor DSC alone are adequate to fully evaluate the reactivity hazards associated with a mixture. For example, a DSC on a mixture of HCl(aq) and NaOH(aq) would show no exothermic activity (to approximately 400°C) since the acid-base neutralization takes place virtually instantaneously and the resultant solution is simply NaCl(aq). A mixing calorimetry test could quantify the heat of neutralization and thus more accurately define the hazards associated with this mixture. If a reaction is autocatalytic, the mixing calorimetry might not detect any heat due to the characteristic induction times for this type of process. The DSC test would probably be able to detect the reaction since it subjects the sample to a continuous temperature ramp.

7.4 The choice of mixing ratio may be important. If the reaction stoichiometry is known, then the maximum heat release will occur with a stoichiometric mixture. The maximum adiabatic temperature rise will also occur near the stoichiometric point unless the heat capacities of the constituents are widely different. If the stoichiometry is unknown, then experiments at several ratios may be necessary. The details of the mixing scenario may also affect the choice of mixing ratio (for example, it may not be possible to get a stoichiometric mixture). In the case of heat generation by dilution, the heat capacities of constituents play a major role in defining the optimum ratio.

7.5 Perhaps the easiest part of the experimental procedure is the actual testing. The hardest part sometimes is an unambiguous interpretation of the results. If there is no substantial mixing heat (or gas generation) and the DSC trace of the mixture is ostensibly a superposition of the DSC traces of the

individual components, no incompatibilities may exist regardless of the scenario. If substantial incompatibility exists between the substances, however, a large mixing heat will be observed or the DSC trace will show a large exotherm detected at a lower temperature (with respect to the individual component DSC traces), or both. Unfortunately, both these behaviors are rare in practice and, often, the results fall in between the two extreme cases. The analyst then may have a more difficult time in assessing the results. For these reasons, it may be desirable to estimate the thermokinetics of the incompatibility reaction and from these data, predict the conditions (temperature, volume, and so forth) whereby a mixture might become a large scale hazard using heat gain - heat loss models. This technique has been described in Ref. (2).<sup>5</sup> Additional information regarding use of DSC for determination of thermal stability may be found in Test Methods E537 and E698, and Practice E1231.

## 8. Report

8.1 An example binary compatibility chart is shown in Fig. 1. The important features of a compatibility chart are:

8.1.1 A clearly defined process or area for which the chart is applicable (given in the title in this example),

8.1.2 The date that the chart is published,

8.1.3 A grid showing hazards resulting from binary combinations,

8.1.4 A clearly defined hazards rating scheme (explained by a legend in this example); the scheme may be as simple as

using an R (reactive) for incompatible combinations, a NR (non-reactive) for compatible combinations, and “?” for unknown. Other schemes are yes/no, and numerical schemes such as 0, 1, 2 (compatible, caution, danger, resp.), and

8.1.5 Documentation of information sources (given by footnotes in this example but may be included in the “notes/comments” cell background of standard spreadsheets).

8.2 In the example chart in Fig. 1, much of the data comes from literature and little of it comes from actual testing. This chart can be considered representative of a chart in its early stages. Ideally, all information is based on tests or experience and no information is unknown.

8.3 It is recommended to define the scenarios in which materials are incompatible. Materials may create a hazard when combined in certain scenarios within a process while not creating a hazard when combined in others. The temperature under which materials are in combination is a good example of a variable that can drastically affect compatibility. It is dangerous to assume materials are compatible at higher temperatures just because they are known to be compatible at lower temperatures. Use of plant experience may be legitimate, but it may be dangerous to extrapolate this information to other conditions (for example, larger scale, longer storage times, higher temperatures).

## 9. Keywords

9.1 chemical compatibility chart; inter-reactivity chart; mixing hazards

## APPENDIXES

### (Nonmandatory Information)

#### X1. THE SCENARIO DEPENDENCE OF MIXING

X1.1 There is a great difference in combining relatively reactive materials, such as strong oxidizers with strong reducing agents, on a small scale (for example, 0.05 ml) under controlled laboratory conditions, as compared to pumping a tank-truck full of the oxidizer into a large storage tank of reducing agent. However, it is important to recognize the potential time and temperature dependency of chemical reactions. Size of the mixture affects both the total amount of energy and the rates at which that energy can be given off to the environment. A small flask may be able to lose heat fast enough to its environment relative to the amount of heat it is giving off, while a rail car of the same mixture will lose heat proportionately at a much slower rate and possibly self-heat to thermal explosion. Chemical reaction rates increase exponentially with temperature. For a typical reaction with an activation energy of 84 kJ/mol (20 kcal/mol), this translates into a >6000-fold increase in rate for a temperature increase from 20 to 120°C. For a reaction with an activation energy of 145 kJ/mol (35

kcal/mol), as is not uncommon in peroxide decomposition, the rate increase is over 4 million for the same temperature increase. These rates translate into changing half-lives from months and days at lower temperatures to minutes and seconds at higher temperatures. For the same reasons, one cannot define incompatibility in terms of a specific temperature at which two materials react. Response, contact time, and cleanup time impact the consideration of compatibility. The answer to many questions depends partly on the confidence placed in the reliability of operating discipline.

X1.2 It is imperative, when making a decision about the compatibility of two chemicals, that a scenario be defined. The scenario should contain the essential information of temperature, quantities, heat transfer characteristics, and the length of time the materials will remain mixed. Other elements that could be included in the scenario are discussed in 6.1.

## X2. RESOURCES FOR COMPATIBILITY INFORMATION

X2.1 *Tools for Preparation of Compatibility Charts*—Standard and commonly available software can be quite useful in the preparation of a compatibility chart. Commercially available spreadsheets are useful, allowing the chart to then be made accessible via a network server to all those involved in a common operation.

### X2.2 *Sources of Compatibility Information:*

NOTE X2.1—The absence of public literature regarding hazards of a binary mixture cannot be taken to imply that no hazard exists.

#### X2.2.1 *Public Literature:*

X2.2.1.1 The public scientific literature may be useful to find compatibility information but sometimes these data are relatively obscure. An excellent source of such data is Bretherick's Handbook of Reactive Chemical Hazards, Ref. (3), which has been in print for at least 20 years and is still published in book form, and has recently been made available for PC searches and now is also available in a format that allows for logical searches (for example, chlorine AND amine). Bretherick's Handbook (3) summarizes the data for individual compounds, mixtures, and certain classes of materials (such as nitro aromatics, and so forth). There is also an extensive discussion of the general field of reactive chemicals hazards, including the basics of hazard evaluation, kinetic factors, adiabatic systems, reactivity versus composition and structure, reaction mixtures, and protective measures. This work covers 4800 elements or compounds with an additional 5000 secondary entries involving two or more materials, with 30000 cross-references.

X2.2.1.2 If the material is a pure substance, as opposed to a chemically complex process stream, a good source for compatibility information in the United States is the Material Safety Data Sheet (MSDS). These data sheets are compiled by the manufacturers and may present detailed, known incompatibility problems that might be otherwise difficult to find. A useful book which appears to be a detailed compilation of compatibility data from MSDS sources may be found in (4)

X2.2.1.3 Other good sources of chemical reactivity and compatibility information include NFPA 491 and Refs. 5, 6, 7, 8, and 9. Finally, do not overlook the myriad of college text books on organic and inorganic chemistry that provide valuable information about chemical synthesis.

X2.2.2 *Organic and Inorganic Synthesis Chemists*—These individuals are trained to know what chemicals react under defined conditions. For those unfamiliar with synthesis chemistry, these experts should be consulted.

X2.2.3 *Knowledgeable Process Personnel*—There is no substitute for experience in a complicated chemical process. Those who have practical plant experience may be a good source of historical compatibility information. Capturing this information in a compatibility chart will help ensure this information is not lost.

X2.2.4 *NOAA Chemical Reactivity Worksheet*—The Chemical Reactivity Worksheet (10) is a free program one may use to assess the binary reactivity of substances or mixtures of substances. It includes a database of reactivity information for more than 6000 common hazardous chemicals. The database also includes information about the special hazards of each chemical and about whether a chemical reacts with air, water, or other materials. One advantage of this tool is its categorization not only be individual chemical names but also by functional group (such as alcohols, ethers, and so forth). The reactivity decisions were made by a number of chemists using chemical knowledge and a variety of standard references, many of which have already been described in this guide. This program may be downloaded at <http://response.restoration.noaa.gov/chemaids/react.html>.

X2.2.5 *Public Compatibility Charts*—Several published charts are available for consultation in the preparation of a specific chart (11, 12). Ref. (12) covers a large number of materials, but was superseded by Ref. (11), which includes the information in Ref. (12) as well as additional information. Although it was never adopted as a full consensus ASTM standard, Proposed Guide PS168 is still widely used since it was subsequently adopted by the U.S. EPA. Use public domain charts carefully as they may have missing or inaccurate information. See Ref. (13) for a review of known errors and pitfalls in these charts. In spite of some errors, these charts can provide helpful insights, and usually reference supporting compatibility information. The charts in Refs. (11 and 12) and in Proposed Guide PS168 have similarities in their approach, including:

- (1) Reactivity groups are used,
- (2) Charts are displayed as a matrix showing consequences of binary mixtures,
- (3) Charts consider only binary mixtures,
- (4) Scenarios are limited to near room temperature (less than 55°C) and ambient pressure conditions,
- (5) Charts attempt to be conservative, in that the most reactive materials are considered for each binary mixture, and
- (6) Charts contain warnings regarding application.

**REFERENCES**

- (1) Johnson, R.W., Rudy, S.W., Unwin, S.D., *Essential Practices for Managing Chemical Reactivity Hazards*, Center of Chemical Process Safety of the American Institute of Chemical Engineers, 3 Park Avenue, New York, NY 10016–59, 2003.
- (2) Hofelich T.C., Frurip D.J., and Powers J.B., “The Determination of Compatibility via Thermal Analysis and Mathematical Modeling,” *Process Safety Progress*, Vol 13, No. 4, 1994, 227–233.
- (3) Bretherick L., *Bretherick’s Handbook of Reactive Chemical Hazards*, Sixth Ed., Butterworths, Boston, MA, 1996.
- (4) Pohanish, R.P., and Greene, S.A., *Wiley Guide to Chemical Compatibility*, Wiley, 2003.
- (5) *The Merck Index, An Encyclopedia of Chemicals, Drugs, and Biologicals*, Thirteenth Ed., Windholz, M., ed., Merck and Co., Inc., Rahway, NJ, 2001.
- (6) Federoff B.T., et al., *Encyclopedia of Explosives and Related Items*, Picatinny Arsenal, Dover, NJ, pp. 1960–1983.
- (7) Sax, N.I., *Dangerous Properties of Industrial Materials*, Eleventh Ed., Van Nostrand Reinhold Co., New York, NY, 2004.
- (8) *Fire Protection Guide to Hazardous Materials*, 13th Ed., National Fire Protection Association, Batterymarch Park, P.O. Box 9101, Quincy, MA 02269-9101, 2001. This contains test to NFPA 491, Guide to Hazardous Chemical Reactions.
- (9) *Guidelines for Chemical Reactivity Evaluation and Application to Process Design*, American Institute of Chemical Engineers, New York, NY, 1995.
- (10) *Chemical Reactivity Worksheet*, Version 1.6, developed by Farr, J.K., Ph.D., Office of Response and Restoration, National Ocean Service, NOAA, 7600 Sand Point Way NE, Seattle, WA 98115.
- (11) “Compatibility of Cargoes,” published in 46 CFR Ch. 1 (10-1-05 Edition) – Part 150 with changes that appeared in the Federal Register dated April 11, 1994 as a Final Rule by Coast Guard (CGD 92-100) for Bulk Hazardous Materials. See also: “Compatibility Guide for Adjacent Loading of Bulk Liquid Cargoes (Final Report),” Report No. USCG-D-156-75. Also available at <http://www.chrismanual.com/Intro/compatib.htm>.
- (12) Steensland, O., Vossgard, R., and Askheim, N.E., “Reactivity Between Chemical Cargoes,” *Norwegian Maritime Research*, Vol 2, No. 2, 1974, pp. 21–34.
- (13) Frurip, D.J., Hofelich, T.C., Leggett, D.J., Kurland, J.J., and Niemeier, J.K. “A Review of Chemical Compatibility Issues,” *Proceedings of the 31<sup>st</sup> Annual Loss Prevention Symposium*, Paper 43c, American Institute of Chemical Engineers, New York, NY, 1997.

*ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.*

*This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or [service@astm.org](mailto:service@astm.org) (e-mail); or through the ASTM website ([www.astm.org](http://www.astm.org)). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; <http://www.copyright.com/>*