



Standard Test Method for Measuring Thermal Insulation of Sleeping Bags Using a Heated Manikin¹

This standard is issued under the fixed designation F1720; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

INTRODUCTION

Sleeping bags are used by people in outdoor environments to insulate them from the cold (that is, reduce their body heat loss to the environment). Sleeping bags often are used with ground pads and clothing inside tents that provide additional protection from the environment. The amount of insulation needed in a sleeping bag depends upon the air temperature and a number of other environmental factors (for example, wind speed, radiant temperature, moisture in the air), human factors (for example, a person's metabolic heat production that is affected by gender, age, fitness level, body type, size, position, and movement), and physical factors (for example, amount of body coverage and the quality of the insulating materials). The insulation value, expressed in clo units, can be used to characterize sleeping bags and sleeping bag systems. Insulation values can be used in body heat loss models to predict the temperature ratings for comfort.

1. Scope

1.1 This test method covers determination of the insulation value of a sleeping bag or sleeping bag system. It measures the resistance to dry heat transfer from a constant skin temperature manikin to a relatively cold environment. This is a static test that generates reproducible results, but the manikin cannot simulate real life sleeping conditions relating to some human and environmental factors, examples of which are listed in the introduction.

1.2 The insulation values obtained apply only to the sleeping bag or sleeping bag system, as tested, and for the specified thermal and environmental conditions of each test, particularly with respect to air movement past the manikin.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

¹ This test method is under the jurisdiction of ASTM Committee F08 on Sports Equipment, Playing Surfaces, and Facilities and is the direct responsibility of Subcommittee F08.22 on Camping Softgoods.

Current edition approved Nov. 1, 2014. Published November 2014. Originally approved in 1996. Last previous edition approved in 2011 as F1720 – 06 (2011). DOI: 10.1520/F1720-14.

2. Referenced Documents

2.1 *ASTM Standards*:²

F1291 Test Method for Measuring the Thermal Insulation of Clothing Using a Heated Manikin

2.2 *ISO Standards*:³

ISO 13537 2002 Requirements for Sleeping Bags

ISO 15831 2004 Clothing—Physiological Effects—Measurement of Thermal Insulation by Means of a Thermal Manikin

3. Terminology

3.1 *Definitions*:

3.1.1 *auxiliary products, n*—items used with a sleeping bag to create a sleeping bag system such as clothing, ground pad, and bivy sack.

3.1.2 *clo, n*—unit of thermal resistance (insulation) equal to $0.155^{\circ}\text{C}\cdot\text{m}^2/\text{W}$.

3.1.2.1 *Discussion*—A heavy men's business suit provides 1 clo of insulation.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036.

3.1.3 *dry heat loss, n*—heat transferred from the body surface to a cooler environment by means of conduction, convection, and radiation.

3.1.4 *manikin, n*—a life-size model of the human body with a surface temperature similar to that of a human being.

3.1.5 *sleeping bag, n*—a structure made of down, synthetic fiberfill, shell fabrics, or other materials, or a combination thereof, that is designed for people to use for thermal protection when sleeping (for example, outdoors, tent, cabin).

3.1.6 *sleeping bag system, n*—sleeping bag used with auxiliary products such as clothing, ground pad, and bivy sack.

3.1.7 *thermal insulation, n*—resistance to dry heat transfer by way of conduction, convection, and radiation.

3.1.8 *total insulation (I_T), n*—the resistance to dry heat loss from the manikin that includes the resistance provided by the sleeping bag, auxiliary products (if used) and the air layer around the manikin.

3.1.8.1 *Discussion*—Total insulation values (I_T) are measured directly with a manikin. They can be used to compare different sleeping bags, as long as each test is conducted using the same experimental procedures and test conditions.

4. Summary of Test Method

4.1 A heated manikin is placed inside a sleeping bag or sleeping bag system in a cold environmental chamber.

4.2 The power needed to maintain a constant body temperature is measured.

4.3 The total thermal insulation of the sleeping bag or sleeping bag system (including the resistance of the external air layer) is calculated based on the skin temperature and surface area of the manikin, the air temperature, and the power level.

5. Significance and Use

5.1 This test method can be used to quantify and compare the insulation provided by sleeping bags or sleeping bag systems. It can be used for material and design evaluations.

5.2 The measurement of the insulation provided by clothing (see Test Method F1291) and sleeping bags is complex and dependent on the apparatus and techniques used. It is not practical in a test method of this scope to establish details sufficient to cover all contingencies. Departures from the instructions in this test method may lead to significantly different test results. Technical knowledge concerning the theory of heat transfer, temperature and air motion measurement, and testing practices is needed to evaluate which departures from the instructions given in this test method are significant. Standardization of the method reduces, but does not eliminate, the need for such technical knowledge. Any departures should be reported with the results.

6. Apparatus

6.1 *Manikin*⁴—Use a supine manikin that is formed in the shape and size of an adult male or female and is capable of

being heated to a constant average surface temperature of 35°C. The manikin's height should be between 1.5 and 1.9 m with a surface area between 1.5 and 2.1 m².

6.1.1 *Size and Shape*—Construct the manikin to simulate the body of a human being, that is, construct a head, chest/back, abdomen/buttocks, arms, hands, legs, and feet. Total surface area shall be 1.8 ± 0.3 m², and height shall be 180 ± 10 cm. Any departures from this description should be reported.

6.1.2 *Surface Temperature*—Construct the manikin so as to maintain a constant temperature distribution over the entire nude body surface with no local hot or cold spots. Ensure that the mean skin temperature of the manikin is 35°C. Do not allow local deviations from the mean skin temperature to exceed ± 0.3 °C. Evaluate temperature uniformity of the nude manikin at least once annually using an infrared thermal imaging system, a surface (contact) temperature probe, or equivalent method. This procedure also should be repeated after repairs or alterations are completed that could affect temperature uniformity, for example, replacing a heating element.

6.2 *Power-Measuring Instruments*—Measure the power to the manikin so as to give an accurate average over the period of a test. If time proportioning or phase proportioning is used for power control, then devices that are capable of averaging over the control cycle are required. Integrating devices (watt-hour metres) are preferred over instantaneous devices (watt metres). Overall accuracy of the power monitoring equipment must be within ± 2 % of the reading for the average power for the test period. Since there are a variety of devices and techniques used for power measurement, this standard does not provide specific calibration procedures. Develop and document an appropriate power calibration procedure.

6.3 *Equipment for Measuring the Manikin's Skin Temperature*—The mean skin temperature may be measured with point sensors or distributed temperature sensors.

6.3.1 *Point Sensors*—Point sensors may be thermocouples, resistance temperature devices (RTDs), thermistors, or equivalent sensors. Ensure that they are no more than 3-mm thick and are well bonded, both mechanically and thermally, to the manikin's surface. Bond lead wires to the surface or pass through the interior of the manikin, or both. Distribute the sensors so that each one represents the same surface area or area-weight each sensor temperature when calculating the mean skin temperature for the body. A minimum of 11 point sensors are required. It is recommended that a sensor be placed on the head, chest, back, arms, legs, hands, and feet.

6.3.2 *Distributed Sensors*—If distributed sensors are used (for example, resistance wire), then the sensors must be distributed over the surface so that all areas are equally weighted. If several such sensors are used to measure the temperature of different parts of the body, then their respective temperatures should be area-weighted when calculating the mean skin temperature. Distributed sensors must be small in diameter (that is, less than 1 mm) and firmly bonded to the manikin surface at all points.

⁴ Information on laboratories with heated manikins can be obtained from the Institute for Environmental Research, Kansas State University, Manhattan, KS 66506.

6.4 *Controlled Environmental Chamber*—Place the manikin in a chamber at least 3 by 2 by 2.6 m in dimension that can provide uniform conditions, both spatially and temporally.

6.4.1 *Spatial Variations*—Do not exceed the following: air temperature $\pm 1.0^{\circ}\text{C}$, relative humidity $\pm 5\%$, and air velocity $\pm 50\%$ of the mean value. In addition, the mean radiant temperature shall not be more than 1.0°C different from the mean air temperature. Verify the spatial uniformity at least annually or after any significant modifications are made to the chamber. Verify spatial uniformity by recording values for the conditions stated above at 0.6 m (the midline elevation of the manikin on the cot) and 1.1 m above the floor at the location occupied by the manikin. Use sensing devices specified below when measuring the environmental conditions.

6.4.2 *Temporal Variations*—Do not exceed the following: air temperature $\pm 0.5^{\circ}\text{C}$, mean radiant temperature $\pm 0.5^{\circ}\text{C}$, relative humidity $\pm 5\%$, and air velocity $\pm 20\%$ of the mean value for data averaged over 5 min (see 6.4.5).

6.4.3 *Relative Humidity Measuring Equipment*—Any humidity sensing device with an accuracy of $\pm 5\%$ relative humidity and a repeatability of $\pm 3\%$ is acceptable (for example, wet bulb/dry bulb, dew point hygrometer). Only one location needs to be monitored during a test to ensure that the temporal uniformity requirements are met.

6.4.4 *Air Temperature Sensors*—Shielded air temperature sensors shall be used. Any sensor with an overall accuracy of $\pm 0.15^{\circ}\text{C}$ is acceptable (for example, RTD, thermocouple, thermistor). The sensor shall have a time constant not exceeding 1 min. The sensor(s) shall be located at the midline elevation of the manikin (0.6 m from the floor), at least 0.4 m from the manikin. A single sensor may be used, but multiple sensors are preferred. If a single sensor is used, it shall be located midway between the head and the feet. If multiple sensors are used, they shall be spaced equally from the head to the feet and their readings averaged.

6.4.5 *Air Velocity Indicator*—Use an omnidirectional anemometer with ± 0.05 m/s accuracy. Average measurements for at least 1 min at each location. If it is demonstrated that velocity does not vary temporally by more than ± 0.05 m/s, then it is not necessary to monitor air velocity during a test. The value of the mean air velocity must be reported, however. If air velocity is monitored, then measurement location requirements are the same as for temperature.

7. Sampling

7.1 It is desirable to test three identical sleeping bags so that sample variability will be reflected in the test results. Sample variance generally is larger for sleeping bags as compared with clothing. If only one sample is available, which is often the case with prototypes, replicate measurements can be made on one sleeping bag.

8. Preparation of Sleeping Bags

8.1 The sleeping bag should be the appropriate size for the manikin with respect to its width and length. A bag that fits tightly and causes compression in the head, feet, or hip areas may have a lower insulation value than one that does not cause compression.

8.2 Bags normally should not be laundered or dry cleaned prior to testing because the procedures may affect the results.

8.3 If auxiliary products are used, the correct size should be selected for the manikin.

9. Test Procedure

9.1 *Environmental Test Conditions*—The standard conditions for all tests are given as follows.

9.1.1 *Air Temperature*—The air temperature shall be at least 25°C lower than the manikin's mean temperature during a test.

9.1.2 *Air Velocity*—Use a fan to produce an air velocity of 0.3 ± 0.05 m/s. Position the bag and manikin so that the direction of the air flow is from the head to the feet.

9.1.3 *Relative Humidity*—Maintain the relative humidity between 40 and 80 % for all tests.

9.2 *Mean Skin Temperature of Manikin*—The manikin's mean surface temperature shall be $35 \pm 0.3^{\circ}\text{C}$ for all tests.

9.3 *Options*—Select one of the following procedures.

9.3.1 *Option 1: Sleeping Bag Test*—Place the sleeping bag on the nude manikin on a cot in the environmental chamber and measure its insulation.

9.3.1.1 This approach is used when comparing the design, construction, and filling materials of different bags. Small differences in insulation will be easier to detect when the bag is tested alone.

9.3.2 *Option 2: Sleeping Bag System Test*—Test the sleeping bag with selected auxiliary products such as clothing and a ground pad. Describe the auxiliary products used in the report.

9.3.2.1 The insulation value of sleeping bag systems is usually used when determining the temperature ratings of sleeping bags. This is because consumers rarely use a sleeping bag by itself. They generally use some auxiliary products with it. Clothing and ground pads can greatly increase the insulation of a sleeping bag and lower the temperature rating for comfort. In addition, this is the approach used in EN 13537.

9.4 *Procedures*—Before testing, fluff the sleeping bag by tumbling it in a dryer without any load for 15 min at a temperature of less than 30°C .

9.4.1 Position the manikin horizontally on a cot with a wooden frame that is 69 by 193 by 43 cm in dimensions and has a nylon cover (plain weave, 246 g/m^2 , 24 by 18 yarns/cm).⁵

9.4.2 Dress the manikin in the appropriate clothing (if using option 2).

9.4.3 Insert the manikin in the sleeping bag to be tested, securing all closures. Make sure the sides and ends of the bag are not compressed. For bags with a hood, secure the head opening by pulling the draw cord as snug as possible around the manikin's head. The diameter of the opening should not be smaller than 5 cm. For bags without a hood, secure the head opening around the neck, exposing the head. Add other auxiliary products (for example, a pad or bivy sack, or both), if applicable (if using option 2).

⁵ The sole source of supply of the apparatus known to the committee at this time is Byer Manufacturing Co., 74 Mill Street, Orono, ME 04473. If you are aware of alternative suppliers, please provide this information to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee,¹ which you may attend.

9.4.4 Bring the manikin's skin temperature to 35°C and allow the system to reach steady state (that is, the mean skin temperature of the manikin shall remain constant $\pm 0.1^\circ\text{C}$, and the power input shall remain constant $\pm 3\%$).

9.4.5 After the sleeping bag reaches steady-state conditions, record the manikin's skin temperatures and the air temperature at least every 5 min. The average of these measurements taken over a period of 30 min will be sufficient to determine the insulation value. Measure heater wattage (power) every 5 min or continuously over the test period.

9.5 *Replication of Tests*—The following options are permissible.

9.5.1 *Most Preferred*—Conduct three independent replications of the test using three samples of a sleeping bag type. Sample variance, dressing variability, and instrumentation variability are reflected in the measurements.

9.5.2 *Preferred*—If only one sample of a sleeping bag is being tested, conduct three independent replications of the test by dressing the manikin in the bag three different times and taking data each time. Dressing variability and instrumentation variability are reflected in the measurements.

9.5.3 *Adequate*—If only one sample of a sleeping bag is being tested, three replications of the test may be conducted in a row, a minimum of 1 h apart (for example, military method). Instrumentation variability is reflected in the measurements.

10. Calculation

10.1 The parallel method of calculating the total thermal resistance (insulation) shall be used, where the area-weighted temperatures of all body segments are summed and averaged, the power levels to all body segments are summed, and the areas are summed before the total resistance is calculated. Calculate the total thermal insulation of the sleeping bag including the air layer resistance (I_T), using the following equation:

$$I_T = \frac{K(T_s - T_a)A}{P}$$

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; http://www.copyright.com/

where:

K = units constant = $6.45 \times \text{clo} \times \text{W/m}^2 \cdot ^\circ\text{C}$,
 T_s = mean skin temperature of manikin, $^\circ\text{C}$,
 T_a = air temperature, $^\circ\text{C}$,
 A = surface area of manikin, m^2 , and
 P = power supplied to the manikin, W .

11. Report

11.1 Report the following information:

11.1.1 State that the sleeping bags were tested as directed in this test method. Explain any departures from the specified apparatus or procedure,

11.1.2 Report the weight and surface area of the manikin,

11.1.3 Describe the sleeping bags and auxiliary products that were tested,

11.1.4 Specify the environmental test conditions and procedure option used, and

11.1.5 Report the total insulation value (I_T) in clo units and the number and type of replications conducted (see 9.5). Report clo values to two decimal points.

11.1.6 *Optional*—Report the local total insulation values for each body segment of the manikin in clo units.

12. Precision and Bias⁶

12.1 In comparing three observations of the thermal insulation value (I_T) (measured on the same bag) the variation shall not exceed $\pm 3\%$ of the average of the three measurements when the measurements are taken in a row by the same well-trained operator using the same testing equipment. When measurements are made on different samples of the same type, the variance may be higher.

13. Keywords

13.1 clo; insulation; sleeping bags

⁶ Supporting data have been filed at ASTM International Headquarters and may be obtained by requesting Research Report RR:F08-1004.