Designation: F1753 - 96 (Reapproved 2014)

Standard Specification for Classification and Marking of Single-Lens Scopes for Use with Archery Bows¹

This standard is issued under the fixed designation F1753; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

- 1.1 This specification covers lenses and scopes used in conjunction with archery bows. It establishes a standardized system for the classification of these lenses in terms of their optical magnification, the marking of the scopes in which the lenses are mounted, and charts depicting the empirical relationship of the apparent magnification the consumer can expect to obtain when a correctly marked lens is used under specific conditions.
- 1.2 Acuity—The visual acuity of these lenses is related to the magnification of the lens in general. For the average subject there can be an improvement in acuity with lenses having apparent magnifications of 2 to 4× and a decrement in acuity with lenses of 6× and greater.
- 1.2.1 Acuity also is dependent on other factors, such as the specific individual, lens quality, and the size and quality of the rear aperture (peep) used in conjunction with the lens. Beyond this statement, acuity is not the subject of this specification.
- 1.3 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

2. Terminology

- 2.1 Definitions:
- 2.1.1 apparent magnification, n—apparent increase in size of an object as viewed through the subject lens held at a specific distance from the user's eye.
- 2.1.2 *diopter*, *n*—reciprocal of the focal length of the lens as measured in metres. One diopter is the rating obtained when the constant 1 is divided by the focal length value of a lens having a 1-m focal length.
- 2.1.3 eye-to-scope distance (ETS), n—distance the (scope) lens is placed from the individual's eye when in use. If the eye-to-scope distance is measured in metres, it is specified as (ESM) and no conversion factor is required in the apparent

Current edition approved Sept. 1, 2014. Published November 2014. Originally approved in 1996. Last previous edition approved in 2010 as F1753 - 96 (2010). DOI: 10.1520/F1753-96R14.

magnification formula. When the eye-to-scope distance is measured in inches, it is designated as (ESI). To calculate apparent magnification, the metres-to-inches conversion factor of 39.37 appears in the equation.

- 2.1.4 *focal length*, *n*—distance, measured in metres, from the center of the subject lens to the point where incident plane light waves passing through the lens are brought to the sharpest possible focus.
- 2.1.5 optical magnification, n—characteristic of a particular lens defined as the reciprocal of the lens focal length as measured in metres and stated in diopters.
- 2.1.6 *peep sight, n*—rear sighting device placed in or onto the bow string, having a small opening in it that the archer peers through to view the lens or scope being used as a sighting device. The combination of the lens and rear peep sight used in this manner mimics a primitive telescope.

3. Classification

- 3.1 Optical Magnification—This is the magnifying power of a lens as measured by the reciprocal of the focal length of the lens in metres. It is expressed as a practical unit in terms of a focal length equal to one metre (the unit diopter). The larger the diopter number, the greater the magnifying power of the lens.
- 3.2 Apparent Magnification—This is the apparent increase in object size one experiences when viewing the object through one of these magnifying lenses. It is dependent on the following two factors:
- 3.2.1 The optical magnification of the scope lens as measured in diopters, and
 - 3.2.2 The distance the scope is placed from the user's eye.
- 3.3 Apparent magnification is defined empirically by the following relationship:

Apparent magnification =
$$1/(1 - D \times ESM)$$
 (1)

where:

D = lens optical magnification, diopters, and

ESM = eye-to-scope distance, m.

3.3.1 If the eye-to-scope distance is measured in inches (ESI), the relationship becomes:

Apparent magnification =
$$1/(1 - D \times ESI/39.37)$$
 (2)

¹ This specification is under the jurisdiction of ASTM Committee F08 on Sports Equipment, Playing Surfaces, and Facilities and is the direct responsibility of Subcommittee F08.16 on Archery Products.

where:

ESI = eye-to-scope distance, in., and 39.37 = metres-to-inches conversion factor.

- 3.4 Fig. 1 and Fig. 2 are graphic representations of the magnification relationship. Individually, one might prefer one chart over the other. Both charts contain the same information but display that information in a different format.
- 3.4.1 Given the optical magnification of a lens in diopters and the distance it is to be placed from the user's eye, one can determine the apparent magnification, that is, $2 \times$, $3 \times$, $4 \times$, etc.

Note 1—Fig. 3 and Fig. 4 are simply the metric versions of the charts in Fig. 1 and Fig. 2.

3.5 Classification Tolerance—The classification of lenses used in archery scopes shall be determined by measurement of their focal length in metres. These lenses shall be specified as a given diopter and will conform to that classification by having a focal length that corresponds to that diopter value within ± 3 %.

4. Significance and Use

- 4.1 This specification is intended to ensure uniform classification of the lenses and the marking of scopes to avoid confusion of the consumer, which results form the use of different classification and identification systems.
- 4.2 This specification is based on the use of the diopter that is the reciprocal of the focal length of the lens as measured in metres.

5. Product Marking

5.1 Scopes for use on archery bows shall be marked clearly and permanently with the diopter number of the lens used in that scope.

6. Keywords

6.1 archery lenses; diopter; focal length; magnifying sights; scopes




FIG. 1 Apparent Magnification of Single-Lens Scopes




FIG. 2 Apparent Magnification of Single-Lens Scopes




FIG. 3 Apparent Magnification of Single-Lens Scopes




FIG. 4 Apparent Magnification of Single-Lens Scopes

RATIONALE

A number of manufacturers of lenses and scopes used in archery recognized the need for uniformity in specifying the magnifying power of single-lens bow scopes and contacted Subcommittee F08.16 for assistance. Various lenses were obtained, tests were done to determine the actual and apparent magnification, and mathematical relationships were developed leading to the establishment of this specification.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; http://www.copyright.com/