



Standard Test Method for Treestand Static Stability and Adherence¹

This standard is issued under the fixed designation F2125; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers the determination of the static stability and adherence of treestands relative to the manufacturer's rated capacity.

1.2 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Terminology

2.1 The terminology and definitions in the referenced documents are applicable to this test method.

2.2 Definitions:

2.2.1 *backbar or V-bar*—adjustable component of a climbing treestand or handclimber that engages the tree to provide support. The backbar may be rigid or flexible.

2.2.2 *climbing stick*—device used to assist climbing a tree primarily to a fixed position treestand. A structure that is secured to the tree and allows the user to support his weight and climb to the desired height on the tree.

2.2.3 *climbing treestand*—treestand that provides both the means to ascend the tree, and allow the user to remain at a desired elevation.

2.2.4 *handclimber, or climbing aid*—device to assist climbing with a climbing treestand. A structure that allows the user to support his weight when lifting a climbing treestand with his legs.

2.2.5 *ladder treestand*—treestand that is secured to the tree at the elevation where the platform is located. (The ladder treestand may be secured to the tree at other locations and has steps that are used to reach the platform or hunting position.)

¹ This test method is under the jurisdiction of ASTM Committee F08 on Sports Equipment, Playing Surfaces, and Facilities and is the direct responsibility of Subcommittee F08.18 on Treestands.

Current edition approved Nov. 1, 2013. Published January 2014. Originally approved in 2001. Last previous edition approved in 2009 as F2125 – 09. DOI: 10.1520/F2125-09R13.

2.2.6 *non-climbing, fixed position or hang-on treestand*—treestand that is secured to the tree at the elevation where it is used. (The user usually ascends the tree by some means and then lifts the treestand to the desired position and secures it for use.)

2.2.7 *platform*—horizontal structural area of a treestand on which the user stands and/or places his feet.

2.2.8 *treestand*—device designed to be affixed to a tree or its branches so as to permit an individual to sit or stand thereon for the purpose of attaining an elevated position from which to observe, photograph or hunt.

2.2.9 *tripod or tower stand*—tripod or tower stand is constructed to be self-supporting and is not required to be secured to a tree.

3. Summary of Test Method

3.1 A climbing treestand is mounted so that its platform is perpendicular to a rigid wood or metal pole when the rated load is applied parallel to the mounting pole, at selected points. A fixed position or ladder stand shall be mounted with the platform perpendicular to the mounting pole. A tripod stand shall be positioned so that the platform is perpendicular to the application of the load. A climbing stick shall be mounted such that the steps are perpendicular to the pole. The platform is equipped with deflection measurement devices. The load is applied, in order, at the selected points and recordings are made of the deflection at each point unless the test subject moves from its initial position or until permanent deflection from the load occurs. During this test, the test subject will rotate, but shall not slip or have permanent deformation.

3.2 In addition, for climbing treestands, only the test given in 3.1 is duplicated, except that the treestand platform is not perpendicular to the mounting pole, but at an angle approximately 15°, such as that used in ascending or descending a tree.

4. Significance and Use

4.1 This test method is intended for quality assurance and production control purposes. This test method is not intended to be an independent material or product-acceptance test.

5. Apparatus

5.1 A rigid round wood or metal pole, preferably vertical, is used to mount the subject product such that pole deflection is minimized.

5.1.1 The mounting pole diameter shall be 10 ± 1 in. (254 ± 25.4 mm).

5.2 The load shall be applied using either calibrated weights or a mechanical device in conjunction with a calibrated load cell.

5.2.1 The use of calibrated weights requires that weight placement be accurate to assure that the load application centroid is coincident with the boundaries defined and meets the requirements as given in 5.3.1 and in 5.4.3. Caution should be exercised for operator protection with the use of weights in case of slippage or premature failure.

5.2.2 The use of a mechanical device such as a tensile testing machine or hydraulic power, in combination with pulleys, fulcrums or bearings to re-direct forces, requires the use of a calibrated load cell attached adjacent to the test subject to account for friction losses.

5.3 Calibrated deflection measuring devices (such as dial indicators or optical laser) shall be used to measure movement of the test subject under load. The accuracy of the measuring devices shall be at within .010 in. (0.254 mm) and repeatable within .005 in. (0.127 mm). The devices shall measure movement parallel to the direction of the applied load and shall be mounted in such a manner to eliminate deflection of the test apparatus and be placed, as a minimum, as follows:

5.3.1 There shall be at least four platform deflection measurements taken when the load is applied.

5.3.1.1 One measurement on each side of the test subject, symmetrical about the test subject centerline and at points furthest from the mounting pole, that is, the outermost corners of the platform.

5.3.1.2 One measurement on each side of the test subject, symmetrical about the test subject centerline and at points closest to the mounting pole, but on the outermost sides of the platform, that is, the outermost edges closest to the mounting pole.

5.4 The application of the load shall be at the points as given in 5.3.1 on the platform area.

5.4.1 The load shall be applied, one at a time, to the points as given in 5.3.1.1, each side, and then as given in 5.3.1.2, each side.

5.4.2 The load shall be applied to the test subject over a 50 in.² (0.032 m²) area by means of a flat rectangular steel plate 5 in. (127 mm) wide by 10 in. (254 mm) long and a minimum of $\frac{1}{2}$ in. (12.7 mm) thick. The edges of the load plate adjacent to the test subject shall be deburred with $0.015/0.030$ in. ($0.381/0.762$ mm) radius to reduce damage to the test subject by sharp corners. A single layer of thin masking tape may be applied to the surface of the load plate contacting the test subject to reduce scratching and improve friction.

NOTE 1—Load attachment structure must be secured to this load plate therefore fabrication by welding must assure that the plate remain flat and free of distortion.

5.4.3 The load plate shall be positioned on the test subject with its long axis and its center as close to the point as given in 5.3.1 as possible, yet maintaining the 50 in.² (0.032 m²) contact area. The centerline of the load plate need not be parallel to the major axis (axis of symmetry) of the test subject.

5.5 Climbing stands are to be tested at approximately 15° below level, and above level, as per manufacturer's directions.

5.5.1 Apparatus shall be as given in 5.1 through 5.3.1.2.

5.5.2 The load shall be applied as given in 5.4.2 except that the load plate shall be 100 in.² (0.065 m²) by using a 10 in.² (254 mm²) by $\frac{1}{2}$ in. (12.7 mm) thick plate.

6. Procedure

6.1 Read instructions accompanying the test subject to ascertain the proper procedure for use and mounting and secure the test subject to the mounting pole such that the platform (plane of the platform) is approximately perpendicular to the mounting pole when its rated load is applied. If necessary, use minimum auxiliary temporary means to maintain the subject in the correct position during set-up. (Frictional forces, without a load on the subject, may not be sufficient in some cases for the subject to remain in position. A small band on the mounting pole may be necessary).

6.2 By geometric means, determine the location of the load application points as given in 5.3.1 and 5.4.3 and mark accordingly.

6.3 Determine if the test subject will deflect sufficiently during the test to allow the load plate to slip or shift. If so, provide auxiliary means such as clamps or stops to eliminate sideways movement of the load plate. The load must be applied as given in 5.4 and must be continuously applied parallel to the mounting pole throughout the entire test.

6.4 Locate and mount deflection measurement devices, or reference points using optical laser, as given in 5.3.

6.5 The initial trial load for beginning the test, at the first test point only, shall be 80% of the test subjects' rated capacity. For example, a test subject with a rated capacity of 300 lb (661.4 kg) shall begin the test at a trial load of 240 lb (529.1 kg).

6.5.1 The trial load shall be applied to one of the two points as given in 5.3.1.1. Place the load plate centerline coincident with the mark as given in 5.4.3. With the initial trial (80%) load, verify that the test subject does not move (shift) from its initial static equilibrium position on the mounting pole and that deflection from the load returns to its value with no yielding. If this initial trial load verification fails, record the test as a failure to meet trial load conditions.

6.5.2 After verification of the initial trial load, perform a load test at the test subjects' rated capacity. Duplicate this test at the opposite (remaining) point as given in 5.3.1.1 and repeat for the test points given in 5.3.1.2.

6.6 At each of the four test points, the load and all deflection measurements shall be recorded. The load shall then be removed and the deflection measurements re-recorded. A note shall be made of any measurement that does not return to within 0.200 in. (5.080 mm) of the maximum measured deflection from its initial position (before loading). A note shall be made for any test point in which the test subject moves (shifts) from its initial static equilibrium position on the mounting pole.

6.7 Climbing treestands are only to be retested at: (1) approximately 15° below level, and (2) approximately 15° above level, in accordance with the manufacturer's instructions.

6.7.1 The application of the load for a standing platform only shall be at a point that is the geometric centroid of the test subject's placement area for the users' feet while ascending or descending a tree. Repeat the test procedure as given in 6.3 – 6.6 at each angle.

6.7.2 The application of the load for a sitting platform (the upper platform of a two piece stand/sit climbing treestand) shall be with a load plate as given in 5.4.2. Repeat the test procedure as given in 6.3 – 6.6 at each angle, except that only two points instead of four, specifically those given in 5.3.1.1 shall be used at each angle.

7. Report

7.1 Deflection readings shall be discarded only when a calibration change is discovered after readings have been made or when improper operator techniques can be cited.

7.2 Recording of results shall include the following:

7.2.1 Identification of test subject model, manufacturer, and rated capacity.

7.2.2 Photograph of test subject.

7.2.3 Photograph of test set-up (three views: side, top, and end).

7.2.4 Load and deflection measurements at all test points.

7.2.5 Verification of calibration.

7.2.6 Date of test.

7.2.7 If yielding or permanent deformation has been reached, or movement (shifting) has been detected as given in 6.6 or 6.7 (for climbing treestands), the corresponding load in pounds and the test point shall be noted.

7.3 *Pass-Fail Criterion:*

7.3.1 A treestand is considered failed if (after applying loads and measurements in accordance with 5.3.1) yielding or permanent deformation has been reached, or movement (shifting) has been detected as given in 6.6 or 6.7 in any section of the treestand.

7.3.2 A treestand is considered failed if (after applying loads and measurement in accordance with 5.3.1) the treestand shifts as defined in 6.6 or 6.7.

7.3.3 If a treestand fails this test, the stand and a copy of the test data shall be returned to the manufacturer.

8. Precision and Bias

8.1 No statement is made about either the precision or bias of this test method for measuring load capacity since the result merely states whether there is conformance to the criteria for success specified in the procedure.

9. Keywords

9.1 backbar; climbing aid; climbing stick; platform; treestand; tripod

APPENDIX

(Nonmandatory Information)

X1. Additional Information

X1.1 This standard is provided for use by manufacturers of treestands and testing companies. Criteria has been developed for certification of treestands and this standard is an integral part of the certification. However, a treestand conforming to

this standard alone does not constitute certification and those manufacturers desiring certification must meet all applicable standards as a minimum requirement.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; http://www.copyright.com/