



# Standard Test Method for Treestand Static Load Capacity<sup>1</sup>

This standard is issued under the fixed designation F2126; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope

1.1 This test method covers the determination of the static load capacity of treestands in terms of a factor of safety relative to the manufacturer's rated capacity.

1.2 The values stated are in inch-pound units and are to be regarded as the standard.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

## 2. Referenced Documents

2.1 *ASTM Standards*:<sup>2</sup>  
[F2531 Test Method for Load Capacity of Treestand Seats](#)

## 3. Terminology

3.1 The terminology and definitions in the referenced documents are applicable to this test method.

### 3.2 Definitions:

3.2.1 *backbar or V-bar*—adjustable component of a climbing treestand or handclimber that engages the tree to provide support. The backbar may be rigid or flexible.

3.2.2 *climbing stick*—device used to assist climbing a tree primarily to a fixed position treestand. A structure that is secured to the tree and allows the user to support his weight and climb to the desired height on the tree.

3.2.3 *climbing treestand*—treestand that provides both the means to ascend the tree, and allow the user to remain at a desired elevation.

3.2.4 *handclimber, or climbing aid*—device to assist climbing with a climbing treestand. A structure that allows the user to support his weight when lifting a climbing treestand with his legs.

3.2.5 *ladder treestand*—treestand that is secured to the tree at the elevation where the platform is located. (The ladder treestand may be secured to the tree at other locations and has steps that are used to reach the platform or hunting position.)

3.2.6 *non-climbing, fixed position or hang-on treestand*—treestand that is secured to the tree at the elevation where it is used. (The user usually ascends the tree by some means and then lifts the treestand to the desired position and secures it for use.)

3.2.7 *platform*—horizontal structural area of a treestand on which the user stands and/or places his feet.

3.2.8 *treestand*—device designed to be affixed to a tree or its branches so as to permit an individual to sit or stand thereon for the purpose of attaining an elevated position from which to observe, photograph or hunt.

3.2.9 *tripod or tower stand*—tripod or tower stand is constructed to be self-supporting and is not required to be secured to a tree.

## 4. Summary of Test Method

4.1 A climbing treestand is mounted so that its platform is perpendicular or slightly above horizontal to a rigid wood or metal pole when the rated load is applied parallel to the mounting pole. A fixed position or ladder treestand shall be mounted with the platform perpendicular to the mounting pole. A tripod stand shall be positioned so that the platform is perpendicular to the application of the load. A climbing stick shall be mounted such that the steps are perpendicular to the pole. The platform is equipped with deflection measurement devices. The load is applied step-wise and recordings are made of the load and deflection at each step until yielding or permanent deflection occurs or until twice the rated load is applied. The ladder, tripod and climbing sticks do not require deflection measurements be taken.

## 5. Significance and Use

5.1 This test method is intended for quality assurance and production control purposes.

<sup>1</sup> This test method is under the jurisdiction of ASTM Committee F08 on Sports Equipment, Playing Surfaces, and Facilities and is the direct responsibility of Subcommittee F08.18 on Treestands.

Current edition approved May 1, 2010. Published May 2010. Originally approved in 2001. Last previous edition approved in 2006 as F2126 – 06. DOI: 10.1520/F2126-06R10.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

## 6. Apparatus

6.1 A rigid round wood or metal pole, preferably vertical, is used to mount the subject product such that pole deflection is minimized.

6.1.1 The mounting pole diameter shall be 10 in. (254 mm),  $\pm$  1 in. (25.4 mm).

6.2 The load shall be applied using either calibrated weights or a mechanical device in conjunction with a calibrated load cell.

6.2.1 The use of calibrated weights requires that weight placement be accurate to assure that the load application centroid is coincident with the boundaries defined and meets the requirements as given in 6.4. Caution should be exercised for operator protection with the use of weights in case of slippage or premature failure.

6.2.2 The use of a mechanical device such as a tensile testing machine or hydraulic power, in combination with pulleys, fulcrums or bearings to re-direct forces, requires the use of a calibrated load cell attached adjacent to the test subject to account for friction losses.

6.3 Calibrated deflection measuring devices (such as dial indicators or optical laser) shall be used to measure movement of the test subject under load. The accuracy of the measuring devices shall be at within 0.010 in. (0.254 mm) and repeatable within 0.005 in. (0.127 mm). The devices shall measure movement parallel to the direction of the applied load and shall be mounted in such a manner to eliminate deflection of the test apparatus and be placed, as a minimum, as follows:

6.3.1 There shall be at least two measurements taken at the load; one on each side and 6 in. (152.4 mm) from the center of load application.

6.3.2 A deflection measurement shall be taken at two points furthest from the mounting pole, one on each side symmetrical with the test subject.

6.3.3 A deflection measurement shall be taken at two points 6 in. (152.4 mm) from the mounting pole, one on each side symmetrical with the test subject.

6.4 The application of the load shall be at the centroid of the platform area for standing platforms or the centroid of the users load application area for handclimber (climbing aids).

6.4.1 For standing platforms, the load shall be applied to the test subject over one hundred 100 in.<sup>2</sup> (0.065 m<sup>2</sup>) area by means of a flat square steel plate 10-in. (254-mm) wide and a minimum of 1/2-in. (12.7-mm) thick. The edges of the load plate adjacent to the test subject shall be de-burred with 0.015/0.030 in. (0.381/0.762 mm) radius to reduce damage to the test subject by sharp corners. A single layer of thin masking tape may be applied to the surface of the load plate contacting the test subject to reduce scratching and improve friction.

NOTE 1—Load attachment structure must be secured to this load plate therefore fabrication by welding must assure that the plate remain flat and free of distortion.

6.4.2 Handclimbers (climbing aids) shall have the load applied along the centroid of the supporting structure furthest from the test pole (which by design must be capable of directly supporting the user's weight during normal use) by means of a

4-in. (101.6-mm) wide steel plate or rigid shape of sufficient length to horizontally span the width of the test subject.

6.4.3 For two piece (stand/sit) climbing treestands with movable non-rigid seats (such as mesh, slings, or similar) that can be slid forward or backward during normal use, two additional separate tests shall be conducted on the seat. The first test shall be conducted with the load applied to the centroid of the non-rigid platform with the non-rigid platform located in its normal position, typically in the center of the supporting structure, using the square plate in accordance with 6.4.1. The second test shall be conducted with the load applied along the centroid of the supporting structure furthest from the test pole, which by design must be capable of directly supporting the user's weight during normal use. (For example, the horizontal framing member of a treestand where the user must support his or her weight during normal stand up/sit down climbing procedures.) For this second case, a rigid steel bar should be used to distribute the load over a 16-in. (406.4-mm) wide area length of the supporting structure

6.5 For fixed position treestands, the test shall be repeated with the load applied to the seat and in accordance with 6.4.1, 7.5 and 7.7. For climbing treestands in which the seat is not used during the climbing, that is, a handclimber or climbing aid is used, refer to Test Method F2531 for seat requirements.

6.6 In addition to the platform ladder, tripod and climbing sticks shall have a minimum of two steps tested for static load with the load applied over a 3-in. (76.2-mm) wide portion of the step in the center of the step, or where a foot would interface with the step.

## 7. Procedure

7.1 Read instructions accompanying the test subject to ascertain the proper procedure for use and mounting and secure the test subject to the mounting pole such that the platform (plane of the platform) is perpendicular to the mounting pole. If necessary, use minimum auxiliary temporary means to maintain the subject in the correct position during set-up. (Frictional forces, without a load on the subject, may not be sufficient in some cases for the subject to remain in position. A small band on the mounting pole may be necessary).

7.2 By geometric means, determine the location of the centroid of the platform area and mark accordingly. Place the load plate centerline coincident with the centroid of the platform.

7.3 Determine if the test subject will deflect sufficiently during the test to allow the load plate to slip or shift. If so, provide auxiliary means such as clamps or stops to eliminate sideways movement of the load plate. The load must be applied as given in 6.4 and must be continuously applied parallel to the mounting pole throughout the entire test.

7.4 Locate and mount deflection measurement devices, or reference points using optical laser, as given in 6.3.

7.5 The initial load for beginning the test shall be one-fourth of the test subjects' rated capacity. Example: a test subject with a rated capacity of 400 lbs (882 kg) shall begin the test at a load of 100 lbs (200 kg). Loads shall be increased by 25 %

increments up to the test subjects' rated capacity after which the load shall be increased to 150 %, 175 % and 200 % of the rated capacity, respectively. After the load meets or exceeds the rated capacity, it shall be returned to zero and checked for yielding.

7.6 At each load value exceeding the rated capacity (test point), the load and all deflection measurements shall be recorded. The load shall then be removed and the deflection measurements re-recorded. A note shall be made of any measurement that does not return to within 0.200 in. (5.080 mm) of its initial value. After the load is removed, all deflection measurements shall be checked, and the test subject visually inspected for permanent deformations by yielding.

7.7 The load shall incrementally increase until it is determined that (1) a factor of safety of 2.0 has been met, or (2) permanent deformation (yielding) has occurred.

## 8. Report

8.1 Deflection readings shall be discarded only when a calibration change is discovered after readings have been made or when improper operator techniques can be cited.

8.2 Recording of results shall include the following:

8.2.1 Identification of test subject model, manufacturer, and rated capacity.

8.2.2 Photograph of test subject.

8.2.3 Photograph of test set-up (three views: side, top, and end).

8.2.4 Load and deflection measurements at all test points.

8.2.5 Verification of calibration.

8.2.6 Date of test.

8.3 *Determination of Factor of Safety:*

8.3.1 When yielding or permanent deformation has been reached as given in 7.7, the corresponding load in pounds shall be noted as the yield load.

8.3.2 The factor of safety shall be calculated by dividing the manufacturer's rated capacity of the test subject into the resulting yield load. For example, rated capacity-300 lbs (661.4 kg), yield load-630 lbs (1,388.9 kg); therefore the factor of safety is 630/300 or 2.10 (usually noted as 2.10 SF).

8.3.3 The factor of safety must meet or exceed 2.0.

8.4 *Pass-Fail Criterion:*

8.4.1 A treestand is considered failed if it cannot support twice its rated load capacity without yielding or permanent deformation. The deflection measurements can be used as an indication of permanent deformation but shall not be used as pass-fail criterion.

8.4.2 If a treestand fails this test, the treestand and a copy of the test data shall be returned to the manufacturer.

## 9. Precision and Bias

9.1 No statement is made about either the precision or bias of this test method for measuring load capacity since the result merely states whether there is conformance to the criteria for success specified in the procedure.

## 10. Keywords

10.1 backbar; climbing aid; climbing stick; platform; treestand; tripod

## APPENDIX

### (Nonmandatory Information)

#### X1. Additional Information

X1.1 This test method is provided for use by manufacturers of treestands and testing companies. Criteria has been developed for certification of treestands and this test method is an integral part of the certification. However, a treestand conform-

ing to this test method alone does not constitute certification and those manufacturers desiring certification must meet all applicable standards as a minimum requirement.

*ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.*

*This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; http://www.copyright.com/*