



Standard Specification for Design and Performance Requirements for Powered Parachute Aircraft¹

This standard is issued under the fixed designation F2244; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 The following requirements apply for the manufacture of powered parachute aircraft. This specification includes design and performance requirements for powered parachute aircraft.

1.2 This specification applies to powered parachute aircraft seeking civil aviation authority approval, in the form of flight certificates, flight permits, or other like documentation.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory requirements prior to use.*

2. Referenced Documents

2.1 *ASTM Standards:*²

F2241 Specification for Continued Airworthiness System for Powered Parachute Aircraft

F2242 Specification for Production Acceptance Testing System for Powered Parachute Aircraft

F2243 Specification for Required Product Information to be Provided with Powered Parachute Aircraft

F2483 Practice for Maintenance and the Development of Maintenance Manuals for Light Sport Aircraft

F2563 Practice for Kit Assembly Instructions of Aircraft Intended Primarily for Recreation

F2972 Specification for Light Sport Aircraft Manufacturer's Quality Assurance System

3. Terminology

3.1 *Definitions:*

¹ This specification is under the jurisdiction of ASTM Committee F37 on Light Sport Aircraft and is the direct responsibility of Subcommittee F37.30 on Power Parachute.

Current edition approved Nov. 1, 2014. Published November 2014. Originally approved in 2003. Last previous edition approved in 2013 as F2244 – 13. DOI: 10.1520/F2244-14.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

3.1.1 *gross weight, n*—total aircraft system weight(s) at takeoff.

3.1.2 *maximum takeoff weight, n*—gross weight limit as defined by the manufacturer, proven through compliance with this specification and placarded on the aircraft as the not-to-exceed gross weight.

3.1.3 *powered parachute, n*—aircraft comprised of a flexible or semi-rigid wing connected to a fuselage in such a way that the wing is not in position for flight until the aircraft is in motion. That aircraft has a fuselage with seats, engine, and wheels (or floats), such that the wing and engine cannot be flown without the wheels (or floats) and seat(s). Unique to the powered parachute is the large displacement between the center of lift (high) and the center of gravity (low), which is pendulum effect. Pendulum effect limits angle of attack changes, provides stall resistance and maintains flight stability.

4. Flight

4.1 *Performance Requirements:*

4.1.1 *Proof of Compliance*—Each of the following requirements shall be met at the maximum takeoff weight and most critical center of gravity (CG) position. To the extent that CG adjustment devices may be adjusted for flight, these components will be evaluated in the least favorable recommended position as it affects either performance or structural strength.

4.1.2 *General Performance*—All performance requirements apply in and shall be corrected to International Civil Aviation Organization (ICAO) defined standard atmosphere in still air conditions at sea level. Speeds shall be given in indicated (IAS) and calibrated (CAS) airspeeds in miles per hour (MPH).

4.1.2.1 *Wing Performance*—For straight-ahead flight and turns in either direction during climb, cruise, descent, and landing flare, it shall be shown that the limits of control input are less than the wing stall limitations:

(1) If a fixed wing trim is available;

(2) If adjustable wing trim is available, it shall be tested to both the most negative and most positive trim settings; and

(3) If separate left wing and right wing trim devices are available, each shall be tested to both the maximum-left-and-minimum-right trim settings and the minimum-left-and-maximum-right trim settings.

4.1.2.2 *Climb*—The following shall be measured:

(1) Distance to clear a 15 m (50 ft) obstacle not to exceed 213 m (700 ft) from point of liftoff.

(2) *Landing*—The total landing distance over a 15 m (50 ft) obstacle shall be achieved within 183 m (600 ft) total distance.

4.1.2.3 *Controllability and Maneuverability*—The aircraft shall be safely controllable and maneuverable during takeoff, climb, level flight (cruise), approach, and landing (power off and on) with primary controls of turn and throttle and the possibility of combined turn displacement for flare.

(1) Demonstrate a smooth transition between all flight conditions shall be possible without excessive pilot skills nor exceeding pilot forces of 59.1 kg (130 lb) for the rudder pedal, 9.1 kg (20 lb) prolonged application.

(2) *Landing*—It must be shown that in the event of an engine or propeller failure that a safe descent and landing can be made. It must be shown that a pilot of normal skill can achieve landing sink rates of no more than 2.4 m/s (8 ft/s).

4.1.2.4 *Reference Parameters*—Reference velocity parameters $V(S1)$ and $V(H)$ are to be calculated as follows:

$$V(S1) = \text{square root}(W*391/S)$$

$$V(H) = 2*V(S1) = \text{square root}(4*W*391/S)$$

where:

V = mph,
 W = lbs, and
 S = ft².

4.1.3 *Stability and Control:*

4.1.3.1 *Longitudinal Stability*—Longitudinal stability of the aircraft will be demonstrated by performing two minutes of flight without control input for three conditions. In each case, the aircraft must not enter into dangerous or unusual attitudes. Test must be conducted at maximum gross weight, with minimum of in-flight turbulence.

4.1.3.2 The three conditions are:

- (1) Maximum power setting climb,
- (2) Zero power descent, and
- (3) Cruise setting power level flight.

4.1.3.3 *Lateral and Directional Stability:*

(1) Lateral stability will be demonstrated by maintaining the controls in a neutral position, which will initially give an unaccelerated level flight condition. The aircraft must not enter into a dangerous attitude during the 2 min that the flight controls are fixed. Test must be conducted at maximum takeoff weight, with minimum of in-flight turbulence

(2) Directional stability will be demonstrated by a separate and full deflection of each directional flight control for three full turns of 360° without the aircraft entering any dangerous flight attitude during the maneuver. Test must be conducted at minimum flight weight, with minimum of in-flight turbulence. The demonstrated turn rate shall not be less than 12°/s (30 s for a 360° turn) in either direction.

4.1.3.4 *Parachute Re-Inflation*—Chute re-inflation may be conducted detached from the cage, or on a suitable test apparatus.

(1) *Ground Roll Chute Collapse*—The chute manufacturer shall demonstrate techniques that recover tip and wing collapse conditions as documented in the Aircraft Operating Instructions.

(2) *In-Flight Collapse*—At least one type of in-flight chute collapse and recovery shall be demonstrated.

5. Structure

5.1 *Loads*—Unless otherwise specified, all requirements are specified in terms of limit load.

5.1.1 Ultimate loads are limit loads multiplied by the factor of safety defined below.

5.1.1.1 Loads shall be redistributed if the deformations affect them significantly.

5.1.2 *Factors of Safety*—The factor of safety is 1.5, except as shown in the following:

5.1.2.1 3.0 on castings,

5.1.2.2 1.8 on fittings,

5.1.2.3 6.67 on control surface hinges,

5.1.2.4 3.3 on push-pull control systems, and

5.1.2.5 2.0 on cable control systems.

5.1.3 *Strength and Deformation:*

5.1.3.1 The structure must be able to support limit loads without permanent deformation of the structure.

5.1.3.2 The structure must be shown by analysis, test or analysis supported by test, to be able to withstand ultimate loads without failure.

5.1.3.3 The structure shall be able to withstand ultimate loads for 3 s without failure when proof is by static test. When dynamic tests are used to demonstrate strength, the three-second requirement does not apply. Local failures or structural instabilities between limit load and ultimate load are acceptable if the structure can sustain the required ultimate load for three seconds.

5.2 *Proof of Structure*—Each critical load requirement shall be investigated either by conservative analysis or tests, or a combination of both.

5.2.1 *Proof of Strength-Wings*—Test the wing design for a powered parachute aircraft to verify the critical ultimate loads. The wing designer shall provide the wing and risers design load capability to the point of attachment of the risers. The wing designer shall provide the factor of safety demonstrated in wing and riser tests to the fuselage designer.

NOTE 1—Advisory information—Wing designer information provided to the fuselage designer shall be known as “pass-through” information.

5.2.2 *Load Factor:*

5.2.2.1 *Positive*— $n = 2.25$ (comprised of a 1.5 maneuvering load multiplied by a 1.5 gust load factor). The maneuvering load must be increased for any conditions for which the following equation indicates a g loading higher than 1.5 g's. The calculated g load shall then be used as the maneuvering load. Maneuvering Load Factor: $N = 1/\cos(B)$, where $B = \arctan(RT \times V/1255)$, where RT is turning rate in degrees per second, and V is true airspeed in mph. For example, $V = 26$ mph, $RT = 60^\circ/s$ (360° turn in 6 s), $N = 1.595$. $N > 1.5$ and the maneuvering load factor rises to 1.595. As a result, the limit load is $1.5 \times 1.595 = 2.393$ gs. See Fig. 1 for a reference graph.

5.2.2.2 *Negative*— $n = 0$.

5.2.3 *Fuselage Loads*—The airframe must be capable of supporting all lifting forces created by the parachute, any propulsive device, systems, persons, and landing loads.




FIG. 1 Reference Graph

5.2.4 *Control Surface Loads*—Control surface loads on a powered parachute are related through the turn lines and shall be evaluated at loads defined in flight tests of the wing by the wing manufacturer.

5.2.5 *Ground Gust Conditions*—A powered parachute wing is not inflated for normal ground conditions. As a result, classical ground gust load concerns do not exist. Rolling gust loads for takeoff or landing are considered as part of the landing ground load conditions.

5.2.6 *Control System and Supporting Structure*—The control system structure shall be designed to withstand maximum forces and in the case of dual controls the relevant system shall be designed for the pilots operating in opposition, if greater than the control system forces.

5.2.7 *Ground Load Conditions*—Design features shall limit the landing sink rate to less than, or equal to, 3 m/s (10 ft/s). Testing by drop test will use a drop height to achieve a 3 m/s (10 ft/s) drop rate in a nose high simulation of flare. This will be a “dead drop” test at maximum takeoff weight.

5.2.8 *Nose Wheel Conditions*—A 2.25 times maximum loaded static load vertical in each case with 1.8 times maximum static load applied at the axle acting aft, or 0.9 times maximum static load at the axle acting forward, or 1.57 times maximum static load acting at the surface as a side load. Where maximum static load is the vertical load on the nose wheel at maximum takeoff weight and the related forward most CG.

5.2.9 *Emergency Landing Conditions*—Design structure to protect each occupant from serious injury when the aircraft experiences three independent ultimate load conditions: 1.5-g’s upward; 6-g’s forward; 3-g’s sideward. Test articles that hold this load for more than 3 s are considered to have passed.

NOTE 2—Advisory Information—(1) Occupants restrained by available safety harnesses. (2) Consider all items of mass behind, above, below, and

lateral to the occupants (engine, baggage, fuel, ballast, and so forth). (3) The design must have design features to protect an occupant or occupants in the event of a turnover.

6. Design and Construction

6.1 *General*—The integrity of any novel or unusual design feature having an important bearing on safety shall be established by a test.

6.2 *Materials and Workmanship*—Materials shall be suitable and durable for the intended use and design values (strength) must be chosen so that structural under strength because of material variations is unlikely as shown by test, analysis, service history or manufacturer certification.

6.2.1 Fabrication Methods:

6.2.1.1 Workmanship of manufactured parts, assemblies, and aircraft shall be of high standard.

6.2.1.2 Methods of fabrication shall produce consistently sound structures.

6.2.1.3 Process specifications shall be followed where required.

6.2.2 *Protection of Structure*—Protection of the structure against weathering, corrosion, and abrasion, as well as suitable ventilation and drainage shall be provided.

6.2.3 *Accessibility*—Accessibility for principal structural and control system inspection, adjustment, maintenance, and repair shall be provided.

6.2.4 *Control Systems-Operation Tests*—It must be shown by functional test that the control system is free from jamming, excessive friction, or excessive deflection when the maximum pilot forces are applied from the cockpit.

6.2.5 *Pilot Compartment*—Pilot comfort, good visibility (instruments, placards and outside), accessibility, exit, and ability to reach all controls for smooth and positive operation shall be provided.

7. Power Plant

7.1 The power plant installation shall be easily accessible for inspection and maintenance.

7.2 *Engine*—A FAA type certificate is not required for a powered parachute aircraft engine. Engine installation and testing shall demonstrate operation and reliability consistent with industry-accepted practices.

NOTE 3—Advisory Information—Powered parachutes are light low speed aircraft with excellent short field landing capabilities. The craft are not intended for flight in airspace in which safety depends on continued engine operation. The engine is not considered to be a safety-of-flight component.

7.3 *Fuel Tank Tests*—The fuel tank shall be pressure tested to 24.1 kPa (3.5 psi) (2.4 m (8 ft) of water column) and installed to withstand prescribed load factors.

7.4 *Fuel Tank Vents*—A fuel tank vent that does not siphon in flight shall be provided. The fuel vent system does not siphon in the event of roll over.

7.5 *Fuel Strainer or Filter*—A replaceable fuel filter, accessible for drainage and cleaning, or both, shall be included in the system.

8. Equipment

8.1 *Instruments*—An airspeed indicator is not a required instrument. Required instruments include:

- 8.1.1 A fuel quantity indicator,
- 8.1.2 An engine kill switch, and
- 8.1.3 Engine instruments identified as necessary by the engine designer or manufacturer.

NOTE 4—Advisory Information—(1) Powered parachute aircraft are limited to a very small and low velocity speed range. An airspeed indicator is of negligible use on these aircraft. (2) Some acceptable fuel quantity indicators include: a) a sight tube, and b) a translucent fuel tank.

8.2 *Occupant Safety Restraint Systems*—Occupant safety restraint systems of a minimum three point attach or better, shall be available for each occupant and their attachments to the aircraft, when used as instructed by the designer and manufacturer, shall be designed for the appropriate load factors. See 5.2.9.

9. Operating Limitations

9.1 *General*—The operating limitations and other information necessary for safe operation shall be established and made available to the pilot upon aircraft delivery.

9.2 *Weight and Center of Gravity*—Weight and center of gravity limitations shall be provided, including reference and leveling data.

9.3 *Power Plant*—Power plant limitations shall be provided.

10. Keywords

10.1 light sport aircraft; powered parachute aircraft; special airworthiness certificates

ANNEX

(Mandatory Information)

A1. Requirements

A1.1 Manufacturing Quality Assurance requirements are defined in Specification F2972.

A1.2 Continued Airworthiness requirements are defined under a separate Specification F2241.

A1.3 Aircraft Manual (Aircraft Operating Instructions) requirements, which include a flight training manual showing the model specific training issues necessary for transition from general powered parachute training to the model specific information necessary for safe flight, are defined under Specification F2242.

A1.4 Final Production Acceptance Requirements are provided under Specification F2243.

A1.5 Standard Practice for Maintenance and the Development of Maintenance Manuals for Light Sport Aircraft F2483.

A1.6 Standard Practice for Kit Assembly Instructions of Aircraft Intended Primarily for Recreation F2563.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; <http://www.copyright.com/>