



Standard Consumer Safety Specification for Non-Powered Scooters¹

This standard is issued under the fixed designation F2264; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

INTRODUCTION

This consumer safety performance specification addresses scooter incidents that were identified by the Consumer Product Safety Commission (CPSC). With the recent introduction and popularity of new lightweight scooters, related injuries to children less than 15 years old have dramatically increased. The purpose of this consumer safety specification is to establish nationally recognized safety requirements for nonpowered scooters.

1. Scope

1.1 This consumer safety specification covers establishment of performance requirements, test methods, and labeling requirements to minimize the hazards to users of scooters as identified in the introduction.

1.2 This specification is intended to cover use of this product for children ages 5 years and older.

1.3 No scooter produced after the approval date of this specification shall, either by label or other means, indicate compliance with this specification unless it conforms to all requirements herein.

1.4 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

1.5 The following precautionary caveat pertains only to the test method portion, Section 7, of this consumer safety specification: *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Referenced Documents

2.1 ASTM Standards:²

[D3359 Test Methods for Measuring Adhesion by Tape Test](#)

¹ This specification is under the jurisdiction of ASTM Committee F15 on Consumer Products and is the direct responsibility of Subcommittee F15.52 on Scooters.

Current edition approved June 1, 2014. Published June 2014. Originally approved in 2003. Last previous edition approved in 2009 as F2264 – 09a. DOI: 10.1520/F2264-14.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

2.2 Federal Standards:

[16 CFR-1303 Ban of Lead-Containing Paint and Certain Consumer Products Bearing Lead-Containing Paint](#)

[16 CFR-1500 Hazardous Substances Act Regulations, including sections:](#)

[1500.48 Technical Requirements for Determining a Sharp Point in Toys or Other Articles Intended for Use by Children Under Eight Years of Age](#)

[1500.49 Technical Requirements for Determining a Sharp Metal or Glass Edge in Toys or Other Articles Intended for Use by Children Under Eight Years of Age](#)

[1500.50-53 Tests Methods for Simulating Use and Abuse of Toys and Other Articles Intended for Use by Children](#)

3. Terminology

3.1 Definitions of Terms Specific to This Standard:

3.1.1 *conspicuous, adj*—a label that is visible when the unit is assembled.

3.1.2 *deck, n*—the generally low horizontal platform on a scooter upon which the user places one or both feet.

3.1.3 *dynamic load, n*—force applied to an item by means of motion or impact.

3.1.4 *manufacturer's recommended use position, n*—any position that is presented as a normal, allowable, or acceptable configuration for use of the product by the manufacturer in any descriptive or instructional literature. This specifically excludes conditions such as when the scooter is unassembled (completely or partially) or folded, and positions that the manufacturer shows or explains as being unacceptable, unsafe, or not recommended.

3.1.5 *protective components, n*—specific items added to a product with the primary purpose of reducing a hazard such as sharp edges, entrapment holes, protrusions, etc.; normally these components cover or shield the area of the hazard.

3.1.6 *scooter, n*—a vehicle that has two or more wheels, a low platform, a vertical element for the user to grasp, and a method of steering and is propelled by the user pushing one foot against the ground with the other foot resting on the platform.

3.1.7 *static load, n*—a vertically downward load applied by a dead weight or other means.

4. General Testing Requirements

4.1 The unit shall be completely assembled, unless otherwise noted, in accordance with the manufacturer's instructions.

4.2 The product to be tested shall be in a room with an ambient temperature of $73 \pm 9^\circ\text{F}$ ($23 \pm 5^\circ\text{C}$) for at least 1 h prior to testing. Testing shall then be conducted within this temperature range unless a test specifically requires another temperature.

4.3 All testing required by this specification shall be conducted on the same unit unless otherwise specified (see 7.1).

5. General Requirements

5.1 The unit shall conform to the federal regulations specified in 2.2 of this specification both before and after all testing.

5.2 Prior to testing, any exposed parts shall be smooth and free of splinters, spurs, and burrs.

5.3 *Latching Mechanisms*—Any unit that folds shall have a latching device or other provision in the design that will prevent the unit from unintentional folding when properly placed in the manufacturer's recommended use position. Products with latching devices for prevention of unintentional folding shall be tested in accordance with 7.9. During and upon completion of this test, the unit shall remain latched in its manufacturer's recommended use position.

5.4 *Folding Mechanisms, Hinges, and Clearances*—This requirement is intended to eliminate possible crushing, laceration, or pinching hazards that might occur in folding mechanisms and hinges. Examples are the motion of a hinge that produces a scissor action and the changing clearances at the hinge line between two hinged portions, such that the gap will admit fingers at one position of the hinge but not at all positions. This requirement is also intended to eliminate possible hazards that may be caused by changing clearances. The different pinch clearance requirements listed reflect the different modes of entrapment or pinching that may be encountered. Scooters shall meet these requirements after they are tested in accordance with Section 7.

5.4.1 *Hinge-Line Clearance*—Scooters having a gap or clearance along the hinge line between a stationary portion and a moveable portion that weighs more than $\frac{1}{2}$ lb (0.2 kg) shall be so constructed that, if the accessible gap at the hinge line will admit a $\frac{3}{16}$ -in. (5-mm) diameter rod, it will also admit a $\frac{1}{2}$ -in. (13-mm)-diameter rod at all positions of the hinge.

5.4.2 *Accessible Clearances for Moveable Segments*—This requirement concerns clearances between movable segments on scooters intended for children, where the potential for pinching or crushing fingers or other appendages exists. It includes, but is not limited to, wheels and rigid-wheel wells, fenders, or the radial clearance between the wheels and chassis

of scooters. If such accessible clearances admit a $\frac{3}{16}$ -in. (5-mm) diameter rod, they shall also admit a $\frac{1}{2}$ -in. (13-mm) diameter rod in order to prevent the trapping of fingers.

5.4.3 *Inaccessibility of Mechanisms*—Mechanisms in scooters shall not have any accessible part of the mechanism present a pinch or laceration hazard.

5.5 *Labeling*—Warning labels or warnings applied directly onto the surface of the product shall be permanent when tested in accordance with 7.10.

6. Performance Requirements

6.1 All components specified under Test Methods 7.1 – 7.7 shall not show any evidence of material separation, visible cracking, or component failure that presents a hazard to the user. Permanent deformation of the scooter deck shall be allowed after the test, provided there is no contact with the ground by any structural or rigid component when the scooter is stood upright, resting on all wheels with the steering in the forward direction.

6.2 *Brakes (for Scooters with Brakes)*—The braking system (hand or foot operated) shall prevent the scooter's wheel from rotating more than $\frac{1}{4}$ revolution when tested in accordance with 7.8.

7. Test Methods

7.1 If, during the course of conducting the test methods in this safety specification, a test sample suffers any permanent deformation or damage, an additional test sample of the same model shall be used for the remainder of the test methods.

7.2 Deck Test:

7.2.1 Apply a static load of three times the manufacturer's maximum specified weight limit, or 600 lb (273 kg) if there is no maximum specified weight limit, to a nominal 6 by 6 by 2-in. (15 by 15 by 5-cm) wooden block centered between the front and rear axles of the scooter and centered axially. The load shall be applied for a period of 5 min.

7.3 Handle/Stem Compression Test:

7.3.1 Close the handle bar/stem adjustment lock in the uppermost position according to the manufacturer's instructions. If a quick release mechanism is used (that is, no tools required), the maximum force used to close the quick release shall not exceed 15 lbf (67 N) when applied to a point $\frac{1}{4}$ in. (6 mm) from the end of the lever.

7.3.2 Apply a static 100-lb (45-kg) load in compression to the center top of the handlebar gradually over a period of 5 s and maintain for 10 s.

7.4 Handle/Stem Fatigue Test:

7.4.1 Secure the deck of the scooter so that it cannot move and the front wheel so that it cannot rotate about its steering axis.

7.4.2 Apply a 60-lb (267 N) total force 1 in. (2.5 cm) from the ends of both hand grips in the upward/rearward direction, 45° from vertical, then in the opposite (downward/forward) direction.

7.4.3 Repeat 7.4.2 for 5000 cycles, not to exceed 1 cycle per second.

7.5 *Grip Retention Test/Handle Retention Test*—Apply a 15-lbf (67 N) to the grips along the axis of the handlebar gradually over a period of 5 s and maintain for 10 s.

7.6 *Curb Impact Test:*

7.6.1 A scooter shall be impacted in the forward direction onto the front wheel with an energy of 135 J and an impact velocity of 10 ± 1 mph (4.5 ± 0.5 m/s).

7.6.2 The type of suspension shall ensure that the energy is absorbed by the front wheel of the scooter.

7.7 *Dynamic Strength Test:*

7.7.1 A 44 lb (20 kg) mass shall consist of a 6.0 in. (15.2 cm) diameter bag filled with steel shot.

7.7.2 Drop the mass onto the center of the deck surface from a height of 2.0 ft (0.6 m) from the deck surface.

7.7.3 Repeat 7.7.2 for a total of three times.

7.8 *Brake Test:*

7.8.1 *Hand Brakes:*

7.8.1.1 Place the scooter on a smooth surface inclined 10° to the horizontal plane.

7.8.1.2 Apply a 110-lb (50-kg) static load to the deck of the scooter. The load shall be applied to the center of the deck with the major axis perpendicular to the true horizontal.

7.8.1.3 Apply a force of 15 lbf (67 N) to the hand-braking lever with the lever adjusted in accordance with the manufacturer's recommended use position.

NOTE 1—15 lb is based on gripping strength of a 5-year-old.

7.8.1.4 Observe and record any movement.

7.8.2 *Foot Brakes:*

7.8.2.1 Place the scooter on a smooth surface inclined 10° to the horizontal plane.

7.8.2.2 Apply a static load of 30 lb (14 kg) to the deck of the scooter. The load shall be applied to the center of the deck with the major axis perpendicular to the true horizontal.

7.8.2.3 Apply a static load of 18 lb (8 kg) to the foot brake.

7.8.2.4 Observe and record any movement.

7.8.2.5 Repeat steps 7.8.2.1 – 7.8.2.4 with a 150-lb (68-kg) static load to the deck and a 90-lb (41-kg) static load to the foot brake.

NOTE 2—The deck forces represent a 5th-percentile 5-year-old and a 95th-percentile 14-year-old, respectively; the brake forces represent 60 % of the deck weight to simulate the shift in the rider's weight required to apply the brakes.

7.9 *Latching Mechanisms for Prevention of Unintentional Folding:*

7.9.1 Erect the product in accordance with the manufacturer's instructions.

7.9.2 Place the product in the manufacturer's recommended use position so that the normal folding motion is not impeded.

7.9.3 Apply a force of 200 lbf (880 N) at the location normally associated with the folding action and in the direction normally associated with folding the product in accordance with the manufacturer's instructions. Gradually apply the force within 5 s and maintain for an additional 10 s. Do not apply this force to the latching or unlatching means itself.

7.9.4 Repeat 7.9.3 for a total of five times within 2 min.

7.9.5 Fold the unit in accordance with the manufacturer's instructions and repeat 7.9.1 – 7.9.3 one additional time.

7.10 *Test Method for Warning Labels:*

7.10.1 A label shall be considered permanent if, during an attempt to remove it without the aid of tools or solvents, it cannot be removed, it tears into pieces upon removal, or such action damages the surface to which it is attached.

7.10.2 *Adhesion Test Method for Warnings Applied Directly to the Surface of the Product:*

7.10.2.1 Apply the tape test method defined in Test Method B of Test Methods D3359 eliminating the parallel cuts.

7.10.2.2 Perform this test method once in each different location where warnings are applied.

7.10.2.3 The warning statements will be considered permanent if the printing in the area tested is still legible and attached after being subjected to this test.

8. Marking and Labeling

8.1 Each product and its retail carton shall be marked clearly and legibly to indicate the following:

8.1.1 Name and place (city, state, and mailing address, including zip code) of business, manufacturer, importer, distributor, or seller.

8.1.2 Model number, stock number, catalog number, item number, or other symbol expressed numerically, or otherwise.

8.2 Code mark or other means that identifies the date (month and year at a minimum) manufactured shall be on the product.

8.3 Each product shall have warning statements. The warning statements shall be in contrasting color(s), permanent, conspicuous, and in sans serif style font.

8.3.1 In warning statements, the safety alert symbol “ Δ ” and the word “**WARNING**” shall not be less than 0.2 in. (5 mm) high. The remainder of the text shall be characters whose upper case shall be at least 0.1 in. (2.5 mm) high except as specified.

8.3.2 The product warning statements shall, at a minimum, address the following concerns:

8.3.2.1 Use of safety equipment (for example, helmet, knee pads, elbow pads).

9. Instructional Literature

9.1 Instructions shall be provided with the scooter, whether on the package or on a separate document, within the package. The instructions shall include information on assembly, maintenance, operation (including folding), and warnings.

9.2 Statements shall address the following items:

9.2.1 The appropriate age of the user.

9.2.2 The weight limit of the user.

9.2.3 Always wear safety equipment such as helmet, knee pads and elbow pads. Always wear a helmet when riding your scooter and keep the chinstrap securely buckled. Always wear shoes.

9.2.4 Ride on smooth, paved surfaces away from motor vehicles.

9.2.5 Avoid sharp bumps, drainage grates, and sudden surface changes. Scooter may suddenly stop.

9.2.6 Avoid streets and surfaces with water, sand, gravel, dirt, leaves, and other debris. Wet weather impairs traction, braking, and visibility.

9.2.7 Do not ride at night.

9.2.8 Brake will get hot from continuous use. Do not touch after braking.

9.2.9 Avoid excessive speed associated with downhill rides.

9.2.10 Adults must assist children in the initial adjustment procedures to unfold scooter, adjust handlebar and steering to height, and finally to fold scooter.

9.2.11 Obey all local traffic and scooter riding laws and regulations.

9.2.12 Watch out for pedestrians.

9.2.13 Check and secure all fasteners before every ride.

9.2.14 Replace worn or broken parts immediately.

10. Keywords

10.1 children; safety; scooter

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the ASTM website (www.astm.org/COPYRIGHT/).