



Standard Guide for Selection of Airborne Remote Sensing Systems for Detection and Monitoring of Oil on Water¹

This standard is issued under the fixed designation F2327; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This guide provides information and criteria for selection of remote sensing systems for the detection and monitoring of oil on water.

1.2 This guide applies to the remote sensing of oil-on-water involving a variety of sensing devices used alone or in combination. The sensors may be mounted on vessels, in helicopters, fixed-wing aircraft, unmanned aerial vehicles (UAVs), or aerostats. Excluded are situations where the aircraft is used solely as a telemetry or visual observation platform and exo-atmosphere or satellite systems.

1.3 The context of sensor use is addressed to the extent it has a bearing on their selection and utility for certain missions or objectives.

1.4 This guide is generally applicable for all types of crude oils and most petroleum products, under a variety of marine or fresh water situations.

1.5 Many sensors exhibit limitations with respect to discriminating the target substances under certain states of weathering, lighting, wind and sea, or in certain settings.

1.6 This guide gives information for evaluating the capability of a remote surveillance technology to locate, determine the areal extent, as well as measure or approximate certain other characteristics of oil spilled upon water.

1.7 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.8 Remote sensing of oil-on-water involves a number of safety issues associated with the modification of aircraft and their operation, particularly at low altitudes. Also, in some instances, hazardous materials or conditions (for example, certain gases, high voltages, etc.) can be involved. *This standard does not purport to address all of the safety concerns,*

if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory requirements prior to use.

2. Significance and Use

2.1 The contributions that an effective remote sensing system can make are:

- 2.1.1 Provide a strategic picture of the overall spill,
- 2.1.2 Assist in detection of slicks when they are not visible by persons operating at, or near, the water's surface or at night,
- 2.1.3 Provide location of slicks containing the most oil,
- 2.1.4 Provide input for the operational deployment of equipment,
- 2.1.5 Extend the hours of clean-up operations to include darkness and poor visibility,
- 2.1.6 Identify oceanographic and geographic features toward which the oil may migrate,
- 2.1.7 Locate unreported oil-on-water,
- 2.1.8 Collect evidence linking oil-on-water to its source,
- 2.1.9 Help reduce the time and effort for long range planning,
- 2.1.10 A log, or time history, of the spill can be compiled from successive data runs, and
- 2.1.11 A source of initial input for predictive models and for "truthing" or updating them over time.

3. Remote Sensing Equipment Capabilities and Limitations

3.1 The capability of remote sensing equipment is, in large measure, determined by the physical and chemical properties of the atmosphere, the water, and the target oil. There may be variations in the degree of sophistication, sensitivity, and spatial resolution of sensors using the same portion of the electromagnetic spectrum and detector technology. Sensors within a given class tend to have the same general capabilities and typically suffer from the same limitations.

3.2 Combinations of sensors offer broader spectral coverage which, in turn, permit better probability of detection, better discrimination, and effective operation over a broader range of weather and lighting conditions. Certain combinations, or

¹ This guide is under the jurisdiction of ASTM Committee F20 on Hazardous Substances and Oil Spill Response and is the direct responsibility of Subcommittee F20.16 on Surveillance and Tracking.

Current edition approved Oct. 1, 2015. Published November 2015. Originally approved in 2003. Last previous edition approved in 2008 as F2327 – 08. DOI: 10.1520/F2327-15.

sensor suites, are well documented, and their use is particularly suited to oil spill response missions.

3.3 The performance of virtually all sensors can be enhanced by a variety of real-time, near real-time or post processing techniques applied to the acquired data or imagery. Furthermore, image or data fusion can greatly enhance the utility of the remote sensing output or product. Similarly, there exists a variety of technological considerations and organizational ramifications that relate to the delivery of the remote sensing information to the user.

3.4 Certain parameters need to be identified and quantified to provide an oil spill response decision-maker with all of the information needed to best respond to a spill. These are:

3.4.1 Location—of the approximate center and edges of the spill,

3.4.2 Geometry—source or origin, total area, orientation and lengths of major and minor axes, fragmentation, and distribution,

3.4.3 Physical conditions—oil appearance, entrained debris,

3.4.4 Environmental conditions—wave height and direction; water temperature; position of oceanic fronts, convergence and divergence zones,

3.4.5 Proximity of threatened resources, and

3.4.6 Location of response equipment.

3.4.7 Thickness or relative thickness of the slick.

3.5 Remote sensing can contribute to all of the above data needs. Depending on the spill situation and the employment of remote sensing, some of this information may already be available, or can be determined more cost effectively by other means. For example, in a response mode, or tactical employment of remote sensing, it is likely that the source, general location and type of oil have been reported well in advance of the launch of the remote sensing platform. In a regulatory or patrol context, this information may not be available. The spill situation influences the priorities among the elements of information and, thereby, influences the selection priorities for sensors.

3.6 A responder may require the data on an oil spill, 24 hours per day, independent of the prevailing weather.

3.7 Information from remote sensing is required in a timely manner. Strategic or enforcement information, such as the overall extent and location of a spill, should be available preferably within two to four hours from information gathering to presentation.

3.8 Tactical information, such as steering information for response vessels, should be available in as little as five minutes from detection to communication. The acceptable data delivery time is a function of the dynamics of the slick, proximity to critical areas, and the availability of clean-up resources.

3.9 Thermal imaging may provide relative thickness information useful to oil spill countermeasures, that is information that the slick is thicker than sheen.

3.10 The passive microwave sensor is currently available to give information on oil thickness.

3.11 **Table 1** lists sensors based upon their mode of operation. Summary information on their advantages and disadvantages is presented.

3.12 **Table 2** presents a summary of key attributes which generally influence the selection of remote sensing instrumentation.

3.13 **Table 3** addresses the mission specific aspects of sensor selection.

4. Summary

4.1 The information presented in this guide should be considered a starting point for sensor selection. In addition to the context of use and the attributes of the various types of sensors, the system planner will have to give due consideration to the capabilities of the aircraft and the information needs of the users before finalizing the system design. Both sensor technology, and image and data analysis capabilities are evolving rapidly. Some equipment is not commercially-available and requires assembly and in some cases requires development. Up to two years lead time may be required for some equipment.

TABLE 1 Sensor Characteristics

Sensor/ Band	Principal of Operation	Positive Features	Limitations
Visual	Operate in, and near, the (human) visible spectrum (400 to 750 nm). Using photographic films, scanners with one or more narrow band detectors or charge coupled devices (CCD) to capture an image.	Equipment is widely available, generally inexpensive, light and easily accommodated on most any aerial platform. Imagery is in every-day use and the layman can easily relate to its content. This characteristic makes the imagery an excellent base for recording and presenting other data.	Oil is generally perceptible over the entire visible spectrum, but not uniquely so. As such, instances of not being able to discriminate the oil from its background, or differentiate it from other substances or phenomena in or on the water's surface, lead to frequent non-detects and false positives. Night vision cameras may extend the operational window, but visual technologies are limited by available light.
Infrared	While the infrared (IR) spectrum ranges from 750 nm to 1 mm, the bulk of the available remote sensing systems operate in the thermal or mid-IR, 3 μm (3000 nm) to 30 μm (30 000 nm). Within this range there are two predominant sub-groups operating at 3 to 5 μm and 8 to 12 or 14 μm . The latter range offers the most useful data for oil spills.	Fresh oil shows a contrast to open water in the thermal infrared. This characteristic is not unique to hydrocarbons. Slicks thicker than about 20 to 70 μm^A can be seen. Newer IR cameras have excellent thermal discrimination, fairly good resolution, are light-weight, have modest power demands, and typically have both digital and video outputs.	Sheen may not be detectable. Other heterogeneities such as high seaweed or debris content, oil in or on ice, oil on beaches, etc. may render the oil undetectable in the IR.
Ultraviolet	Oil is highly reflective in the ultraviolet (UV–200 to 400 nm).	Very thin (<10 nm) layers of oil can be detected in the UV. ^B Thus, even sheen, a common regulatory definition of oil pollution, can be delineated. UV cameras have fairly good resolution, are light-weight and have minimal power demands.	High UV reflectance is not unique to oil. Sun glint, biogenic and other materials and phenomena can yield strong returns in the UV. This technology is limited to available light situations, and is best used in combination with other sensors, typically IR.
Radar	Oil has a damping effect on high frequency, low amplitude (1 to 10 cm) capillary waves. These waves, yielding a "rougher" surface, return considerably more radar energy to the receiver than calm water. As such, under the proper conditions, oil can appear as a low return, dark area in a larger, bright field of un-oiled waves. Specially tuned Side Looking Airborne Radar (SLAR) and Synthetic Aperture Radar (SAR) are two types suited to oil detection. Ship-borne radars can be optimized to detect oil slicks.	Radar has some unique advantages over other oil spill sensors: it can operate day or night; it can operate in times of reduced visibility; it can operate at higher, safer and more fuel-efficient altitudes. Typical ranges are 10 to 50 km. Ship-mounted radars have a range of typically 25 km.	Oil is not the only source of calms. Other, naturally occurring substances and phenomena can give rise to smooth water. ^C If the prevailing wind is less than about 1.5 m/s, there will not be enough "roughness" in oiled water to create the necessary roughness contrast. Likewise, above about 6 m/s the calming effect of, at least thin, oil begins to diminish. ^D The potential for false positives is high. Airborne radar equipment is expensive and it requires fairly extensive modifications to an aircraft, thus adding to both the acquisition and the operational costs.
Microwave Radiometer	Oil is a stronger emitter of microwave radiation than water (emissivity factor of 0.8 versus 0.4, respectively). ^E Therefore it shows up as a bright area against a darker background.	The passive microwave radiometer has been demonstrated to detect oil on water even under low visibility conditions.	The technology is subject to the same limitations as radar. This is an evolving technique requiring additional development and demonstration before a commercial unit is marketable. Current units are installed in dedicated aircraft and this trend is likely to continue in the near term.
Fluoro-sensors	Oil targeted or illuminated with UV light will adsorb this energy and re-emit, or fluoresce, in the visible band. Other materials fluoresce as well, but there is enough spectral uniqueness to oil to render it readily discernable. In fact it is possible that various generic types of oil and petroleum products can be differentiated. The coherent light from a laser permits the delivery of more energy from greater distances making an airborne fluorosensors feasible.	The laser fluorosensor permits the positive identification of oil and even permits some discrimination between types of oil. It appears to be the only sensor available today that permits the detection of oil against complex backgrounds as is the case with oil on beaches and in, or with, the ice.	Laser fluorosensors are fairly bulky and require significant modifications to relatively large, dedicated aircraft. Laser fluorosensors require flights as low as 1000 feet (300 m) to provide sufficient illumination by the laser. Non-scanning instruments provide only a narrow footprint of data.

^A Fingas, M. F. and Brown, C., "Review of Oil Spill Remote Sensing" Marine Pollution Bulletin, (83), 1, pp. 9–23, 2014.

^B Fingas, M. F. and Brown, C. E., "An Update on Oil Spill Remote Sensors," in *Proceedings of the Twenty-eighth Arctic and Marine Oil Spill Program Technical Seminar*, Environment Canada, Ottawa, Ontario, 2005, pp. 825–860.

^C Frysinger, G. S., Asher, W. E., Korenowski, G. M., Barger, W. R., Klusty, M. A., Frew, N. M., and Nelson, R. K., "Study of Ocean Slicks by Nonlinear Laser Processes in Second Harmonic Generation," *Journal of Geophysical Research*, 1992.

^D Wisman, V., Alpers, W., Theis, R., and Hühnerfuss, H., "The Damping of Short Gravity-Capillary Waves by Monomolecular Sea Slicks Measured by Airborne Multi-frequency Radars," *Journal of Geophysical Research*, 1993.

^E Ulbay, F. T., Moore, R. K., and Fung, A. K., *Microwave Remote Sensing: Active and Passive*, ArchtHous, Inc., 1989.

TABLE 2 Key Attributes for Sensor Selection^A

Sensor	State of Development	Experience in Use ^B	Specific to Oil	Immunity to False Targets	Acquisition Cost Range k\$	Special Aircraft Requirements ^C
Still Camera—Film	High	High	Low	Low	0.25 to 5	no
Still Camera—CCD	High	High	Low	Low	1 to 20	no
Video	High	High	Low	Low	1-10	no
IR Camera (3 to 5 µm)	High	Medium	Low	Low	4 to 40	no
IR Camera (8 to 14 µm)	Medium	Medium	Medium	Medium	20 to 200	no
UV Camera	Medium	Medium	Low	Low	4 to 20	no
Multi-spectral Scanner	Medium	Medium	Low	Low	100 to 300	some
Radar	High	High	Medium	Low	2000 to 6000	yes-Dedicated
Microwave Radiometer	Medium	Medium	Medium	Medium	400 to 2000	yes-Dedicated
Laser Fluorosensor	Medium	Low	High	High	300 to 2000	yes-Dedicated

^A Information presented in this table was adapted from: Fingas, M. F. and Brown, C. E., "An Update on Oil Spill Remote Sensors," in *Proceedings of the Twenty-eighth Arctic and Marine Oil Spill Program Technical Seminar*, Environment Canada, Ottawa, Ontario, 2005, pp. 825–860.

^BThe Experience in Use refers to the amount of historical use.

^C This column refers to *physical* requirements. A thorough review of regulatory requirements is in order in *all* instances.

TABLE 3 Sensor Suitability for Various Missions^A

Context or Mission	Tactical / Operational		Strategic / Command and Control				
			Regulatory				
Sensor	Support for Cleanup	Night Operation	Fog Operation	Detection of Oil with Debris	Oiled Shoreline Survey	Spill Mapping	Ship Discharge Surveillance
Still Camera—Film	1	n/a	n/a	n/a	1	1	3
Still Camera—CCD	4	n/a	n/a	2	2	2	2
Video	4	n/a	n/a	2	2	2	2
IR Camera (8 to 14 µm)	4	2	n/a	1	n/a	3	3
UV Camera	2	n/a	n/a	n/a	n/a	3	2
UV/IR Scanner	4	2	n/a	1	n/a	4	3
Multi-spectral Scanner	4	n/a	n/a	n/a	1	2	1
Airborne or Space Radar	1	4	4	n/a	n/a	4	3
Ship-mounted Radar	4	4	4	n/a	n/a	4	2
Microwave Radiometer	1	3	3	n/a	n/a	2	2
Laser Fluorosensor	4	3	n/a	5	5	1	5

^A Information presented in this table was adapted from: Fingas, M. F. and Brown, C. E., "An Update on Oil Spill Remote Sensors," in *Proceedings of the Twenty-eighth Arctic and Marine Oil Spill Program Technical Seminar*, Environment Canada, Ottawa, Ontario, 2005, pp. 825–860.

Key: n/a = not applicable; numerical values represent a scale from 1 = poorly suited to 5 = ideally suited.

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; http://www.copyright.com/