

**Surface active agents
— Detergents —
Determination of
anionic-active matter
hydrolysable and non-
hydrolysable under
acid conditions (ISO
2870:2009)**

ICS 71.100.40

National foreword

This British Standard is the UK implementation of EN ISO 2870:2009. It supersedes BS EN ISO 2870:1994 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee CII/34, Methods of test for surface active agents.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 March 2009

© BSI 2009

ISBN 978 0 580 57872 4

Amendments/corrigenda issued since publication

| Date | Comments |
|------|----------|
| | |
| | |
| | |
| | |

EUROPEAN STANDARD

EN ISO 2870

NORME EUROPÉENNE

EUROPÄISCHE NORM

February 2009

ICS 71.100.40

Supersedes EN ISO 2870:1994

English Version

Surface active agents - Detergents - Determination of anionic-active matter hydrolysable and non-hydrolysable under acid conditions (ISO 2870:2009)

Agents de surface - Détergents - Détermination de la matière active anionique hydrolysable et non hydrolysable en milieu acide (ISO 2870:2009)

Grenzflächenaktive Stoffe - Waschmittel - Bestimmung von sauer hydrolysierbaren und nicht-hydrolysierbaren anionaktiven Anteilen (ISO 2870:2009)

This European Standard was approved by CEN on 28 January 2009.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

This document (EN ISO 2870:2009) has been prepared by Technical Committee CEN/TC 276 "Surface active agents", the secretariat of which is held by AFNOR, in collaboration with Technical Committee ISO/TC 91 "Surface active agents".

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by August 2009, and conflicting national standards shall be withdrawn at the latest by August 2009.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 2870:1994.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

Contents

Page

| | |
|---|----|
| Foreword..... | iv |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Principle..... | 1 |
| 4 Reagents..... | 2 |
| 5 Apparatus | 2 |
| 6 Sampling..... | 2 |
| 7 Procedure | 2 |
| 7.1 Test portion and test solution | 2 |
| 7.2 Determination of total anionic-active matter | 3 |
| 7.3 Determination of hydrolyzable anionic-active matter | 3 |
| 8 Calculation and expression of results..... | 3 |
| 8.1 Calculations..... | 3 |
| 8.2 Precision..... | 4 |
| 9 Test report | 4 |
| Bibliography | 5 |

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 2870 was prepared by the European Committee for Standardization (CEN) Technical Committee CEN/TC 276, *Surface active agents*, in collaboration with Technical Committee ISO/TC 91, *Surface active agents*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This third edition cancels and replaces the second edition (ISO 2870:1986) which has been technically revised.

The following major change was introduced: introduction of the potentiometric two-phase titration.

Surface active agents — Detergents — Determination of anionic-active matter hydrolysable and non-hydrolysable under acid conditions

1 Scope

This International Standard specifies a method for the determination, in detergents, of anionic-active matter hydrolysable and non-hydrolysable under acid conditions.

This active matter includes alkyl sulfates and hydroxysulfates and alkylphenol and fatty alcohol ethoxysulfates.

The mean relative molecular mass of the two types of active matter must be known or previously determined, if their content is expressed as a percentage by mass. If the detergent contains any oxidizing agent, this must be destroyed before the hydrolysis.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 607, *Surface active agents and detergents — Methods of sample division*

ISO 2271, *Surface active agents — Detergents — Determination of anionic-active matter by manual or mechanical direct two-phase titration procedure*

ISO 3696, *Water for analytical laboratory use — Specification and test methods*

EN 14480, *Surface active agents — Determination of anionic surface active agents — Potentiometric two-phase titration method*

3 Principle

Titration of an aliquot of a sample solution with benzethonium chloride solution according to the direct two-phase titration procedure specified in ISO 2271 or the potentiometric two-phase titration specified in EN 14480.

Hydrolysis, by refluxing under acidic conditions, of a second aliquot of the sample solution after destruction, if necessary, of any oxidizing agent in the sample by the addition of sodium sulfite.

Titration of non-hydrolyzed anionic-active matter as before.

Calculation of the contents of hydrolysable and non-hydrolysable anionic-active matter from the results obtained.

4 Reagents

4.1 General.

WARNING — The procedures described in this International Standard involve the use of hazardous materials. The necessary precautions as described in regulations covering the handling of hazardous substances should be taken. Technical, organizational and personal protection measures should be observed.

During the analysis, unless otherwise specified, use only reagents of recognized analytical grade that have been checked in advance as to not interfere with the analytical results and water complying with grade 1 as defined in ISO 3696.

4.2 Sulfuric acid, $c(\text{H}_2\text{SO}_4) = 490$ g/l solution (CAS number: 7664-93-9).

4.3 Sodium sulfite, $c(\text{Na}_2\text{SO}_3) 20$ g/l solution (CAS number: 7757-83-7).

4.4 Phenolphthalein, $c(\text{C}_{20}\text{H}_{14}\text{O}_4) = 10$ g/l ethanolic solution (CAS number: 77-09-8).

4.5 Sodium hydroxide, $c(\text{NaOH}) = 400$ g/l solution (CAS number: 1310-73-2).

4.6 Sodium hydroxide, $c(\text{NaOH}) = 40$ g/l solution (CAS number: 1310-73-2).

4.7 Benzethonium chloride, (Hyamine 1622) standard volumetric solution, $c(\text{C}_{27}\text{H}_{42}\text{ClNO}_2 \cdot \text{H}_2\text{O}) = 0,004$ mol/l (CAS number: 121-54-0).

In addition, the other reagents mentioned in ISO 2271 or, respectively, EN 14480 shall be used for the active matter titration.

5 Apparatus

Ordinary laboratory apparatus and in addition, the other apparatus mentioned in EN 14480 shall be used for the potentiometric active matter titration and the following:

5.1 Conical flask, of capacity 250 ml, with a conical ground glass joint.

5.2 Reflux condenser, water-cooled, with a conical ground glass joint at the bottom, fitting on to the conical flask (5.1).

6 Sampling

The test sample shall be prepared and stored in accordance with ISO 607.

7 Procedure

7.1 Test portion and test solution

Weigh, to the nearest 1 mg, a sample amount which contains 3 to 5 milli-equivalents of anionic-active matter, and dissolve in 30 ml of water. Transfer the solution quantitatively to a 100 ml volumetric flask and dilute to the mark (test solution A).

7.2 Determination of total anionic-active matter

Transfer a 10 ml aliquot of the solution A to a 100 ml volumetric flask and make up to the volume with water. Take a 10 ml aliquot of this solution and carry out the determination of total anionic-active matter present in the sample visually by the procedure described in ISO 2271 or potentiometrically by the procedure described in EN 14480.

7.3 Determination of hydrolyzable anionic-active matter

By means of a pipette, transfer a second aliquot of 10 ml of the solution A (7.1) to the conical flask (5.1). Add, by means of a pipette, 5 ml of the sulfuric acid solution (4.2) and a few anti-bumping granules. If the sample contains oxidizing agents, add also 10 ml of the sodium sulfite solution (4.3).

Attach the water-cooled reflux condenser (5.2), well washed with water, to the conical flask and reflux for 3 h. Apply heat cautiously at the start to avoid excessive foaming.

At the end of the reflux period of 3 h, allow to cool, wash down the water-cooled reflux condenser with at least 5 ml of water, detach the conical flask and wash the ground glass joint with a little water, collecting the washings in the conical flask.

Add a few drops of the phenolphthalein solution (4.4) and neutralize with the sodium hydroxide solution (4.5); add most of the sodium hydroxide solution at once and then complete the neutralization drop wise with the sodium hydroxide solution (4.6) until the solution turns pink.

Quantitatively transfer the content of the conical flask to a 100 ml volumetric flask and dilute to the mark with water.

Take a 10 ml aliquot of this solution and carry out the determination of non-hydrolyzed anionic active matter present in the sample visually by the procedure described in ISO 2271 or potentiometrically by the procedure described in EN 14480.

8 Calculation and expression of results

8.1 Calculations

8.1.1 Anionic-active matter

The content of total anionic active matter c_1 , expressed as mmol/100 g, is given by Equation (1):

$$c_1 = \frac{V_1 \times c}{m} \times 100 \times 100 \quad (1)$$

where

m is the mass, in grams, of the test portion;

c is the actual concentration, expressed in moles per litre, of the benzethonium chloride solution (4.7);

V_1 is the volume, in millilitres, of the benzethonium chloride solution (4.7) used for the titration of total anionic-active matter.

8.1.2 Anionic-active matter non-hydrolyzable under acid conditions

The content of non-hydrolyzable anionic active matter c_2 , expressed as mmol/100 g, is given by Equation (2):

$$c_2 = \frac{V_2 \times c}{m} \times 100 \times 100 \quad (2)$$

where

m is the mass, in grams, of the test portion;

c is the actual concentration, expressed in moles per litre, of the benzethonium chloride solution (4.7);

V_2 is the volume, in millilitres, of the benzethonium chloride solution (4.7) used for the titration of anionic-active matter after acid hydrolysis.

8.1.3 Anionic-active matter hydrolyzable under acid conditions

The content of hydrolyzable anionic active matter c_3 , expressed as mmol/100 g, is given by Equation (3):

$$c_3 = c_1 - c_2 \quad (3)$$

8.2 Precision

8.2.1 Repeatability limit

The difference found between the results of two determinations carried out on the same sample simultaneously or in rapid succession by the same analyst using the same apparatus should not exceed 2 % of the mean value.

8.2.2 Reproducibility limit

The difference between the results obtained on the same sample in two different laboratories should not exceed 4 % of the average value.

9 Test report

The test report shall include the following information:

- a) all information necessary for the identification of the sample tested;
- b) a reference to this International Standard (ISO 2870);
- c) the test results;
- d) details of any operation not specified in this International Standard or in the standards to which reference is made, and any operations regarded as optional, as well as any incidents likely to have affected the results.

Bibliography

- [1] REID, V.W. *et al.*, *Tenside 5*, 1968, pp. 90-96

BSI - British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001. Fax: +44 (0)20 8996 7001 Email: orders@bsigroup.com You may also buy directly using a debit/credit card from the BSI Shop on the Website <http://www.bsigroup.com/shop>

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact Information Centre. Tel: +44 (0)20 8996 7111 Fax: +44 (0)20 8996 7048 Email: info@bsigroup.com

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration. Tel: +44 (0)20 8996 7002 Fax: +44 (0)20 8996 7001 Email: membership@bsigroup.com

Information regarding online access to British Standards via British Standards Online can be found at <http://www.bsigroup.com/BSOL>

Further information about BSI is available on the BSI website at <http://www.bsigroup.com>.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright and Licensing Manager. Tel: +44 (0)20 8996 7070 Email: copyright@bsigroup.com