

BS EN ISO 4210-1:2014



BSI Standards Publication

Cycles — Safety requirements for bicycles

Part 1: Terms and definitions (ISO
4210-1:2014)

bsi.

...making excellence a habit.™

National foreword

This British Standard is the UK implementation of EN ISO 4210-1:2014. Together with BS EN ISO 4210-2:2014, BS EN ISO 4210-3:2014, BS EN ISO 4210-4:2014, BS EN ISO 4210-5:2014, BS EN ISO 4210-6:2014, BS EN ISO 4210-7:2014, BS EN ISO 4210-8:2014, BS EN ISO 4210-9:2014 it supersedes BS EN 14764:2005, BS EN 14766:2005 and BS EN 14781:2005, which are withdrawn.

The UK participation in its preparation was entrusted to Technical Committee GME/25, Cycles.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014.
Published by BSI Standards Limited 2014

ISBN 978 0 580 78232 9

ICS 43.150

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 September 2014.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

English Version

Cycles - Safety requirements for bicycles - Part 1: Terms and definitions (ISO 4210-1:2014)

Cycles - Exigences de sécurité des bicyclettes - Partie 1:
Termes et définitions (ISO 4210-1:2014)

Fahrräder - Sicherheitstechnische Anforderungen an
Fahrräder - Teil 1: Begriffe (ISO 4210-1:2014)

This European Standard was approved by CEN on 21 June 2014.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

This document (EN ISO 4210-1:2014) has been prepared by Technical Committee ISO/TC 149 "Cycles" in collaboration with Technical Committee CEN/TC 333 "Cycles" the secretariat of which is held by UNI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by January 2015, and conflicting national standards shall be withdrawn at the latest by July 2015.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 14764:2005, EN 14766:2005, EN 14781:2005.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 4210-1:2014 has been approved by CEN as EN ISO 4210-1:2014 without any modification.

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Terms and definitions	1
Bibliography	6

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 149, *Cycles*, Subcommittee SC 1, *Cycles and major sub-assemblies*.

This first edition of ISO 4210-1, together with ISO 4210-2, ISO 4210-3, ISO 4210-4, ISO 4210-5, ISO 4210-6, ISO 4210-7, ISO 4210-8, and ISO 4210-9, cancels and replaces ISO 4210:1996, which has been technically revised.

ISO 4210 consists of the following parts, under the general title *Cycles — Safety requirements for bicycles*:

- *Part 1: Terms and definitions*
- *Part 2: Requirements for city and trekking, young adult, mountain and racing bicycles*
- *Part 3: Common test methods*
- *Part 4: Braking test methods*
- *Part 5: Steering test methods*
- *Part 6: Frame and fork test methods*
- *Part 7: Wheels and rim test methods*
- *Part 8: Pedals and drive system test methods*
- *Part 9: Saddles and seat-post test methods*

Introduction

This International Standard has been developed in response to demand throughout the world, and the aim has been to ensure that bicycles manufactured in compliance with this International Standard will be as safe as is practically possible. The tests have been designed to ensure the strength and durability of individual parts as well as of the bicycle as a whole, demanding high quality throughout and consideration of safety aspects from the design stage onwards.

The scope has been limited to safety considerations and has specifically avoided standardization of components.

If the bicycle is to be used on public roads, national regulations apply.

Cycles — Safety requirements for bicycles —

Part 1: Terms and definitions

1 Scope

This part of ISO 4210 specifies terms and definitions related to safety and performance requirements for the design, assembly, and testing of bicycles and sub-assemblies having saddle height as given in [Table 1](#).

This part of ISO 4210 does not apply to specialized types of bicycle such as delivery bicycles, recumbent bicycles, tandems, BMX bicycles, and bicycles designed and equipped for use in severe applications such as sanctioned competition events, stunting, or aerobatic manoeuvres.

NOTE For bicycles with a maximum saddle height of 435 mm or less, see ISO 8124-1, and with a maximum saddle height of more than 435 mm and less than 635 mm, see ISO 8098.

Table 1 — Maximum saddle height

Dimensions in millimetres

Bicycle type	City and trekking bicycles	Young adult bicycles	Mountain bicycles	Racing bicycles
Maximum saddle height	635 or more	635 or more and less than 750	635 or more	635 or more

2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

2.1

aerodynamic extension

extension (or extensions) secured to the handlebar or stem, to improve the rider's aerodynamic posture

2.2

band brake

brake in which a circumferential band is wrapped around the exterior of a cylindrical drum which is attached to or incorporated in the wheel-hub

2.3

bar end

extension secured to the end of a handlebar to provide an additional hand grip and usually with its axis perpendicular to the axis of the end of the handlebar

2.4

bicycle

two-wheeled vehicle that is propelled solely or mainly by the muscular energy of the person on that vehicle, in particular by means of pedals

2.5

bolted joint

components joined together with threaded fasteners

2.6

brake lever

lever that operates a braking device

2.7

braking distance

distance travelled by a bicycle between the *commencement of braking* (2.10) and the point at which the bicycle comes to rest

2.8

braking force

F_{Br}
tangential rearward force between the tyre and the ground, or the tyre and the drum or belt of the test machine

2.9

city and trekking bicycle

bicycle designed for use on public roads primarily for means of transportation or leisure

2.10

commencement of braking

point on the test track or test machine at which the brake-actuating device operated directly by the rider's hand or foot or by a test mechanism starts to move from its rest position

Note 1 to entry: On the test track, this point is determined by the first brake-actuating device (front or rear) to operate.

2.11

composite material

component that is entirely or partially made of a non-metallic matrix materials which is reinforced by metallic or non-metallic materials such as short or long fibres, fabric, or particles

2.12

composite wheels

wheel assembly containing any composite material

2.13

crank assembly

assembly for fatigue testing consisting of the drive side and the non-drive side crank arm, the pedal-spindle adaptors, the bottom-bracket spindle, and the first component of the drive system

EXAMPLE The chain-wheel set.

2.14

delivery bicycle

bicycle designed for the primary purpose of carrying goods

2.15

disc brake

brake in which pads are used to grip the lateral faces of a thin disc attached to or incorporated in the wheel hub

2.16

drive belt

seamless ring belt which is used as a means of transmitting motive force

2.17

exposed protrusion

protrusion which, through its location and rigidity, could present a hazard to the rider either through heavy contact with it in normal use or should the rider fall onto it in an accident

2.18

dummy fork

test fork manufactured to specific characteristics which can be substituted within a test for either the fork supplied by the manufacturer or where a fork has not been supplied

2.19

folding bicycle

bicycle designed to fold into a compact form, facilitating transport and storage

2.20

fracture

unintentional separation into two or more parts

2.21

fork steerer (fork stem)

part of a fork that rotates about the steering axis of a bicycle frame head tube

Note 1 to entry: It is normally connected to the fork crown or directly to the fork legs and is normally the point of connection between the fork and the handlebar stem.

2.22

fully assembled bicycle

bicycle fitted with all components necessary for its intended use

2.23

highest gear

gear ratio which gives the greatest distance travelled for one rotation of the cranks

2.24

hub brake

brake which acts directly on the wheel hub

2.25

hub generator

electric generating device built in the wheel hub

2.26

lowest gear

gear ratio which gives the shortest distance travelled for one rotation of the cranks

2.27

maximum inflation pressure

maximum tyre pressure recommended by the tyre or rim manufacturer for a safe and efficient performance

Note 1 to entry: If the rim and tyre both indicate a maximum inflation pressure, the maximum inflation pressure is the lower of the two pressures indicated.

2.28

maximum saddle height

vertical distance from the ground to the point where the top of the seat surface is intersected by the seat-post axis, measured with the seat in a horizontal position and with the seat-post set to the minimum insertion-depth mark

2.29

minimum insertion-depth mark

mark indicating the minimum insertion-depth of handlebar stem into fork steerer (fork stem) or seat-post into frame

2.30

mountain bicycle

bicycle designed for use off-road on rough terrain, on public roads, and on public pathways, equipped with a suitably strengthened frame and other components, and, typically, with wide-section tyres with coarse tread patterns and a wide range of transmission gears

2.31

off-road rough terrain

coarse pebble tracks, forest trails, and other general off-road tracks where tree roots and rocks are likely to be encountered

2.32

pedal tread surface

surface of a pedal that is presented to the underside of the foot

2.33

primary retention system

system that keeps the front/rear wheel securely attached to the frame/fork dropouts while riding

2.34

public pathway

any designated and adopted road, path, or track on which a bicycle is legally permitted to travel where motorized traffic is excluded

2.35

public road

any designated and adopted road, pavement, path, or track on which a bicycle is legally permitted to travel and, on most though not all such public roads, bicycles will share use with other forms of transport including motorized traffic

2.36

pulley

rotating wheel mounted on an axle that contains, around its circumference, teeth or grooves over which a belt can pass to transmit power

2.37

quick-release device

lever actuated mechanism that connects, retains, or secures a wheel or any other component

2.38

quick-release pedal (clip-less pedal)

pedal that contains a device for the attachment of a rider's foot/shoe that can be released by foot movement alone

2.39

racing bicycle

bicycle intended for high-speed amateur use on public roads and having a steering assembly with multiple grip positions (allowing for an aerodynamic posture), a multi-speed transmission system, tyre width not greater than 28 mm, and a maximum mass of 12 kg for the fully assembled bicycle

2.40

recumbent bicycle

bicycle that places the rider in a laid-back reclining position

2.41

rim-brake

brake in which brake shoes act on the rim of the wheel

2.42

screw thread locking devices

devices attached or applied to the threads of a nut or bolt, so that they do not unintentionally become unlocked

EXAMPLE Lock washers, lock nuts, thread locking compound, or stiff nuts.

2.43

seat-post

component that clamps the saddle (with a bolt or assembly) and connects it with the frame

2.44

secondary retention system

system that retains the front wheel in the fork dropouts when the primary retention system is in the open (unlocked) position

2.45

simulated ground plane

plane used to orient a test part or assembly in a way that represents the cycles alignment to the ground in a fully assembled cycle

2.46

suspension fork

front fork incorporating controlled, axial flexibility to reduce the transmission of road shocks to the rider

2.47

suspension frame

frame incorporating controlled, vertical flexibility to reduce the transmission of road shocks to the rider

2.48

tandem

bicycle with saddles for two or more riders, one behind the other

2.49

toe clip

device attached to the pedal to grip the toe end of the rider's shoe but permitting withdrawal of the shoe

2.50

visible crack

crack which results from a test, wherein that crack is visible to the naked eye

2.51

wheel

assembly or combination of hub, spokes or disc, and rim, but excluding the tyre assembly

2.52

wheelbase

distance between the axes of the front and rear wheels of an unladen bicycle

2.53

young adult bicycle

bicycle designed for use on public roads by a young adult whose weight is less than 40 kg, with maximum saddle height of 635 mm or more and less than 750 mm

Bibliography

- [1] ISO 8124-1, *Safety of toys — Part 1: Safety aspects related to mechanical and physical properties*
- [2] ISO 8098, *Cycles — Safety requirements for bicycles for young children*

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com



...making excellence a habit.™