BS EN ISO 8502-12:2004 BS 7079-B12:2004

Incorporating Amendment No. 1 to BS 7079-B12:2003 (renumbers the BS as BS EN ISO 8502-12:2004)

Preparation of steel substrates before application of paints and related products — Tests for the assessment of surface cleanliness —

Part 12: Field method for the titrimetric determination of water-soluble ferrous ions

The European Standard EN ISO 8502-12:2004 has the status of a British Standard

 $ICS\ 25.220.10$



National foreword

This British Standard is the official English language version of EN ISO 8502-12:2004. It is identical with ISO 8502-12:2003.

The UK participation in its preparation was entrusted to Technical Committee STI/21, Surface preparation of steel, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the *BSI Catalogue* under the section entitled "International Standards Correspondence Index", or by using the "Search" facility of the *BSI Electronic Catalogue* or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the EN ISO title page, the EN ISO foreword page, the ISO title page, pages ii to v, a blank page, pages 1 to 4, an inside back cover and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 4 March 2003

© BSI 3 February 2005

Amendments issued since publication

Amd. No.	Date	Comments
15513	3 February 2005	Implementation of the European Standard

EUROPEAN STANDARD

NORME EUROPÉENNE

EUROPÄISCHE NORM

December 2004

EN ISO 8502-12

ICS 25.220.10

English version

Preparation of steel substrates before application of paints and related products - Tests for the assessment of surface cleanliness - Part 12: Field method for the titrimetric determination of water-soluble ferrous ions (ISO 8502-12:2003)

Préparation des subjectiles d'acier avant application de peintures et de produits assimilés - Essais pour apprécier la propreté d'une surface - Partie 12: Méthode in situ pour la détermination titrimétrique des ions ferreux hydrosolubles (ISO 8502-12:2003) Vorbereitung von Stahloberflächen vor dem Auftragen von Beschichtungsstoffen - Prüfungen zur Bewertung der Oberflächenreinheit - Teil 12: Feldprüfung zur titrimetrischen Bestimmung von wasserlöslichen Eisenionen (ISO 8502-12:2003)

This European Standard was approved by CEN on 21 December 2004.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Foreword

The text of ISO 8502-12:2003 has been prepared by Technical Committee ISO/TC 35 "Paints and varnishes" of the International Organization for Standardization (ISO) and has been taken over as EN ISO 8502-12:2004 by Technical Committee CEN/TC 139 "Paints and varnishes", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2005, and conflicting national standards shall be withdrawn at the latest by June 2005.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

Endorsement notice

The text of ISO 8502-12:2003 has been approved by CEN as EN ISO 8502-12:2004 without any modifications.

INTERNATIONAL STANDARD

ISO 8502-12

First edition 2003-02-15

Preparation of steel substrates before application of paints and related products — Tests for the assessment of surface cleanliness —

Part 12:

Field method for the titrimetric determination of water-soluble ferrous ions

Préparation des subjectiles d'acier avant application de peintures et de produits assimilés — Essais pour apprécier la propreté d'une surface —

Partie 12: Méthode in situ pour la détermination des ions ferreux hydrosolubles par titrimétrie



EN ISO 8502-12:2004

Cor	ntents	Page
	eword	
Intro	oduction	
1	Scope	
2	Normative references	
3	Principle	1
4	Reagents	
5	Apparatus	
6	Removal of water-soluble contaminants from the surface	
7	Procedure	
8	Expression of results	3
9	Precision	3
10	Toot report	

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this part of ISO 8502 may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 8502-12 was prepared by Technical Committee ISO/TC 35, *Paints and varnishes*, Subcommittee SC 12, *Preparation of steel substrates before application of paints and related products*.

ISO 8502 consists of the following parts, under the general title *Preparation of steel substrates before application of paints and related products* — *Tests for the assessment of surface cleanliness*:

- Part 1: Field test for soluble iron corrosion products [Technical Report]
- Part 2: Laboratory determination of chloride on cleaned surfaces
- Part 3: Assessment of dust on steel surfaces prepared for painting (pressure-sensitive tape method)
- Part 4: Guidance on the estimation of the probability of condensation prior to paint application
- Part 5: Measurement of chloride on steel surfaces prepared for painting (ion detection tube method)
- Part 6: Extraction of soluble contaminants for analysis The Bresle method
- Part 7: Field method for the determination of oil and grease
- Part 8: Field method for the refractometric determination of moisture
- Part 9: Field method for the conductometric determination of water-soluble salts
- Part 10: Field method for the titrimetric determination of water-soluble chloride
- Part 11: Field method for the turbidimetric determination of water-soluble sulfate
- Part 12: Field method for the titrimetric determination of water-soluble ferrous ions
- Part 13: Field method for the determination of soluble salts by conductometric measurement

At the time of publication of this part of ISO 8502, parts 7, 11 and 13 were in preparation.

Introduction

The performance of protective coatings of paint and related products applied to steel is significantly affected by the state of the steel surface immediately prior to painting. The principal factors that are known to influence this performance are:

- a) the presence of rust and mill scale;
- b) the presence of surface contaminants, including salts, dust, oils and greases;
- c) the surface profile.

International Standards ISO 8501, ISO 8502 and ISO 8503 have been prepared to provide methods of assessing these factors, while ISO 8504 provides guidance on the preparation methods that are available for cleaning steel substrates, indicating the capabilities of each in attaining specified levels of cleanliness.

These International Standards do not contain recommendations for the protective coating system to be applied to the steel surface. Neither do they contain recommendations for the surface quality requirements for specific situations even though surface quality can have direct influence on the choice of protective coating to be applied and on its performance. Such recommendations are found in other documents such as national standards and codes of practice. It will be necessary for the users of these International Standards to ensure that qualities specified are:

- compatible and appropriate both for the environmental conditions to which the steel will be exposed and for the
 protective coating system to be used;
- within the capability of the cleaning procedure specified.

The four International Standards referred to above deal with the following aspects of preparation of steel substrates:

ISO 8501 — Visual assessment of surface cleanliness;

ISO 8502 — Tests for the assessment of surface cleanliness;

ISO 8503 — Surface roughness characteristics of blast-cleaned steel substrates;

ISO 8504 — Surface preparation methods.

Each of these International Standards is in turn divided into separate parts.

There are a number of methods for the analysis of ferrous ions in solution. However, most of these are for laboratory use and very few are suitable for field use, i.e. in conjunction with sampling in workshops, at building sites, on board ships, etc., often under severe environmental conditions.

The proposed field method for ferrous ions and the corresponding methods of analysis that have been developed for other contaminants (such as sulfate, chlorides, and oil and grease) are intended to be used in conjunction with the Bresle method for the removal of contaminants from a surface, ISO 8502-6. These methods of analysis provide results which, after application of a simple conversion factor, indicate directly the amount of contaminants per unit surface area, usually expressed in mg/m². The same method of analysis can also be used in conjunction with other contaminant extraction methods.

Preparation of steel substrates before application of paints and related products — Tests for the assessment of surface cleanliness —

Part 12:

Field method for the titrimetric determination of water-soluble ferrous ions

WARNING — The method described in this part of ISO 8502 involves drop titration with a solution of potassium dichromate. The small quantity of titrant solution and its low concentration are not likely to make it a hazard (e.g. by ingestion). Attention is drawn, however, to national and/or local legislation regarding possible environmental pollution hazards.

1 Scope

This part of ISO 8502 describes a field method for the determination, by drop titration, of soluble ferrous ions on steel surfaces before and/or after surface preparation.

The method is intended mainly for use in the assessment of contaminants on a surface. It is easy for unskilled personnel to carry out and it is sufficiently accurate for most practical purposes.

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO 8502. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO 8502 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

ISO 3696, Water for analytical laboratory use — Specification and test methods

ISO 8502-6:1995, Preparation of steel substrates before application of paints and related products — Tests for the assessment of surface cleanliness — Part 6: Extraction of soluble contaminants for analysis — The Bresle method

3 Principle

The surface contaminants to be assessed are removed by the Bresle method (ISO 8502-6), or any other convenient method, using water as the solvent. After removal of contaminants and acidifying the solvent with phosphoric acid, the ferrous ion concentration of the solvent is determined by drop titration with a dichromate solution as titrant, using diphenylamine sulfonate as indicator.

The concentration of the titrant, the size of the drops and the area of the test surface (normally 1250 mm²) are chosen so that the number of drops required for the titration multiplied by a simple conversion factor gives the surface density of water-soluble ferrous ions.

Reaction:
$$Cr_2O_7^{2-} + 6Fe^{2+} + 14H^+ \rightarrow 2Cr^{3+} + 6Fe^{3+} + 7H_2O$$

4 Reagents

During the analysis, use only water conforming to the requirements of at least grade 3 of ISO 3696.

NOTE Usually, distilled or de-ionized water of conductivity less than 0,5 mS/m (5 µS/cm) meets this requirement.

- **4.1 Phosphoric acid** (H₃PO₄) **solution**, 85 %, in de-ionized water, the ratio by volume being 1:2 (one volume of phosphoric acid to two volumes of water).
- **4.2 Indicator solution:** a colourless 0,5 % solution of the sodium salt of diphenylamine sulfonate $(C_6H_5NHC_6H_4SO_3Na)$ in de-ionized water, kept in bottle A (5.2).

Check once a year that ageing has not destroyed the indicator, by using the solution to titrate a sulfate-containing solution, e.g. ordinary tap water.

4.3 Potassium dichromate solution, $c(K_2Cr_2O_7) = 0,002 \text{ mol/l}$, for use as titrant, kept in bottle B (5.3).

5 Apparatus

- **5.1 Plastic beaker**, of suitable size, usually about 20 ml.
- **5.2 Bottle A,** volume about 30 ml, having a device for dropwise release of indicator solution (4.2), about 0,05 ml being released with each drop.
- **5.3** Bottle B, volume about 30 ml, having a device for dropwise release of titrant solution (4.3), (0.050 ± 0.002) ml being released with each drop.

6 Removal of water-soluble contaminants from the surface

Remove the water-soluble contaminants from the steel surface using the Bresle method given in ISO 8502-6 or any other convenient method.

When using the Bresle method, use a patch of size A-1250 (compartment area 1250 mm²), unless another size proves to be necessary. Whatever the patch size, use a volume of solvent water which is proportional to the compartment area of the patch, i.e. $(2,5 \pm 0,5) \mu l$ per square mm of surface area.

7 Procedure

Using the procedure given in clause 5 of ISO 8502-6:1995, collect the solution containing the ferrous ions to be analysed in the plastic beaker (5.1).

Add approximately 1 ml of indicator solution (4.2) and mix by carefully swirling the plastic beaker so that the solution becomes homogeneous.

Determine the ferrous ion concentration by drop titration as follows:

Add 4 ml of phosphoric acid solution (4.1) and mix by carefully swirling the plastic beaker so that the solution becomes homogeneous.

Add 1 drop $[(0,050 \pm 0,002) \text{ ml}]$ of the titrant solution (4.3) as blank.

Add further drops of the titrant solution slowly one by one, briefly swirling the solution in the plastic beaker after each addition, until the colour of the solution turns from colourless through greyish blue to violet. Note the number of drops required for the colour change (not counting the first drop added as blank).

NOTE The colour change is not very pronounced. The addition of more drops does not give any further change.

8 Expression of results

If a Bresle patch of size A-1250 is used, the relationship between the number of drops required for the titration in clause 7 and the surface density of the ferrous ions is as given in Table 1. The conversion factor is 27 mg/m² per drop.

Number of drops required for titration in clause 7	Surface density of ferrous ions mg/m ²					
	min.	max.				
1	0	27				
2	27	54				
3	54	81				
4	81	108				
5	108	135				
6	135	162				
7	162	189				

Table 1 — Result of titration

If the compartment area of the Bresle patch is not 1250 mm², multiply the result by 1250 and divide by the numerical value of the actual compartment area in mm².

Express the result as the range of the surface density of ferrous ions, in mg/m².

9 Precision

The precision of this method is independent of the surface density of the ferrous ions (see Table 1).

10 Test report

The test report shall contain at least the following information:

- a) a reference to this part of ISO 8502 (i.e. ISO 8502-12:2003);
- b) all details necessary for complete identification of the surface tested;
- c) the method used to remove soluble contaminants from the steel surface:
- d) the area of the test surface;

EN ISO 8502-12:2004

e)	the results of the test	, expressed as	the	surface	density	of ferrous	ions a	and	determined	in	accordance	with
	clause 8;											

f) the date of the test.

BS EN ISO 8502-12:2004 BS 7079-B12:2004

BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001. Fax: +44 (0)20 8996 7001. Email: orders@bsi-global.com. Standards are also available from the BSI website at http://www.bsi-global.com.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre. Tel: +44 (0)20 8996 7111. Fax: +44 (0)20 8996 7048. Email: info@bsi-global.com.

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration.

Tel: +44 (0)20 8996 7002. Fax: +44 (0)20 8996 7001.

Email: membership@bsi-global.com.

Information regarding online access to British Standards via British Standards Online can be found at http://www.bsi-global.com/bsonline.

Further information about BSI is available on the BSI website at http://www.bsi-global.com.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means — electronic, photocopying, recording or otherwise — without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright & Licensing Manager. Tel: +44 (0)20 8996 7070. Fax: +44 (0)20 8996 7553. Email: copyright@bsi-global.com.

BSI 389 Chiswick High Road London W4 4AL