

**Surface active
agents — Sulfated
ethoxylated alcohols
and alkylphenols —
Determination of
content of unsulfated
matter (ISO 8799:2009)**

ICS 71.100.40

National foreword

This British Standard is the UK implementation of EN ISO 8799:2009. It is identical to ISO 8799:2009. It supersedes BS EN ISO 8799:1996 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee CII/34, Methods of test for surface active agents.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 April 2009

© BSI 2009

ISBN 978 0 580 65933 1

Amendments/corrigenda issued since publication

Date	Comments

EUROPEAN STANDARD

EN ISO 8799

NORME EUROPÉENNE

EUROPÄISCHE NORM

March 2009

ICS 71.100.40

Supersedes EN ISO 8799:1995

English Version

**Surface active agents - Sulfated ethoxylated alcohols and
alkylphenols - Determination of content of unsulfated matter
(ISO 8799:2009)**

Agents de surface - Sulfates d'alcools et d'alkylphénols
éthoxylés - Détermination de la teneur en matière insulfatée
(ISO 8799:2009)

Grenzflächenaktive Stoffe - Sulfatierte ethoxylierte Alkohole
und Alkylphenole - Bestimmung der unsulfatierten Anteile
(ISO 8799:2009)

This European Standard was approved by CEN on 28 February 2009.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	iv
1 Scope	1
2 Normative references	1
3 Principle.....	1
4 Reagents and materials	1
5 Apparatus	2
6 Sampling.....	2
7 Procedure	2
7.1 Test portion	2
7.2 Preparation of the ion-exchange resins	2
7.2.1 Anion-exchange resin clean-up	2
7.2.2 Cation-exchange resin clean-up	2
7.3 Final preparation of resins.....	3
7.4 Arrangement of the mixed-bed exchange column	3
7.5 Separation of unsulfated matter.....	3
7.6 Check of the ion-exchange resin	3
8 Calculation and expression of results.....	3
9 Precision.....	4
9.1 Repeatability limit	4
9.2 Reproducibility limit	4
10 Test report	4
Annex A (informative) Statistical and other data derived from the results of interlaboratory tests.....	5
Bibliography	6

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 8799 was prepared by the European Committee for Standardization (CEN) Technical Committee CEN/TC 276, *Surface active agents*, in collaboration with ISO Technical Committee ISO/TC 91, *Surface active agents*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 8799:1988), which has been technically revised.

Surface active agents — Sulfated ethoxylated alcohols and alkylphenols — Determination of content of unsulfated matter

1 Scope

This International Standard specifies a method for the determination of the content of unsulfated matter present in ordinary commercial neutralized products of sulfation of ethoxylated alcohols or alkylphenols [alkyl oxyethylene sulfates (ethoxylated alcohol sulfates) or alkylphenol oxyethylene sulfates (ethoxylated alkylphenol sulfates)] containing an average of not more than 20 oxyethylene groups per molecule.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 607, *Surface active agents and detergents — Methods of sample division*

ISO 2271, *Surface active agents — Detergents — Determination of anionic-active matter by manual or mechanical direct two-phase titration procedure*

ISO 3696, *Water for analytical laboratory use — Specification and test methods*

EN 14480, *Surface active agents — Determination of anionic surface active agents — Potentiometric two-phase titration method*

3 Principle

From a methanolic solution of the test portion, the unsulfated matter is separated on an ion-exchange column (filled with a mixture of cation-exchange resins and anion-exchange resins).

The unsulfated matter is recovered from the eluate by evaporation and weighing of the residue.

4 Reagents and materials

4.1 General.

WARNING — The procedures described in this International Standard involve the use of hazardous substances. The necessary precautions, as described in regulations covering the handling of hazardous substances, should be taken. Technical, organizational and personal protection measures should be observed.

During the analysis, unless otherwise specified, use only reagents of recognized analytical grade that have been checked in advance so as to not interfere with the analytical results, and water of grade 1 as defined in ISO 3696.

4.2 Methanol, CH₃OH, (CAS number: 67-56-1).

4.3 Hydrochloric acid solution, *c*(HCl), about 1 mol/l, (CAS number: 7647-01-0).

4.4 Sodium hydroxide solution, *c*(NaOH), about 2 mol/l, (CAS number 1310-73-2).

4.5 Cation-exchange resin, polystyrene sulfonic acid type, 2 % to 3 % crosslinked, 150 µm to 330 µm, hydrogen form.

4.6 Anion-exchange resin, polystyrene quaternary ammonium type, 2 % to 3 % crosslinked, 150 µm to 330 µm, chloride form.

5 Apparatus

Ordinary apparatus and the following:

5.1 Rotary evaporator, with round-bottom flasks of capacity 250 ml.

5.2 Ion-exchange column: open glass column of internal diameter 25 mm and length 200 mm, provided with a 10 mm to 20 mm layer of glass wool or sintered glass filter and with a stopcock.

5.3 Water bath, the temperature of which can be adjusted between 25 °C to 40 °C.

6 Sampling

The test sample shall be prepared and stored in accordance with ISO 607.

7 Procedure

7.1 Test portion

From the laboratory sample, if necessary homogenized by introducing an appropriate and known quantity of water, weigh, to the nearest 1 mg, into a 100 ml beaker, a quantity of the homogeneous laboratory sample corresponding to 5 mmol of anionic-active matter.

7.2 Preparation of the ion-exchange resins

7.2.1 Anion-exchange resin clean-up

Take 100 g of the anion-exchange resin (4.6) and allow to swell in water for 24 h. Transfer the resin to a suitable column and pass 500 ml of the sodium hydroxide solution (4.4) through the column, followed by about 1 000 ml of water. Then pass 400 ml of the hydrochloric acid solution (4.3) through the column and again wash with enough water until the washings have a pH between 5 and 7. The treated resin may be stored in water.

7.2.2 Cation-exchange resin clean-up

Take 100 g of the cation-exchange resin (4.5) and allow it to swell in water for 24 h. Transfer the resin to a suitable column, pass 500 ml of the hydrochloric acid solution (4.3) through the column and wash with water until the washings have a pH between 5 and 7. The treated resin may be stored in water.

7.3 Final preparation of resins

Take the required amount of anion-exchange resin, prepared as specified in 7.2.1, namely 25 ml per determination, and transfer to a suitable column. Pass five times the volume of the sodium hydroxide solution (4.4) through the column, wash with water until neutral, then wash with 1 to 2 volumes of methanol (4.2).

Take the required amount (25 ml) of cation-exchange resin, prepared as specified in 7.2.2, place it in a suitable column and wash it with twice its volume of methanol (4.2).

7.4 Arrangement of the mixed-bed exchange column

Mix with the help of a glass rod 25 ml of the cation-exchange resin and 25 ml of the anion-exchange resin, prepared as specified in 7.3, in a beaker. Fill the column (5.2) with the mixed resin in small portions, let the mixed resin settle to a volume between 50 ml and 60 ml and wash with 500 ml of methanol (4.2).

7.5 Separation of unsulfated matter

Dissolve the test portion (7.1) in 50 ml of methanol (4.2). Filter off the insoluble matter through a fast-running filter paper above the prepared column (see 7.4). Pass the filtrate through the column at a flow rate of 2 ml/min and collect the eluate in a 500 ml beaker.

Adjust the flow to 3 ml/min and wash with about 450 ml of methanol. Transfer the eluate and the washings in portions to a tared 250 ml round-bottom flask (see 5.1) and evaporate by means of the rotary evaporator (5.1) on the water bath (5.3) at not more than 40 °C, under vacuum.

Rinse the beaker and evaporator with about 40 ml to 50 ml of methanol and allow the methanol to evaporate.

When the flask appears to be free from methanol, leave it on the evaporator for about 15 min. Weigh the flask plus residue, then dry again in the vacuum desiccator for 15 min.

Weigh again and repeat the procedure of drying and weighing until a mass constant to ± 3 mg is obtained.

7.6 Check of the ion-exchange resin

In the case of ethoxylated alcohols, it may happen that the exchange of anions is not complete. Dissolve the residue obtained in 7.5 in 20 ml of water and determine the content of total active matter by direct two-phase titration in accordance with ISO 2271 or EN 14480.

If the anion-active matter content exceeds 0,005 mmol, reject the result and repeat the determination with a fresh sample, using a flow rate of less than 2 ml/min and washing with 250 ml of methanol instead of 450 ml or using separate ion-exchange columns.

8 Calculation and expression of results

The unsulfated matter content, w , expressed as a percentage by mass, is given by Equation (1):

$$w = \frac{m_1 \times 100}{m_0} \quad (1)$$

where

m_0 is the mass, in grams, of the test portion (see 7.1);

m_1 is the mass, in grams, of the residue obtained in 7.5.

9 Precision

9.1 Repeatability limit

The absolute difference between two independent single test results, obtained using the same method on identical test material in the same laboratory by the same operator using the same equipment within a short interval of time, will not exceed the repeatability limit, r , in more than 5 % of cases.

9.2 Reproducibility limit

The absolute difference between two independent single test results, obtained using the same method on identical test material in different laboratories by different operators using different equipment, will not exceed the reproducibility limit, R , in more than 5 % of cases.

10 Test report

The test report shall include the following information:

- a) all information necessary for the identification of the sample tested;
- b) a reference to this International Standard (ISO 8799);
- c) the test results;
- d) details of any operation not specified in this International Standard or in the standards to which reference is made, and any operations regarded as optional, as well as any incidents likely to have affected the results.

Annex A (informative)

Statistical and other data derived from the results of interlaboratory tests

Comparative analyses of two samples with unsulfated mass fractions of 0,6 % and 2,3 %, respectively, carried out in 15 laboratories, have given the following statistical results:

- standard deviation of repeatability, σ_r : 0,18;
- standard deviation of reproducibility, σ_R : 0,39.

Bibliography

- [1] ISO 6842, *Surface active agents — Sulfated ethoxylated alcohols and alkylphenols — Determination of total active matter content*

BSI - British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001. Fax: +44 (0)20 8996 7001 Email: orders@bsigroup.com You may also buy directly using a debit/credit card from the BSI Shop on the Website <http://www.bsigroup.com/shop>

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact Information Centre. Tel: +44 (0)20 8996 7111 Fax: +44 (0)20 8996 7048 Email: info@bsigroup.com

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration. Tel: +44 (0)20 8996 7002 Fax: +44 (0)20 8996 7001 Email: membership@bsigroup.com

Information regarding online access to British Standards via British Standards Online can be found at <http://www.bsigroup.com/BSOL>

Further information about BSI is available on the BSI website at <http://www.bsigroup.com>.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright and Licensing Manager. Tel: +44 (0)20 8996 7070 Email: copyright@bsigroup.com