

Safety requirements for industrial laundry machinery

**Part 6: Ironing and fusing presses (ISO
10472-6:1997)**

ICS 97.060

National foreword

This British Standard is the UK implementation of EN ISO 10472-6:2008. It is identical to ISO 10472-6:1997. It supersedes BS EN ISO 10472-6:1998 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee TCI/33, Textile machinery.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 December 2008

© BSI 2008

ISBN 978 0 580 63657 8

Amendments/corrigenda issued since publication

Date	Comments

English Version

Safety requirements for industrial laundry machinery - Part 6:
Ironing and fusing presses (ISO 10472-6:1997)

Exigences de sécurité pour les machines de blanchisserie
industrielle - Partie 6: Presses à repasser et à thermocoller
(ISO 10472-6:1997)

Sicherheitsanforderungen für industrielle
Wäschereimaschinen - Teil 6: Bügel- und Fixierpressen
(ISO 10472-6:1997)

This European Standard was approved by CEN on 23 October 2008.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Foreword

The text of ISO 10472-6:1997 has been prepared by Technical Committee ISO/TC 72 “Textile machinery and machinery for dry-cleaning and industrial laundering” of the International Organization for Standardization (ISO) and has been taken over as EN ISO 10472-6:2008 by Technical Committee CEN/TC 214 “Textile machinery and accessories” the secretariat of which is held by SNV.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by May 2009, and conflicting national standards shall be withdrawn at the latest by December 2009.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 10472-6:1997.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EC Directives.

For relationship with EC Directives, see informative Annexes ZA and ZB, which are integral parts of this document.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

Endorsement notice

The text of ISO 10472-6:1997 has been approved by CEN as a EN ISO 10472-6:2008 without any modification.

Annex ZA (informative)

Relationship between this European Standard and the Essential Requirements of EU Directive 98/37/EC

This European Standard has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association to provide a means of conforming to Essential Requirements of the New Approach Directive Machinery 98/37/EC, amended by 98/79/EC.

Once this standard is cited in the Official Journal of the European Communities under that Directive and has been implemented as a national standard in at least one Member State, compliance with the normative clauses of this standard confers, within the limits of the scope of this standard, a presumption of conformity with the relevant Essential Requirements (except 1.7.4. (f)) of that Directive and associated EFTA regulations.

WARNING — Other requirements and other EU Directives may be applicable to the product(s) falling within the scope of this standard.

Annex ZB (informative)

Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EC

This European Standard has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association to provide a means of conforming to Essential Requirements of the New Approach Directive Machinery 2006/42/EC.

Once this standard is cited in the Official Journal of the European Communities under that Directive and has been implemented as a national standard in at least one Member State, compliance with the normative clauses of this standard confers, within the limits of the scope of this standard, a presumption of conformity with the relevant Essential Requirements (except 1.4.2.1 § 2, 1.7.3, 1.7.4.2 t) and u)) of that Directive and associated EFTA regulations.

WARNING — Other requirements and other EU Directives may be applicable to the product(s) falling within the scope of this standard.

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 10472-6 was prepared by Technical Committee ISO/TC 72, *Textile machinery and machinery for dry-cleaning and industrial laundering*, Subcommittee SC 5, *Industrial laundry and dry-cleaning machinery*.

ISO 10472 consists of the following parts, under the general title *Safety requirements for industrial laundry machinery*:

- *Part 1: Common requirements*
- *Part 2: Washing machines and washer-extractors*
- *Part 3: Washing tunnel lines including component machines*
- *Part 4: Air dryers*
- *Part 5: Flatwork ironers, feeders and folders*
- *Part 6: Ironing and fusing presses*

Introduction

This part of ISO 10472 is intended to instruct the designer of industrial laundry machinery in a systematic manner, focusing on his particular type of machine, regarding the relevant essential safety requirements, and to suggest possible state-of-the-art safety solutions.

The extent to which hazards are covered is indicated in the scope of this part of ISO 10472. In addition, machinery should comply as appropriate with ISO/TR 12100-1 and ISO/TR 12100-2 for hazards which are not specifically referred to in this part of ISO 10472.

All examples given in this part of ISO 10472 represent the state of the art. Equivalent solutions are acceptable, provided they attain at least the same safety level.

The designer is presumed to have taken into account all the provisions of ISO 10472-1 before considering this part of ISO 10472.

Safety requirements for industrial laundry machinery —

Part 6: Ironing and fusing presses

1 Scope

This part of ISO 10472 covers, together with ISO 10472-1, most significant hazards associated with ironing and fusing presses used in the laundry, garment and dry-cleaning industry, and in particular:

- scissor presses;
- cabinet presses;
- drawer presses;
- rotary presses (carousel) and other presses with multiple bucks.

This part of ISO 10472 complements the basic requirements as laid down in ISO/TR 12100-1 and ISO/TR 12100-2. It also gives guidance to the designer on assessing the risks associated with the hazards (see EN 1050) and on selecting measures for attaining the required safety level.

This part of ISO 10472 does not apply to ancillary equipment, e. g steam boilers, steam valves and supply pipe work, vent systems, work feed systems and discharge systems, and ducting to the atmosphere.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 10472. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreement based on this part of ISO 10472 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 10472-1:1997, *Safety requirements for industrial laundry machinery — Part 1: Common requirements.*

ISO/TR 12100-1:1992, *Safety of machinery — Basic concepts, general principles for design — Part 1: Basic terminology, methodology.*

ISO/TR 12100-2:1992, *Safety of machinery — Basic concepts, general principles for design — Part 2: Technical principles and specifications.*

ISO 13849-1:—¹⁾, *Safety of machinery — Safety-related parts of control systems — Part 1: General principles for design.*

ISO 13850:1996, *Safety of machinery — Emergency stop — Principles for design.*

ISO 13852:1996, *Safety of machinery — Safety distances to prevent danger zones being reached by the upper limbs.*

1) To be published.

ISO 14119:—¹⁾, *Safety of machinery — Interlocking devices associated with guards — Principles for design and selection.*

EN 574:1996, *Safety of machinery — Two-hand control device.*

EN 626-1:1994, *Safety of machinery — Elimination or reduction of risk to health from hazardous substances emitted by machinery — Part 1: Principles and specifications for machinery manufacturers.*

EN 953:1997, *Safety of machinery — General requirements for the design and construction of guards (fixed, movable).*

EN 1050:1996, *Safety of machinery — Risk assessment.*

EN 1760-1:1997, *Safety machinery — Pressure sensitive protective devices — Part 1: General principles for the design and testing of pressure sensing mats and floors.*

EN 60204-1:1992, *Safety of machinery — Electrical equipment of machines — Part 1: General requirements.* [IEC 204-1: modified]

3 Definitions

For the purposes of this part of ISO 10472, the following definitions apply:

3.1

ironing press

Machine for the smoothing or shaping of fabric items by pressing them between two components, at least one of which is heated and, if required, equipped with a steaming device.

3.2

fusing press

Machine for the fusing of two textile layers by pressing them between two components, at least one of which is heated to a temperature such that the coating of one layer becomes adhesive.

3.3

buck

Component of the press, covered with one or more layers of textile material, upon which the fabric item is laid, positioned and prepared if necessary.

NOTE — The buck may be heated and equipped with a steaming and/or suction device and/or blowing device.

3.4

head

Component of the press which executes the required pressure by interacting with the buck.

NOTE — Generally the head is heated and may be equipped with a steaming and/or suction device. Heads for industrial laundry machinery usually have a polished metallic pressing surface; those for outerwear are covered with one or more layers of textile material.

3.5

scissor press

Ironing or fusing press whose head is moved on a circular path or a combination of circular and linear paths against a stationary buck.

3.6

cabinet press

Machine into which a garment is placed on a vertical buck (or former) which is moved to a position between two or more vertical press heads which move horizontally to press the garment against the buck.

1) To be published.

NOTE — A cabinet press may have one or more vertical bucks which travel horizontally such that the entire equipment may be operated by two or more operators in concert.

3.7

drawer press

Ironing or fusing press whose horizontal buck is moved on a horizontal linear path under the head, then the buck (or head) is pressed against the head (or buck) on a vertical, linear path.

3.8

rotary press

Press in which the loading, unloading and pressing operations are assigned to different positions of the movement of a turntable carrying the bucks.

3.9

upstroke press

Press comprising an upper head and a lower buck, upon which the fabric item is prepared, after which the action of the press raises the lower buck to the press head either mechanically or pneumatically.

3.10

multiple-buck press

Press similar to a rotary press in which the bucks can travel in a straight path.

4 Hazards

4.1 General

The hazards common to most industrial laundry machinery are listed in ISO 10472-1. Significant particular hazards found in ironing and fusing presses are listed in 4.2 to 4.8.

4.2 Mechanical hazards

4.2.1 Closing and pressing of the head and buck of all presses:

— crushing, impact;

— shifting or swinging around of the buck of cabinet, rotary, drawer and multiple-buck presses: shearing, crushing, impact.

4.2.2 Operating mechanism of the head or buck for all presses: crushing and shearing.

4.2.3 Falling of the head of scissor presses: impact and crushing.

4.3 Electrical hazards

See ISO 10472-1:1997, 4.2.

4.4 Thermal hazards

4.4.1 Hot surfaces of all presses, covered and uncovered: burns.

4.4.2 Free steam affecting the operator, for scissor presses: burns.

4.4.3 Radiated and convected heat affecting the operator, for scissor presses: burns.

4.5 Hazards generated by noise

Noise emitted by compressed air exhaust of cabinet presses may cause a hazard. See ISO 10472-1:1997, 4.4.

4.6 Hazards caused by harmful fumes of fusing presses: intoxication.

4.7 Hazards due to neglect of ergonomic principles in machine design of all presses

4.7.1 Inappropriate posture and effort due to:

- height and position of press buck;
- height and position of automatic cabinet press buck for loading.

4.7.2 Inadequate local lighting.

4.8 Failure of energy supply or control systems, leading to closing of the head or unexpected movement of the buck

5 Safety requirements and/or measures for the hazards identified in clause 4

5.1 General

The designer shall consider the common safety requirements and measures described in ISO 10472-1 in addition to the particular hazards and measures described in this part of ISO 10472.

5.2 Mechanical hazards

5.2.1 Closing and pressing of the head and buck of all presses

- a) Scissor presses: The head shall be fitted with a trip device (e.g. trip frame) which shall prevent crushing without preventing efficient machine operation (see ISO 10472-1:1997, 5.1.2).

EXAMPLE

The trip device shall:

- be fitted around the periphery of the head or at the front and sides only with fixed guard at the back; and
 - have a minimum lead over the head of 60 mm; and
 - have a maximum horizontal clearance over the buck of 75 mm; and
 - be of rigid construction and require light activation pressure; and
 - operate, when contacted, to cause reversal of the movement before crushing can occur; and
 - allow restart only by activating the start control.
- b) Scissor presses with fabric-covered head: The measures taken to respect safety shall conform to at least the following: the head shall be lowered with reduced force (≤ 300 N), actuated by a hand- or foot-operated hold-to-run control, until it is not possible to insert fingers into the danger zone. Full pressure shall be applied only after the head is lowered to a safe position leaving less than 6 mm clearance, and then only by two-hand control type II in accordance with EN 574.

NOTE — For hand-operated scissor presses, none of these measures need be applied.

- c) Cabinet presses: Guards and/or safety devices shall be provided to prevent hazard between head and buck and also between moving buck and fixed elements (see ISO 10472-1:1997, 5.1.2).

EXAMPLE

Fixed guards in conjunction with trip devices (e.g. trip plates, extending the full height of both sides of the opening) shall be operated by a horizontal movement of less than 6 mm. Pressure-sensitive mats or floors at least 500 mm wide and of at least the length of travel of the buck shall be provided in addition (see EN 1760-1). Both safety devices shall stop the movement of the buck before entrapment can occur and reverse the closure of the head. The machine cycle shall be started by two-hand control type II (according to EN 574) only, but it is not necessary to hold the control continuously after the cycle has been initiated.

The press shall be fitted with an emergency stop device category 1 (in accordance with ISO 13850), which shall stop the movement of the buck and reverse the closure of the head.

- d) Cabinet-type presses which rotate: The complete machine shall be enclosed with a fixed guard which prevents entrance into the danger zone during normal machine operation, e.g. fence. Means shall be provided to protect any person entering the guard area for maintenance purposes; see ISO 10472-1:1997, annex A. These means may include a key switch to the cycle start control, and shall enable a clear visibility of the machine from operating positions. The manufacturer shall describe, in the instruction handbook, the measures to be taken by the operator and maintenance staff for safe operation and the training necessary.
- e) Sleeve and trouser cabinet presses: Trip bars shall protect the hazard zones between head and buck and between the moving buck and fixed elements of the machine, and shall operate within a movement of 6 mm. They shall reverse the moving buck and the closure of the head. The machine cycle shall be started by two-hand control type II only (in accordance with EN 574).
- f) Rotary presses and other multiple-buck presses: The danger zones created by the closing of the press and by the transfer movement of the buck shall be protected by guards and/or safety devices (see ISO 10472-1:1997, 5.1.2).

EXAMPLE 1

Enclosing guards or fences may be provided as a complete protection for these danger zones. The start control shall be located in a position where the operator can clearly see but cannot reach the danger zones (see ISO 10472-1:1997, annex A).

EXAMPLE 2

Access to the pressing zone shall be prevented by one or more devices, e.g.:

- a trip frame which reverses the closure of the head;
- a fixed guard, attached to the head, which prevents access to the danger zone.

Entry to the shearing, crushing and impact zones created by the moving buck shall be prevented by a fence guard (see ISO 10472-1:1997, annex A). The start control shall be located in a position where the operator can clearly see but cannot reach the danger zones.

NOTE — The pressing and opening parts of the cycle are controlled automatically and not manually.

- g) Upstroke presses: The same measures shall be employed as for scissor presses. Alternatively, a control guard with an associated interlocking device in accordance with ISO/TR 12100-2:1992, 4.2.2.5, and ISO 14119:—, 5.7.2.1 shall be fitted, which allows the machine to start only if the guard is completely closed. The action of the guard may start the machine. For the category of the control system, the requirement of 5.8 shall apply.

- h) Any machine described above: Means shall be provided for the rapid release of any person trapped within the machine. These means shall enable the separation of the head and buck, even in the case of failure of energy supply, e.g.:
- manual opening of the hinge between head and buck;
 - training system for the hydraulic or pneumatic circuits.

The procedure for releasing entrapped persons shall be marked on the machine and shall be described in the instruction handbook.

An emergency stop button is not required for scissor presses, for rotary and other multiple-buck presses, nor for upstroke presses.

5.2.2 Operating mechanism of the head and buck of all presses

- a) Scissor presses: The operating mechanism shall be protected by fixed guards (see ISO 10472-1:1997, 5.1.2).
- b) Cabinet presses: The measures taken to protect the danger zone between head and buck shall be extended to the operating mechanism and the danger zone of the moving buck.

The transfer mechanism for the buck shall be guarded at the opening, for example by flexible covers (rubber, metal etc).

A warning notice that the operator shall not stand on the cover shall be fitted to the machine, and this information shall be contained in the instruction handbook.

If pressure sensitive mats or floors are used (see EN 1760-1), the unprotected danger zone shall be guarded by a fixed guard provided by the user in accordance with details given by the manufacturer in the instruction handbook.

- c) Rotary and multiple-buck presses: The guard described in 5.2.1 shall be extended to protect the transfer mechanism, or the transfer mechanism shall be guarded separately (see ISO 10472-1:1997, 5.1.2).

5.2.3 Falling of the head of scissor presses

For maintenance, setting or repair of scissor presses, a mechanical restraint (e.g. a brace or locking pin) shall be provided to prevent inadvertent closing of the press.

Detailed information shall be given in the instruction handbook.

5.3 Electrical hazards

The requirements of EN 60204-1 shall apply to all machines covered by this part of ISO 10472 (see ISO 10472-1:1997, 5.2).

5.4 Thermal hazards

5.4.1 Hot surfaces of all presses, covered and uncovered

Measures shall be taken in accordance with ISO 10472-1:1997, 5.3. For polished heads the access to the operating surfaces shall be protected with fixed guards (see ISO 10472-1:1997, table 1). If for process reasons this is not totally possible, the manufacturer shall draw the attention, in the instruction handbook, to the residual risk. In addition, the manufacturer shall place a warning sign near the danger zone.

For presses with fabric-covered heads, the surface temperature of the fabric shall not exceed 110 °C.

5.4.2 Free steam affecting the operator (for scissor presses)

For scissor presses whose head may eject free steam, it shall not be possible for ejection to occur until the head is at a distance of < 50 mm from the buck.

5.4.3 Radiated and convected heat affecting the operator (for scissor presses)

The instruction handbook shall contain advice for the user concerning the means that may be taken to prevent the operator being exposed to unacceptable working temperatures.

The instruction handbook shall advise the user that the temperature at the normal operating position (at 1200 mm height above the floor and at 500 mm horizontal distance from the machine) shall not exceed 35 °C with a normal ambient condition of 25 °C at 65 % relative humidity. Advice for the user shall include reducing steam pressure, ventilation and other means.

5.5 Hazards generated by noise

See ISO 10472-1:1997, 5.4.

Compressed air exhausts shall be fitted with silencers.

5.6 Hazards caused by harmful fumes, for fusing presses

A warning shall be given in the instruction handbook that harmful fumes can be generated when certain fabrics are processed, and the machine shall be provided with means for fixing an exhaust system (see EN 626-1).

5.7 Hazards due to neglect of ergonomic principles in machine design of all presses

5.7.1 Inappropriate posture and effort

The advice given in ISO 10472-1:1997, 5.6 should be followed.

5.7.2 Inadequate local lighting

Information shall be given in the instruction handbook concerning correct lighting for safe and efficient operation.

5.8 Failure of energy supply or control systems

A failure of the energy supply or of the control system or unexpected movement of the buck shall not cause the press to close.

For presses with covered heads ISO 10472-1:1997, 5.7.2 applies.

For presses with uncovered heads, the safety-related part of the control system shall be at least one failure fail-safe (category 3, see ISO 13849-1:—, clause 6).

For presses which require cyclic access, the safety-related part of:

- the electrical control system shall be at least two failures fail-safe (category 4, see ISO 13849-1:—, clause 6);
- the pneumatic control system shall be at least one failure fail-safe (category 3, see ISO 13849-1:—, clause 6).

6 Verification of safety requirements and/or measures

The verification shall follow the general requirements of ISO 10472-1 and the particular requirements of clause 5 of this part of ISO 10472. Table 1 gives a list of verifications.

Table 1 (continued)

Sub-clause	Subject	Reference	Test method
5.2.1	f) <u>Rotary presses and multiple-buck presses</u>		
	EXAMPLE 1		
	Enclosing guard	ISO 10472-1:1997, 5.1.2	Visual inspection Measurement
	Fence	ISO 10472-1:1997, annex A	Visual inspection Measurement
	Start control		Test and visual inspection
	EXAMPLE 2		
	Trip device (trip frame)		Demonstration
	Barrier	EN 953 ISO 13852	Visual inspection Measurement
	Start control		Test and visual inspection
	g) <u>Upstroke presses</u>	See scissor presses in this table	
	Control guard	ISO/TR 12100-2:1992, 4.2.2.5 ISO 14119	Visual inspection and check function
	Category	5.8	Check manufacturer's technical file
	h) <u>For any machine</u>		
Means for releasing any entrapped persons		Visual inspection	
Procedure for release	Instruction handbook	Confirm accuracy and content	
Marking		Visual inspection	

Table 1 (continued)

Sub-clause	Subject	Reference	Test method
5.2.2	<u>Operating mechanism of the head and buck</u> a) <u>Scissor presses</u> Fixed guards b) <u>Cabinet presses</u> Flexible cover Warning notice Pressure sensitive mats or floors Details for fixed guard c) <u>Rotary presses and multiple buck presses</u> Separate guards	ISO 10472-1:1997, 5.1.2 Instruction handbook EN 1760-1 Instruction handbook See 5.2.1 in this table ISO 10472-1:1997, 5.1.2	Visual inspection Demonstration and check function Visual inspection Confirm accuracy and content Check function Confirm accuracy and content
5.2.3	<u>Falling of the head</u> Mechanical restraint device Information	Instruction handbook	Demonstration Confirm accuracy and content
5.3	Electrical hazards	ISO 10472-1:1997, 5.2 EN 60204-1	
5.4.1	<u>Hot surfaces of the machine</u> Residual risks	ISO 10472-1:1997, 5.3 Instruction handbook	Measurement after 30 min of operation Confirm accuracy and content
5.4.2	<u>Free steam affecting the operator</u> Distance between head and buck Interlock with steam ejection		Measurement Test function

Table 1 (concluded)

Sub-clause	Subject	Reference	Test method
5.4.3	<u>Radiated and convected heat affecting the operator</u> Means and advice for preventing unacceptable working temperature	Instruction handbook	Confirm accuracy and content, measurement
5.5	<u>Noise reduction measures</u> Silencers		Demonstration
5.6	Harmful fumes	Instruction handbook	Confirm accuracy and content
5.7.1	Inappropriate posture and effort	ISO 10472-1:1997, 5.6	
5.7.2	Inadequate local lighting	Instruction handbook	Confirm accuracy and content Visual inspection
5.8	<u>Failure of energy supply or control system</u> Category	ISO 10472-1:1997, 5.7.2 ISO 13849-1:—, clause 6	Check manufacturer's technical file
7.1	Instruction handbook	ISO 10472-1:1997, 7.1	Check completeness
7.2	Warning signs	ISO 10472-1:1997, 7.2	Visual inspection

7 Information concerning machine use

7.1 Instruction handbook

All information called for in ISO 10472-1:1997, 7.1 shall be provided. Furthermore, the manufacturer shall provide in the instruction handbook detailed information as required in clause 5 of this part of ISO 10472 on:

- 5.2.1, operating rotary cabinet machine;
- 5.2.1, release of entrapped person;
- 5.2.2, warning notice for access to machine;
- 5.2.2, pressure mat, guarding;
- 5.2.3, mechanical support for head;
- 5.4.1, operating surfaces;
- 5.4.3, environmental heat;
- 5.6, harmful fumes;
- 5.7.2, lighting.

7.2 Warning signs

The manufacturer shall provide machine marking in accordance with ISO 10472-1:1997, 7.2, and in addition marking required in clause 5 of this part of ISO 10472 on:

- 5.2.2, flexible covers;
- 5.4.1, uncovered hot surfaces.

BSI - British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001. Fax: +44 (0)20 8996 7001 Email: orders@bsigroup.com You may also buy directly using a debit/credit card from the BSI Shop on the Website <http://www.bsigroup.com/shop>

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact Information Centre. Tel: +44 (0)20 8996 7111 Fax: +44 (0)20 8996 7048 Email: info@bsigroup.com

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration. Tel: +44 (0)20 8996 7002 Fax: +44 (0)20 8996 7001 Email: membership@bsigroup.com

Information regarding online access to British Standards via British Standards Online can be found at <http://www.bsigroup.com/BSOL>

Further information about BSI is available on the BSI website at <http://www.bsigroup.com>.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright and Licensing Manager. Tel: +44 (0)20 8996 7070 Email: copyright@bsigroup.com