

Colorimetry

Part 4: CIE 1976 L*a*b* Colour space

ICS 17.180.20

National foreword



FSC
100%
From well-managed forests

Cert no. SW-COC-004238
www.fsc.org
© 1996 Forest Stewardship Council

This British Standard is the UK implementation of EN ISO 11664-4:2011. It is identical to ISO 11664-4:2008. It supersedes BS ISO 11664-4:2008, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee STI/14, Colour measurement and schedules.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 April 2010

© BSI 2011

Amendments/corrigenda issued since publication

Date	Comments
30 June 2011	This corrigendum renumbers BS ISO 11664-4:2008 as BS EN ISO 11664-4:2011

ISBN 978 0 580 72262 2

ICS 17.180.20

English Version

Colorimetry - Part 4: CIE 1976 L*a*b* Colour space (ISO 11664-4:2008)

Colorimétrie - Partie 4: Espace chromatique L*a*b* CIE
1976 (ISO 11664-4:2008)

Farbmetrik - Teil 4: CIE 1976 L*a*b* Farbenraum (ISO
11664-4:2008)

This European Standard was approved by CEN on 17 March 2011.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

The text of ISO 11664-4:2008 has been prepared by Technical Committee CIE “International Commission on Illumination” of the International Organization for Standardization (ISO) and has been taken over as EN ISO 11664-4:2011 by Technical Committee CEN/TC 139 “Paints and varnishes” the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2011, and conflicting national standards shall be withdrawn at the latest by October 2011.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

Endorsement notice

The text of ISO 11664-4:2008 has been approved by CEN as a EN ISO 11664-4:2011 without any modification.



Standard

COMMISSION INTERNATIONALE DE L'ÉCLAIRAGE
INTERNATIONAL COMMISSION ON ILLUMINATION
INTERNATIONALE BELEUCHTUNGSKOMMISSION

Colorimetry - Part 4: CIE 1976 L*a*b* Colour Space

Colorimétrie - Partie 4: Espace chromatique L*a*b* CIE 1976

Farbmessung - Teil 4: CIE 1976 L*a*b* Farbenraum

CIE Standards are copyrighted and shall not be reproduced in any form, entirely or partly,
without the explicit agreement of the CIE.

CIE Central Bureau, Vienna
Kegelgasse 27, A-1030 Vienna, Austria

CIE S 014-4/E:2007

UDC: 535.65:006
535.643.2

Descriptor: Standardisation of colour measurement
Standard colorimetric systems

© CIE, 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from CIE Central Bureau at the address below.

CIE Central Bureau
Kegelgasse 27
A-1030 Vienna
Austria
Tel.: +43 1 714 3187 0
Fax: +43 1 714 3187 18
e-mail: ciecb@cie.co.at
Web: www.cie.co.at

FOREWORD

Standards produced by the Commission Internationale de l'Eclairage (CIE) are a concise documentation of data defining aspects of light and lighting, for which international harmony requires such unique definition. CIE Standards are therefore a primary source of internationally accepted and agreed data, which can be taken, essentially unaltered, into universal standard systems.

This CIE Standard has been prepared by the Technical Committee TC 1-57* of Division 1 "Vision and Colour" and was approved by the National Committees of the CIE.

The following ISO and IEC committees and working groups co-operated in the preparation of this standard:

IEC TC100/TA2 (Audio, Video and Multimedia Systems)
ISO TC6 (Paper, Board and Pulps)
ISO TC35/SC9/WG22 (Paint and Varnishes)
ISO TC38/SC1/WG7 (Textiles)
ISO TC42 (Photography)
ISO TC130 (Graphic Technology)
ISO/IEC/JTC1/SC28 (Office Systems)

* The chairperson of this TC was A.R. Robertson (CA), members were: P.J. Alessi (US), J.A. Bristow (SE), J. Campos Acosta (ES), R. Connelly (US), J.-F. Decarreau (FR), R. Harold (US), R. Hirschler (HU), H. Ikeda (JP), B. Jordan (CA), C. Kim (KR), D. McDowell (US), P. McGinley (AU), Y. Ohno (US), M.R. Pointer (GB), K. Richter (DE), G. Rösler (DE), J.D. Schanda (HU), R. Sève (FR), K. Smith (GB), K. Witt (DE), H. Yaguchi (JP), J. Zwinkels (CA).

TABLE OF CONTENTS

FOREWORD	vii
INTRODUCTION	1
1. SCOPE	1
2. NORMATIVE REFERENCES	1
3. DEFINITIONS, SYMBOLS AND ABBREVIATIONS	1
4. CALCULATION METHOD	2
4.1 Basic coordinates	2
4.2 Correlates of lightness, chroma and hue	3
4.3 Colour differences	4
ANNEX (INFORMATIVE): REVERSE TRANSFORMATION	6
BIBLIOGRAPHY	7

COLORIMETRY - PART 4: CIE 1976 L*a*b* COLOUR SPACE

INTRODUCTION

The three-dimensional colour space produced by plotting CIE tristimulus values (X, Y, Z) in rectangular coordinates is not visually uniform, nor is the (x, y, Y) space nor the two-dimensional CIE (x, y) chromaticity diagram. Equal distances in these spaces do not represent equally perceptible differences between colour stimuli. For this reason, in 1976, the CIE introduced and recommended two new spaces (known as CIELAB and CIELUV) whose coordinates are non-linear functions of X, Y and Z . The recommendation was put forward in an attempt to unify the then very diverse practice in uniform colour spaces and associated colour difference formulae (Robertson, 1990; CIE, 2004). Both these more-nearly uniform colour spaces have become well accepted and widely used. Numerical values representing approximately the magnitude of colour differences can be described by simple Euclidean distances in the spaces or by more sophisticated formulae that improve the correlation with the perceived size of differences. The purpose of this CIE Standard is to define procedures for calculating the coordinates of the CIE 1976 L*a*b* (CIELAB) colour space and the Euclidean colour difference values based on these coordinates. The standard does not cover more sophisticated colour difference formulae based on CIELAB, such as the CMC formula (Clarke et al., 1984), the CIE94 formula (CIE, 1995), the DIN99 formula (DIN, 2001), and the CIEDE2000 formula (CIE, 2001), nor does it cover the alternative uniform colour space, CIELUV.

1. SCOPE

This CIE Standard specifies the method of calculating the coordinates of the CIE 1976 L*a*b* colour space including correlates of lightness, chroma and hue. It includes two methods for calculating Euclidean distances in this space to represent the perceived magnitude of colour differences.

The Standard is applicable to tristimulus values calculated using colour-matching functions of the CIE 1931 standard colorimetric system or the CIE 1964 standard colorimetric system. The Standard may be used for the specification of colour stimuli perceived as belonging to a reflecting or transmitting object, where a three-dimensional space more uniform than tristimulus space is required. It does not apply to colour stimuli perceived as belonging to an area that appears to be emitting light as a primary light source, or that appears to be specularly reflecting such light. This Standard does apply to self-luminous displays, like cathode ray tubes, if they are being used to simulate reflecting or transmitting objects and if the stimuli are appropriately normalized.

2. NORMATIVE REFERENCES

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

CIE 17.4-1987. *International Lighting Vocabulary* (Joint publication IEC/CIE).

CIE S 014-1:2006. *Colorimetry Part 1. CIE Standard Colorimetric Observers*. [ISO 11664-1:2007]

CIE S 014-2:2006. *Colorimetry Part 2. CIE Standard Illuminants*. [ISO 11664-2:2007]

3. DEFINITIONS, SYMBOLS AND ABBREVIATIONS

For the purposes of this International Standard, the terms and definitions given in CIE 17.4-1987 (International Lighting Vocabulary), as amended by this standard and the following symbols and abbreviations apply.

X, Y, Z	tristimulus values of test stimulus calculated using the colour-matching functions of the CIE 1931 standard colorimetric system (also known as the CIE 2° standard colorimetric system)
-----------	---

X_n, Y_n, Z_n	tristimulus values of a specific white colour stimulus calculated using the colour-matching functions of the CIE 1931 standard colorimetric system
L^*	CIELAB lightness
a^*, b^*	CIELAB a^*, b^* coordinates
C^*_{ab}	CIELAB chroma
h_{ab}	CIELAB hue angle
ΔL^*	CIELAB lightness difference
$\Delta a^*, \Delta b^*$	CIELAB a^*, b^* difference
ΔC^*_{ab}	CIELAB chroma difference
Δh_{ab}	CIELAB hue angle difference
ΔH^*_{ab}	CIELAB hue difference
ΔE^*_{ab}	CIELAB colour difference

If the character "Δ" is not available, it may be replaced by the character "D".
 The phrase "CIE 1976 L*a*b*" and the term "CIELAB" may be used interchangeably.

Where tristimulus values are calculated using the colour-matching functions of the CIE 1964 standard colorimetric system (also known as the CIE 10° standard colorimetric system), a subscript 10 shall be added to all the above symbols.

4. CALCULATION METHOD

4.1 Basic coordinates

The CIE 1976 L*a*b* colour space is a three-dimensional, approximately uniform colour space produced by plotting in rectangular coordinates, L^*, a^*, b^* , quantities defined by the equations:

$$L^* = 116f(Y/Y_n) - 16 \tag{1}$$

$$a^* = 500 [f(X/X_n) - f(Y/Y_n)] \tag{2}$$

$$b^* = 200 [f(Y/Y_n) - f(Z/Z_n)] \tag{3}$$

where

$$f(X/X_n) = (X/X_n)^{1/3} \quad \text{if } (X/X_n) > (6/29)^3 \tag{4}$$

$$f(X/X_n) = (841/108)(X/X_n) + 4/29 \quad \text{if } (X/X_n) \leq (6/29)^3 \tag{5}$$

and

$$f(Y/Y_n) = (Y/Y_n)^{1/3} \quad \text{if } (Y/Y_n) > (6/29)^3 \tag{6}$$

$$f(Y/Y_n) = (841/108)(Y/Y_n) + 4/29 \quad \text{if } (Y/Y_n) \leq (6/29)^3 \tag{7}$$

and

$$f(Z/Z_n) = (Z/Z_n)^{1/3} \quad \text{if } (Z/Z_n) > (6/29)^3 \tag{8}$$

$$f(Z/Z_n) = (841/108)(Z/Z_n) + 4/29 \quad \text{if } (Z/Z_n) \leq (6/29)^3 \tag{9}$$

where X, Y, Z are the tristimulus values of the test colour stimulus based on the CIE 1931 standard colorimetric system defined in CIE S 014-1, and X_n, Y_n, Z_n are the corresponding tristimulus values of a specified white stimulus.

Licensed copy: Lee Shau Kee Library, HKUST, Version correct as of 03/01/2015, (c) The British Standards Institution 2013

In the case of simulated reflecting or transmitting objects produced on a self-luminous display, all the tristimulus values shall be first normalized by the same factor so that Y would be equal to 100 for an object with 100% reflectance or transmittance.

If the angle subtended at the eye by the test stimulus is between about 1° and 4° the tristimulus values X, Y, Z calculated using the colour-matching functions of the CIE 1931 standard colorimetric system should be used. If this angular subtense is greater than 4° the tristimulus values X_{10} , Y_{10} , Z_{10} calculated using the colour-matching functions of the CIE 1964 standard colorimetric system should be used. The same colour-matching functions and the same specified white stimulus shall be used for all stimuli to be compared with each other.

When tristimulus values based on the CIE 1964 standard colorimetric system defined in CIE S 014-1 are used, a subscript 10 shall be added to all the symbols in equations (1) to (9).

If the tristimulus values X, Y, Z are obtained by spectrophotometry, the tristimulus values X_n , Y_n , Z_n of the specified white stimulus shall be calculated using the same method as used for the test stimulus (same colour-matching functions, same range and interval of wavelength, and same bandwidth). If the tristimulus values X, Y, Z are obtained by direct measurement using a tristimulus colorimeter, X_n , Y_n , Z_n shall be measured using the same tristimulus colorimeter and a white reflectance standard calibrated relative to a perfect reflecting diffuser.

NOTE 1 For real object colours, the specified white stimulus normally chosen for X_n , Y_n , Z_n is light reflected from a perfect reflecting diffuser illuminated by the same light source as the test object. In this case, X_n , Y_n , Z_n are the tristimulus values of the light source normalized by a common factor so that Y_n is equal to 100. For simulated object colours, the specified white stimulus normally chosen is one that has the appearance of a perfect reflecting diffuser, again normalized by a common factor so that Y_n is equal to 100.

NOTE 2 Examples of values of X_n , Y_n and Z_n for specific illuminants and specific calculation methods have been published (CIE, 2004).

NOTE 3 Equations (5), (7) and (9) are based on a suggestion by Pauli (1976).

NOTE 4 A value of 7,787 is approximately equal to the term $(841/108)$ in equations (5), (7) and (9). The approximate value may be used in practice.

NOTE 5 A value of 0,008856 is approximately equal to the term $(6/29)^3$ in equations (4), (5), (6), (7), (8) and (9). The approximate value may be used in practice.

NOTE 6 The fractions 6/29 and 4/29 in equations (4) through (9) are exactly equal to the fractions 24/116 and 16/116 appearing in CIE 15:2004.

NOTE 7 The term $(841/108)$ in equations (5), (7) and (9) is derived from and exactly equal to $(1/3)(29/6)^2$.

NOTE 8 Equation (1) reduces to $L^* \approx 903,3(Y/Y_n)$ when $Y/Y_n \leq (6/29)^3$.

When CIELAB values are reported, they should be accompanied by all relevant information relating to the measurement conditions and the procedures used to calculate the input tristimulus values.

4.2 Correlates of lightness, chroma and hue

Approximate correlates of the perceived attributes lightness, chroma, and hue shall be calculated as follows:

CIE 1976 lightness: L^* as defined in section 4.1

CIE 1976 a,b chroma (CIELAB chroma): $C^*_{ab} = \left[(a^*)^2 + (b^*)^2 \right]^{1/2}$ (10)

CIE 1976 a,b hue angle (CIELAB hue angle): $h_{ab} = \arctan(b^*/a^*)$ (11)

CIELAB hue angle, h_{ab} shall lie between 0° and 90° if a^* and b^* are both positive, between 90° and 180° if b^* is positive and a^* is negative, between 180° and 270° if b^* and a^* are both negative, and between 270° and 360° if b^* is negative and a^* is positive.

NOTE When the linear equations (5), (7) or (9) are used for X/X_n , Y/Y_n or Z/Z_n , anomalous values of h_{ab} may be obtained (McLaren, 1980). Anomalous values are unlikely to occur for reflecting object colours but may occur for transparent object colours of low luminance factor lying close to the spectrum locus or purple line.

4.3 Colour differences

Euclidean distances in CIELAB colour space can be used to represent approximately the perceived magnitude of colour differences between object colour stimuli of approximately the same size, viewed in identical white to middle-grey surroundings, by an observer photopically adapted to a field with the chromaticity of CIE standard illuminant D65 defined in CIE S 014-2. The values given by this Standard may not correlate well with perceived colour differences in other viewing conditions.

Differences between two stimuli denoted by subscripts 0 (usually the reference) and 1 (usually the test) shall be calculated as follows:

$$\Delta L^* = L^*_1 - L^*_0 \quad (12)$$

$$\Delta a^* = a^*_1 - a^*_0 \quad (13)$$

$$\Delta b^* = b^*_1 - b^*_0 \quad (14)$$

$$\Delta C^*_{ab} = C^*_{ab,1} - C^*_{ab,0} \quad (15)$$

$$\Delta h_{ab} = h_{ab,1} - h_{ab,0} \quad (16)$$

$$\Delta H^*_{ab} = 2 \left(C^*_{ab,1} \cdot C^*_{ab,0} \right)^{1/2} \sin(\Delta h_{ab} / 2) \quad (17)$$

For small colour differences away from the achromatic axis $C^*_{ab}=0$, equation (17) reduces to

$$\Delta H^*_{ab} \approx \left(C^*_{ab,1} \cdot C^*_{ab,0} \right)^{1/2} \Delta h_{ab} \quad (18)$$

where the value of Δh_{ab} is in radians.

If the line joining the two colours crosses the positive a^* axis, equation (16) will give a value outside the range $\pm 180^\circ$. In this case, the value of Δh_{ab} must be corrected by adding or subtracting 360° to bring it within this range.

NOTE 1 The quantity ΔH^*_{ab} is introduced to provide congruence with the perceptual understanding that a colour difference can be divided into a vector sum of a lightness difference, a chroma difference and a hue difference.

NOTE 2 The division of CIELAB colour differences into hue and chroma differences is progressively less useful as the absolute value of Δh_{ab} approaches 180° .

NOTE 3 In information technology and other fields the subscripts r (for reference) and t (for test) are sometimes used instead of 0 and 1, respectively. Similarly in industrial evaluation of small colour differences s (for standard) and b (for batch) are sometimes used. In other applications, std (for standard) and spl (for sample) are sometimes used.

The CIE 1976 a, b colour difference, ΔE^*_{ab} between two colour stimuli is calculated as the Euclidean distance between the points representing them in the space:

$$\Delta E^*_{ab} = \left[(\Delta L^*)^2 + (\Delta a^*)^2 + (\Delta b^*)^2 \right]^{1/2} \quad (19)$$

$$\text{or } \Delta E^*_{ab} = \left[(\Delta L^*)^2 + (\Delta C^*_{ab})^2 + (\Delta H^*_{ab})^2 \right]^{1/2} \quad (20)$$

These two definitions of ΔE^*_{ab} are equivalent.

Other ways of calculating ΔH^*_{ab} are:

$$\Delta H^*_{ab} = \left[(\Delta E^*_{ab})^2 - (\Delta L^*)^2 - (\Delta C^*_{ab})^2 \right]^{1/2} \quad (21)$$

where ΔE^*_{ab} is calculated from equation (19) and ΔH^*_{ab} has the same sign as Δh_{ab} ;

$$\Delta H^*_{ab} = k \left[2(C^*_{ab,1} \cdot C^*_{ab,0} - a^*_1 \cdot a^*_0 - b^*_1 \cdot b^*_0) \right]^{1/2} \quad (22)$$

where $k=-1$ if $a^*_1 \cdot b^*_0 \geq a^*_0 \cdot b^*_1$, otherwise $k=1$;

$$\text{and } \Delta H^*_{ab} = (a^*_0 \cdot b^*_1 - a^*_1 \cdot b^*_0) / \left[0,5(C^*_{ab,1} \cdot C^*_{ab,0} + a^*_1 \cdot a^*_0 + b^*_1 \cdot b^*_0) \right]^{1/2} \quad (23)$$

NOTE 4 Equation (23) cannot be used when either of the compared chromas is zero and is imprecise when either chroma is close to zero.

NOTE 5 More details on the various methods of calculating ΔH^*_{ab} are given by Sève (1991) for Eq. 17, by Stokes and Brill (1992) for Eq. 22 and by Sève (1996) for Eq. 23.

NOTE 6 In different practical applications it may be necessary to modify equation (20) by using different weightings for ΔL^* , ΔC^*_{ab} and ΔH^*_{ab} to obtain better correlation with colour-difference perception. In 2001, the CIE recommended such weightings in a new formula for industrial evaluation of small colour differences (CIE, 2001), but this is outside the scope of this Standard. A colour difference obtained in this way is not a CIELAB colour difference and the symbol ΔE^*_{ab} should not be used.

ANNEX (INFORMATIVE): REVERSE TRANSFORMATION

The following equations represent the reverse transformation, i.e. the calculation of X , Y , Z when L^* , a^* , b^* are given.

$$f(Y/Y_n) = (L^* + 16) / 116 \quad (\text{A1})$$

$$f(X/X_n) = a^* / 500 + f(Y/Y_n) \quad (\text{A2})$$

$$f(Z/Z_n) = f(Y/Y_n) - b^* / 200 \quad (\text{A3})$$

$$X = X_n [f(X/X_n)]^3 \quad \text{if } f(X/X_n) > 6/29 \quad (\text{A4})$$

$$X = (108/841) X_n [f(X/X_n) - 4/29] \quad \text{if } f(X/X_n) \leq 6/29 \quad (\text{A5})$$

$$Y = Y_n [f(Y/Y_n)]^3 \quad \text{if } f(Y/Y_n) > 6/29 \quad (\text{A6})$$

$$Y = (108/841) Y_n [f(Y/Y_n) - 4/29] \quad \text{if } f(Y/Y_n) \leq 6/29 \quad (\text{A7})$$

$$Z = Z_n [f(Z/Z_n)]^3 \quad \text{if } f(Z/Z_n) > 6/29 \quad (\text{A8})$$

$$Z = (108/841) Z_n [f(Z/Z_n) - 4/29] \quad \text{if } f(Z/Z_n) \leq 6/29 \quad (\text{A9})$$

NOTE 1 The condition in equation (A6) is equivalent to $L^* > 8$.

NOTE 2 The condition in equation (A7) is equivalent to $L^* \leq 8$.

BIBLIOGRAPHY

CIE, 1995. CIE 116-1995. *Industrial colour difference evaluation*, 1995.

CIE, 2001. CIE 142-2001. *Improvement to industrial colour-difference evaluation*, 2001.

CIE, 2004. CIE 15:2004. *Colorimetry, 3rd edition*, 2004.

CLARKE, F.J.J., MCDONALD, R., RIGG, B., 1984. Modification to the JPC79 colour difference formula. *J. Soc. Dyers Col.*, **100**, 128-131, 1984.

DIN, 2001. DIN6176. *Farbmetrische Bestimmung von Farbständen bei Körperfarben nach der DIN99-Formel*. Deutsches Institut für Normung, 2001.

MCLAREN, K., 1980. CIELAB hue-angle anomalies at low tristimulus ratios. *Color Res. Appl.*, **5**, 139-143, 1980.

PAULI, H., 1976. Proposed extension of the CIE recommendation on "Uniform color spaces, color difference equations, and metric color terms". *J. Opt. Soc. Am.*, **66**, 866-867, 1976.

ROBERTSON, A.R., 1990. Historical development of CIE recommended color difference equations. *Color Res. Appl.*, **15**, 167-170, 1990.

SÈVE, R., 1991. New formula for the computation of CIE 1976 hue difference. *Color Res. Appl.*, **16**, 217-218, 1991.

SÈVE, R., 1996. Practical formula for the computation of CIE 1976 hue difference. *Color Res. Appl.*, **21**, 314, 1996.

STOKES, M., BRILL, M.H., 1992. Efficient computation of ΔH^*_{ab} . *Color Res. Appl.*, **17**, 410-411, 1992.

BS EN ISO 11664-4:2011
EN ISO 11664-4:2011 (E)
CIE S 014-4/E:2007

Copies of CIE Publications are available from the National Committees of most CIE member countries, or from the CIE webshop (www.cie.co.at).

CIE Central Bureau
Kegelgasse 27
A-1030 Vienna
Austria
Tel.: +43 1 714 3187 0
Fax: +43 1 714 3187 18
e-mail: ciecb@cie.co.at
WWW: <http://www.cie.co.at/>

ICS 17.180.20

Price based on 7 pages

This page has been intentionally left blank

BSI - British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001. Fax: +44 (0)20 8996 7001 Email: orders@bsigroup.com You may also buy directly using a debit/credit card from the BSI Shop on the Website <http://www.bsigroup.com/shop>

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact Information Centre. Tel: +44 (0)20 8996 7111 Fax: +44 (0)20 8996 7048 Email: info@bsigroup.com

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration. Tel: +44 (0)20 8996 7002 Fax: +44 (0)20 8996 7001 Email: membership@bsigroup.com

Information regarding online access to British Standards via British Standards Online can be found at <http://www.bsigroup.com/BSOL>

Further information about BSI is available on the BSI website at <http://www.bsigroup.com>

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright and Licensing Manager. Tel: +44 (0)20 8996 7070 Email: copyright@bsigroup.com