

# Natural gas — Standard reference conditions

The European Standard EN ISO 13443:2005 has the status of a  
British Standard

ICS 75.060

# National foreword

This British Standard is the official English language version of EN ISO 13443:2005. It is identical with ISO 13443:1996, including Corrigendum 1:1997.

The UK participation in its preparation was entrusted to Technical Committee PTI/15, Natural gas and gas analysis, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request.

## Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the *BSI Catalogue* under the section entitled “International Standards Correspondence Index”, or by using the “Search” facility of the *BSI Electronic Catalogue* or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

**Compliance with a British Standard does not of itself confer immunity from legal obligations.**

## Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, the EN ISO title page, the EN ISO foreword page, the ISO title page, pages ii and iii, a blank page, pages 1 to 9 and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

## Amendments issued since publication

Amd. No.	Date	Comments
16149	March 2006	Renumbers BS ISO 13443:1996 as BS EN ISO 13443:2005

This British Standard, having been prepared under the direction of the Sector Board for Materials and Chemicals, was published under the authority of the Standards Board and comes into effect on 15 April 1997

© BSI 21 March 2006

ISBN 0 580 27240 0

# Contents

	Page
National foreword	Inside front cover
Foreword	iii
Text of ISO 13443	1



EUROPEAN STANDARD

**EN ISO 13443**

NORME EUROPÉENNE

EUROPÄISCHE NORM

May 2005

---

ICS 75.060

English version

## Natural gas — Standard reference conditions (ISO 13443:1996 including Corrigendum 1:1997)

Gaz naturel — Conditions de référence standard (ISO  
13443:1996, Corrigendum 1:1997 inclus)

This European Standard was approved by CEN on 17 April 2005.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**Management Centre: rue de Stassart, 36 B-1050 Brussels**

## Foreword

The text of ISO 13443:1996 has been prepared by Technical Committee ISO/TC 193, Natural gas, of the International Organization for Standardization (ISO) and has been taken over as EN ISO 13443:2005 by CMC.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by November 2005, and conflicting national standards shall be withdrawn at the latest by November 2005.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

### Endorsement notice

The text of ISO 13443:1996 has been approved by CEN as EN ISO 13443:2005 without any modifications.

INTERNATIONAL  
STANDARD

**ISO**  
**13443**

First edition  
1996-12-15

---

---

**Natural gas — Standard reference  
conditions**

*Gaz naturel — Conditions de référence standard*



Reference number  
ISO 13443:1996(E)

## Contents

	Page
Foreword	iii
Introduction	1
1 Scope	1
2 Normative reference	1
3 Standard reference conditions	1
Annex A (normative) Factors for conversion between reference conditions	3
Annex B (informative) Equations for conversion between reference conditions	5
Annex C (normative) Symbols	7
Annex D (informative) Example calculations	7
Annex E (informative) National usage of reference conditions	8
Annex F (informative) Bibliography	9
Table A.1 — Factors for conversion between reference conditions	4
Table E.1 — National usage of reference conditions	9

**Descriptors:** Natural gas, tests, measurement, computation, testing conditions.



## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 13443 was prepared by Technical Committee ISO/TC 193, *Natural gas*.

Annex A and Annex C form an integral part of this International Standard. Annex B, Annex D, Annex E and Annex F are for information only.



## Introduction

The multiplicity of so-called “standard reference conditions” of temperature, pressure and humidity (state of saturation) used in the measurement of natural-gas quality and quantity can cause much confusion. Failure to take unrecognized differences of reference conditions into account can have serious consequences in, for example, custody transfer applications. Often enough, even an experienced gas engineer may not recognize the potential for error, as the units of measurement usually employ identical terminology, irrespective of differences in the reference conditions. All of the ambiguity and its undesirable consequences may easily be removed by the adoption of a single standardized set of reference conditions. The set chosen in this International Standard will be known as the ISO standard reference conditions.

## 1 Scope

This International Standard specifies the standard reference conditions of temperature, pressure and humidity to be used for measurements and calculations carried out on natural gases, natural-gas substitutes and similar fluids.

The primary application is expected to be in international custody transfer, where the reduction to a common basis of those physical attributes of a gas which describe both its quality and quantity will simplify the practice of world trade and commerce.

## 2 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 6976:1995, *Natural gas — Calculation of calorific values, density, relative density and Wobbe index from composition*.

## 3 Standard reference conditions

The standard reference (or base) conditions of temperature, pressure and humidity (state of saturation) to be used for measurements and calculations carried out on natural gases, natural-gas substitutes and similar fluids in the gaseous state are 288,15 K and 101,325 kPa for the real dry gas.

The physical properties to which these ISO standard reference conditions apply include volume, density, relative density, compression factor, superior calorific value, inferior calorific value and Wobbe index. Full definitions of these quantities are given in ISO 6976:1995. In the cases of calorific value and Wobbe index, both the volume of gas burned and the energy released by combustion shall relate to the ISO standard reference conditions.

It is recognized, however, that in certain circumstances it may be impracticable or even unallowable to use the ISO standard reference conditions. For example, national legislation or contractual obligations may demand the use of alternative reference conditions. For this reason, Annex A provides factors for conversion between several sets of metric reference conditions which are known to be in regular use, and Annex B gives equations which enable values of properties (relating to any other known reference conditions) to be converted to values for the ISO standard reference conditions. Annex D gives some example calculations. Annex E gives the metric reference conditions which, at present time, are believed to be those in most common usage in the countries listed.

NOTE 1 Among other considerations, the ISO standard reference conditions have been chosen to conform with those standardized in ISO 5024<sup>[1]</sup> for use in the measurement of petroleum liquids and gases.

NOTE 2 288,15 K = 15 °C = 59 °F

101,325 kPa = 1,013 25 bar = 14,695 9 psia = 1 standard atmosphere (atm)

NOTE 3 In ISO 6976:1995, a dry gas is defined as one for which the mole fraction of water vapour is less than 0,000 05, but this criterion is unnecessarily restrictive in the context of this International Standard, where a mole fraction of up to 0,001 may be allowable.

NOTE 4 The conditions 273,15 K, 101,325 kPa and 288,15 K, 101,325 kPa are commonly referred to as “normal” and “(metric) standard” conditions, respectively, in gas-measurement practice (see IGU/G-64<sup>[4]</sup>, IGU/G-73<sup>[5]</sup> and IGU/G-76<sup>[6]</sup>). This usage should not be confused with “NTP” (normal temperature and pressure) and “STP” (standard temperature and pressure), both of which conventionally refer to the former conditions. The definitions of “normal” and “standard” given in ISO 7504<sup>[2]</sup> conflict with the usage given above, and are incorrect.

NOTE 5 Good practice requires that the relevant reference conditions are incorporated as part of the symbol (and *not* the unit) for the physical quantity represented wherever ambiguity is possible. For example:

- use  $Z(273,15\text{ K}, 101,325\text{ kPa})$  or  $Z(t/^\circ\text{C} = 0, p/\text{atm} = 1)$ , not  $Z_n$ , for compression factor at “normal” conditions;
- use  $V(273,15\text{ K}, 101,325\text{ kPa})\text{ m}^3$  for the volume of gas in cubic metres at “normal” conditions, not  $m_n^3$ ,  $m^3(n)$ ,  $\text{nm}^3$  or  $\text{Nm}^3$ , and certainly not simply  $\text{m}^3$ ;
- use  $V(t/^\circ\text{C} = 15, p/\text{kPa} = 101,325)\text{ m}^3$  for the volume of gas in cubic metres at “standard” conditions, not  $\text{m}^3(\text{st})$ ,  $\text{sm}^3$  or  $\text{m}_s^3$ .

Abbreviated versions such as  $Z(0)$ ,  $V(0)/\text{m}^3$  and  $V(15)/\text{m}^3$ , respectively, are acceptable when no misinterpretation is possible. In the latter case,  $V(\text{ISO})/\text{m}^3$  is probably the best designation.

## Annex A (normative)

### Factors for conversion between reference conditions

To obtain the value of a property at the reference condition given in row [b] of Table A.1 from a known value in the same units at the reference condition in row [a], multiply by the factor indicated. To carry out the reverse conversion, divide by the factor indicated.

Conversions for properties of the ideal gas are expected to be accurate to within – 0,01 % for all natural gases. For the real-gas volumetric properties (volume per unit amount, density, relative density, compression factor), the expected accuracy is – 0,02 %, and for the real-gas combustion properties (calorific values, Wobbe index) – 0,05 %.

Conversion factors for non-metric (e.g. Imperial) reference conditions are not provided, as the continued use of these — particularly in international trade — is discouraged. Most non-metric reference conditions use a temperature base of 60 °F, but several distinct pressure bases have been invoked. Annex B provides equations which will allow the conversion of property values from reference conditions not shown in Table A.1 to equivalent values for the ISO standard reference conditions.

In Table A.1, the pressure base for both combustion and volumetric metering is always 101,325 kPa and the gas is taken to be dry.

Table A.1 — Factors for conversion between reference conditions

		Metering $t_2/^\circ\text{C}$			Combustion $t_1/^\circ\text{C}$					
[a]	fi	20	20	15	25	25	25	20	20	15
		to	to	to	to	to	to	to	to	to
[b]	fi	15	00	00	20	15	00	15	00	00
1	Ideal volume	0,982 9	0,931 8	0,947 9						
2	Ideal density	1,017 4	1,073 2	1,054 9						
3	Ideal relative density	1,000 0	1,000 0	1,000 0						
4	Compression factor	0,999 9	0,999 5	0,999 6						
5	Real volume	0,982 8	0,931 3	0,947 6						
6	Real density	1,017 5	1,073 8	1,055 3						
7	Real relative density	1,000 1	1,000 3	1,000 2						
8	Molar-basis ideal superior calorific value				1,000 5	1,001 0	1,002 6	1,000 5	1,002 1	1,001 6
9	Molar-basis ideal inferior calorific value				1,000 1	1,000 1	1,000 3	1,000 0	1,000 2	1,000 2
10	Mass-basis ideal superior calorific value				1,000 5	1,001 0	1,002 6	1,000 5	1,002 1	1,001 6
11	Mass-basis ideal inferior calorific value				1,000 1	1,000 1	1,000 3	1,000 0	1,000 2	1,000 2
12	Molar-basis real superior calorific value				1,000 5	1,001 0	1,002 6	1,000 5	1,002 1	1,001 6
13	Molar-basis real inferior calorific value				1,000 1	1,000 1	1,000 3	1,000 0	1,000 2	1,000 2
14	Mass-basis real superior calorific value				1,000 5	1,001 0	1,002 6	1,000 5	1,002 1	1,001 6
15	Mass-basis real inferior calorific value				1,000 1	1,000 1	1,000 3	1,000 0	1,000 2	1,000 2
		Combustion $t_1/^\circ\text{C}$ : Metering $t_2/^\circ\text{C}$								
		[a]	fi		25:20	25:20	25:20	25:00	25:00	15:15
					to	to	to	to	to	to
		[b]	fi		25:00	15:15	00:00	15:15	00:00	00:00
16	Volume-basis ideal superior calorific value				1,073 2	1,018 4	1,076 0	0,948 9	1,002 6	1,056 6
17	Volume-basis ideal inferior calorific value				1,073 2	1,017 5	1,073 5	0,948 1	1,000 3	1,055 1
18	Ideal Wobbe index				1,073 2	1,018 4	1,076 0	0,948 9	1,002 6	1,056 6
19	Volume-basis real superior calorific value				1,073 8	1,018 5	1,076 6	0,948 6	1,002 6	1,057 0
20	Volume-basis real inferior calorific value				1,073 8	1,017 6	1,074 1	0,947 7	1,000 3	1,055 5
21	Real Wobbe index				1,073 6	1,018 5	1,076 4	0,948 7	1,002 6	1,056 9

## Annex B (informative)

### Equations for conversion between reference conditions

Equations B.1 to B.21 allow the conversion of values of the properties listed from reference conditions  $T_1/\text{K}$ ,  $T_2/\text{K}$ ,  $p_1/\text{kPa}$  and  $p_2/\text{kPa}$  to the equivalent values in the same units of measurement at the ISO standard reference conditions. The equations given are valid for the ranges:  $270 < T/\text{K} < 300$  and  $95 < p/\text{kPa} < 105$ .

The equations given use simple linear functions of temperature and pressure. These have been derived by approximating  $(\partial Z/\partial p)_T$ ,  $(\partial Z/\partial T)_p$ ,  $(\partial Z_{\text{air}}/\partial T)_p$ ,  $1/\bar{H}_S^0(\partial \bar{H}_S^0/\partial T)$  and  $1/\bar{H}_1^0(\partial \bar{H}_1^0/\partial T)$  as constants, the respective values being determined by trial calculations for a wide range of natural gases. The values used are

$$(\partial Z/\partial p)_T = -0,000\ 020/\text{kPa}$$

$$(\partial Z/\partial T)_p = +0,000\ 025/\text{K}$$

$$(\partial Z_{\text{air}}/\partial T)_p = +0,000\ 011/\text{K}$$

$$1/\bar{H}_S^0(\partial \bar{H}_S^0/\partial T) = -0,000\ 10/\text{K}$$

$$1/\bar{H}_1^0(\partial \bar{H}_1^0/\partial T) = -0,000\ 01/\text{K}$$

The values of  $\partial \bar{H}_S^0/\partial p$  and  $\partial \bar{H}_1^0/\partial p$  are taken to be zero.

Despite the simplicity of these approximations, it is expected that the accuracy of conversion will usually still be within the limits quoted in Annex A. The equations may *not* be used to increase the number of digits given in the conversion factors given in Annex A.

Note that if the reference conditions for the source data are not given in K and kPa (for example in °C or °F, and in atm, mbar, psia or psig, respectively) then these must be converted appropriately before the equations may be applied (see BS 350-1:1974<sup>[3]</sup>).

#### Ideal volume $V^0$

$$V^0(\text{ISO}) = V^0(T_2, p_2) \times 288,15 p_2/101,325 T_2 \quad \dots \text{(B.1)}$$

#### Ideal density $\rho^0$

$$\rho^0(\text{ISO}) = \rho^0(T_2, p_2) \times 101,325 T_2/288,15 p_2 \quad \dots \text{(B.2)}$$

#### Ideal relative density $d^0$

$$d^0(\text{ISO}) = d^0(T_2, p_2) \quad \dots \text{(B.3)}$$

#### Compression factor $Z$

$$Z(\text{ISO}) = Z(T_2, p_2) \times [1 + 0,000\ 020 (p_2 - 101,325)]/[1 + 0,000\ 025 (T_2 - 288,15)] \quad \dots \text{(B.4)}$$

#### Real volume $V$

$$V(\text{ISO}) = V(T_2, p_2) \times [288,15 p_2/101,325 T_2] \times [1 + 0,000\ 020 (p_2 - 101,325)]/[1 + 0,000\ 025 (T_2 - 288,15)] \quad \dots \text{(B.5)}$$

#### Real density $\rho$

$$\rho(\text{ISO}) = \rho(T_2, p_2) \times [101,325 T_2/288,15 p_2] \times [1 + 0,000\ 025 (T_2 - 288,15)]/[1 + 0,000\ 020 (p_2 - 101,325)] \quad \dots \text{(B.6)}$$

#### Real relative density $d$

$$d(\text{ISO}) = d(T_2, p_2) \times [1 + 0,000\ 014 (T_2 - 288,15)]/[1 + 0,000\ 020 (p_2 - 101,325)] \quad \dots \text{(B.7)}$$

#### Molar-basis ideal superior calorific value $\bar{H}_S^0$

$$\bar{H}_S^0(\text{ISO}) = \bar{H}_S^0(T_1, p_1) \times [1 + 0,000\ 10 (T_1 - 288,15)] \quad \dots \text{(B.8)}$$

**Molar-basis ideal inferior calorific value  $\bar{H}_1^0$** 

$$\bar{H}_1^0 \text{ (ISO)} = \bar{H}_1^0 (T_1, p_1) \times [1 + 0,000\ 01 (T_1 - 288,15)] \quad \dots \text{ (B.9)}$$

**Mass-basis ideal superior calorific value  $\hat{H}_S^0$** 

$$\hat{H}_S^0 \text{ (ISO)} = \hat{H}_S^0 (T_1, p_1) \times [1 + 0,000\ 10 (T_1 - 288,15)] \quad \dots \text{ (B.10)}$$

**Mass-basis ideal inferior calorific value  $\hat{H}_1^0$** 

$$\hat{H}_1^0 \text{ (ISO)} = \hat{H}_1^0 (T_1, p_1) \times [1 + 0,000\ 01 (T_1 - 288,15)] \quad \dots \text{ (B.11)}$$

**Molar-basis real superior calorific value  $\bar{H}_S$** 

$$\bar{H}_S \text{ (ISO)} = \bar{H}_S (T_1, p_1) \times [1 + 0,000\ 10 (T_1 - 288,15)] \quad \dots \text{ (B.12)}$$

**Molar-basis real inferior calorific value  $\bar{H}_1$** 

$$\bar{H}_1 \text{ (ISO)} = \bar{H}_1 (T_1, p_1) \times [1 + 0,000\ 01 (T_1 - 288,15)] \quad \dots \text{ (B.13)}$$

**Mass-basis real superior calorific value  $\hat{H}_S$** 

$$\hat{H}_S \text{ (ISO)} = \hat{H}_S (T_1, p_1) \times [1 + 0,000\ 10 (T_1 - 288,15)] \quad \dots \text{ (B.14)}$$

**Mass-basis real inferior calorific value  $\hat{H}_1$** 

$$\hat{H}_1 \text{ (ISO)} = \hat{H}_1 (T_1, p_1) \times [1 + 0,000\ 01 (T_1 - 288,15)] \quad \dots \text{ (B.15)}$$

**Volume-basis ideal superior calorific value  $\tilde{H}_S^0$** 

$$\tilde{H}_S^0 \text{ (ISO)} = \tilde{H}_S^0 (T_1, T_2, p_1, p_2) \times [101,325 T_2/288,15 p_2] \times [1 + 0,000\ 10 (T_1 - 288,15)] \quad \dots \text{ (B.16)}$$

**Volume-basis ideal inferior calorific value  $\tilde{H}_1^0$** 

$$\tilde{H}_1^0 \text{ (ISO)} = \tilde{H}_1^0 (T_1, T_2, p_1, p_2) \times [101,325 T_2/288,15 p_2] \times [1 + 0,000\ 01 (T_1 - 288,15)] \quad \dots \text{ (B.17)}$$

**Ideal Wobbe index  $W^0$** 

$$W^0 \text{ (ISO)} = W^0 (T_1, T_2, p_1, p_2) \times [101,325 T_2/288,15 p_2] \times [1 + 0,000\ 10 (T_1 - 288,15)] \quad \dots \text{ (B.18)}$$

**Volume-basis real superior calorific value  $\tilde{H}_S$** 

$$\tilde{H}_S \text{ (ISO)} = \tilde{H}_S (T_1, T_2, p_1, p_2) \times [101,325 T_2/288,15 p_2] \times [1 + 0,000\ 10 (T_1 - 288,15)] \times [1 + 0,000\ 025 (T_2 - 288,15)] / [1 + 0,000\ 020 (p_2 - 101,325)] \quad \dots \text{ (B.19)}$$

**Volume-basis real inferior calorific value  $\tilde{H}_1$** 

$$\tilde{H}_1 \text{ (ISO)} = \tilde{H}_1 (T_1, T_2, p_1, p_2) \times [101,325 T_2/288,15 p_2] \times [1 + 0,000\ 01 (T_1 - 288,15)] \times [1 + 0,000\ 025 (T_2 - 288,15)] / [1 + 0,000\ 020 (p_2 - 101,325)] \quad \dots \text{ (B.20)}$$

**Real Wobbe index  $W$** 

$$W \text{ (ISO)} = W (T_1, T_2, p_1, p_2) \times [101,325 T_2/288,15 p_2] \times [1 + 0,000\ 10 (T_1 - 288,15)] \times \{ [1 + 0,000\ 020 (p_2 - 101,325)] / [1 + 0,000\ 036 (T_2 - 288,15)] \}^{-1/2} \quad \dots \text{ (B.21)}$$



## Annex C (normative)

### Symbols

Symbol	Meaning	SI unit (or multiple)
$d$	relative density	—
$\bar{H}_1$	molar-basis inferior calorific value	$\text{kJ mol}^{-1}$
$\hat{H}_1$	mass-basis inferior calorific value	$\text{MJ kg}^{-1}$
$\tilde{H}_1$	volume-basis inferior calorific value	$\text{MJ m}^{-3}$
$\bar{H}_S$	molar-basis superior calorific value	$\text{kJ mol}^{-1}$
$\hat{H}_S$	mass-basis superior calorific value	$\text{MJ kg}^{-1}$
$\tilde{H}_S$	volume-basis superior calorific value	$\text{MJ m}^{-3}$
$p$	(absolute) pressure	kPa
$T$	(absolute) temperature	K
$t$	Celsius temperature = $T - 273,15$	$^{\circ}\text{C}$
$V$	volume	$\text{m}^3$
$W$	Wobbe index	$\text{MJ m}^{-3}$
$Z$	compression factor	—
$\rho$	density	$\text{kg m}^{-3}$

#### Subscripts

- 1 for the combustion reference condition  
 2 for the volumetric or metering reference condition

#### Superscript

- o for the ideal-gas state (no superscript indicates the real-gas state)

## Annex D (informative)

### Example calculations

The examples given below are all for real dry natural gases consisting preponderantly (greater than about 70 % molar) of methane.

#### EXAMPLE 1

What is the compression factor at ISO standard reference conditions of a natural gas which has a compression factor of 0,997 1 at a temperature of 273,15 K and a pressure of 101,325 kPa?

From Table A.1, line 4, column 3 (used inversely):

$$Z(\text{ISO}) = 0,997\ 1 \times (1/0,999\ 6) = 0,997\ 5$$

The same value (to four significant digits) is obtained from equation (B.4).

#### EXAMPLE 2

What is the volume occupied at ISO standard reference conditions of a natural gas which occupies 1 000  $\text{m}^3$  at normal conditions?

The term “normal conditions” is taken to mean 273,15 K ( $0^{\circ}\text{C}$ ) at 101,325 kPa.

From Table A.1, line 5, column 3 (used inversely):

$$V(\text{ISO}) = 1\ 000 \times (1/0,947\ 6) = 1\ 055,3\ \text{m}^3$$

The same value (to five significant digits) is obtained from equation (B.5).

## EXAMPLE 3

What is the mass-basis superior calorific value at ISO standard reference conditions of a natural gas determined as having a calorific value of 54,21 MJ·kg<sup>-1</sup> at 25 °C and a pressure of 100 kPa?

Molar-basis and mass-basis calorific values are taken to be independent of pressure  $p_1$  within the pressure range given in Annex B (which covers the range of normal atmospheric variation); the pressure assignment is therefore irrelevant in this case.

From Table A.1, line 14, column 2:

$$\hat{H}_S(\text{ISO}) = 54,21 \times 1,001\ 0 = 54,26 \text{ MJ}\cdot\text{kg}^{-1}$$

The same value (exactly) is obtained from equation (B.14).

## EXAMPLE 4

What is the volume-basis superior calorific value at ISO standard reference conditions of a natural gas determined as having a calorific value of 38,57 MJ·m<sup>-3</sup> at 60 °F and 101,560 kPa?

This example cannot be solved using Table A.1 because that table is only valid for a pressure of 101,325 kPa and does not include the Fahrenheit temperature quoted.

First convert 60 °F to the kelvin scale:

$$60\ \text{°F} = [(60 - 32) \times 5/9] + 273,15 = 288,706\ \text{K}$$

Then, from equation (B.19):

$$\begin{aligned} \tilde{H}_S^o(\text{ISO}) &= \{38,57 \times 101,325 \times 288,706 \times [1 + 0,000\ 10(288,706 - 288,15)] \times \\ &\quad [1 + 0,000\ 025(288,706 - 288,15)]\} / \{288,15 \times 101,560 \times \\ &\quad [1 + 0,000\ 020(101,560 - 101,325)]\} \\ &= 38,56 \text{ MJ}\cdot\text{m}^{-3} \text{ to four significant digits.} \end{aligned}$$

## EXAMPLE 5

What is the volume-basis inferior calorific value at ISO standard reference conditions of a natural gas determined as having a calorific value of 37,35 MJ·m<sup>-3</sup> when the volume of gas burned is measured at 0 °C, combustion takes place at 25 °C and the reference pressure in both cases is one standard atmosphere?

The term “one standard atmosphere” is taken to mean 101,325 kPa.

From Table A.1, line 20, column 4:

$$\tilde{H}_I(\text{ISO}) = 37,35 \times 0,947\ 7 = 35,40 \text{ MJ}\cdot\text{m}^{-3}$$

The same value (to four significant digits) is obtained from equation (B.20).

## Annex E (informative)

### National usage of reference conditions

For those countries where the use of non-metric (e.g. Imperial) measurement units and reference conditions are still in use alongside metric units and reference conditions, only the metric reference conditions are listed.

In Table E.1 below:

$t_1$ /°C = combustion reference temperature

$t_2$ /°C = volumetric or metering reference temperature

The reference pressure is 101,325 kPa in all cases.

Table E.1 — National usage of reference conditions

	$t_1/^\circ\text{C}$	$t_2/^\circ\text{C}$		$t_1/^\circ\text{C}$	$t_2/^\circ\text{C}$
Argentina		15	Indonesia		0
Australia	15	15	Iran		15
Austria	25	0	Ireland	15	15
Belgium	25	0	Italy	25	0
Brazil		0	Japan	0	0
Canada	15	15	Netherlands	25	0
China	20	20	New Zealand		15
Czechoslovakia	25	20 and 0	Norway		15
Denmark	25	0	Pakistan		15
Egypt		15	Romania	25	15 and 0
Finland		15	Russia	25	20 and 0
France	0	0	Spain	0	0
Germany	25	0	Sweden		0
Hong Kong		15	United Kingdom	15	15
Hungary		0	USA	15	15
India		0	Yugoslavia	0	0

## Annex F (informative)

### Bibliography

- [1] ISO 5024:1976, *Petroleum liquids and gases — Measurement — Standard reference conditions*.
- [2] ISO 7504:1984, *Gas analysis — Vocabulary*.
- [3] BS 350-1:1974, *Conversion factors and tables — Part 1: Basis of tables — Conversion factors*.
- [4] IGU/G-64:1964, *Report of the committee on documentation and sundry questions — Report of the subcommittee on units*, pp. 24–38.
- [5] IGU/G-73:1973, *Report of the committee on documentation and sundry questions — Report of the subcommittee on units*, pp. 83–101.
- [6] IGU/G-76:1976, *Report of the committee on statistics, documentation and sundry questions — Report of the subcommittee on units*, pp. 36–43.

---

---

## BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

### Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

### Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001. Fax: +44 (0)20 8996 7001. Email: [orders@bsi-global.com](mailto:orders@bsi-global.com). Standards are also available from the BSI website at <http://www.bsi-global.com>.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

### Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre. Tel: +44 (0)20 8996 7111. Fax: +44 (0)20 8996 7048. Email: [info@bsi-global.com](mailto:info@bsi-global.com).

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration. Tel: +44 (0)20 8996 7002. Fax: +44 (0)20 8996 7001. Email: [membership@bsi-global.com](mailto:membership@bsi-global.com).

Information regarding online access to British Standards via British Standards Online can be found at <http://www.bsi-global.com/bsonline>.

Further information about BSI is available on the BSI website at <http://www.bsi-global.com>.

### Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright & Licensing Manager. Tel: +44 (0)20 8996 7070. Fax: +44 (0)20 8996 7553. Email: [copyright@bsi-global.com](mailto:copyright@bsi-global.com).