# BS EN ISO 17932:2011



# **BSI Standards Publication**

Palm oil — Determination of the deterioration of bleachability index (DOBI) and carotene content (ISO 17932:2011)



### National foreword

This British Standard is the UK implementation of EN ISO 17932:2011. It supersedes BS EN ISO 17932:2007 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee AW/307, Oilseeds, animal and vegetable fats and oils and their by-products.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© BSI 2011

ISBN 978 0 580 70241 9

ICS 67.200.10

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 September 2011.

# Amendments issued since publication

Date Text affected

# **EUROPEAN STANDARD**

# NORME EUROPÉENNE

# EUROPÄISCHE NORM

September 2011

**EN ISO 17932** 

ICS 67.200.10

Supersedes EN ISO 17932:2007

## **English Version**

# Palm oil - Determination of the deterioration of bleachability index (DOBI) and carotene content (ISO 17932:2011)

Huile de palme - Détermination de la détérioration de l'indice de blanchiment (DOBI) et de la teneur en carotène (ISO 17932:2011)

Palmöl - Bestimmung des Bleichindex zur Beurteilung der Qualität von rohem Palmöl (DOBI Deterioration of bleachability index) sowie des Carotingehaltes (ISO 17932:2011)

This European Standard was approved by CEN on 14 September 2011.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

# **Foreword**

This document (EN ISO 17932:2011) has been prepared by Technical Committee ISO/TC 34 "Food products" in collaboration with Technical Committee CEN/TC 307 "Oilseeds, vegetable and animal fats and oils and their by-products - Methods of sampling and analysis" the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by March 2012, and conflicting national standards shall be withdrawn at the latest by March 2012.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 17932:2007.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

### **Endorsement notice**

The text of ISO 17932:2011 has been approved by CEN as a EN ISO 17932:2011 without any modification.

# **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 17932 was prepared by Technical Committee ISO/TC 34, *Food products*, Subcommittee SC 11, *Animal and vegetable fats and oils*.

This second edition cancels and replaces the first edition (ISO 17932:2005), which has been technically revised.

# Palm oil — Determination of the deterioration of bleachability index (DOBI) and carotene content

# 1 Scope

This International Standard specifies a method for the determination of the deterioration of bleachability index (DOBI) of crude palm oil and the carotene content of crude or bleached palm oil and their fractions by spectrophotometric examination in the ultraviolet and visible range of the spectrum.

# 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 661, Animal and vegetable fats and oils — Preparation of test sample

ISO/IEC 17025, General requirements for the competence of testing and calibration laboratories

ISO Guide 34, General requirements for the competence of reference material producers

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 3.1

# deterioration of bleachability index DOBI

 $I_{\mathsf{DoB}}$ 

ratio of the absorbance of the test portion at 446 nm to that at 269 nm, as determined spectrophotometrically in a 10 mm (1 cm) pathlength cell

NOTE DOBI is expressed to one decimal place without a dimension.

### 3.2

# carotene content of vegetable oil

 $w_{c}$ 

mass fraction of β-carotene in oil

NOTE The carotene content of vegetable oil is expressed in milligrams per kilogram.

# 4 Principle

A homogenized sample is dissolved in isooctane and the absorbance is measured spectrophotometrically at 446 nm and 269 nm. The DOBI value is the ratio of the absorbance at 446 nm to that at 269 nm. The test is a measure of the ease of refining crude palm oil. A low DOBI value can indicate difficulty in refining the oil to a low Lovibond colour. The absorbance at 446 nm is used for calculation of the carotene content.

### 5 Reagents

WARNING — Attention is drawn to the regulations which specify the handling of dangerous substances. Technical, organizational and personal safety measures shall be followed.

During the analysis, unless otherwise stated, use only reagents of recognized analytical grade and distilled or demineralized water or water of equivalent purity.

**5.1 Solvent**: isooctane (2,2,4-trimethylpentane), having an absorbance less than 0,12 at 230 nm and less than 0,05 at 250 nm against water, measured in a cell with a pathlength of 10 mm (1 cm).

# 6 Apparatus

The glassware used for the determination shall be thoroughly cleaned and rinsed with the solvent (5.1) before use, so that it is free from impurities having an absorbance within the wavelength range of 220 nm to 500 nm.

Usual laboratory apparatus and, in particular, the following.

**6.1 Spectrometer**, capable of operating in the ultraviolet and visible range and using 10 mm (1 cm) pathlength quartz cells and preferably having a recording instrument.

Before use, it is recommended that the wavelength and absorbance scales of the spectrometer be checked as follows.

- a) **Wavelength scale**: This may be checked using a reference material consisting of an optical glass filter containing holmium oxide which has distinct absorption bands. The reference material is designed for the verification and calibration of the wavelength scales of visible and ultraviolet spectrophotometers having nominal spectral bandwidths of 5 nm or less. The holmium glass filter is measured in the absorbance mode against an air blank over the wavelength range of 640 nm to 240 nm. For each spectral bandwidth (0,10 0,25 0,50 1,00 1,50 2,00 and 3,00), a baseline correction is performed with an empty cell holder. The wavelengths of the spectral bandwidth are listed in the certificate of the reference material<sup>1)</sup>. All procedures shall be implemented in accordance with ISO/IEC 17025 and ISO Guide 34.
- b) **Absorbance scale**: Secondary calibration standards can be used to check the ordinate accuracy. The set of standards consisting of gray glass filters<sup>2)</sup> provide nominal absorbance, *A*, values of 0,3*A*, 0,5*A*, and 1,0*A* respectively. The ordinate readings of the filters are measured at each of the selected wavelengths and the readings obtained compared with those listed in the certificate of the secondary calibration standards.

Alternatively, prepare a 200 mg/l solution of potassium chromate<sup>3)</sup> in 0,05 mol/l potassium hydroxide solution. Transfer 25 ml of this solution to a volumetric flask, capacity 500 ml, ISO 1042<sup>[1]</sup>, class A, and make up to the mark with additional 0,05 mol/l potassium hydroxide solution. The absorbance of this solution, measured in a cell 10 mm thick at 275 nm against the 0,05 mol/l potassium hydroxide solution, should be 0,200  $\pm$  0,005.

WARNING — Potassium chromate is very toxic, dangerous to the environment and a carcinogen by inhalation. Attention is drawn to regulations which specify handling and disposal procedures for toxic and dangerous substances. Users should be aware of and comply with technical, organizational, and personal safety measures.

- **6.2 Matched quartz cells**, of pathlength 10 mm (1 cm), suitable for measurements at ultraviolet and visible wavelengths.
- **6.3** Volumetric flask, capacity 25 ml, ISO 1042<sup>[1]</sup>, class A.
- **6.4** Analytical balance, capable of being read to the nearest 0,001 g.

<sup>1)</sup> Starna Scientific Ltd (<a href="www.starna.com">www.starna.com</a>) is an example of a supplier of suitable holmium filters and potassium dichromate sealed cell available commercially. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO of these products.

<sup>2)</sup> A suitable supplier is PerkinElmer Ltd. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO of the supplier named.

<sup>3)</sup> NIST 935a is an example of a suitable product available commercially. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO of the product named.

# 7 Sampling

Sampling is not part of the method specified in this International Standard. A recommended sampling method is given in ISO 5555<sup>[2]</sup>.

A representative sample should have been sent to the laboratory. It should not have been damaged or changed during transport or storage.

Ensure that the sample is taken and stored away from strong light, kept cold and contained in completely filled glass containers, hermetically sealed with ground glass or waxed cork stoppers.

# 8 Preparation of test sample

Prepare the test sample in accordance with ISO 661.

### 9 Procedure

#### 9.1 General

Melt the sample at 60 °C to 70 °C and homogenize thoroughly before taking a test portion. Filter through a fast filter paper [Whatman No. 1<sup>4</sup>] if the sample contains impurities and is not clear.

# 9.2 Test portion and preparation of the test solution

Weigh, to the nearest 0,1 mg, about 0,1 g to 0,5 g of the test sample (Clause 8), sufficient to obtain absorbance values between 0,2 and 0,8, into a 25 ml volumetric flask (6.3).

Dissolve the test portion in a few millilitres of isooctane (5.1) at ambient temperature and then make up to the mark with the same solvent. Mix thoroughly.

# 9.3 Determination

Rinse a quartz cell (6.2) three times with the test solution (9.2). Fill the cell with the test solution and fill a second matched cell with isooctane (5.1). Measure the absorbance of the test solution against the solvent by means of the spectrometer (6.1) at wavelengths 446 nm and 269 nm. If necessary, dilute the original test solution (9.2) to a measured volume and take further readings so that the observed absorptions are between (0,2 and 0,8) absorbance values.

# 10 Calculation

**10.1** The deterioration of bleachability index (DOBI),  $I_{DoB}$ , is calculated as follows:

© ISO 2011 – All rights reserved

<sup>4)</sup> Example of a suitable product available commercially. This information is given for the convenience of users of this document and does not constitute an endorsement by ISO of this product. Equivalent products may be used if they can be shown to lead to the same results.

# BS EN ISO 17932:2011 **ISO 17932:2011(E)**

$$I_{\text{DoB}} = \frac{A_{446}}{A_{269}}$$

where

 $A_{446}$  is the absorbance at 446 nm;

 $A_{269}$  is the absorbance at 269 nm.

Express the results to one decimal place.

**10.2** Calculate the total carotene content,  $w_c$ , of oil as  $\beta$ -carotene, in milligrams per kilogram, using the following formula:

$$w_{\rm c} = \frac{383 \, \Delta A}{l \, \rho}$$

where

 $= 10^6/2$  610, in which 2 610 is the percentage solution extinction coefficient of β-carotene in isooctane at 446 nm;

 $\Delta A$  is the observed difference in absorption, A, between the sample solution and the solvent (5.1);

*l* is the pathlength, in centimetres, of the cell;

ρ is the concentration, in grams per 100 ml, used for absorption measurement.

Express the results to the nearest whole number.

# 11 Precision

# 11.1 Interlaboratory test

Details of an interlaboratory test on the precision of the method for the DOBI and carotene content are summarized in Annex A and Annex B respectively. It is possible that the values derived from these interlaboratory tests are not applicable to concentration ranges and matrices other than those given.

# 11.2 Repeatability

The absolute difference between two independent single test results, obtained using the same method on identical test material in the same laboratory by the same operator using the same equipment within a short interval of time, will in not more than 5 % of cases exceed the values of r given in Table A.1 and Table B.1.

# 11.3 Reproducibility

The absolute difference between two single test results, obtained using the same method on identical test material in different laboratories with different operators using different equipment, will in not more than 5 % of cases exceed the values of *R* given in Table A.1 and Table B.1.

# 12 Test report

The test report shall contain at least the following information:

a) all information necessary for the complete identification of the sample;

- b) the sampling method used, if known;
- c) the test method used, with reference to this International Standard (ISO 17932:2011);
- d) all operating details not specified in this International Standard, or regarded as optional, together with any details of any incident which may have influenced the test result;
- e) the test result obtained;
- f) if the repeatability has been checked, the final quoted result obtained.

# Annex A

(informative)

# Results of an interlaboratory test on DOBI

An international collaborative trial using six samples of palm oil was organized by the Department of Standards Malaysia (DSM) in 2003 in accordance with ISO 5725-1 $^{[3]}$  and ISO 5725-2 $^{[4]}$ . See Table A.1.

Table A.1 — Precision data for DOBI value

Parameter	Sample						
	CPO1	CPO2	CPO3	CPO4	CPO5	CPO6	
No. of laboratories participating	14	14	14	14	14	14	
No. of laboratories after eliminating outliers	13	14	13	14	11	12	
Number of tests in all laboratories	37	40	38	39	31	34	
Mean	2,43	2,42	2,04	2,01	3,49	3,48	
Repeatability standard deviation, $s_r$	0,04	0,05	0,04	0,03	0,04	0,06	
Coefficient of variation of repeatability, %	1,7	2,1	1,9	1,7	1,2	1,8	
Repeatability limit, r	0,12	0,14	0,11	0,09	0,12	0,18	
Reproducibility standard deviation, $s_R$	0,12	0,16	0,09	0,12	0,13	0,12	
Coefficient of variation of reproducibility, %	4,8	6,7	4,4	5,7	3,6	3,3	
Reproducibility limit, R	0,32	0,45	0,25	0,32	0,35	0,32	

# Annex B

(informative)

# Results of an interlaboratory test on carotene content

A national inter-laboratory test was carried out in 2001 by the Malaysian Palm Oil Board. Nine laboratories in Malaysia participated. The results are summarized in Table B.1.

Table B.1 — Summary of statistical results (β-carotene content, expressed as mg/kg)

Parameter	Sample					
Faranietei	CPO A	СРО В	СРО С	CPO D		
No. of participating laboratories, $N$	9	9	9	9		
No. of laboratories retained after eliminating outliers, <i>n</i>	9	9	8	9		
Mean value, mg/kg	608	579	614	522		
Repeatability standard deviation, $s_r$	2,2	3,2	2,2	2,6		
Coefficient of variation of repeatability, %	0,4	0,6	0,4	0,5		
Repeatability limit, r	6,1	9,1	6,2	7,3		
Reproducibility standard deviation, $s_R$	16,1	13,5	9,5	11,5		
Coefficient of variation of reproducibility, %	2,6	2,3	1,5	2,2		
Reproducibility limit, R	45,2	37,9	26,5	32,2		
NOTE Statistical analysis of results was carried out according to ISO 5725-1 <sup>[3]</sup> and ISO 5725-2 <sup>[4]</sup> .						

Overall repeatability standard deviation  $s_r = 2,6$ 

Overall repeatability limit r = 7,2

Overall reproducibility standard deviation  $s_R = 12,7$ 

Overall reproducibility limit R = 35,4

# **Bibliography**

- [1] ISO 1042, Laboratory glassware One-mark volumetric flasks
- [2] ISO 5555, Animal and vegetable fats and oils Sampling
- [3] ISO 5725-1, Accuracy (trueness and precision) of measurement methods and results Part 1: General principles and definitions
- [4] ISO 5725-2, Accuracy (trueness and precision) of measurement methods and results Part 2: Basic method for the determination of repeatability and reproducibility of a standard measurement method
- [5] BS 684: Section 2.20, Determination of carotene in vegetable oils
- [6] Malaysian Standard MS 817:9, Determination of carotene content
- [7] MPOB Test Methods, MPOB p2.6, Methods of test for palm oil and palm oil products Determination of carotene content
- [8] SWOBODA, P.A.T. UV-VIS spectrophotometric assays for palm oil quality. In: *Proceedings of the International Conference on Palm Oil Product Technology in the Eighties*, 1981-06-22/24, Kuala Lumpur, 1983, pp. 433-445
- [9] SIEW, W.L. Deterioration of bleachability index (DOBI). *Inform* 2001, **12**, pp. 1183-1187





# British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

### About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards -based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

#### Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

## **Buying standards**

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

# **Subscriptions**

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

**PLUS** is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

# **BSI Group Headquarters**

389 Chiswick High Road London W4 4AL UK

### **Revisions**

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

# Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

#### **Useful Contacts:**

### **Customer Services**

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com
Email (enquiries): cservices@bsigroup.com

# Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

### Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

### **Copyright & Licensing**

Tel: +44 20 8996 7070 Email: copyright@bsigroup.com

