BS EN ISO 18541-4:2015



BSI Standards Publication

Road vehicles — Standardized access to automotive repair and maintenance information (RMI)

Part 4: Conformance test



National foreword

This British Standard is the UK implementation of EN ISO 18541-4:2015.

The UK participation in its preparation was entrusted to Technical Committee AUE/20, Vehicle on-board diagnostics, repair and maintenance information.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2015. Published by BSI Standards Limited 2015

ISBN 978 0 580 71391 0

ICS 43.040.15; 43.180

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 November 2015.

Amendments/corrigenda issued since publication

Date Text affected

EN ISO 18541-4 **EUROPEAN STANDARD**

NORME EUROPÉENNE **EUROPÄISCHE NORM**

November 2015

ICS 43.040.15; 43.180

English Version

Road vehicles - Standardized access to automotive repair and maintenance information (RMI) - Part 4: Conformance test (ISO 18541-4:2015)

Véhicules routiers - Normalisation de l'accès aux informations relatives à la réparation et à la maintenance pour l'automobile (RMI) - Partie 4: Tests de conformité (ISO 18541-4:2015)

Straßenfahrzeuge - Standardisierter Zugang zur Reparatur und Wartungsinformationen (RMI) - Teil 4: Konformitätsprüfungen (ISO 18541-4:2015)

This European Standard was approved by CEN on 12 September 2015.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

European foreword

This document (EN ISO 18541-4:2015) has been prepared by Technical Committee ISO/TC 22 "Road vehicles" in collaboration with Technical Committee CEN/TC 301 "Road vehicles" the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by May 2016, and conflicting national standards shall be withdrawn at the latest by May 2016.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 18541-4:2015 has been approved by CEN as EN ISO 18541-4:2015 without any modification.

Co	ntent	S	Page					
Fore	eword		xiii					
Intr	oductio	n	xiv					
1	Scop	e	1					
2	-	native references						
_		Terms, definitions and abbreviated terms						
3	3.1	Terms and definitions	1					
	3.2	Abbreviated terms						
4	Conf	ormance test basic principles and clustering						
T	4.1	Basic principles for conformance test case definition						
	4.2	Conformance test clustering						
		4.2.1 General						
		4.2.2 Main conformance test case clusters	3					
5	Test	case structure	7					
	5.1	Conformance test case — General structure						
		5.1.1 Overview						
		5.1.2 Test case reference number and title [RMI-CT] [title]						
		5.1.3 Test purpose						
		5.1.4 Configuration						
		5.1.5 Preamble (setup state)						
		5.1.7 Postamble						
	5.2	Result criteria						
6	CT cl	uster 1 — Test technical infrastructure	0					
U	6.1	[RMI-CT_TREQ-13, 14, 15, 16, 18, Annex A] Test client configuration						
	0.1	6.1.1 Overview	9					
		6.1.2 Test purpose						
		6.1.3 Configuration	9					
		6.1.4 Preamble (setup state)						
		6.1.5 Test execution						
	6.0	6.1.6 Postamble						
	6.2	[RMI-CT_TREQ-17] Test presentation formats for information packages						
		6.2.2 Test purpose						
		6.2.3 Configuration						
		6.2.4 Preamble (setup state)						
		6.2.5 Test execution						
		6.2.6 Postamble	10					
7	CT cl	uster 2 — Test client's external interfaces	10					
	7.1	[RMI-CT_TREQ-9] Test vehicle communication interface (VCI)						
		7.1.1 Overview	10					
		7.1.2 Test purpose						
		7.1.3 Configuration						
		7.1.4 Preamble (setup state)						
		7.1.5 Test execution 7.1.6 Postamble						
	7.2	[RMI-CT_TREQ-11] Test parts ordering for security-related features						
	,	7.2.1 Overview						
		7.2.2 Test purpose						
		7.2.3 Configuration						
		7.2.4 Preamble (setup state)						
		7.2.5 Test execution						
		7.2.6 Postamble	12					

	7.3		CT_TREQ-12] Test partnered accessory provider systems	
		7.3.1	Overview	
		7.3.2	Test purpose	12
		7.3.3	Configuration	12
		7.3.4	Preamble (setup state)	
		7.3.5	Test execution	
		7.3.6	Postamble	13
8	CT c	luctor 3	— Test user authentication, authorization and administration	12
O	8.1	TRMI_	CT_UC1.1] Test to register IO for use of the VM RMI system	13 12
	0.1	8.1.1	Overview	13
		8.1.2	Test purpose	
		8.1.3	Configuration	
		8.1.4	Preamble (setup state)	
		8.1.5	Test execution	
		8.1.6	Postamble	
	8.2		CT_UC1.2_A] Test to register IO employee for use of the VM RMI system —	
	0.2		rio A	14
		8.2.1	Overview	
		8.2.2	Test purpose	
		8.2.3	Configuration	
		8.2.4	Preamble (setup state)	
		8.2.5	Test execution	
	8.3		CT_UC1.2_B] Test to register IO employee for use of the VM RMI system —	10
	0.0		rio B	15
		8.3.1	Overview	
		8.3.2	Test purpose	
		8.3.3	Configuration	
		8.3.4	Preamble (setup state)	
		8.3.5	Test execution	
		8.3.6	Postamble	
	8.4		CT_UC1.3] Test to maintain IO status	
	-	8.4.1	Overview	
		8.4.2	Test purpose	
		8.4.3	Configuration	
		8.4.4	Preamble (setup state)	
		8.4.5	Test execution	
		8.4.6	Postamble	
	8.5		CT_UC1.4] Test to maintain user status	
		8.5.1	- Overview	
		8.5.2	Test purpose	
		8.5.3	Configuration	
		8.5.4	Preamble (setup state)	
		8.5.5	Test execution	
		8.5.6	Postamble	
	8.6	[RMI-0	CT_UC1.5] Test to de-register an IO employee	18
		8.6.1	Overview	18
		8.6.2	Test purpose	18
		8.6.3	Configuration	18
		8.6.4	Preamble (setup state)	18
		8.6.5	Test execution	18
		8.6.6	Postamble	
	8.7	[RMI-0	CT_UC1.6] Test login to VM RMI system	
		8.7.1	Overview	
		8.7.2	Test purpose	19
		8.7.3	Configuration	19
		8.7.4	Preamble (setup state)	
		8.7.5	Test execution	
		8.7.6	Postamble	20

	8.8	[RMI-CT	[_UC1.7] Test for granting access to security-related RMI	
		8.8.1	Overview	20
		8.8.2	Test purpose	20
		8.8.3	Configuration	20
		8.8.4	Preamble (setup state)	20
		8.8.5	Test execution	20
		8.8.6	Postamble	21
9	CT cl	uctor 1. —	· Test functional user interface implementation	21
9	9.1	IRMI_CT	'FREQ-1] Test for RMI access mode	21 21
	7.1	9.1.1	Overview	
		9.1.2	Test purpose	
		9.1.3	Configuration	
		9.1.4	Preamble (setup state)	
		9.1.5	Test execution	
		9.1.6	Postamble	
	9.2		[-FREQ-2] Test for registration and login support	
	7.2	9.2.1	Overview	
		9.2.2	Test purpose	
		9.2.3	Configuration	
		9.2.4	Preamble (setup state)	
		9.2.5	Test execution	
		9.2.6	Postamble	
		9.2.7	Result criteria	
	9.3		Γ_FREQ-3] Test for implemented use cases map	
	7.5	9.3.1	Overview	
		9.3.2	Test purpose	
		9.3.3	Configuration	
		9.3.4	Preamble (setup state)	
		9.3.5	Test execution	
		9.3.6	Postamble	
	9.4		[FREQ-4] Test for download area	
	7.1	9.4.1	Overview	
		9.4.2	Test purpose	
		9.4.3	Configuration	
		9.4.4	Preamble (setup state)	
		9.4.5	Test execution	
		9.4.6	Postamble	
	9.5		'-FREQ-5] Test for navigational pathway	
	7.0	9.5.1	Overview	
		9.5.2	Test purpose	
		9.5.3	Configuration	
		9.5.4	Preamble (setup state)	
		9.5.5	Test execution	
		9.5.6	Postamble	
4.0	om 1			
10			Test payment for RMI	
	10.1		C_UC2] Test payment for RMI	
			Overview	
			Test purpose	
			Configuration	
			Preamble (setup state)	
			Test execution	
		10.1.6	Postamble	26
11	CT cl		Test for vehicle identification	
	11.1		[_UC3.1] Test vehicle identification through use of VIN	
		11.1.1	Overview	26
			Test purpose	
		11.1.3	Configuration	26

		11.1.4 Preamble (setup state)	
		11.1.5 Test execution	27
		11.1.6 Postamble	27
	11.2	[RMI-CT_UC3.2] Test vehicle identification via product features	27
		11.2.1 Overview	27
		11.2.2 Test purpose	27
		11.2.3 Configuration	
		11.2.4 Preamble (setup state)	
		11.2.5 Test execution	
		11.2.6 Postamble	
12	CT cl	uster 7 — Test selection methods for RMI	28
	12.1	[RMI-CT_UC4.1] Test selection of information type	
	12.1	12.1.1 Overview	
		12.1.2 Test purpose	
		12.1.3 Configuration	
		12.1.4 Preamble (setup state)	
		12.1.5 Test execution	
		12.1.6 Postamble	
	122		
	12.2	[RMI-CT_UC4.2] Test search by standardized terms	
		12.2.1 Overview	
		12.2.2 Test purpose	
		12.2.3 Configuration	
		12.2.4 Preamble (setup state)	
		12.2.5 Test execution	
		12.2.6 Postamble	
	12.3	[RMI-CT_UC4.3] Test navigation using product structure	
		12.3.1 Overview	
		12.3.2 Test purpose	
		12.3.3 Configuration	30
		12.3.4 Preamble (setup state)	30
		12.3.5 Test execution	30
		12.3.6 Postamble	31
	12.4	[RMI-CT_UC4.4] Test selection by document identifier	31
		12.4.1 Overview	
		12.4.2 Test purpose	
		12.4.3 Configuration	
		12.4.4 Preamble (setup state)	
		12.4.5 Test execution	31
		12.4.6 Postamble	
13		uster 8 — Test retrieval of information packages	
	13.1	[RMI-CT_UC5.1.1] Test retrieval of general workshop procedures	
		13.1.1 Overview	
		13.1.2 Test purpose	
		13.1.3 Configuration	
		13.1.4 Preamble (setup state)	32
		13.1.5 Test execution	32
		13.1.6 Postamble	32
	13.2	[RMI-CT_UC5.1.2] Test retrieval of body repair procedures	32
		13.2.1 Overview	
		13.2.2 Test purpose	
		13.2.3 Configuration	
		13.2.4 Preamble (setup state)	
		13.2.5 Test execution	
		13.2.6 Postamble	
	13.3	[RMI-CT_UC5.1.3] Test retrieval of temporary repair procedures	
	13.3		
		13.3.1 Overview	
		13.3.2 Test purpose	33

	13.3.3	Configuration	
	13.3.4	Preamble (setup state)	34
	13.3.5	Test execution	34
	13.3.6	Postamble	34
13.4	[RMI-C'	Γ_UC5.1.4] Test retrieval of preparation for PTI	34
	13.4.1	Overview	34
	13.4.2	Test purpose	34
	13.4.3	Configuration	34
	13.4.4	Preamble (setup state)	
	13.4.5	Test execution	
	13.4.6	Postamble	
13.5		$\Gamma_{\rm UC5.2]$ Test retrieval of wiring diagrams	
10.0	13.5.1	Overview	
	13.5.2	Test purpose	
	13.5.3	Configuration	
	13.5.4	Preamble (setup state)	
	13.5.5	Test execution	
	13.5.6	Postamble	
13.6		Γ_UC5.3] Test retrieval of technical service bulletin	
13.0	13.6.1	Overview	
	13.6.2		
		Test purpose	
	13.6.3	Configuration	
	13.6.4	Preamble (setup state)	
	13.6.5	Test execution	
10.7	13.6.6	Postamble	
13.7		Γ_UC5.4] Test retrieval of recall information	
	13.7.1	Overview	
	13.7.2	Test purpose	
	13.7.3	Configuration	
	13.7.4	Preamble (setup state)	
	13.7.5	Test execution	
	13.7.6	Postamble	
13.8	[RMI-C'	Γ_UC5.5] Test retrieval of maintenance schedule	
	13.8.1	Overview	
	13.8.2	Test purpose	
	13.8.3	Configuration	
	13.8.4	Preamble (setup state)	
	13.8.5	Test execution	38
	13.8.6	Postamble	
13.9	[RMI-C'	Γ_UC5.6.1] Test retrieval of spare parts (identification)	39
	13.9.1		
	13.9.2	Test purpose	39
	13.9.3	Configuration	39
	13.9.4	Preamble (setup state)	39
	13.9.5	Test execution	
	13.9.6	Postamble	
13.10	[RMI-C	Γ_UC5.6.2] Test retrieval of spare parts (access)	
		Overview	
		Test purpose	
		Configuration	
		Preamble (setup state)	
		Test execution	
		Postamble	
13 11		$\Gamma_{\rm UC5.7.1]$ Test retrieval of accessory information factory fitted (included	TU
10.11		ral RMI)	40
		Overview	
		Test purpose Configuration	
	13.11.3	Configuration	41

		13.11.4 Preamble (setup state)	
		13.11.5 Test execution	
	40.40	13.11.6 Postamble	41
	13.12	[RMI-CT_UC5.7.2] Test retrieval of accessory information partnered with a VM	4.1
		part number	
		13.12.1 Overview	
		13.12.2 Test purpose	
		13.12.3 Configuration	
		13.12.4 Preamble (setup state)	
		13.12.5 Test execution 13.12.6 Postamble	
	12 12		42
	13.13	[RMI-CT_UC5.7.3] Test retrieval of fitting information for accessories with no VM part number	12
		13.13.1 Overview	
		13.13.2 Test purpose	
		13.13.3 Configuration	42 1.2
		13.13.4 Preamble (setup state)	42 42
		13.13.5 Test execution	
		13.13.6 Postamble	
	13 14	[RMI-CT_UC5.8] Test retrieval of labour times	
	13.11	13.14.1 Overview	
		13.14.2 Test purpose	
		13.14.3 Configuration	
		13.14.4 Preamble (setup state)	
		13.14.5 Test execution	
		13.14.6 Postamble	
	13.15	[RMI-CT_UC5.9] Test retrieval of converted vehicle information	
	10.10	13.15.1 Overview	44
		13.15.2 Test purpose	
		13.15.3 Configuration	
		13.15.4 Preamble (setup state)	
		13.15.5 Test execution	
		13.15.6 Postamble	
	13.16	[RMI-CT_UC5.10] Test retrieval of special tool information	
		13.16.1 Overview	
		13.16.2 Test purpose	45
		13.16.3 Configuration	
		13.16.4 Preamble (setup state)	
		13.16.5 Test execution	45
		13.16.6 Postamble	46
14	CT clu	ster 9 — Test vehicle diagnostics	46
LT	14.1	[RMI-CT_UC6.1] Test DTC resolution	
	11.1	14.1.1 Overview	
		14.1.2 Test purpose	
		14.1.3 Configuration	
		14.1.4 Preamble (setup state)	
		14.1.5 Test execution	
		14.1.6 Postamble	
	14.2	[RMI-CT_UC6.2] Test VM symptom resolution	
	- ··-	14.2.1 Overview	
		14.2.2 Test purpose	
		14.2.3 Configuration	
		14.2.4 Preamble (setup state)	
		14.2.5 Test execution	
		14.2.6 Postamble	
	14.3	[RMI-CT_UC6.3] Test integrated diagnostics	
		14.3.1 Overview	
		14.3.2 Test purpose	48

		14.3.3	Configuration	48
		14.3.4 F	Preamble (setup state)	48
		14.3.5 T	Test execution	48
		14.3.6 F	Postamble	48
15	CT ch	ictor 10	- Test updating, replacing and tuning of modules (ECUs)	10
13	15.1		UC7.1] Test updating and replacing modules information	
	13.1		Oc7.1] Test updating and replacing modules mior mation Overview	
			Cest purpose	
			Configuration	
			Preamble (setup state)	
			Test execution	
	152		Postamble	
	15.2		UC7.2] Test tuning kit Overview	
			Cest purpose	
			Configuration Preamble (setup state)	
			Teatingle (secup state)	
		15.2.6 F	Postamble	50
16	CT cl	ıster 11 –	- Test electronic maintenance history	50
	16.1	[RMI-CT_	UC8] Test electronic maintenance history	50
		16.1.1	Overview	50
		16.1.2 T	Test purpose	51
		16.1.3	Configuration	51
			Preamble (setup state)	
			Test execution	
		16.1.6 F	Postamble	51
17	CT ch	ictor 12	- Test repair assistance, technical support	E 1
1/	17.1	ISTEL 12 —	UC9] Test repair assistance, technical supportUC9] Test repair assistance technical support	
	17.1		OcerviewOcerani assistance technical support	
			Fest purpose	
			Configuration	
			Preamble (setup state)	
			Teatrible (secup state)	
			Postamble	
18	CT cl	ıster 13 —	- Test request for contact information	52
	18.1	[RMI-CT_	UC10.1] Test for retrieval of electronic tool information (Diagnostic,	
			mming, VCI)	
			Overview	
			l'est purpose	
		18.1.3	Configuration	53
		18.1.4 F	Preamble (setup state)	53
		18.1.5 T	lest execution	53
		18.1.6 F	Postamble	53
	18.2	[RMI-CT_	UC10.2] Test for retrieval of test equipment and diagnostic tool	
		manufact	rurers information	53
		18.2.1	Overview	53
		18.2.2 T	lest purpose	53
		18.2.3	Configuration	53
		18.2.4 F	Preamble (setup state)	54
		18.2.5	Test execution	54
		18.2.6 F	Postamble	54
	18.3	[RMI-CT_	UC10.3] Test for retrieval of training material (delegate information)	54
		18.3.1	Overview	54
		18.3.2 T	Test purpose	54
		18.3.3	Configuration	54

	18.3.4	Preamble (setup state)	.54
	18.3.5	Test execution	
	18.3.6	Postamble	
18.4		Γ_UC10.4] Test for retrieval of redistributor contact information	
10.1	18.4.1	Overview	
	18.4.2	Test purpose	
		Configuration	
	18.4.3		
	18.4.4	Preamble (setup state)	
	18.4.5	Test execution	
	18.4.6	Postamble	
18.5	-	Γ_UC10.5] Test for retrieval of republisher information	
	18.5.1	Overview	
	18.5.2	Test purpose	
	18.5.3	Configuration	.56
	18.5.4	Preamble (setup state)	.56
	18.5.5	Test execution	.56
	18.5.6	Postamble	.56
18.6	[RMI-C]	[_UC10.6] Test for retrieval of inspection and testing services information	.56
	18.6.1	Overview	
	18.6.2	Test purpose	.57
	18.6.3	Configuration	
	18.6.4	Preamble (setup state)	
	18.6.5	Test execution	
	18.6.6	Postamble	
18.7		Γ_UC10.7] Test for retrieval of alternative fuels retrofit system information	
10.7	_	Overview	
	18.7.1		
	18.7.2	Test purpose	
	18.7.3	Configuration	
	18.7.4	Preamble (setup state)	
	18.7.5	Test execution	
	18.7.6	Postamble	.58
18.8		Γ_UC10.8] Test for retrieval of engine and components	
		facturing information	
	18.8.1	Overview	
	18.8.2	Test purpose	. 58
	18.8.3	Configuration	.58
	18.8.4	Preamble (setup state)	.58
	18.8.5	Test execution	.59
	18.8.6	Postamble	.59
18.9		$\Gamma_{\rm L}$ UC10.9] Test for retrieval of component and parts manufacturer information .	
	18.9.1	Overview	
	18.9.2	Test purpose	
		Configuration	
	18.9.4	Preamble (setup state)	
	18.9.5	Test execution	
		Postamble	
10 10		$\Gamma_{\rm UC10.10]$ Test for retrieval of validation of independently developed non-	.00
18.10			<i>(</i> 0
		tary VCI information	
		Overview	
		Test purpose	
		Configuration	
		Preamble (setup state)	
		Test execution	
	18.10.6	Postamble	.61
CT clu	ster 14 .	— Test courses and training information	61
19.1		Γ_UC11] Test for courses and training information	
		Overview	
	19.1.2	Test purpose	
		r - r	-

19

		19.1.3	Configuration	
		19.1.4	Preamble (setup state)	61
		19.1.5	Test execution	
		19.1.6	Postamble	62
20	CT ch	uster 15	— Test data administration requirements	62
	20.1	[RMI-C	T_TREQ-1] Test general access-related data administration	62
	_0.1	20.1.1	Overview	62
		20.1.2	Test purpose	
		20.1.3	Configuration	
		20.1.4	Preamble (setup state)	
		20.1.5	Test execution	
		20.1.6	Postamble	
	20.2		T_TREQ-2] Test administration of IO data by the VM	
		20.2.1	Overview	
		20.2.2	Test purpose	
		20.2.3	Configuration	
		20.2.4	Preamble (setup state)	
		20.2.5	Test execution	
		20.2.6	Postamble	
	20.3	[RMI-C	T_TREQ-3] Test administration of IO employee data by the VM	
			Overview	
		20.3.2	Test purpose	
		20.3.3	Configuration	
		20.3.4	Preamble (setup state)	
		20.3.5	Test execution	63
		20.3.6	Postamble	64
	20.4	[RMI-C	T_TREQ-4] Test administration of payment data by VM	64
		20.4.1	0verview	64
		20.4.2	Test purpose	64
		20.4.3	Configuration	
		20.4.4	Preamble (setup state)	64
		20.4.5	Test execution	64
		20.4.6	Postamble	64
	20.5	[RMI-C	T_TREQ-5] Test administration of access event data by VM	64
		20.5.1	0verview	64
		20.5.2	Test purpose	64
		20.5.3	Configuration	64
		20.5.4	Preamble (setup state)	
		20.5.5	Test execution	
			Postamble	65
	20.6		T_TREQ-6] Test administration of access event data to security-related RMI	
		by VM		
		20.6.1	Overview	
		20.6.2	Test purpose	
		20.6.3	Configuration	
		20.6.4	Preamble (setup state)	
		20.6.5	Test execution	
		20.6.6	Postamble	65
21	CT ch	uster 16	— Test VM software installation on the IO client	66
	21.1		T_TREQ-20] Test for requirements for installing VM-specific software on	
			client	66
		21.1.1	Overview	
		21.1.2	Test purpose	
		21.1.3	Configuration	
		21.1.4	Preamble (setup state)	
		21.1.5	Test execution	
			Postamble	

	21.2		1_1REQ-21] lest for requirements for updating of installed VM data and	
		applica	tions on the IO client	
		21.2.1	Overview	
		21.2.2	Test purpose	67
		21.2.3	Configuration	67
		21.2.4	Preamble (setup state)	
		21.2.5	Test execution	
			Postamble	
	21.3		T_TREQ-22] Test for requirements for the operation of VM-specific	
	21.5		re on the IO client	67
		21.3.1	Overview	
		_	Test purpose	
		21.3.2		
		21.3.3	Configuration	
			Preamble (setup state)	
		21.3.5	Test execution	
			Postamble	68
	21.4		T_TREQ-23] Test for requirements for the uninstalling of VM-specific	
			re on the IO client	
		21.4.1	Overview	
		21.4.2	Test purpose	68
		21.4.3	Configuration	68
		21.4.4	Preamble (setup state)	69
		21.4.5		
		21.4.6	Postamble	
	21.5		T_TREQ-24] Test for requirements for restoring in case of an abnormal	
	21.0		ation of the VM specific software on the IO client	69
		21.5.1	•	
		21.5.1	Test purpose	
		21.5.3	• •	
			Preamble (setup state)	
		21.5.4	Test execution	
			Postamble	
22		uster 17	— Test VM RMI operations	70
	22.1		T_TREQ-25] Test for VM RMI system availability time	
		22.1.1	0verview	70
		22.1.2	Test purpose	70
		22.1.3	Configuration	70
		22.1.4	Preamble (setup state)	70
		22.1.5	Test execution	
			Postamble	
	22.2		T_TREQ-26] Test for support for the usage of the VM RMI system	
		_	Overview	
		22.2.2	Test purpose	
			Configuration	
			Preamble (setup state)	
		22.2.5		
			Test execution	
		22.2.6	Postamble	/ 1
23	CT clu	uster 18	— Test trust centre (certificate management)	72
	23.1		T_TREQ-10] Test for trust centre (certificate management)	
			Overview	
		23.1.2	Test purpose	
		23.1.3	Configuration	
			Preamble (setup state)	
		23.1.5	Test execution	
		23.1.6	Postamble	
Biblio	graphy	y		73

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

ISO 18541-4 was prepared by the European Committee for Standardization (CEN) Technical Committee CEN/TC 301, *Road vehicles*, in collaboration with ISO Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 31, *Data communication*, in accordance with the agreement on technical cooperation between ISO and CEN (Vienna Agreement).

ISO 18541 consists of the following parts, under the general title *Road vehicles* — *Standardized access to automotive repair and maintenance information (RMI)*:

- Part 1: General information and use case definition
- Part 2: Technical requirements
- Part 3: Functional user interface requirements
- Part 4: Conformance test

Introduction

This International Standard includes the requirements to be fulfilled by Repair and Maintenance Information (RMI) systems as applied by the

EUROPEAN COMMISSION - ENTERPRISE AND INDUSTRY DIRECTORATE-GENERAL, Consumer goods - Automotive industry EC mandate M/421 $^{[\![1]\!]}$

"MANDATE TO THE EUROPEAN STANDARDIZATION ORGANISATIONS FOR STANDARDIZATION IN THE FIELD OF VEHICLE OBD, REPAIR AND MAINTENANCE INFORMATION"

dated Brussels, 21 January 2008.

This mandate relates to the EC type-approval system for vehicles falling into the scopes of Directives 2007/46/EC[4], 2002/24/EC[2] and 2003/37/EC[3] and, in particular, to requirements for access to vehicle repair and maintenance information by independent operators.

This part of ISO 18541 only covers the access to automotive repair and maintenance information for light passenger, commercial vehicles¹⁾ and heavy duty vehicles²⁾ based on Directive 2007/46/EC[4].

The purpose of the EC Mandate M/421^[1] is to develop a standard or set of standards which specify the requirements to provide "standardized access to repair and maintenance information (RMI)" for independent operators.

The information included in this part of ISO 18541 derives from the legislative requirements on European level in the field of repair and maintenance information and related security requirements and can be referenced by legislation in other countries.

¹⁾ REGULATION (EC) No 715/2007 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2007 on type approval of motor vehicles with respect to emissions from light passenger and commercial vehicles (Euro 5 and Euro 6) and on access to vehicle repair and maintenance information [5] and COMMISSION REGULATION (EC) No 692/2008 of 18 July 2008 implementing and amending Regulation (EC) No 715/2007 of the European Parliament and of the Council on type-approval of motor vehicles with respect to emissions from light passenger and commercial vehicles (Euro 5 and Euro 6) and on access to vehicle repair and maintenance information [6] and amending COMMISSION REGULATION (EU) No 566/2011 of 8 June 2011 [7] amending Regulation (EC) No 715/2007 of the European Parliament [5] and of the Council and Commission Regulation (EC) No 692/2008 [6] as regards access to vehicle repair and maintenance information.

²⁾ REGULATION (EC) No 595/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 June 2009 on type approval of motor vehicles with respect to emissions from heavy duty vehicles (Euro VI) and on access to vehicle repair and maintenance information^[5], COMMISSION REGULATION (EU) No 582/2011 of 25 May 2011 implementing and amending Regulation (EC) No 595/2009 of the European Parliament and of the Council with respect to emissions from heavy duty vehicles (Euro VI), and COMMISSION REGULATION (EU) No 64/2012 of 23 January 2012^[Z] amending Regulation (EU) No 582/2011 2011 implementing and amending Regulation (EC) No 595/2009 of the European Parliament and of the Council with respect to emissions from heavy duty vehicles (Euro VI).

Road vehicles — Standardized access to automotive repair and maintenance information (RMI) —

Part 4:

Conformance test

1 Scope

This part of ISO 18541 specifies a conformance test for a vehicle manufacturer assessment of self-conformance of the VM RMI system. The conformance test cases follow the use case definition of ISO 18541-1 and the requirements stated in ISO 18541-2 and ISO 18541-3.

The primary but not exclusive purpose of this part of ISO 18541 is to provide information to the VM RMI system provider to build and test the VM RMI system against the conformance test cases. This final step in the development process of the VM RMI system is an enabler for all providers that their VM RMI system meets a high degree of functional requirements expected by the end user.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 18541-1:2014, Road vehicles — Standardized access to automotive repair and maintenance information (RMI) — Part 1: General information and use case definition

ISO 18541-2:2014, Road vehicles — Standardized access to automotive repair and maintenance information (RMI) — Part 2: Technical requirements

ISO 18541-3:2014, Road vehicles — Standardized access to automotive repair and maintenance information (RMI) — Part 3: Functional user interface requirements

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 18541-1, ISO 18541-2, ISO 18541-3 and the following apply.

3.1.1

conformance

to determine whether a product or system meets some specified standard that has been developed for efficiency or interoperability

3.1.2

self-conformance

conformance test performed by the owner of the product or system, that is required to meet some specified standard that has been developed for efficiency or interoperability

3.2 Abbreviated terms

AR authorized repairer

CT conformance test

FREQ functional user interface requirement

IO independent operator

RMI repair and maintenance information

TREQ technical requirement

UC use case

VCI vehicle communication interface

VM vehicle manufacturer

4 Conformance test basic principles and clustering

4.1 Basic principles for conformance test case definition

Basic principles have been established as a guideline to define the RMI conformance test cases.

- BP1: The primary objective of the conformance test is to support a "VM assessment of self-conformance" of the VM RMI system. The conformance test is not limited to usage by VMs. Some test cases may not be performed by third parties due to the nature of the test cases.
- BP2: The person performing the conformance test shall be qualified i.e. test experience, knowledge about vehicle coverage in VM RMI system, familiarity and understanding of the relevant ISO 18541 documents, and shall have a keen understanding of the business application of the VM RMI system.
- BP3: The conformance test addresses the access behaviour to automotive RMI and not the VM RMI system implementation.
- BP4: The conformance test is a positive test in order to test the proper functioning of the VM RMI system i.e., correct input data provides correct output data.
- BP5: The person performing the conformance test shall verify that the purpose of the use case is achieved following the descriptions of the VM regarding the implementation of the use case and the steps to enter the input and to obtain the output according to FREQ 5 in ISO 18541-3.
- BP6: The name of the test case should be the same as the name of the use case (see ISO 18541-1) or requirement (see ISO 18541-2 and ISO 18541-3).
- BP7: Each test case should have a preamble (setup state).
- BP8: Classification for each test case is included in order to support the classification criteria specified for use cases and requirements.
- BP9: A test case is only applicable if the use case or requirement is supported by the VM RMI system.
- BP10: Some test cases can require payment or a valid subscription before processing the next step.

CAUTION — The person performing the conformance test is responsible for entering valid data and correctly executing necessary actions in order to maintain integrity of the VM RMI system and the vehicle.

4.2 Conformance test clustering

4.2.1 General

4.2.2 provides an overview of all conformance test clusters and the associated test cases for mandatory and optional use cases and requirements. Test cases for optional use cases and requirements will only be possible if the VM RMI system has implemented them. Each test case is assigned to one conformance test cluster. The clusters cover technical areas, where the assigned test case(s) apply.

Each test case is identified by the mnemonic "[RMI-CT_UCx.y], [RMI-CT_TREQ-m], [RMI-CT_FREQ-n]" combined with an alpha-numeric number. The name of the test case is descriptive.

4.2.2 Main conformance test case clusters

Table 1 defines the main conformance test case clusters.

Table 1 — Main conformance test case clusters

# — Main title of cluster	Brief description	Test case reference
1 – Test technical infrastructure	This cluster describes the test cases that check the behaviour of the VM RMI system	[RMI-CT_TREQ-13, 14, 15, 16, 18, Annex A] Test client configuration,
	to support the technical requirements, i.e., client hardware and software installation and configuration is correct, as stated in ISO 18541-2.	[RMI-CT_TREQ-17] Test presentation formats for information packages.
2 – Test client's external inter-	This cluster describes the test cases that check the behaviour of the VM RMI system	[RMI-CT_TREQ-9] Test vehicle communication interface (VCI),
faces	to support the technical requirements, i.e., client communication to the vehicle, as stated in ISO 18541-2.	[RMI-CT_TREQ-11] Test parts ordering for security-related features,
	Stated III 150 105 11 2.	[RMI-CT_TREQ-12] Test partnered accessory provider systems.
3 – Test user authentication,	This cluster describes the test cases that check the behaviour of the VM RMI system	[RMI-CT_UC1.1] Test to register IO for use of the VM RMI system,
authorization and administration	to obtain a license to use, keep user data and access level up-to-date, protect RMI against misuse and how to access the VM RMI system as stated in ISO 18541-1.	[RMI-CT_UC1.2_A] Test to register IO employee for use of the VM RMI system – Scenario A,
		[RMI-CT_UC1.2_B] Test to register IO employee for use of the VM RMI system – Scenario B,
		[RMI-CT_UC1.3] Test to maintain IO status,
		[RMI-CT_UC1.4] Test to maintain user status,
		[RMI-CT_UC1.5] Test to de-register an IO employee,
		[RMI-CT_UC1.6] Test login to VM RMI system,
		[RMI-CT_UC1.7] Test for granting access to security-related RMI.

 Table 1 (continued)

# — Main title of cluster	Brief description	Test case reference	
1	This cluster describes the test cases	[RMI-CT_FREQ-1] Test for RMI access mode,	
user interface implementation	that check the behaviour of the VM RMI system to support the requirements of the functional user interface as stated in	[RMI-CT_FREQ-2] Test for registration and login support,	
	ISO 18541-3.	Result criteria:	
		In case one of three expected functions (i.e. registration, login, password recovery) is not possible, FREQ-4 has failed.	
		In case all functions are possible, but the correct process is not provided in the use cases map, FREQ-5 has failed.	
		[RMI-CT_FREQ-3] Test for implemented use cases map,	
		[RMI-CT_FREQ-4] Test for download area,	
		[RMI-CT_FREQ-5] Test for navigational pathway.	
5 – Test payment for RMI	This cluster describes the test cases that check the behaviour of the VM RMI system to support the handling of payments as stated in ISO 18541-1.	[RMI-CT_UC2] Test payment for RMI.	
6 -Test for vehicle identification	This cluster describes the test cases that test the behaviour of the VM RMI system	[RMI-CT_UC3.1] Test vehicle identification through use of VIN,	
	to support the identification of a specific vehicle and type of vehicle as stated in ISO 18541-1.	[RMI-CT_UC3.2] Test vehicle identification via product features.	
7 – Test selection methods for RMI	This cluster describes the test cases that check the behaviour of the VM RMI system to support the selection methods	[RMI-CT_UC4.1] Test selection of information type,	
	— by information types,	[RMI-CT_UC4.2] Test search by standardized terms,	
	— by standardized terms,	[RMI-CT_UC4.3] Test navigation using prod-	
	— by product structure, and	uct structure,	
	— by document identifier,	[RMI-CT_UC4.4] Test selection by document	
	as stated in ISO 18541-1.	identifier.	

 Table 1 (continued)

# — Main title of cluster	Brief description	Test case reference
8 – Test retrieval of information	This cluster describes the test cases that check the behaviour of the VM RMI system	[RMI-CT_UC5.1.1] Test retrieval of general workshop procedures,
packages	to support the retrieval of selected repair and maintenance information packages	[RMI-CT_UC5.1.2] Test retrieval of body repair procedures,
	— workshop procedures (for body repair, temporary repair, periodic technical inspection),	[RMI-CT_UC5.1.3] Test retrieval of temporary repair procedures,
	— wiring diagrams,	[RMI-CT_UC5.1.4] Test retrieval of preparation for PTI,
	technical service bulletins,recall information, and	[RMI-CT_UC5.2] Test retrieval of wiring diagrams,
	— maintenance information, as stated in ISO 18541-1.	[RMI-CT_UC5.3] Test retrieval of technical service bulletin,
	as stated in 150 105 11 1.	[RMI-CT_UC5.4] Test retrieval of recall information,
		[RMI-CT_UC5.5] Test retrieval of maintenance schedule,
		[RMI-CT_UC5.6.1] Test retrieval of spare parts (identification),
		[RMI-CT_UC5.6.2] Test retrieval of spare parts (access),
		[RMI-CT_UC5.7.1] Test retrieval of accessory information factory fitted (included in general RMI),
		[RMI-CT_UC5.7.2] Test retrieval of accessory information partnered with a VM part number,
		[RMI-CT_UC5.7.3] Test retrieval of fitting information for accessories with no VM part number,
		[RMI-CT_UC5.8] Test retrieval of labour times,
		[RMI-CT_UC5.9] Test retrieval of converted vehicle information,
		[RMI-CT_UC5.10] Test retrieval of special tool information.
9 – Test vehicle	This cluster describes the test cases that	[RMI-CT_UC6.1] Test DTC resolution,
diagnostics	check the behaviour of DTC resolution, symptom resolution or integrated diagnos-	[RMI-CT_UC6.2] Test VM symptom resolution,
	tics as stated in ISO 18541-1.	[RMI-CT_UC6.3] Test integrated diagnostics.
10 – Test updating, replacing and	This cluster describes the test cases that check the behaviour of the VM RMI sys-	[RMI-CT_UC7.1] Test updating and replacing modules information,
tuning of modules (ECUs)	tem to support the legitimate update or replacement of vehicle modules/ECUs to return to an operational state after repair or tuning with a VM application as stated in ISO 18541-1 using a known VCI and approved by the VM which meet the standards required by legislation.	[RMI-CT_UC7.2] Test tuning kit.

 Table 1 (continued)

# — Main title of cluster	Brief description	Test case reference
11 – Test electronic maintenance history	This cluster describes the test cases that check the behaviour of the VM RMI system to get access and to update the history of VM prescribed maintenance actions for a specific vehicle as identified by the VIN as stated in ISO 18541-1.	[RMI-CT_UC8] Test electronic maintenance history.
12 – Test repair assistance, techni- cal support	This cluster describes the test cases that check the behaviour of the VM RMI system to get advice from the VM if repair assistance or technical support is needed as stated in ISO 18541-1.	[RMI-CT_UC9] Test repair assistance technical support.
13 – Test request for contact infor- mation	This cluster describes the test cases that check the behaviour of the VM RMI system to support the request contact information	[RMI-CT_UC10.1] Test for retrieval of electronic tool information (diagnostic, reprogramming, VCI),
	in order to receive information about — electronic tool,	[RMI-CT_UC10.2] Test for retrieval of test equipment and diagnostic tool manufacturers information,
	— diagnostics, — VCI,	[RMI-CT_UC10.3] Test for retrieval of training material (delegate information),
	— training material,— etc.,	[RMI-CT_UC10.4] Test for retrieval of redistributor contact information,
	as stated in ISO 18541-1.	[RMI-CT_UC10.5] Test for retrieval of republisher information,
		[RMI-CT_UC10.6] Test for retrieval of inspection and testing services information,
		[RMI-CT_UC10.7] Test for retrieval of alternative fuels retrofit system information,
		[RMI-CT_UC10.8] Test for retrieval of engine and components remanufacturing information,
		[RMI-CT_UC10.9] Test for retrieval of component and parts manufacturer information,
		[RMI-CT_UC10.10] Test for retrieval of validation of independently developed non-proprietary VCI information.
14 – Test courses and training information	This cluster describes the test cases that check the behaviour of the VM RMI system to get information regarding training course availability (online or Web-based training) as stated in ISO 18541-1.	[RMI-CT_UC11] Test for courses and training information.

Table 1 (continued)

# — Main title of cluster	Brief description	Test case reference
15 – Test data administration	This cluster describes the test cases that check the behaviour of the VM RMI system	[RMI-CT_TREQ-1] Test general access-related data administration,
requirements		[RMI-CT_TREQ-2] Test administration of IO data by the VM,
		[RMI-CT_TREQ-3] Test administration of IO employee data by the VM,
		[RMI-CT_TREQ-4] Test administration of payment data by VM,
		[RMI-CT_TREQ-5] Test administration of access event data by VM,
		[RMI-CT_TREQ-6] Test administration of access event data to security-related RMI by VM.
16 – Test VM soft- ware installation on the IO client	This cluster describes the test cases that check the behaviour of the VM RMI system to check that the VM software installed on the "off-the-shelf" PC behaves according to the requirement as specified in ISO 18541-2.	[RMI-CT_TREQ-20] Test for requirements for installing VM-specific software on the IO client,
		[RMI-CT_TREQ-21] Test for requirements for updating of installed VM data and applications on the IO client,
		[RMI-CT_TREQ-22] Test for requirements for the operation of VM-specific software on the IO client,
		[RMI-CT_TREQ-23] Test for requirements for the uninstalling of VM-specific software on the IO client,
		[RMI-CT_TREQ-24] Test for requirements for restoring in case of an abnormal termination of the VM specific software on the IO client.
17 – Test VM RMI operations	This cluster describes the test cases that check the behaviour of the VM RMI system	[RMI-CT_TREQ-25] Test for VM RMI system availability time,
	to check that the VM RMI system is operational except for scheduled maintenance downtime and whether the VM offers support for the usage of the VM RMI system as stated in ISO 18541-2.	[RMI-CT_TREQ-26] Test for support for the usage of the VM RMI system.
18 – Test trust centre (certificate management)	This cluster describes the test cases that check the behaviour of the VM RMI system to check that the client has installed the software driver to support the digital certificate and that the infrastructure processes the certificate content as stated in ISO 18541-2.	[RMI-CT_TREQ-10] Test for trust centre (certificate management).

5 Test case structure

5.1 Conformance test case — General structure

5.1.1 Overview

Each test case is structured by six titles. In the following, details and examples for each of these titles (ordered list) are given.

5.1.2 Test case reference number and title [RMI-CT_...] [title]

A reference to the corresponding test case requirement is specified through unique abbreviation, number and title as follows:

- a) [RMI-CT_UCx.y] of ISO 18541-1;
- b) [RMI-CT_TREQ-m] of ISO 18541-2;
- c) [RMI-CT_FREQ-n] of ISO 18541-3.

where

- "x", "y" are numeric numbers as assigned in ISO 18541-1, and
- "m", "n" are numeric numbers which are used in ascending numeric order.

5.1.3 Test purpose

The test purpose gives a short description of the test case and a reference to the corresponding requirement specified in ISO 18541-1 to ISO 18541-3.

NOTE The test case approach depends on the definition of the referenced requirement in ISO 18541-1 to ISO 18541-3.

5.1.4 Configuration

The configuration subclause addresses the configuration of the VM RMI system.

5.1.5 Preamble (setup state)

The preamble defines preconditions which are used for preparation and initialization of the VM RMI system with a view to performing the specific test. For example, a precondition could be the successful establishment of an Internet connection.

5.1.6 Test execution

Test execution of a single test case is organized in steps. These steps are described in <u>Table 2</u> as shown in the example below.

Table 2 — Test execution example

Step #	Description
1	Description of 1st test step.
2	Description of 2 nd test step.
N	Description of N th test step.

5.1.7 Postamble

The "Postamble" defines post conditions which are used to return the VM RMI system back to a definite state. For example, a post condition could be "go back to standardized navigation".

5.2 Result criteria

The test result criteria are composed of three different results as listed in <u>Table 3</u>.

Table 3 — Test result criteria

Result	Definition
Pass	The test purpose was achieved by passing all steps in the test execution as expected.
Deficiency	The test purpose was achieved with opportunities for improvement identified and documented in detail.
Fail	The test purpose was not achieved. Reason(s) shall be documented in detail.
Not applicable	The test case is not applicable because the use case or requirement is not supported by the VM RMI system.

All test cases comply with the test result criteria specified in <u>Table 3</u>, except those test cases which require specific test results.

6 CT cluster 1 — Test technical infrastructure

6.1 [RMI-CT_TREQ-13, 14, 15, 16, 18, Annex A] Test client configuration

6.1.1 Overview

This is a conformance test for checking the client configuration requirements specified in ISO 18541-2.

6.1.2 Test purpose

The purpose of the conformance test is to verify that the used client and the installed software are according to requirements as specified in ISO 18541-2.

6.1.3 Configuration

No additional configuration required.

6.1.4 Preamble (setup state)

Setup conditions: None.

6.1.5 Test execution

Table 4 defines the test execution.

Table 4 — [RMI-CT_TREQ-13, 14, 15, 16, 18, Annex A] Test client configuration test execution

Step #	Description
1	Check if the client PC and the installed software are according to the technical requirements TREQ-13 Type of device in ISO 18541-2.
2	Check if the client PC and the installed software are according to the technical requirements TREQ-14 Hardware features in ISO 18541-2.
3	Check if the client PC and the installed software are according to the technical requirements TREQ-15 Operating systems in ISO 18541-2.
4	Check if the client PC and the installed software are according to the technical requirements TREQ-16 Web browser in ISO 18541-2.
5	Check if the client PC and the installed software are according to the technical requirements TREQ-18 Internet connection (VM recommendations i.e., bandwidth, type of network) in ISO 18541-2.
6	Check if the client PC and the installed software are according to the actual version of ISO 18541-2, ANNEX A.

6.1.6 Postamble

No post conditions.

6.2 [RMI-CT_TREQ-17] Test presentation formats for information packages

6.2.1 Overview

This is a conformance test for checking the presentation formats for information packages specified in ISO 18541-2.

6.2.2 Test purpose

The purpose of the conformance test is to verify that information packages are presented using the open text and open graphic formats or can be printed using standard software plug-ins as specified in ISO 18541-2 and available via the download area as specified in ISO 18541-3.

6.2.3 Configuration

No additional configuration required.

6.2.4 Preamble (setup state)

Existence of download area as defined in FREQ-4 of ISO 18541-3.

6.2.5 Test execution

Table 5 defines the test execution.

Table 5 — [RMI-CT_TREQ-17] Test presentation formats for information packages test execution

Step #	Description
1	Check the existence of download area as stated in FREQ-4.
2	In case no download area is present, go to step #4.
3	Download and install, if needed, all applications/plug-ins available via download area.
4	Perform all tests present in cluster 8 to verify that all information packages are properly displayed without any additional applications/plug-ins.

6.2.6 Postamble

No post conditions.

7 CT cluster 2 — Test client's external interfaces

7.1 [RMI-CT_TREQ-9] Test vehicle communication interface (VCI)

7.1.1 Overview

This is a conformance test for checking the VCI requirements specified in ISO 18541-2.

7.1.2 Test purpose

This conformance test is used to verify that the VM RMI system client communicates to the vehicle via a VCI compliant to TREQ-9 VCI in ISO 18541-2.

7.1.3 Configuration

The communication device for testing is validated by VM according to VM RMI web site statement.

Any necessary driver for communication device as required by the VM RMI technical requirements according to both VM and VCI manufacturer installation instructions is installed [e.g. TREQ-9 Vehicle communication interface (VCI)].

7.1.4 Preamble (setup state)

Setup conditions are as follows:

- all test cases passed of CT cluster 1 Test technical infrastructure;
- if required by the VM, a battery charger with minimum requirements according to VM specification is connected to the vehicle;
- VCI is connected to PC and OBD plug of the vehicle;
- navigate to VM RMI home page;
- according to VM RMI system registration, login and payment might be required.

7.1.5 Test execution

Table 6 defines the test execution.

Table 6 — [RMI-CT_TREQ-9] Test vehicle communication interface (VCI) test execution

Step #	Description
1	Start one conformance test among RMI_CT_UC 6.3, RMI_CT_UC 7.1, RMI_CT_UC 7.2.
2	Check if VM RMI application indicates VCI detection.
3	Proceed with the same conformance test up to the first step where confirmation of communication between vehicle and VM RMI system is possible (e.g. reading of data from ECU, activation of actuators via ECU).
4	Abort conformance test under execution before writing on ECU has started.
5	In case the VCI is not detected, verify and check if all necessary configuration and preamble steps are properly fulfilled (this can require technical support).
	Repeat step #1 to step #4.

7.1.6 Postamble

No post conditions.

7.2 [RMI-CT_TREQ-11] Test parts ordering for security-related features

7.2.1 Overview

This is a conformance test for checking the interface to parts ordering system for security-related parts if and only if such an interface is supported by the VM RMI system as specified in ISO 18541-2.

7.2.2 Test purpose

This conformance test is used to verify the proper functioning of the interface to the online ordering system. The test case is only applicable if the online ordering of security-related parts is supported by the VM RMI system.

7.2.3 Configuration

VM RMI system supports an online ordering feature for security-related parts.

7.2.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid digital certificate and authorization for access to security-related RMI according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- according to VM RMI system registration, login and payment might be required.

7.2.5 Test execution

<u>Table 7</u> defines the test execution.

Table 7 — [RMI-CT_TREQ-11] Test parts ordering for security-related features test execution

Step #	Description
1	Check if VM RMI system supports the online interface for ordering security-related parts. If not, the conformance test [RMI-CT_TREQ-11] is not applicable.
2	Follow the instruction given by the VM RMI system to order security-related parts online.
3	Check if the interface is functioning.

NOTE [RMI-CT_TREQ-11] is applicable only if the VM RMI system supports the online ordering of security-related parts.

7.2.6 Postamble

No post conditions.

7.3 [RMI-CT_TREQ-12] Test partnered accessory provider systems

7.3.1 Overview

This is a conformance test for checking the interface to a partnered accessory provider system if and only if such an interface is supported by the VM RMI system as specified in ISO 18541-2.

7.3.2 Test purpose

This conformance test is used to verify the proper functioning of the interface or link to the partnered accessory provider system. The test case is only applicable if an interface or a link to a partnered accessory provider system is supported by the VM RMI system.

7.3.3 Configuration

VM RMI system supports an interface or a link to a partnered accessory provider system.

7.3.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- according to VM RMI system registration, login and payment might be required.

7.3.5 Test execution

<u>Table 8</u> defines the test execution.

Table 8 — [RMI-CT_TREQ-12] Test partnered accessory provider systems test execution

Step #	Description
	Access UC 5.7.2 Accessory information partnered with a VM part number following instructions according to FREQ-5.
	Check if VM RMI system supports an interface or a link to a partnered accessory provider system. If not, the conformance test [RMI-CT_TREQ-12] is not applicable.
3	Check if the interface or link is functioning.

NOTE [RMI-CT_TREQ-12] is applicable only if the VM RMI system supports the interface or link to a partnered accessory provider system.

7.3.6 Postamble

No post conditions.

8 CT cluster 3 — Test user authentication, authorization and administration

8.1 [RMI-CT_UC1.1] Test to register IO for use of the VM RMI system

8.1.1 Overview

This is a conformance test for use case 1.1 specified in ISO 18541-1.

8.1.2 Test purpose

This conformance test is used to verify that the VM RMI system allows registration of new IOs as specified in the test steps.

8.1.3 Configuration

No additional configuration required.

8.1.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid registration data;

- optional: access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

8.1.5 Test execution

<u>Table 9</u> defines the test execution.

Table 9 — [RMI-CT_UC1.1] Test to register IO for use of the VM RMI system test execution

Step #	Description
1	Tester (in the role of the IO legal representative) selects UC 1.1 and follows the instructions provided, according to FREQ-5, verifying that all following steps are possible.
2	Tester (in the role of the IO legal representative) accepts Terms and Conditions.
3	Tester (in the role of the IO legal representative) accepts agreement on registration fee, if applicable.
4	Optional: Further input may be requested in recognition of local legislation.
5	The registration application will be processed.
6	The tester is notified about further steps in the registration process.
7	The tester is notified about
	— contract agreement between IO and VM,
	— success of registration of tester (in the role of the IO legal representative),
	— acceptance or rejection of the IO approval to access security-related RMI,
	— access level of the tester (in the role of the IO legal representative), granted if the presented digital certificate and the authorization are valid, and
	— reason for rejection, if applicable.
8	In case registration is accepted, agreement on User ID and Password.

8.1.6 Postamble

No post conditions.

8.2 [RMI-CT_UC1.2_A] Test to register IO employee for use of the VM RMI system — Scenario A

8.2.1 Overview

This is a conformance test for use case 1.2 specified in ISO 18541-1.

8.2.2 Test purpose

This conformance test is used to verify that the VM RMI system allows registration of new IO employees for use of the VM RMI system as defined by the IO legal representative and specified in the test steps.

8.2.3 Configuration

No additional configuration required.

8.2.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid registration data;
- optional: access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

8.2.5 Test execution

<u>Table 10</u> defines the test execution for scenario A: Tester's role is an IO legal representative.

Table 10 — [RMI-CT_UC1.2_A] Test to register IO employee for use of the VM RMI system — Scenario A test execution

Step #	Description
1	Tester (in the role of the IO legal representative) selects UC 1.2_A and follows the instructions provided, according to FREQ-5, verifying that all following steps are possible.
2	The system requests the tester (in the role of the IO legal representative) to confirm the validity of the IO data.
3	The VM RMI system asks the tester to choose a User ID and either assigns an initial password to the user or allows them to enter one that satisfies the VM's password security requirements.
4	Agreement on User ID and password (the User ID shall be unique in the VM system).
5	The tester is notified about the successful registration of the IO employee.

8.3 [RMI-CT_UC1.2_B] Test to register IO employee for use of the VM RMI system — Scenario B

8.3.1 Overview

This is a conformance test for use case 1.2 specified in ISO 18541-1.

8.3.2 Test purpose

This conformance test is used to verify that the VM RMI system allows registration of new IO employees for use of the VM RMI system on his request as specified in the test steps.

8.3.3 Configuration

No additional configuration required.

8.3.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid registered user data of the IO legal representative;

- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

8.3.5 Test execution

Table 11 defines the test execution for scenario B.

Table 11 — [RMI-CT_UC1.2_B] Test to register IO employee for use of the VM RMI system — Scenario B test execution

Step #	Description
1	Tester (in the role of the IO employee) selects UC 1.2_B and follows the instructions provided, according to FREQ-5, verifying that all following steps are possible.
2	The tester enters the requested identification data for the IO: company name, etc.
3	The VM RMI system either assigns an initial password to the tester or allows the user to enter one that satisfies the VM's password security requirements.
4	Agreement on User ID and Password (the User ID shall be unique in the VM system).
5	The VM RMI system sends a request to the tester (in the role of the IO legal representative) asking to agree on the registration of the IO employee.
6	The VM RMI system processes the decision from the tester (in the role of the IO legal representative).
	NOTE This may need some time due to the response time by the IO legal representative.
7	The tester is notified about the successful or rejected registration.

8.3.6 Postamble

No post conditions.

8.4 [RMI-CT_UC1.3] Test to maintain IO status

8.4.1 Overview

This is a conformance test for use case 1.3 specified in ISO 18541-1.

8.4.2 Test purpose

This conformance test is used to verify that the VM RMI system allows modifications of modifiable user data and keeps user data up to date of already registered users performed by the IO legal representative as specified in the test steps.

8.4.3 Configuration

No additional configuration required.

8.4.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;

standardized navigation map is visible.

8.4.5 Test execution

Table 12 defines the test execution.

Table 12 — [RMI-CT_UC1.3] Test to maintain IO status test execution

Step #	Description
1	Tester (in the role of the IO legal representative) selects UC 1.3 and follows the instructions provided, according to FREQ-5, verifying that all following steps are possible.
2	Tester (in the role of the IO legal representative) changes (updates) IO data and confirms. The data will be processed.
3	— Case #1: The tester is notified if the change of data was successful.
	— Case #2: The tester is notified that a new validation of the IO company is required and further steps are necessary.
	— Case #3: The tester is notified that a new registration according to use case 1.1 is required.

8.4.6 Postamble

No post conditions.

8.5 [RMI-CT_UC1.4] Test to maintain user status

8.5.1 Overview

This is a conformance test for use case 1.4 specified in ISO 18541-1.

8.5.2 Test purpose

This conformance test is used to verify that the VM RMI system allows modification of modifiable user data of already registered users performed by the IO employee as specified in the test steps.

8.5.3 Configuration

No additional configuration required.

8.5.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

8.5.5 Test execution

<u>Table 13</u> defines the test execution.

Table 13 — [RMI-CT_UC1.4] Test to maintain user status test execution

Step #	Description
1	Tester (in the role of the IO employee) selects UC 1.4 and follows instructions provided, according to FREQ-5, verifying that all following steps are possible.
2	Tester (in the role of the IO employee) changes (updates) password, preferred language and e-mail address.
3	Notify the tester if change of data was successful.

8.5.6 Postamble

No post conditions.

8.6 [RMI-CT_UC1.5] Test to de-register an IO employee

8.6.1 Overview

This is a conformance test for use case 1.5 specified in ISO 18541-1.

8.6.2 Test purpose

This conformance test is used to verify that the VM RMI system allows withdrawing access rights of a registered user by the IO legal representative as specified in the test steps.

8.6.3 Configuration

No additional configuration required.

8.6.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid registered user data of the IO legal representative and the IO employee;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

8.6.5 Test execution

Table 14 defines the test execution.

Table 14 — [RMI-CT_UC1.5] Test to de-register an IO employee test execution

Step #	Description
1	Tester (in the role of the IO legal representative) selects UC 1.5 and follows the instructions provided, according to FREQ-5, verifying that all following steps are possible.
2	Tester (in the role of the IO legal representative) selects User ID for whom access rights have to be withdrawn.
3	Tester (in the role of the IO legal representative) selects access rights to be withdrawn, then confirms. Withdrawal of user rights will be processed.
4	VM RMI system confirms successful action.
5	Tester (in the role of the IO legal representative) is notified of the result of the deactivation of the IO employee account(s).

8.6.6 Postamble

No post conditions.

8.7 [RMI-CT_UC1.6] Test login to VM RMI system

8.7.1 Overview

This is a conformance test for use case 1.6 specified in ISO 18541-1.

8.7.2 Test purpose

This conformance test is used to verify that the VM RMI system allows login of registered users as specified in the test steps.

8.7.3 Configuration

No additional configuration required.

8.7.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid registered user data;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

8.7.5 Test execution

<u>Table 15</u> defines the test execution.

Table 15 — [RMI-CT_UC1.6] Test login to VM RMI system test execution

Step #	Description
	Tester selects UC 1.6 and follows the instructions provided, according to FREQ-5, verifying that all following steps are possible.
2	Tester is given access to the VM RMI system.

8.7.6 Postamble

No post conditions.

8.8 [RMI-CT_UC1.7] Test for granting access to security-related RMI

8.8.1 Overview

This is a conformance test for use case 1.7 specified in ISO 18541-1.

8.8.2 Test purpose

This conformance test is used to verify that the VM RMI system allows the access to security-related RMI.

8.8.3 Configuration

No additional configuration required.

8.8.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid registered user data;
- valid digital certificate according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

8.8.5 Test execution

<u>Table 16</u> defines the test execution granting access to security-related RMI for an IO legal representative.

Table 16 — [RMI-CT_UC1.7] Test for granting access to security-related RMI for an IO legal representative test execution

Step #	Description
1	Tester (in the role of an IO legal representative/IO employee) selects UC 1.7 and follows the instructions provided, according to FREQ5, verifying that all following steps are possible.
2	Tester presents the digital certificate according to the SERMI scheme.
	NOTE Hardware certificate has to be the one associated with the User ID and Passwords used in step #1.
3	The VM RMI system checks the approval of the IO for which the IO legal representative/IO employee is registered.
4	The VM RMI system checks the validity of the certificate and authorization via request to the trust centre that issued the certificate.
5	Access level for security-related RMI is granted according to the presented digital certificate.
6	The VM RMI system communicates the granted access level to the tester (both at IO employee and IO legal representative level if different).

8.8.6 Postamble

No post conditions.

9 CT cluster 4 — Test functional user interface implementation

9.1 [RMI-CT_FREQ-1] Test for RMI access mode

9.1.1 Overview

This is a conformance test for functional user interface requirement FREQ-1 specified in ISO 18541-3.

9.1.2 Test purpose

This conformance test is used to verify that the VM RMI system implements the requirements for the ISO 18541-3 RMI access mode.

9.1.3 Configuration

No additional configuration required.

9.1.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible.

9.1.5 Test execution

<u>Table 17</u> defines the test execution.

Table 17 — [RMI-CT_FREQ-1] Test for RMI access mode test execution

Step #	Description
1	A button or link called "Standardized Navigation" shall be present.

9.1.6 Postamble

No post conditions.

9.2 [RMI-CT_FREQ-2] Test for registration and login support

9.2.1 Overview

This is a conformance test for functional user interface requirement FREQ-2 specified in ISO 18541-3.

9.2.2 Test purpose

This conformance test is used to verify that the VM RMI system implements the requirements for the registration and login support.

9.2.3 Configuration

No additional configuration required.

9.2.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid registration data for login support;
- VM RMI system is not under maintenance;
- VM RMI home page is visible.

9.2.5 Test execution

Table 18 defines the test execution.

Table 18 — [RMI-CT_FREQ-2] Test for registration and login support test execution

Step #	Description
1	The VM RMI system provides support for registrations and login issues.
	Examples: contact area, Frequently Asked Questions, support area or online help.

9.2.6 Postamble

No post conditions.

9.2.7 Result criteria

In case one of three expected functions (i.e. registration, login, password recovery) is not possible, FREQ-4 has failed.

In case all functions are possible, but the correct process is not provided in the use cases map, FREQ-5 has failed.

9.3 [RMI-CT_FREQ-3] Test for implemented use cases map

9.3.1 Overview

This is a conformance test for functional user interface requirement FREQ-3 specified in ISO 18541-3.

9.3.2 Test purpose

This conformance test is used to verify that the VM RMI system implements the requirements for the implemented use cases.

9.3.3 Configuration

No additional configuration required.

9.3.4 Preamble (setup state)

Setup conditions are as follows:

— valid and operational technical infrastructure according to ISO 18541-2;

- VM RMI system is not under maintenance;
- VM RMI home page is visible.

9.3.5 Test execution

Table 19 defines the test execution.

Table 19 — [RMI-CT_FREQ-3] Test for implemented use cases map test execution

Step #	Description
1	Access to "standardised navigation".
2	The implemented "use cases map" with all relevant use cases shall be displayed.
3	All implemented use cases shall have active links or context related navigation instructions.

9.3.6 Postamble

No post conditions.

9.4 [RMI-CT_FREQ-4] Test for download area

9.4.1 Overview

This is a conformance test for functional user interface requirement FREQ-4 specified in ISO 18541-3.

9.4.2 Test purpose

This conformance test is used to verify that the VM RMI system implements the requirements for the download area.

9.4.3 Configuration

No additional configuration required.

9.4.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

9.4.5 Test execution

Table 20 defines the test execution.

Table 20 — [RMI-CT_FREQ-4] Test for download area test execution

Step #	Description
1	In case a specific use case requires the download of applications to the IO client for the usage of the RMI system, a visual widget shall be in a visible position in the use cases map.
2	By selecting the widget, user shall be guided through the different steps required for downloading and installing the application.

NOTE FREQ-4 is mandatory only if manual download and installation of applications to the IO client are required for the particular VM system, thus, [RMI-CT_FREQ-4] Test for download area could be not applicable for a specific VM RMI system.

9.4.6 Postamble

No post conditions.

9.5 [RMI-CT_FREQ-5] Test for navigational pathway

9.5.1 Overview

This is a conformance test for functional user interface requirement FREQ-5 specified in ISO 18541-3.

9.5.2 Test purpose

This conformance test is used to verify that the VM RMI system implements the requirements for the standardized VM RMI navigation support.

9.5.3 Configuration

No additional configuration required.

9.5.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

9.5.5 Test execution

Table 21 defines the test execution.

Table 21 — [RMI-CT_FREQ-5] Test for navigational pathway test execution

Step #	Description
	At a minimum, the VM RMI system shall provide a use case sensitive help. A use case sensitive help will provide the order in which prerequisite use cases shall be chosen in order to reach the target use case.
2	An example of a more sophisticated solution would be an interactive use cases map that will guide a user through the prerequisite use cases that shall be chosen in order to reach the target use case.
3	By following the provided navigational path, user shall be able to access selected use case.

9.5.6 Postamble

No post conditions.

10 CT cluster 5 — Test payment for RMI

10.1 [RMI-CT_UC2] Test payment for RMI

10.1.1 Overview

This is a conformance test for use case 2 specified in ISO 18541-1.

10.1.2 Test purpose

This conformance test is used to verify proper handling of payments and that the VM RMI systems

- a) provides the possibility
 - 1) to select subscription,
 - 2) to select payment arrangements, and
 - 3) payment-relevant data (card data, account id, etc.),
- b) activates (enables) the selected subscription, and
- c) produces a receipt.

10.1.3 Configuration

No additional configuration required.

10.1.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data;
- subscriptions for security-related RMI may require a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

10.1.5 Test execution

Table 22 defines the test execution.

Table 22 — [RMI-CT_UC2] Test payment for RMI test execution

Step #	Description
1	Select UC 2 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	Select subscription (content and period).
3	Select payment arrangement.
4	Fill in requested payment relevant data (card data, account id, etc.).
5	Confirm. Data will be processed.
6	VM notifies user about further steps (e.g., invoicing).
7	VM grants access to VM RMI system according to subscription process.

10.1.6 Postamble

No post conditions.

11 CT cluster 6 —Test for vehicle identification

11.1 [RMI-CT_UC3.1] Test vehicle identification through use of VIN

11.1.1 Overview

This is a conformance test for use case 3.1 specified in ISO 18541-1.

11.1.2 Test purpose

This conformance test is used to verify that the VM RMI system provides vehicle identification via VIN input.

11.1.3 Configuration

No additional configuration required.

11.1.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

11.1.5 Test execution

Table 23 defines the test execution.

Table 23 — [RMI-CT_UC3.1] Test vehicle identification through use of VIN test execution

Step #	Description
1	Select UC 3.1 and follow the instruction provided according to FREQ-5.
2	Provide a valid VIN as required by the VM RMI system.
3	The VM RMI system will provide vehicle summary information for this specific VIN as defined in UC 3.1 - Use case output.
4	The VM RMI system will provide the vehicle type approval of the vehicle model.

11.1.6 Postamble

The retention of the vehicle identification can only be verified in the subsequent use cases where that specific vehicle identification is required.

11.2 [RMI-CT_UC3.2] Test vehicle identification via product features

11.2.1 Overview

This is a conformance test for use case 3.2 specified in ISO 18541-1. Conformance testing for classification C2 is outside the scope of this conformance test as conformance will be VM-specific.

11.2.2 Test purpose

This conformance test is used to verify that the VM RMI system provides vehicle identification via product features in cases where this functionality is provided to ARs.

11.2.3 Configuration

No additional configuration required.

11.2.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

11.2.5 Test execution

Table 24 defines the test execution.

Table 24 — [RMI-CT_UC3.2] Test vehicle identification via product features test execution

Step #	Description
1	Select UC 3.2 and follow the instruction provided according to FREQ-5.
2	Input or select allowed product feature option where offered by the VM RMI system.
3	Make information request using product feature(s) such as model, vehicle year, etc.
4	The VM RMI system will provide available vehicle information relevant to the submitted product features.

11.2.6 Postamble

The retention of the vehicle identification can only be verified in the subsequent use cases where that specific vehicle identification is required.

12 CT cluster 7 — Test selection methods for RMI

12.1 [RMI-CT_UC4.1] Test selection of information type

12.1.1 Overview

This is a conformance test for use case 4.1 specified in ISO 18541-1.

12.1.2 Test purpose

This conformance test is used to verify that the VM RMI system provides the relevant information types.

12.1.3 Configuration

No additional configuration required.

12.1.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible;
- either VIN is according to UC 3.1 or product features according to UC 3.2 are selected.

12.1.5 Test execution

Table 25 defines the test execution.

Table 25 — [RMI-CT_UC4.1] Test selection of information type test execution

Step #	Description
1	Select UC 4.1 and follow the instruction provided according to FREQ-5.
2	VM RMI system displays a list of information types.
3	Select at least one of the listed information types.

12.1.6 Postamble

The retention of the information type(s) selected can only be verified in the subsequent use case(s) where that specific information type(s) is required.

12.2 [RMI-CT_UC4.2] Test search by standardized terms

12.2.1 Overview

This is a conformance test for use case 4.2 specified in ISO 18541-1.

12.2.2 Test purpose

This conformance test is used to verify that the VM RMI system provides searching by terms from the Digital Annex according to ISO 18541.

12.2.3 Configuration

Latest implemented version of the RMI Terminology Digital Annex.

12.2.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible;
- either VIN according to UC 3.1 or product features according to UC 3.2 are selected.

12.2.5 Test execution

<u>Table 26</u> defines the test execution.

Table 26 — [RMI-CT_UC4.2] Test search by standardized terms test execution

Step#	Description
1	Select UC 4.2 and follow the instruction provided according to FREQ-5.
2	Input a term from the digital annex.
3	Submit the search request.
4	The VM RMI system returns a list of document titles containing either the standardized term or the mapped term in the title or in the metadata of the document.

12.2.6 Postamble

No post conditions.

12.3 [RMI-CT_UC4.3] Test navigation using product structure

12.3.1 Overview

This is a conformance test for use case 4.3 specified in ISO 18541-1.

12.3.2 Test purpose

This conformance test is used to verify that the VM RMI system provides navigation capability via the product structure to enable the user to browse the information.

12.3.3 Configuration

No additional configuration required.

12.3.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible;
- either VIN according to UC 3.1 or product features according to UC 3.2 are selected.

12.3.5 Test execution

Table 27 defines the test execution.

Table 27 — [RMI-CT_UC4.3] Test navigation using product structure test execution

Step #	Description
1	Select UC 4.3 and follow the instruction provided according to FREQ-5.
2	Navigate within the product structure to the required level.
3	The VM RMI system provides a list of available information packages for the selected item.

12.3.6 Postamble

No post conditions.

12.4 [RMI-CT_UC4.4] Test selection by document identifier

12.4.1 Overview

This is a conformance test for use case 4.4 specified in ISO 18541-1.

12.4.2 Test purpose

This conformance test is used to verify that the VM RMI system provides searching by document identifier, if offered to VMs ARs.

12.4.3 Configuration

No additional configuration required.

12.4.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

12.4.5 Test execution

Table 28 defines the test execution.

Table 28 — [RMI-CT_UC4.4] Test selection by document identifier test execution

Step #	Description
1	Select UC 4.4 and follow the instruction provided according to FREQ-5.
2	Enter a valid document identifier.
3	The VM RMI system displays the document title relevant to the identifier.

12.4.6 Postamble

No post conditions.

13 CT cluster 8 — Test retrieval of information packages

13.1 [RMI-CT_UC5.1.1] Test retrieval of general workshop procedures

13.1.1 Overview

This is a conformance test for use case 5.1.1 specified in ISO 18541-1.

13.1.2 Test purpose

This conformance test is used to verify that the VM RMI system provides access to selected general workshop procedure.

13.1.3 Configuration

No additional configuration required.

13.1.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

13.1.5 Test execution

Table 29 defines the test execution.

Table 29 — [RMI-CT_UC5.1.1] Test retrieval of general workshop procedures test execution

Step #	Description
	Select UC 5.1.1 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	Select one document in the search result list.
3	The document corresponding to the pre-selected options shall open to be read.

13.1.6 Postamble

No post conditions.

13.2 [RMI-CT_UC5.1.2] Test retrieval of body repair procedures

13.2.1 Overview

This is a conformance test for use case 5.1.2 specified in ISO 18541-1.

13.2.2 Test purpose

This conformance test is used to verify that the VM RMI system provides access to the selected body repair procedure.

13.2.3 Configuration

No additional configuration required.

13.2.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

13.2.5 Test execution

Table 30 defines the test execution.

Table 30 — [RMI-CT_UC5.1.2] Test retrieval of body repair procedures test execution

Step #	Description
	Select UC 5.1.2 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	Select one document in the search result list.
3	The corresponding document shall open to be read.

NOTE UC 5.1.2 is optional, but mandatory if the repair information exists; thus; RMI-CT_UC5.1.2 could be not applicable for a specific VM RMI system.

13.2.6 Postamble

No post conditions.

13.3 [RMI-CT_UC5.1.3] Test retrieval of temporary repair procedures

13.3.1 Overview

This is a conformance test for use case 5.1.3 specified in ISO 18541-1.

13.3.2 Test purpose

This conformance test is used to verify that the VM RMI system provides access to selected temporary repair procedure.

13.3.3 Configuration

No additional configuration required.

13.3.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

13.3.5 Test execution

Table 31 defines the test execution.

Table 31 — [RMI-CT_UC5.1.3] Test retrieval of temporary repair procedures test execution

Step#	Description
	Select UC 5.1.3 and follow the instruction provided, according to FREQ5, verifying that all following steps are possible.
2	Select one document in the search result list.
3	The corresponding document shall open to be read.

NOTE UC 5.1.3 is optional, but mandatory if provided by VM to VM AR; thus, RMI-CT_UC5.1.3 could be not applicable for a specific VM RMI system.

13.3.6 Postamble

No post conditions.

13.4 [RMI-CT_UC5.1.4] Test retrieval of preparation for PTI

13.4.1 Overview

This is a conformance test for use case 5.1.4 specified in ISO 18541-1.

13.4.2 Test purpose

This conformance test is used to verify that the VM RMI system provides access to selected information for preparation for PTI.

13.4.3 Configuration

No additional configuration required.

13.4.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

13.4.5 Test execution

Table 32 defines the test execution.

Table 32 — [RMI-CT_UC5.1.4] Test retrieval of preparation for PTI test execution

Step #	Description
	Select UC 5.1.4 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	The VM RMI system displays the requested PTI information or offers access to PTI services.
3	The corresponding document shall open to be read.

NOTE UC 5.1.4 is optional, but mandatory if provided by VM to VM AR; thus, RMI-CT_UC5.1.4 could be not applicable for a specific VM RMI system.

13.4.6 Postamble

No post conditions.

13.5 [RMI-CT_UC5.2] Test retrieval of wiring diagrams

13.5.1 Overview

This is a conformance test for use case 5.2 specified in ISO 18541-1.

13.5.2 Test purpose

This conformance test is used to verify that the VM RMI system provides access to selected wiring diagram.

13.5.3 Configuration

No additional configuration required.

13.5.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;

BS EN ISO 18541-4:2015 **ISO 18541-4:2015(E)**

- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

13.5.5 Test execution

Table 33 defines the test execution.

Table 33 — [RMI-CT_UC5.2] Test retrieval of wiring diagrams test execution

Step #	Description
	Select UC 5.2 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	Select one document in the search result list.
3	The corresponding document shall open to be read.

13.5.6 Postamble

No post conditions.

13.6 [RMI-CT_UC5.3] Test retrieval of technical service bulletin

13.6.1 Overview

This is a conformance test for use case 5.3 specified in ISO 18541-1.

13.6.2 Test purpose

This conformance test is used to verify that the VM RMI system provides access to selected technical service bulletin.

13.6.3 Configuration

No additional configuration required.

13.6.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

13.6.5 Test execution

Table 34 defines the test execution.

Table 34 — [RMI-CT_UC5.3] Test retrieval of technical service bulletin test execution

Step #	Description
	Select UC 5.3 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	Select one document in the search result list.
3	The corresponding document shall open to be read.

NOTE UC 5.3 is optional, but mandatory if provided by VM to VM AR; thus, RMI-CT_UC5.3 could be not applicable for a specific VM RMI system.

13.6.6 Postamble

No post conditions.

13.7 [RMI-CT_UC5.4] Test retrieval of recall information

13.7.1 Overview

This is a conformance test for use case 5.4 specified in ISO 18541-1.

13.7.2 Test purpose

This conformance test is used to verify that the VM RMI system provides access to selected recall information.

13.7.3 Configuration

No additional configuration required.

13.7.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

13.7.5 Test execution

Table 35 defines the test execution.

Table 35 — [RMI-CT_UC5.4] Test retrieval of recall information test execution

Step #	Description
	Select UC 5.4 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
	Information package will show the recall title and a message including brief information about the issue that is to be solved and the indication that the VM would provide a free of charge repair through their authorized network.

13.7.6 Postamble

No post conditions.

13.8 [RMI-CT_UC5.5] Test retrieval of maintenance schedule

13.8.1 Overview

This is a conformance test for use case 5.5 specified in ISO 18541-1.

13.8.2 Test purpose

This conformance test is used to verify that the VM RMI system provides access to maintenance schedule.

13.8.3 Configuration

No additional configuration required.

13.8.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

13.8.5 Test execution

<u>Table 36</u> defines the test execution.

Table 36 — [RMI-CT_UC5.5] Test retrieval of maintenance schedule test execution

Step #	Description
	Select UC 5.5 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	The corresponding document shall open to be read.
3	If implemented, links to relevant procedures will lead to the maintenance procedures.

13.8.6 Postamble

No post conditions.

13.9 [RMI-CT_UC5.6.1] Test retrieval of spare parts (identification)

13.9.1 Overview

This is a conformance test for use case 5.6.1 specified in ISO 18541-1.

13.9.2 Test purpose

This conformance test is used to verify that the VM RMI system provides access to spare parts (identification).

13.9.3 Configuration

No additional configuration required.

13.9.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

13.9.5 Test execution

Table 37 defines the test execution.

Table 37 — [RMI-CT_UC5.6.1] Test retrieval of spare parts (identification) test execution

Step#	Description
1	Select UC 5.6.1 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	Select one document in the search result list.
3	The corresponding document shall open to be read.
4	In case spare parts catalogue is not part of standard RMI in a specific VM RMI system, result shall be a link to spare parts catalogue.

13.9.6 Postamble

No post conditions.

13.10 [RMI-CT_UC5.6.2] Test retrieval of spare parts (access)

13.10.10verview

This is a conformance test for use case 5.6.2 specified in ISO 18541-1.

13.10.2 Test purpose

This conformance test is used to verify that the VM RMI system provides direct access to spare parts catalogue.

13.10.3 Configuration

No additional configuration required.

13.10.4Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

13.10.5 Test execution

Table 38 defines the test execution.

Table 38 — [RMI-CT_UC5.6.2] Test retrieval of spare parts (access) test execution

Step #	Description
1	Select UC 5.6.2 and follow the instruction provided, according to FREQ-5.
2	Spare parts catalogue homepage appears.

13.10.6 Postamble

No post conditions.

13.11 [RMI-CT_UC5.7.1] Test retrieval of accessory information factory fitted (included in general RMI)

13.11.10verview

This is a conformance test for use case 5.7.1 specified in ISO 18541-1.

13.11.2 Test purpose

This conformance test is used to verify that the VM RMI system provides access to accessory information factory fitted.

13.11.3 Configuration

No additional configuration required.

13.11.4Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

13.11.5 Test execution

Table 39 defines the test execution.

Table 39 — [RMI-CT_UC5.7.1] Test retrieval of accessory information factory fitted (included in general RMI) test execution

Step #	Description
	Select UC 5.7.1 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	Select one document in the search result list.
3	The corresponding document shall open to be read.

13.11.6Postamble

No post conditions.

13.12 [RMI-CT_UC5.7.2] Test retrieval of accessory information partnered with a VM part number

13.12.10verview

This is a conformance test for use case 5.7.2 specified in ISO 18541-1.

13.12.2 Test purpose

This conformance test is used to verify that the VM RMI system provides access to accessory information partnered with a VM part number.

13.12.3 Configuration

No additional configuration required.

13.12.4Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

13.12.5 Test execution

Table 40 defines the test execution.

Table 40 — [RMI-CT_UC5.7.2] Test retrieval of accessory information partnered with a VM part number test execution

Step #	Description
1	Select UC 5.7.2 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	Select one document in the search result list.
3	The corresponding document shall open to be read.
4	In case a specific partnered accessory information is not part of standard RMI in a specific VM RMI system, result shall be a link to the third party responsible for the accessory.

13.12.6Postamble

No post conditions.

13.13 [RMI-CT_UC5.7.3] Test retrieval of fitting information for accessories with no VM part number

13.13.10verview

This is a conformance test for use case 5.7.3 specified in ISO 18541-1.

13.13.2 Test purpose

This conformance test is used to verify that the VM RMI system provides access to fitting information for accessories with no VM part number.

13.13.3 Configuration

No additional configuration required.

13.13.4Preamble (setup state)

Setup conditions are as follows:

valid and operational technical infrastructure according to ISO 18541-2;

- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

13.13.5 Test execution

Table 41 defines the test execution.

Table 41 — [RMI-CT_UC5.7.3] Test retrieval of fitting information for accessories with no VM part number test execution

Step #	Description
1	Select UC 5.7.3 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	Select one document in the search result list.
3	The corresponding document shall open to be read.
4	A single document shall generally be accessible with each and any of the implemented search criteria.

NOTE UC 5.7.3 is optional, but mandatory if provided by VM to VM AR; thus, RMI-CT_UC5.7.3 could be not applicable for a specific VM RMI system.

13.13.6 Postamble

No post conditions.

13.14 [RMI-CT_UC5.8] Test retrieval of labour times

13.14.10verview

This is a conformance test for use case 5.8 specified in ISO 18541-1.

13.14.2 Test purpose

This conformance test is used to verify that the VM RMI system provides access to labour times.

13.14.3 Configuration

No additional configuration required.

13.14.4Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;

BS EN ISO 18541-4:2015 **ISO 18541-4:2015(E)**

- VM RMI home page is visible;
- standardized navigation map is visible.

13.14.5 Test execution

Table 42 defines the test execution.

Table 42 — [RMI-CT_UC5.8] Test retrieval of labour times test execution

Step #	Description
1	Select UC 5.8 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	Select specific labour times.
3	Selected labour times are displayed.

13.14.6 Postamble

No post conditions.

13.15 [RMI-CT_UC5.9] Test retrieval of converted vehicle information

13.15.10verview

This is a conformance test for use case 5.9 specified in ISO 18541-1.

13.15.2 Test purpose

This conformance test is used to verify that the VM RMI system provides access to information for converted vehicles.

13.15.3 Configuration

No additional configuration required.

13.15.4Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

13.15.5 Test execution

Table 43 defines the test execution.

Table 43 — [RMI-CT_UC5.9] Test retrieval of converted vehicle information test execution

Step #	Description
	Select UC 5.9 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
	The VM RMI system provides RMI on VM components of the converted vehicle and RMI on published or AR available interfaces.

NOTE UC 5.9 is optional, but mandatory if provided by VM to VM AR; thus, RMI-CT_UC5.9 could be not applicable for a specific VM RMI system.

13.15.6 Postamble

No post conditions.

13.16 [RMI-CT_UC5.10] Test retrieval of special tool information

13.16.10verview

This is a conformance test for use case 5.10 specified in ISO 18541-1.

13.16.2 Test purpose

This conformance test is used to verify that the VM RMI system provides access to the special tool information.

13.16.3 Configuration

No additional configuration required.

13.16.4Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

13.16.5 Test execution

Table 44 defines the test execution.

Table 44 — [RMI-CT_UC5.10] Test retrieval of special tool information test execution

Step #	Description
	Select UC 5.10 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	The VM RMI system shall give access to special tool information.

13.16.6 Postamble

No post conditions.

14 CT cluster 9 — Test vehicle diagnostics

14.1 [RMI-CT_UC6.1] Test DTC resolution

14.1.1 Overview

This is a conformance test for use case 6.1 specified in ISO 18541-1.

14.1.2 Test purpose

This conformance test is used to verify that the VM RMI system provides a description of the DTC if it is relevant to the vehicle and module and, if available, a list of potential causes or hints for further investigation.

14.1.3 Configuration

No additional configuration required.

14.1.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

14.1.5 Test execution

Table 45 defines the test execution.

Table 45 — [RMI-CT_UC6.1] Test DTC resolution test execution

Step #	Description
1	Select UC 6.1 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	Enter or select the relevant DTC.
3	The VM RMI system returns a description of the DTC and, if available, a list of potential causes or hints for further investigation, to the same level and content as provided to AR.

14.1.6 Postamble

No post conditions.

14.2 [RMI-CT_UC6.2] Test VM symptom resolution

14.2.1 Overview

This is a conformance test for use case 6.2 specified in ISO 18541-1.

NOTE Depending on the diagnostic strategy chosen by the VM, isolated symptom resolution may not be supported. In such cases, symptom resolution is part of the integrated diagnostics.

14.2.2 Test purpose

This conformance test is used to verify that the VM RMI system delivers a list of potential causes or hints for further investigation when provided with a VM symptom as found by reading the published technical documentation.

14.2.3 Configuration

No additional configuration required.

14.2.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

14.2.5 Test execution

Table 46 defines the test execution.

Table 46 — [RMI-CT_UC6.2] Test VM symptom resolution test execution

Step #	Description
1	Select UC 6.2 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	Input or select valid VM symptom as found by reading the published technical documentation.
3	The system returns a list of potential causes or hints for further investigation, to the same level and content as provided to AR.

14.2.6 Postamble

No post conditions.

14.3 [RMI-CT_UC6.3] Test integrated diagnostics

14.3.1 Overview

This is a conformance test for use case 6.3 specified in ISO 18541-1.

14.3.2 Test purpose

This conformance test is used to verify that the VM RMI system provides integrated diagnostics via standardized non-proprietary VCI functionality using a non-proprietary front end.

14.3.3 Configuration

Test if communication device for testing is validated by VM according to VM RMI web site statement.

Any necessary driver for communication device as required by the VM RMI technical requirements according to both VM and VCI manufacturer installation instructions is installed (e.g. TREQ-8 VCI manufacturer-specific device driver and VM-specific device driver).

14.3.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

14.3.5 Test execution

Table 47 defines the test execution.

Table 47 — [RMI-CT_UC6.3] Test integrated diagnostics test execution

Step #	Description
1	Select UC 6.3 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	When requested, link the vehicle to the VM RMI system via VM validated non-proprietary VCI functionality.
3	The VM RMI system checks the vehicle ECUs and displays diagnostic information. The VM RMI system checks the vehicle ECUs and displays precise diagnostics results and repair recommendation.

NOTE UC 6.3 is optional, but mandatory if provided by VM to VM AR; thus, the RMI-CT_UC6.3 could be not applicable for a specific VM RMI system.

14.3.6 Postamble

No post conditions.

15 CT cluster 10 — Test updating, replacing and tuning of modules (ECUs)

15.1 [RMI-CT_UC7.1] Test updating and replacing modules information

15.1.1 Overview

This is a conformance test for use case 7.1 specified in ISO 18541-1.

15.1.2 Test purpose

This conformance test is used to verify that the VM RMI system provides information about updating and replacing modules.

15.1.3 Configuration

Test if communication device for testing is validated by VM according to VM RMI web site statement.

Any necessary driver for communication device as required by the VM RMI technical requirements according to both VM and VCI manufacturer installation instructions is installed (e.g. TREQ-8 VCI manufacturer-specific device driver and VM-specific device driver).

15.1.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

15.1.5 Test execution

Table 48 defines the test execution.

Table 48 — [RMI-CT_UC7.1] Test updating and replacing modules information test execution

Step #	Description
1	Select UC 7.1 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	The user requests the necessary action for updating or replacing modules. Security measures, i.e. approval/authorization to protect against vehicle theft or emission control and engine calibration tampering may be required.
3	The VM RMI system identifies the required software versions for the individual vehicle. Update the ECU software according to the valid configuration if the prerequisites for software update are fulfilled.

NOTE By performing this conformance test, a valid repair operation is executed on the actual vehicle.

15.1.6 Postamble

In case of installation of tuning kit, the original status of the vehicle has to be restored.

15.2 [RMI-CT_UC7.2] Test tuning kit

15.2.1 Overview

This is a conformance test for use case 7.2 specified in ISO 18541-1.

15.2.2 Test purpose

This conformance test is used to verify that the VM RMI system provides tuning kit information.

15.2.3 Configuration

In case the tuning has to be performed as a whole process, an appropriate vehicle has to be organized, the consent of the vehicle owner has to be available and necessary financial resources for the purchase of the tuning kit has to be allocated.

15.2.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

15.2.5 Test execution

Table 49 defines the test execution.

Table 49 — [RMI-CT_UC7.2] Test tuning kit test execution

Step #	Description
1	Select UC 7.2 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	Tester purchases official VM tuning kit according to VM specific process.
3	Tester installs official VM tuning kit into the relevant vehicle in accordance with VM installation instruction.
4	Tester performs programming/coding according to use case 7.1 if software update of the module is required.

NOTE UC 7.2 is optional, but mandatory if provided by VM to VM AR; thus, the RMI-CT_UC7.2 could be not applicable for a specific VM RMI system. By performing this conformance test, a valid tuning kit installation is executed on the actual vehicle.

15.2.6 Postamble

In case of installation of tuning kit, the original status of the vehicle has to be restored.

16 CT cluster 11 — Test electronic maintenance history

16.1 [RMI-CT_UC8] Test electronic maintenance history

16.1.1 Overview

This is a conformance test for use case 8 specified in ISO 18541-1.

16.1.2 Test purpose

This conformance test is used to verify that the VM RMI system allows the user with a digital certificate to view and update and digitally sign an electronic maintenance history schedule in cases where it is the only record of maintenance available to the customer and to make a printout for the customer.

16.1.3 Configuration

No additional configuration required.

16.1.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- valid digital certificate for electronic signature;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

16.1.5 Test execution

Table 50 defines the test execution.

Table 50 — [RMI-CT_UC8] Test electronic maintenance history test execution

Step #	Description
1	Select UC 8 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	Indicate customer consent where necessary.
3	View maintenance history.
4	Input maintenance data as required.
5	Submit the digitally signed maintenance history update according to ISO 20828 (X509.V3).
6	Print customer copy of maintenance history.

16.1.6 Postamble

No post conditions.

17 CT cluster 12 — Test repair assistance, technical support

17.1 [RMI-CT_UC9] Test repair assistance technical support

17.1.1 Overview

This is a conformance test for use case 9 specified in ISO 18541-1.

17.1.2 Test purpose

This conformance test is used to verify that the VM RMI system provides repair assistance and repair technical support for the purposes of repairing the vehicle.

17.1.3 Configuration

No additional configuration required.

17.1.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- access to security-related RMI requires a valid digital certificate and authorization according to ISO 18541-2;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

17.1.5 Test execution

Table 51 defines the test execution.

Table 51 — [RMI-CT_UC9] Test repair assistance technical support test execution

Step #	Description
1	Select UC 9 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	Follow the instructions and input data if required by the VM RMI system.
3	Verify that assistance and support is provided in accordance with the VM-specific support mechanism and timescales.

17.1.6 Postamble

No post conditions.

18 CT cluster 13 — Test request for contact information

18.1 [RMI-CT_UC10.1] Test for retrieval of electronic tool information (Diagnostic, Reprogramming, VCI)

18.1.1 Overview

This is a conformity test for use case 10.1 specified in ISO 18541-1.

18.1.2 Test purpose

This conformance test is used to verify that the VM RMI system provides contact information on how to obtain manufacturer's diagnostic tool, reprogramming tool and VCI.

18.1.3 Configuration

No additional configuration required.

18.1.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

18.1.5 Test execution

<u>Table 52</u> defines the test execution.

Table 52 — [RMI-CT_UC10.1] Test for retrieval of electronic tool information (Diagnostic, Reprogramming, VCI) test execution

Step #	Description
1	Select UC 10.1 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	The VM RMI system provides the relevant contact information for
	— description of manufacturer's diagnostic tool and VCI, and
	— available list of contacts/link to a supplier (country by country) where diagnostic tools and VCI can be purchased.

18.1.6 Postamble

No post conditions.

18.2 [RMI-CT_UC10.2] Test for retrieval of test equipment and diagnostic tool manufacturers information

18.2.1 Overview

This is a conformity test for use case 10.2 specified in ISO 18541-1.

18.2.2 Test purpose

This conformance test is used to verify that the VM RMI system provides contact information about OBD-related and vehicle repair and maintenance information to design and manufacture test equipment or diagnostic tools.

18.2.3 Configuration

No additional configuration required.

18.2.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

18.2.5 Test execution

Table 53 defines the test execution.

Table 53 — [RMI-CT_UC10.2] Test for retrieval of test equipment and diagnostic tool manufacturers information test execution

Step #	Description
	Select UC 10.2 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
	The VM RMI system provides the relevant VM's contact information and process for test equipment and diagnostic tool manufacturers.

18.2.6 Postamble

No post conditions.

18.3 [RMI-CT_UC10.3] Test for retrieval of training material (delegate information)

18.3.1 Overview

This is a conformity test for use case 10.3 specified in ISO 18541-1.

18.3.2 Test purpose

This conformance test is used to verify that the VM RMI system provides contact information about training material (delegate information).

18.3.3 Configuration

No additional configuration required.

18.3.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

18.3.5 Test execution

Table 54 defines the test execution.

Table 54 — [RMI-CT_UC10.3] Test for retrieval of training material (delegate information) test execution

Step #	Description
	Select UC 10.3 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	The VM RMI system provides the relevant VM's contact information for training material.

18.3.6 Postamble

No post conditions.

18.4 [RMI-CT_UC10.4] Test for retrieval of redistributor contact information

18.4.1 Overview

This is a conformity test for use case 10.4 specified in ISO 18541-1.

18.4.2 Test purpose

This conformance test is used to verify that the VM RMI system provides contact information on how to obtain RMI for redistribution within their own closed network e.g. RAC, ADAC, garage networks.

18.4.3 Configuration

No additional configuration required.

18.4.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

18.4.5 Test execution

Table 55 defines the test execution.

Table 55 — [RMI-CT_UC10.4] Test for retrieval of redistributor contact information test execution

Step #	Description
	Select UC 10.4 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	The VM RMI system provides the relevant VM's contact information for contractual agreement to redistribute the desired information.

18.4.6 Postamble

No post conditions.

18.5 [RMI-CT_UC10.5] Test for retrieval of republisher information

18.5.1 Overview

This is a conformity test for use case 10.5 specified in ISO 18541-1.

18.5.2 Test purpose

This conformance test is used to verify that the VM RMI system provides contact information about how to obtain permission for re-publication and distribution of RMI to an external network.

18.5.3 Configuration

No additional configuration required.

18.5.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

18.5.5 Test execution

Table 56 defines the test execution.

Table 56 — [RMI-CT_UC10.5] Test for retrieval of republisher information test execution

Step #	Description
	Select UC 10.5 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
2	The VM RMI system provides the VM's contact information for contractual agreement to republish the desired information.

18.5.6 Postamble

No post conditions.

18.6 [RMI-CT_UC10.6] Test for retrieval of inspection and testing services information

18.6.1 Overview

This is a conformity test for use case 10.6 specified in ISO 18541-1.

18.6.2 Test purpose

This conformance test is used to verify that the VM RMI system provides contact information about how to find necessary OBD-related and repair and maintenance information to create inspection and testing services according to country-specific legislation.

18.6.3 Configuration

No additional configuration required.

18.6.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

18.6.5 Test execution

Table 57 defines the test execution.

Table 57 — [RMI-CT_UC10.6] Test for retrieval of inspection and testing services information test execution

Step #	Description
	Select UC 10.6 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
	The VM RMI system provides the VM's contact information and process for operators offering inspection and testing services. This may be country-specific.

18.6.6 Postamble

No post conditions.

18.7 [RMI-CT_UC10.7] Test for retrieval of alternative fuels retrofit system information

18.7.1 Overview

This is a conformity test for use case 10.7 specified in ISO 18541-1.

18.7.2 Test purpose

This conformance test is used to verify that the VM RMI system provides contact information on how to obtain emissions-related OBD and repair and maintenance information to properly manufacture or design alternative fuels retrofit systems.

18.7.3 Configuration

No additional configuration required.

18.7.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

18.7.5 Test execution

Table 58 defines the test execution.

Table 58 — [RMI-CT_UC10.7] Test for retrieval of alternative fuels retrofit system information test execution

Step #	Description
	Select UC 10.7 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
	The VM RMI system provides the relevant VM's contact information for emissions-related OBD and repair and maintenance information for building alternative fuels system.

NOTE [RMI-CT_UC10.7] Test for retrieval of alternative fuels retrofit system information is mandatory only if the VM allows such an alternative fuel system and if this information is not available in the VM RMI system.

18.7.6 Postamble

No post conditions.

18.8 [RMI-CT_UC10.8] Test for retrieval of engine and components remanufacturing information

18.8.1 Overview

This is a conformity test for use case 10.8 specified in ISO 18541-1.

18.8.2 Test purpose

This conformance test is used to verify that the VM RMI system provides contact information on how to obtain engine and component remanufacturing OBD-related and repair and maintenance information.

18.8.3 Configuration

No additional configuration required.

18.8.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;

- VM RMI home page is visible;
- standardized navigation map is visible.

18.8.5 Test execution

Table 59 defines the test execution.

Table 59 — [RMI-CT_UC10.8] Test for retrieval of engine and components remanufacturing information test execution

Step #	Description
	Select UC 10.8 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
	The VM RMI system provides the relevant VM's contact information for engine or component OBD-related and repair and maintenance information for remanufacturing.

NOTE [RMI-CT_UC10.8] Test for retrieval of engine and components remanufacturing information is mandatory only if the VM supports remanufacturing and if this information is not available in the VM RMI system.

18.8.6 Postamble

No post conditions.

18.9 [RMI-CT_UC10.9] Test for retrieval of component and parts manufacturer information

18.9.1 Overview

This is a conformity test for use case 10.9 specified in ISO 18541-1.

18.9.2 Test purpose

This conformance test is used to verify that the VM RMI system provides contact information about on how to obtain information for the manufacturing or design of emissions-related OBD system-relevant alternative components and replacement parts.

18.9.3 Configuration

No additional configuration required.

18.9.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

18.9.5 Test execution

Table 60 defines the test execution.

Table 60 — [RMI-CT_UC10.9] Test for retrieval of component and parts manufacturer information test execution

Step #	Description
	Select UC 10.9 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
	The VM RMI system provides the relevant VM's contact information for building emissions-related OBD system-relevant alternative parts and components, including any parameterization information and/or interfaces in order for the part to operate correctly.

18.9.6 Postamble

No post conditions.

18.10 [RMI-CT_UC10.10] Test for retrieval of validation of independently developed non-proprietary VCI information

18.10.10verview

This is a conformity test for use case 10.10 specified in ISO 18541-1.

18.10.2 Test purpose

This conformance test is used to verify that the VM RMI system provides contact information on how to find VM's contact person or necessary information for the validation of the compatibility of the manufacturer-specific application and the independently developed non-proprietary VCIs complying with ISO 18541-2.

18.10.3 Configuration

No additional configuration required.

18.10.4Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

18.10.5 Test execution

<u>Table 61</u> defines the test execution.

Table 61 — [RMI-CT_UC10.10] Test for retrieval of validation of independently developed nonproprietary VCI information test execution

Step #	Description
	Select UC 10.10 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
	The VM RMI system provides the relevant manufacturer's contact information for the validation process of independently developed non-proprietary VCIs or the information about the process required for a VCI manufacturer to conduct such validation himself.

18.10.6 Postamble

No post conditions.

19 CT cluster 14 — Test courses and training information

19.1 [RMI-CT_UC11] Test for courses and training information

19.1.1 Overview

This is a conformity test for use case 11 specified in ISO 18541-1.

19.1.2 Test purpose

This conformance test is used to verify that the VM RMI system provides contact information on how to get information regarding training courses availability and/or online or web-based training.

19.1.3 Configuration

No additional configuration required.

19.1.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

19.1.5 Test execution

Table 62 defines the test execution.

Table 62 — [RMI-CT_UC11] Test for courses and training information test execution

Step #	Description
	Select UC 11 and follow the instruction provided, according to FREQ-5, verifying that all following steps are possible.
	The VM RMI system provides the relevant VM's contact information for training contact information for each market and/or provision of online or web-based training in a non-discriminatory manner as regard to the ARs.

19.1.6 Postamble

No post conditions.

20 CT cluster 15 — Test data administration requirements

20.1 [RMI-CT_TREQ-1] Test general access-related data administration

20.1.1 Overview

This is a conformance test for checking the navigation to the VM-specific administrative area by the VM RMI system as described in requirement TREQ-1 specified in ISO 18541-2.

20.1.2 Test purpose

This conformance test is used to verify that the VM RMI system navigates to the VM-specific administrative area for general access-related data administration.

20.1.3 Configuration

User rights as VM RMI system administrator.

20.1.4 Preamble (setup state)

No preamble.

20.1.5 Test execution

Table 63 defines the test execution.

Table 63 — [RMI-CT_TREQ-1] Test general access-related data administration test execution

Step #	Description
1	Navigate to VM-specific administrative area.
2	User data will be displayed (see TREQ-1 specified in ISO 18541-2).
3	Check data.

NOTE User data and company data might be seen as different categories. In this case, there might be more than one step to retrieve user data including company data.

20.1.6 Postamble

20.2 [RMI-CT_TREQ-2] Test administration of IO data by the VM

20.2.1 Overview

This is a conformance test for checking the administration of IO data managed by the VM RMI system as described in requirement TREQ-2 specified in ISO 18541-2.

20.2.2 Test purpose

This conformance test is used to verify that the VM RMI system manages administration of IO data correctly

20.2.3 Configuration

User rights as VM RMI system administrator.

20.2.4 Preamble (setup state)

No preamble.

20.2.5 Test execution

Table 64 defines the test execution.

Table 64 — [RMI-CT_TREQ-2] Test administration of IO data by the VM test execution

Step #	Description
1	Access the VM RMI system database and verify that all needed fields are present and managed.

20.2.6 Postamble

No post conditions.

20.3 [RMI-CT_TREQ-3] Test administration of IO employee data by the VM

20.3.1 Overview

This is a conformance test for checking the administration of IO employee data managed by the VM RMI system as described in requirement TREQ-3 specified in ISO 18541-2.

20.3.2 Test purpose

This conformance test is used to verify that the VM RMI system manages administration of IO employment data correctly

20.3.3 Configuration

User rights as VM RMI system administrator.

20.3.4 Preamble (setup state)

No preamble.

20.3.5 Test execution

Table 65 defines the test execution.

Table 65 — [RMI-CT_TREQ-3] Test administration of IO employee data by the VM test execution

Step #	Description
1	Access the VM RMI system database and verify that all needed fields are present and managed.

20.3.6 Postamble

No post conditions.

20.4 [RMI-CT_TREQ-4] Test administration of payment data by VM

20.4.1 Overview

This is a conformance test for checking the accuracy of payment data managed by the VM RMI system as described in requirement TREQ-4 specified in ISO 18541-2.

20.4.2 Test purpose

This conformance test is used to verify that the VM RMI system manages payment and invoicing data.

20.4.3 Configuration

User rights as VM RMI system administrator.

20.4.4 Preamble (setup state)

No preamble.

20.4.5 Test execution

Table 66 defines the test execution.

Table 66 — [RMI-CT_TREQ-4] Test administration of payment data by VM test execution

Step #	Description
1	Access the VM RMI system database and verify that all needed fields are present and managed.

20.4.6 Postamble

No post conditions.

20.5 [RMI-CT_TREQ-5] Test administration of access event data by VM

20.5.1 Overview

This is a conformance test for checking the accuracy of access event data managed by the VM RMI system as described in requirement TREQ-5 specified in ISO 18541-2.

20.5.2 Test purpose

This conformance test is used to verify that the VM RMI system manages access event data.

20.5.3 Configuration

User rights as VM RMI system administrator.

20.5.4 Preamble (setup state)

No preamble.

20.5.5 Test execution

Table 67 defines the test execution.

Table 67 — [RMI-CT_TREQ-5] Test administration of access event data by VM test execution

Step #	Description
1	Access the VM RMI system database and verify that all needed fields are present and managed.

20.5.6 Postamble

No post conditions.

20.6 [RMI-CT_TREQ-6] Test administration of access event data to security-related RMI by VM

20.6.1 Overview

This is a conformance test for checking the access event data to security-related RMI managed by the VM RMI system as described in requirement TREQ-6 specified in ISO 18541-2.

20.6.2 Test purpose

This conformance test is used to verify that the VM RMI system manages access event data to security-related RMI correctly.

20.6.3 Configuration

User rights as VM RMI system administrator.

20.6.4 Preamble (setup state)

No preamble.

20.6.5 Test execution

Table 68 defines the test execution.

Table 68 — [RMI-CT_TREQ-6] Test administration of access event data to security-related RMI by VM test execution

Step #	Description
1	Access the VM RMI system database and verify that all needed fields are present and managed.

20.6.6 Postamble

21 CT cluster 16 — Test VM software installation on the IO client

21.1 [RMI-CT_TREQ-20] Test for requirements for installing VM-specific software on the IO client

21.1.1 Overview

This is a conformance test for requirement TREQ-20 specified in ISO 18541-2.

21.1.2 Test purpose

This conformance test is used to verify that if any VM-specific software is to be installed on the IO client, it shall act in such a way that the functionality of the IO PC/laptop is unaffected when the VM software is not running, except for VM installed software files.

21.1.3 Configuration

No additional configuration required.

21.1.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible.

21.1.5 Test execution

Table 69 defines the test execution.

Table 69 — [RMI-CT_TREQ-20] Test for requirements for installing VM-specific software on the IO client test execution

Step#	Description
1	Check the existence of download area as stated in FREQ-4.
2	In case no download area is present, go to step 4.
3	Download and install, if needed, all applications/plug-ins available via download area.
4	Check by inspection of the relevant IO client areas the list of requirements in the brief description of TREQ-20.

21.1.6 Postamble

21.2 [RMI-CT_TREQ-21] Test for requirements for updating of installed VM data and applications on the IO client

21.2.1 Overview

This is a conformance test for requirement TREQ-21 specified in ISO 18541-2.

21.2.2 Test purpose

This conformance test is used to verify that if any VM-specific updating of VM data and applications is to be installed on the IO client, it shall act in such a way that the functionality of the IO PC/laptop is unaffected when the VM software is not running, except for VM installed software files.

21.2.3 Configuration

No additional configuration required.

21.2.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible;
- relevant use case to invoke the installed software selected.

21.2.5 Test execution

Table 70 defines the test execution.

Table 70 — [RMI-CT_TREQ-21] Test for requirements for updating of installed VM data and applications on the IO client test execution

Step #	Description
1	In case an update of the software is available, tester shall accept to update the software.
2	Install according to the VM instructions.
	Check by inspection of the relevant IO client areas the list of requirements in the brief description of TREQ-20 and TREQ-21.

21.2.6 Postamble

No post conditions.

21.3 [RMI-CT_TREQ-22] Test for requirements for the operation of VM-specific software on the IO client

21.3.1 Overview

This is a conformance test for requirement TREQ-22 specified in ISO 18541-2.

21.3.2 Test purpose

This conformance test is used to verify that any VM-specific software on the IO client shall be responsible for resetting the PC/Laptop system configuration to the same state as it was before it started, excepting the VM-specific software configuration and general purpose services and processes.

21.3.3 Configuration

No additional configuration required.

21.3.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible;
- relevant use case to invoke the installed software selected.

21.3.5 Test execution

Table 71 defines the test execution.

Table 71 — [RMI-CT_TREQ-22] Test for requirements for the operation of VM-specific software on the IO client test execution

Step #	Description
1	Close the session.
2	Check by inspection of the relevant IO client areas the list of requirements in the brief description of TREQ-22.

21.3.6 Postamble

No post conditions.

21.4 [RMI-CT_TREQ-23] Test for requirements for the uninstalling of VM-specific software on the IO client

21.4.1 Overview

This is a conformance test for requirement TREQ-23 specified in ISO 18541-2.

21.4.2 Test purpose

This conformance test is used to verify that the VM-specific software is responsible for removing VM-installed software files, data, registry entries and folders when the user requests to uninstall the VM.

21.4.3 Configuration

No additional configuration required.

21.4.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- VM software installed.

21.4.5 Test execution

Table 72 defines the test execution.

Table 72 — [RMI-CT_TREQ-23] Test for requirements for the uninstalling of VM-specific software on the IO client test execution

Step #	Description
1	Uninstall the VM software on the IO client following the instructions of the VM.
	Check by inspection of the relevant IO client areas the list of requirements in the brief description of TREQ-23.

21.4.6 Postamble

Install the system again to be able to perform other test cases.

21.5 [RMI-CT_TREQ-24] Test for requirements for restoring in case of an abnormal termination of the VM specific software on the IO client

21.5.1 Overview

This is a conformance test for requirement TREQ-24 specified in ISO 18541-2.

21.5.2 Test purpose

This conformance test is used to verify that in case of an abnormal termination, the VM-specific software shall make best endeavours to restore the PC/laptop system configuration to the same state as after a normal termination, at the next invocation/call of the VM-specific software.

21.5.3 Configuration

This test is possible only if an abnormal termination of installed software can be generated.

21.5.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;

standardized navigation map is visible.

21.5.5 Test execution

Table 73 defines the test execution.

Table 73 — [RMI-CT_TREQ-24] Test for requirements for restoring in case of an abnormal termination of the VM specific software on the IO client test execution

Step #	Description
1	Log-in to the VM RMI system.
2	Perform some actions where the VM software installed on the client is involved.
3	Cause an abnormal termination of the VM RMI session, e.g. by shutting down the client.
4	Restart the VM RMI system and log-in.
5	Check if the system behaviour is consistent with TREQ-24.

21.5.6 Postamble

Close the session.

22 CT cluster 17 — Test VM RMI operations

22.1 [RMI-CT_TREQ-25] Test for VM RMI system availability time

22.1.1 Overview

This is a conformance test for requirement TREQ-25 specified in ISO 18541-2.

22.1.2 Test purpose

This conformance test is used to verify that the VM RMI system is operational.

22.1.3 Configuration

No additional configuration required.

22.1.4 Preamble (setup state)

Setup conditions are as follows:

- all test cases passed of CT cluster 1 Test technical infrastructure;
- navigate to VM RMI home page;
- check that scheduled maintenance is not being undertaken.

22.1.5 Test execution

<u>Table 74</u> defines the test execution.

Table 74 — [RMI-CT_TREQ-25] Test for VM RMI system availability time test execution

Step#	Description
1	Perform one of the test cases listed above in this part of ISO 18541.
2	Confirm that the test case is successfully completed.

22.1.6 Postamble

No post conditions.

22.2 [RMI-CT_TREQ-26] Test for support for the usage of the VM RMI system

22.2.1 Overview

This is a conformance test for requirement TREQ-26 specified in ISO 18541-2.

22.2.2 Test purpose

This conformance test is used to verify whether the VM offers support for the usage of the VM RMI system.

22.2.3 Configuration

No additional configuration required.

22.2.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible.

22.2.5 Test execution

Table 75 defines the test execution.

Table 75 — [RMI-CT_TREQ-26] Test for support for the usage of the VM RMI system test execution

Step #	Description
1	Check if user manual or context sensitive help is available.
2	Check if FAQs are available.
3	Check if email contact area is available and operational (i.e. answers to requests are provided).
4	If additional support is provided to VM AR, e.g. user help desk, check if it is available for IO.

22.2.6 Postamble

23 CT cluster 18 — Test trust centre (certificate management)

23.1 [RMI-CT_TREQ-10] Test for trust centre (certificate management)

23.1.1 Overview

This is a conformance test for technical requirement TREQ-10 specified in ISO 18541-2.

23.1.2 Test purpose

This conformance test is used to verify that the VM RMI system shall support an online interface to the trust centre. Via this interface, the VM shall check the validity status of the digital certificate presented by the IO and shall verify the IO's authorization status to obtain access to security-related RMI.

23.1.3 Configuration

No additional configuration required.

23.1.4 Preamble (setup state)

Setup conditions are as follows:

- valid and operational technical infrastructure according to ISO 18541-2;
- valid login data and subscription, if required by the VM RMI system;
- VM RMI system is not under maintenance;
- VM RMI home page is visible;
- standardized navigation map is visible;
- the tester has a valid digital certificate and authorization as specified in the SERMI scheme;
- the tester has installed the hardware and SW received from the trust centre for the processing of the digital certificate;
- the tester acts as a user without granted access to security-related RMI in this VM RMI system.

23.1.5 Test execution

Table 76 defines the test execution.

Table 76 — [RMI-CT_TREQ-10] Test for trust centre (certificate management) test execution

Step #	Description
1	Select UC 1.7 and follow the instruction provided, according to FREQ-5.
2	Verify that the certificate and the authorization are validated.

23.1.6 Postamble

Close the session.

Bibliography

- [1] MANDATE E.C. M/421: MANDATE TO THE EUROPEAN STANDARDIZATION ORGANISATIONS FOR STANDARDIZATION IN THE FIELD OF VEHICLE OBD, REPAIR AND MAINTENANCE INFORMATION; Directive 70/156/EEC Light- and Heavy-Duty motor Vehicles of 6 February 1970 on the approximation of the laws of the Member States relating to the type-approval of motor vehicles and their trailers, replaced by Directive 2007/46/EC; source: http://eur-lex.europa.eu/
- [2] Directive 2002/24/EC Motorbikes (consolidated version of Council Directive 2006/96/EC); source: http://eur-lex.europa.eu/
- [3] Directive 2003/37/EC agricultural or forestry tractors (consolidated version of Council Directive 2006/96/EC); source: http://eur-lex.europa.eu/
- [4] Directive 2007/46/EC of the European Parliament and of the Council of 5 September 2007 establishing a framework for the approval of motor vehicles and their trailers, and of systems, components and separate technical units intended for such vehicles (Framework Directive); source: http://eur-lex.europa.eu/
- [5] REGULATION. (EC) No 715/ 2007 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2007 on type approval of motor vehicles with respect to emissions from light passenger and commercial vehicles (Euro 5 and Euro 6) and on access to vehicle repair and maintenance information; source: http://eur-lex.europa.eu/
- [6] COMMISSION REGULATION (EC) No 692/ 2008 of 18 July 2008 implementing and amending Regulation (EC) No 715/2007 of the European Parliament and of the Council on type-approval of motor vehicles with respect to emissions from light passenger and commercial vehicles (Euro 5 and Euro 6) and on access to vehicle repair and maintenance information; source: http://eurlex.europa.eu/
- [7] COMMISSION REGULATION (EU) No 566/ 2011 of 8 June 2011 amending Regulation (EC) No 715/2007 of the European Parliament and of the Council and Commission Regulation (EC) No 692/2008 as regards access to vehicle repair and maintenance information; source: http://eur-lex.europa.eu/
- [8] COMMISSION REGULATION (EU) No 461/2010 of 27 May 2010 on the application of Article 101(3) of the Treaty on the Functioning of the European Union to categories of vertical agreements and concerted practices in the motor vehicle sector; source: http://eur-lex.europa.eu/
- [9] No G.T.R. 5, Technical Requirements for On-Board Diagnostic Systems (OBD) for Road Vehicles, United Nations Economic and Social Council, 15 November 2006; source: http://www.unece.org/trans/main/wp29/wp29wgs/wp29gen/wp29registry/gtr5.html
- [10] ISO 22900-2, Road vehicles Modular vehicle communication interface (MVCI) Part 2: Diagnostic protocol data unit application programming interface (D-PDU API); source: http://www.iso.org/iso/store.htm
- [11] ISO 20828: 2006, Road vehicles Security certificate management; source: http://www.iso.org/iso/store.htm
- [12] X.509v3 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile; source: http://www.ietf.org/rfc/rfc3280.txt
- [13] SAE J2534-1, Recommended Practice for Pass-Thru Vehicle Programming; source: http://store.sae.org/
- [14] SAE J2534-2, Optional Pass-Thru Features; source: http://store.sae.org/

BS EN ISO 18541-4:2015 **ISO 18541-4:2015(E)**

[15] SERMI. EC Forum for Access to Vehicle RMI, Report on Access to security-related RMI, Version 1.1; source: http://www.vehiclesermi.eu





British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards -based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com
Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070 Email: copyright@bsigroup.com

