

BS EN ISO 24534-3:2016



BSI Standards Publication

Intelligent transport systems — Automatic vehicle and equipment identification — Electronic registration identification (ERI) for vehicles

Part 3: Vehicle data (ISO 24534-3:2016)

bsi.

National foreword

This British Standard is the UK implementation of EN ISO 24534-3:2016. It supersedes BS EN ISO 24534-3:2010 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee EPL/278, Intelligent transport systems.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2016.
Published by BSI Standards Limited 2016

ISBN 978 0 580 82566 8

ICS 03.220.20; 35.240.60

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 April 2016.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

EUROPEAN STANDARD

EN ISO 24534-3

NORME EUROPÉENNE

EUROPÄISCHE NORM

April 2016

ICS 03.220.20; 35.240.60

Supersedes EN ISO 24534-3:2010

English Version

Intelligent transport systems - Automatic vehicle and
equipment identification - Electronic registration
identification (ERI) for vehicles - Part 3: Vehicle data (ISO
24534-3:2016)

Systèmes de transport intelligents - Identification
automatique des véhicules et des équipements -
Identification d'enregistrement électronique (ERI)
pour les véhicules - Partie 3: Données du véhicule (ISO
24534-3:2016)

Automatische Identifizierung von Fahrzeugen und
Ausrüstungen - Elektronische Identifizierung für die
Registrierung (ERI) von Fahrzeugen - Teil 3:
Fahrzeugdaten (ISO 24534-3:2016)

This European Standard was approved by CEN on 4 March 2016.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

European foreword

This document (EN ISO 24534-3:2016) has been prepared by Technical Committee ISO/TC 204 “Intelligent transport systems” in collaboration with Technical Committee CEN/TC 278 “Intelligent transport systems” the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2016, and conflicting national standards shall be withdrawn at the latest by October 2016.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 24534-3:2010.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 24534-3:2016 has been approved by CEN as EN ISO 24534-3:2016 without any modification.

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Abbreviations	3
5 Requirements	3
5.1 Vehicle identification data.....	3
5.2 Vehicle identifier.....	4
5.3 ERI data type.....	5
5.4 Additional ERI data type.....	5
5.5 Additional ERI registration data.....	5
5.5.1 Additional ERI registration data type.....	5
5.5.2 Administrative types.....	11
5.5.3 EU vehicle category code type.....	12
5.5.4 Other Vehicle type types.....	13
5.5.5 ISO 3833 vehicle type.....	14
5.5.6 Other vehicle shape types.....	15
5.5.7 Number of passenger, axles, and mass types.....	15
5.5.8 Engine and power source types.....	17
5.5.9 Environmental types.....	18
5.5.10 Official test data type.....	19
5.5.11 Types used for EFC.....	19
5.5.12 Other types.....	26
5.6 Attributes.....	28
5.6.1 Introduction.....	28
5.6.2 Useful types.....	28
5.6.3 Useful sets of attributes.....	29
5.6.4 Information object class ATTRIBUTES.....	29
5.6.5 Attribute definitions.....	29
5.7 Encoding.....	30
Annex A (normative) ASN.1 Modules	31
Annex B (informative) Combined ERI data and local registrations	50
Annex C (informative) Correspondance with EFC attributes	54
Bibliography	56

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 204, *Intelligent transport systems*.

This second edition cancels and replaces the first edition (ISO 2453-3:2010), which has been technically revised.

ISO 24534 consists of the following parts, under the general title *Automatic vehicle and equipment identification — Electronic registration identification (ERI) for vehicles*:

- *Part 1: Architecture*
- *Part 2: Operational requirements*
- *Part 3: Vehicle data*
- *Part 4: Secure communications using asymmetrical techniques*
- *Part 5: Secure communications using symmetrical techniques.*

Introduction

A quickly emerging need has been identified within administrations to improve the unique identification of vehicles for a variety of services. Situations are already occurring where manufacturers intend to fit lifetime tags to vehicles. Various governments are considering the needs and benefits of ERI, such as legal proof of vehicle identity with potential mandatory usages. There is a commercial and economic justification both in respect of tags and infrastructure that a standard enables an interoperable solution.

Electronic registration identification (ERI) is a means of uniquely identifying road vehicles. The application of ERI will offer significant benefits over existing techniques for vehicle identification. It will be an enabling technology for the future management and administration of traffic and transport including applications in free-flow, multi-lane, traffic conditions with the capability to support mobile transactions. ERI addresses the need of authorities, and other users for a trusted electronic identification, including roaming vehicles.

This part of ISO 24534 specifies the vehicle-related data that can be exchanged between an onboard electronic registration tag (ERT) and an ERI reader/writer inside or outside the vehicle. The vehicle-related data consist of the vehicle identifier and may also include additional vehicle data as typically included in a vehicle registration certificate.

This part of ISO 24534 does not provide any accurate definitions for additional vehicle data items. This is left to the local registration authorities and/or local legislation. This part of ISO 24534 only provides the means for an unambiguous exchange of vehicle parameters registered by local registration authorities.

This part of ISO 24534 makes use of the basic automatic vehicle identification (AVI) definitions in ISO 14816.

Intelligent transport systems — Automatic vehicle and equipment identification — Electronic registration identification (ERI) for vehicles —

Part 3: Vehicle data

1 Scope

This part of ISO 24534 provides the requirements for an electronic registration identification (ERI) that is based on an identifier assigned to a vehicle (e.g. for recognition by national authorities) suitable to be used for the following:

- electronic identification of local and foreign vehicles by national authorities;
- vehicle manufacturing, in-life-maintenance, and end-of-life identification (vehicle life cycle management);
- adaptation of vehicle data, e.g. in case of international re-sales;
- safety-related purposes;
- crime reduction;
- commercial services;
- adhering to privacy and data protection regulations.

This part of ISO 24534 defines the vehicle identification data. This data is called the ERI data and includes the following:

- the vehicle identifier;
- possible additional vehicle-related information (as typically included in a vehicle registration certificate).

All additional vehicle data elements are defined as optional. It is left to local legislation and/or the discretion of a registration authority to use or not to use a particular data element. If used, the value is assumed to be the one registered by the registration authority in accordance with local legislation. This part of ISO 24534 only provides the syntax for all these data elements.

NOTE The secure application layer interfaces for the exchange of ERI data with an ERI reader or writer are specified in ISO 24534-4 and in ISO 24534-5.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 612:1978, *Road vehicles — Dimensions of motor vehicles and towed vehicles — Terms and definitions*

ISO 1176:1990, *Road vehicles — Masses — Vocabulary and codes*

ISO 3779, *Road vehicles — Vehicle identification number (VIN) — Content and structure*

ISO 3780, *Road vehicles — World manufacturer identifier (WMI) code*

ISO 3833, *Road vehicles — Types — Terms and definitions*

ISO/IEC 8824 (all parts), *Information technology — Abstract Syntax Notation One (ASN.1)*

ISO/IEC 8825-2:2008, *Information technology — ASN.1 encoding rules: Specification of Packed Encoding Rules (PER)*

ISO 14816, *Road transport and traffic telematics — Automatic vehicle and equipment identification — Numbering and data structure*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1 additional vehicle data

ERI data (3.5) in addition to the vehicle identifier

3.2 attribute

type (3.12) with an associated identifier

[SOURCE: ISO/IEC 8824-1:2008, Annex G.2.15.1, modified]

3.3 distinguishing identifier

information which unambiguously distinguishes an entity

[SOURCE: ISO/IEC 9798-1, 3.12, modified]

3.4 electronic registration identification ERI

action or act of identifying a vehicle with electronic means for purposes as mentioned in the scope of this part of ISO 24534

3.5 ERI data

vehicle identifying data which can be obtained from an *ERT* (3.6)

Note 1 to entry: ERI data consist of the vehicle identifier and possible *additional vehicle data* (3.1).

3.6 electronic registration tag ERT

onboard ERI device that contains the *ERI data* (3.5) including relevant security provisions and one or more interfaces to access that data

Note 1 to entry: In case of high security, the ERT is a secure application module (SAM).

Note 2 to entry: The ERT may be a separate device or may be integrated into an onboard device that also provides other capabilities (e.g. DSRC communications).

3.7 periodic motor vehicle test

compulsory periodic (e.g. annual) test of the roadworthiness of a motor vehicle of above a specified age or a certificate of passing such a test

EXAMPLE The MOT test in the United Kingdom is an example.

3.8 privacy

right of individuals to control or influence what information related to them may be collected and stored and by whom and to whom that information may be disclosed

[SOURCE: ISO 7498-2, 3.3.43]

Note 1 to entry: Since this term relates to the right of individuals, it cannot be very precise and its use should be avoided except as a motivation for requiring security.

3.9 registration authority

<for vehicles> authority responsible for the registration and maintenance of vehicle records

Note 1 to entry: The authority may provide vehicle records to accredited organizations.

3.10 registration authority

<for ERI data> organization responsible for writing *ERI data* (3.5) and security data according to local legislation

Note 1 to entry: The registration authority for ERI data may be the same as the *registration authority* (3.9) for vehicles. This part of ISO 24534, however, does not require this.

3.11 registration certificate

vehicle registration document (paper or smart card) issued by the *registration authority* (3.9) for vehicles in which the vehicle and its owner or lessee are registered

3.12 type

named set of values

[SOURCE: ISO/IEC 8824-1, 3.8.86]

4 Abbreviations

AEI	Automatic Equipment Identification
ASN.1	Abstract Syntax Notation One [as defined in ISO 8824 (all parts)]
AVI	Automatic Vehicle Identification
EEA	European Economic Area
EFC	Electronic Fee Collection
EN	Europäische Norm (German), English: European Standard
ENV	Europäische Norm Vorausgabe (German), English: European Pre-Standard
ERI	Electronic Registration Identification
ERT	Electronic Registration Tag
EU	European Union
IEC	International Electrotechnical Commission
ISO	International Organization for Standardization
VIN	Vehicle Identification Number

5 Requirements

5.1 Vehicle identification data

This subclause is informative only.

The secure onboard environment in which the vehicle identification data is stored is called the electronic registration tag (ERT).

[Clause 5](#) provides an abstract definition of the ERI data to be exchanged between the ERT and an ERI reader or writer. The abstract definitions are defined using abstract syntax notation one (ASN.1) as defined in ISO 8824 (all parts).

The identifier used to identify a vehicle is called the vehicle identifier or `vehicleId`. The preferred vehicle identifier is the VIN that is assigned to the vehicle by its manufacturer in accordance with ISO 3779.

However, in order to make this part of ISO 24534 also applicable in countries where the VIN is not used, an alternative is also supported (see [5.2](#)). The fundamental requirement is that the combination of a registration authority and a vehicle identifier should be globally distinguishing.

NOTE 1 As two vehicles built 30 years after each other may have the same VIN, the VIN is not 100 % unique.

NOTE 2 Empirical data has shown that a database of a registration authority may contain duplicate VIN numbers.

NOTE 3 In this part of ISO 24534, the combination of the almost unique `vehicleId` and a unique ERT number may be used as the unambiguous distinguishing identifier. The ERT number is a unique read-only identifier that is written into the ERT during ERT manufacturing time (see EN ISO 24534-4 and ISO 24534-5 for details).

Apart from the vehicle identifier, this part of ISO 24534 also supports the use of additional vehicle data as typically included in a vehicle registration certificate. This additional vehicle data may, for example, be used as

- additional identification information to improve the trust in a vehicle identifier, and
- certified vehicle information for other applications (e.g. for tolling to determine a tariff).

5.2 Vehicle identifier

The `VehicleId` type shall be used for the vehicle identifier according to local legislation and is defined as follows.

```
VehicleId ::= CHOICE {  
    vin                VIN,                -- preferred choice  
    raSpecificVehicleId RaSpecificVehicleId,  
    ...  
}
```

VIN ::= CS5

NOTE 1 The ‘..’ at the end of the definition designates that the type `VehicleId` may be extended with additional components at the end of the type definition in new versions of this part of ISO 24534, e.g. to cope with a new VIN standard.

The vehicle identifier should be a globally distinguishing identifier.

NOTE 2 When identifying a vehicle, the ERT always delivers the `VehicleId` in combination with the identifier of the registration authority and the ERT number. The identifier of the registration authority may be used to obtain additional information about the vehicle. The ERT number is an extra unique identifier from another source that may be used to resolve potential disputes about the VIN of a vehicle.

NOTE 3 The choice of which alternative is used is outside the scope of this part of ISO 24534. It may, for example, depend on local legislation.

The VIN alternative, if used, shall be of type VIN and is the preferred vehicle identifier. The type VIN is identical to the type CS5 as defined in ISO 14816. The value of the VIN alternative shall be the value of the VIN as assigned conforming to ISO 3779 by a manufacturer or a registration authority.

The `RaSpecificVehicleId` alternative, if used, shall contain a globally distinguishing identifier for the vehicle and shall be of type `raSpecificVehicleId` as defined below.

```
RaSpecificVehicleId ::= SEQUENCE {
    wmi                                UTF8String (SIZE(3)),
    nonIsoStandardId                  UTF8String (SIZE (1..20))
}
```

The `wmi` component shall contain the world manufacturer identifier (WMI) code of the organization that assigned the `nonIsoStandardId` value and the WMI code shall be assigned to this organization according to ISO 3780.

The `nonIsoStandardId` component shall be of type `UTF8String` with a maximum length of 20 characters.

NOTE Any additional meaning conveyed in the value of a `nonIsoStandardId` component is outside the scope of this part of ISO 24534.

5.3 ERI data type

The `EriData` type shall be used for the ERI data and is defined as follows:

```
EriData ::= SEQUENCE {
    vehicleId          VehicleId,
    additionalEriData  AdditionalEriData OPTIONAL
}
```

The `vehicleId` component shall contain the vehicle's identifier as defined in [5.2](#).

The `additionalEriData` component, if present, shall contain the additional ERI data.

5.4 Additional ERI data type

The type `AdditionalEriData` type is used for the additional ERI data and is defined as follows:

```
AdditionalEriData ::= CHOICE {
    additionalEriRegistrationData  AdditionalEriRegistrationData, -
    preferred choice
    ...,
    raSpecificAdditionalEriData    OCTET STRING (SIZE (0..1024))
    -- only to be used if
    AdditionalEriRegistrationData is not supported
}
```

The `additionalEriRegistrationData` alternative is the preferred alternative and shall be chosen whenever a value of the type `AdditionalEriRegistrationData` can be used.

The `raSpecificAdditionalEriData` alternative is of type `OCTET STRING` with a maximum length of 1 024 octets and shall only be used if a value of `additionalEriRegistrationData` cannot be used.

NOTE The '...' in the definition designates that the type `AdditionalEriData` may be extended with additional alternatives at the end of the type definition in new versions of this part of ISO 24534, e.g. to cope with a new version of the alternative ERI registration data.

5.5 Additional ERI registration data

5.5.1 Additional ERI registration data type

5.5.1.1 Definition of the additional ERI registration data type

The `AdditionalEriRegistrationData` type contains the vehicle related data typically found in a vehicle registration certificate and is defined as follows.

```
AdditionalEriRegistrationData ::= SEQUENCE {
    -- Administrative data
    registrationAuthority          RegistrationAuthority OPTIONAL,
    vehicleIdStatus                VehicleIdStatus OPTIONAL,
    dateOfFirstRegistration        DateOfFirstRegistration OPTIONAL,
    dateOfRegistration             DateOfRegistration OPTIONAL,
}
```

```

validThru                ValidThru OPTIONAL,
chassisNumber            ChassisNumber (SIZE (1..23))
                           OPTIONAL,
registrationNumber       RegistrationNumber OPTIONAL,

-- Vehicle type
vehicleMake              VehicleMake OPTIONAL,
vehicleType              VehicleType OPTIONAL,
vehicleTypeStatus        VehicleTypeStatus OPTIONAL,
commercialDescription     CommercialDescription OPTIONAL,
typeApprovalNumber       TypeApprovalNumber OPTIONAL,
vehicleCategory          VehicleCategory OPTIONAL,
vehicleTaxCategory       VehicleTaxCategory OPTIONAL,
euVehicleCategoryCode    EuVehicleCategoryCode OPTIONAL,
raSpecificVehicleClass1  RaSpecificVehicleClass1 OPTIONAL,
raSpecificVehicleClass2  RaSpecificVehicleClass2 OPTIONAL,
raSpecificVehicleClass3  RaSpecificVehicleClass3 OPTIONAL,
vehicleUse                VehicleUse OPTIONAL,
privateUse                PrivateUse OPTIONAL,
colour                    VehicleColour OPTIONAL,

-- Vehicle shape
length                    VehicleLength OPTIONAL,
width                     VehicleWidth OPTIONAL,
height                    VehicleHeight OPTIONAL,
wheelbase                 Wheelbase OPTIONAL,
bodyShape                 VehicleBodyShape OPTIONAL,
euBodyWorkType            EuBodyWorkType OPTIONAL,
iso3833VehicleType       Iso3833VehicleType OPTIONAL,

-- Vehicle number of passengers, axles, and mass
numberOfSeats             NumberOfSeats OPTIONAL, --
                           including the driver seat
numberOfStandingPlaces    NumberOfStandingPlaces OPTIONAL,
maxNumberOfPassengers     MaxNumberOfPassengers OPTIONAL,
                           -- including the driver
unladenWeight             UnladenWeight OPTIONAL,
maxDesignLadenMass        MaxDesignLadenMass OPTIONAL,
maxAuthorizedLadenMass    MaxAuthorizedLadenMass OPTIONAL,
maxAuthorizedTrainMass    MaxAuthorizedTrainMass OPTIONAL,
maxAuthorizedPayload      MaxAuthorizedPayload OPTIONAL,
numberOfAxles             NumberOfAxles OPTIONAL,
authorizedAxleLadenMass   AuthorizedAxleLadenMass OPTIONAL,
                           -- from front to rear axle
maxTowableMassBrakedTrailer MaxTowableMassBrakedTrailer
OPTIONAL,
maxTowableMassUnbrakedTrailer MaxTowableMassUnbrakedTrailer
OPTIONAL,

-- Vehicle engine and power source
engineId                  EngineId (SIZE (1..60)) OPTIONAL,
primeEngineType           PrimeEngineType OPTIONAL,
enginePowerSources        EnginePowerSources OPTIONAL,
primePowerSource          PrimePowerSource OPTIONAL,
engineMaxNetPower         EngineMaxNetPower OPTIONAL,
engineDisplacement        EngineDisplacement OPTIONAL,
ratedEngineSpeed          RatedEngineSpeed OPTIONAL,
powerWeightRatio          PowerWeightRatio OPTIONAL,
maxSpeed                  MaxSpeed OPTIONAL,
fuelTanksCapacity         FuelTanksCapacity OPTIONAL,

-- Environmental characteristics
stationarySoundLevel      StationarySoundLevel OPTIONAL,
engineSpeed               EngineSpeed OPTIONAL,
driveBySoundLevel         DriveBySoundLevel OPTIONAL,

```

```

emissionCO          EmissionCO OPTIONAL,
emissionHC          EmissionHC OPTIONAL,
emissionNOx        EmissionNOx OPTIONAL,
emissionHCandNOx   EmissionHCandNOx OPTIONAL,
particulatesForDiesel ParticulatesForDiesel OPTIONAL,
correctedAbsorptionCoefficient CorrectedAbsorptionCoefficient
OPTIONAL,
emissionCO2        EmissionCO2 OPTIONAL,
combinedFuelConsumption CombinedFuelConsumption OPTIONAL,
environmentalCategory EnvironmentalCategory OPTIONAL,
euroType           EuroType OPTIONAL,

-- Others
lastOfficialTestData OfficialVehicleTestData OPTIONAL,
...,
raSpecificData     RaSpecificData OPTIONAL
axlesPerAxleGroup AxlesPerAxleGroup OPTIONAL,
-- from front to rear axle group
authorizedAxleGroupLadenMass AuthorizedAxleGroupsLadenMass
OPTIONAL,
-- from front to rear axle group

-- ERI data used for EFC (types imported from
ElectronicRegistrationIdentificationEfcVehicleData
efcVehicleDimensions VehicleDimensions,
efcPassengerCapacity PassengerCapacity,
efcVehicleWeightLimits VehicleWeightLimits,
efcAxleWeightLimits AxleWeightLimits,
efcVehicleSpecificCharacteristics
VehicleSpecificCharacteristics,
efcTrailerCharacteristics TrailerCharacteristics,
efcEngine Engine,
efcSoundLevel SoundLevel,
efcCO2EmissionValue CO2EmissionValue,
efcExhaustEmissionValues ExhaustEmissionValues,
efcDieselEmissionValues DieselEmissionValue,
...
}

```

The type of the components of the `AdditionalEriRegistrationData` type is defined in [5.5](#) below.

NOTE 1 The ‘..’ at the end of the `AdditionalEriRegistrationData` definition designates that the `AdditionalEriRegistrationData` type may be still extended with additional components at the end of the type definition in new versions of this part of ISO 24534.

All components are optional. Whether or not an optional component is present or absent depends on local legislation and/or the discretion of the vehicle’s registration authority.

The precise meaning of a value of a component, if present, shall be determined by local legislation and/or the vehicle’s registration authority and shall always take precedence over a definition in this part of ISO 24534.

NOTE 2 This part of ISO 24534 only facilitates the exchange of ERI registration data values for the purpose of vehicle identification. Both the precise definition of terms and the assignment of values in a particular state or country are outside the scope of this part of ISO 24534.

In order to maintain consistency with the vehicle’s registration certificate, the value of a component, if present and applicable, should be equal to or at least as precise as the value of the corresponding data item on the vehicle’s registration certificate.

5.5.1.2 Administrative data components

The `registrationAuthority` component, if present, shall identify the registration authority that registered the vehicle.

The `vehicleIdStatus` component, if present, shall specify the status of the vehicle identifier.

The `vehicleIdStatus` component shall not be present for a VIN-based vehicle identifier.

The `dateOfFirstRegistration` component, if present, shall specify the date of the first registration of the vehicle with its current registration authority.

The `dateOfRegistration` component, if present, shall specify the date of the registration to which this ERI data refers.

The `validThru` component, if present, shall specify the last day the ERI data is valid. If not present, the validity period may be assumed to be unlimited.

The `chassisNumber` component, if present, shall specify the chassis number of the vehicle.

The `registrationNumber` component, if present, shall specify the vehicle's registration number as assigned by the registration authority.

5.5.1.3 Vehicle type components

The `vehicleMake` component, if present, shall specify the make of the vehicle as assigned by the vehicle manufacturer.

The `vehicleType` component, if present, shall specify the variant, if applicable, and/or the version, if applicable, of the vehicle as assigned by the vehicle manufacturer.

The `vehicleTypeStatus` component, if present, shall specify the status of the vehicle type.

The `commercialDescription` component, if present, shall contain the commercial description(s) of the vehicle.

The `typeApprovalNumber` component, if present, shall specify the type-approval number.

The `vehicleCategory` component, if present, shall specify the vehicle category according to local legislation.

The `vehicleTaxCategory` component, if present, shall specify the vehicle tax category according to local legislation.

The `euVehicleCategoryCode` component, if present, shall specify the vehicle category according to the EU directives EU 2001/116, EU 2002/24, and UNECE 1999.

The `raSpecificVehicleClass1` component, if present, shall contain a registration authority specific vehicle class, category, or code.

The `raSpecificVehicleClass2` component, if present, shall contain a registration authority specific vehicle class, category, or code.

The `raSpecificVehicleClass3` component, if present, shall contain a registration authority specific vehicle class, category, or code.

The `vehicleUse` component, if present, shall specify the use of the vehicle.

The `privateUse` component, if present, shall specify whether the vehicle is for private or for commercial use.

The `colour` component, if present, shall specify the colour of the vehicle.

5.5.1.4 Vehicle shape components

The `length` component, if present, shall specify the length of the vehicle.

The `width` component, if present, shall specify the width of the vehicle.

The `height` component, if present, shall specify the height of the vehicle.

The `wheelbase` component, if present, shall specify the wheelbase of the vehicle.

The `bodyShape` component, if present, shall specify the shape of the body of the vehicle.

The `euBodyWorkType` component, if present, shall specify the type of body work of the vehicle according to EU 2001/116.

The `iso3833VehicleType` component, if present, shall specify the type of the vehicle according to ISO 3833.

5.5.1.5 Vehicle number of passengers, axles, and mass components

The `numberOfSeats` component, if present, shall specify the number of seats including the driver seat.

The `numberOfStandingPlaces` component, if present, shall specify the number of standing places.

The `maxNumberOfPassenger` component, if present, shall specify the maximum permissible number of passengers (including the driver) that may use the vehicle.

The `unladenWeight` component, if present, shall specify the nominal unladen mass of the vehicle with bodywork.

The `maxDesignLadenMass` component, if present, shall specify the maximum technically permissible total mass of the vehicle including payload (but excluding the weight of trailers).

The `maxAuthorizedLadenMass` component, if present, shall specify the maximum permissible total mass of the vehicle including payload (but excluding the mass of trailers) when in service in the jurisdiction of the registration authority.

The `maxAuthorizedTrainMass` component, if present, shall specify the maximum permissible total mass in kilograms of the whole vehicle including payload (and including trailers and the payload of trailers) when in service in the jurisdiction of the registration authority.

The `maxAuthorizedPayload` component, if present, shall specify the maximum permissible payload of the vehicle (but excluding the payload of trailers).

The `numberOfAxles` component, if present, shall specify the number of axles of the vehicle (including lifted axles).

The `axlesPerAxleGroup` component, if present, shall specify the number of axles of each axle group of the vehicle (including lifted axles).

The `authorizedAxleLadenMass` component, if present, shall specify the maximum laden mass on each axle in kilograms.

The `authorizedAxleGroupLadenMass` component, if present, shall specify the maximum laden mass on each axle group in kilograms.

The `maxTowableMassBrakedTrailer` component, if present, shall specify the technically permissible maximum braked towable mass of the trailer.

The `maxTowableMassUnbrakedTrailer` component, if present, shall specify the technically permissible maximum unbraked towable mass of the trailer.

5.5.1.6 Vehicle engine and power source components

The `engineId` component, if present, shall specify the engine identification number.

The `primeEngineType` component, if present, shall specify type of the prime engine of the vehicle as assigned by the manufacturer.

The `enginePowerSource` component, if present, shall specify the power source(s) of the vehicle.

The `primePowerSource` component, if present, shall specify the power source of the prime engine.

The `engineMaxNetPower` component, if present, shall specify the nominal (maximum net) power of the engine.

The `engineDisplacement` component, if present, shall specify the displacement of the engine.

The `ratedEngineSpeed` component, if present, shall specify the rated speed.

The `powerWeightRatio` component, if present, shall specify the power/weight ratio of the vehicle.

The `maxSpeed` component, if present, shall specify the maximum speed of the vehicle.

The `fuelTankCapacity` component, if present, shall specify the capacity of the fuel tank(s).

5.5.1.7 Environmental characteristics components

The `stationarySoundLevel` component, if present, shall specify the stationary sound level of the vehicle.

The `engineSpeed` component, if present, shall specify the engine speed.

The `driveBySoundLevel` component, if present, shall specify the drive-by sound level of the vehicle.

The `emissionCO` component, if present, shall specify the CO exhaust emission.

The `emissionHC` component, if present, shall specify the HC exhaust emission.

The `emissionNOx` component, if present, shall specify the NOx exhaust emission.

The `emissionHCandNOx` component, if present, shall specify the HC plus COx exhaust emission.

The `particulatesForDiesel` component, if present, shall specify the exhaust emission of particulates for diesel.

The `correctedAbsorptionCoefficient` component, if present, shall specify the corrected absorption coefficient for diesel.

The `emissionCO2` component, if present, shall specify the CO2 exhaust emission.

The `combinedFuelConsumption` component, if present, shall specify the combined fuel consumption of the vehicle.

The `environmentalCategory` component, if present, shall be of type `EnvironmentalCategory` and shall specify the environmental category of the vehicle.

The `euroType` component, if present, shall reference for light duty vehicles to the environmental category Euro 1...6 according to EU directive 70/220/EEC and EU Regulation 715/2007 and for heavy duty vehicles to the category Euro I...VI according to EU Directive 1988/77, EU Directive 2005/55, and EU Regulation 595/2009.

5.5.1.8 Components used for EFC

The `efcVehicleDimensions` component, if present, shall specify the vehicle's overall length, height and width.

The `efcPassengerCapacity` component, if present, shall specify both the number of seats and the number standing places.

The `efcVehicleWeightLimits` component, if present, shall specify the maximum weight for the laden vehicle, the vehicle train, and the unladen vehicle weight.

The `efcAxleWeightLimits` component, if present, shall specify the maximum laden weight on the vehicle's axles.

The `efcVehicleSpecificCharacteristics` component, if present, shall specify the vehicle's environmental characteristics, engine characteristics, descriptive characteristics, and future characteristics.

The `efcTrailerCharacteristics` component, if present, shall specify for a trailer its type, the number of axles, the maximum permissible total weight, and the unladen weight.

The `efcEngine` component, if present, shall specify the engine's capacity and power.

The `efcSoundLevel` component, if present, shall specify the vehicle's stationary and drive-by soundlevels.

The `efcCO2EmissionValue` component, if present, shall specify the vehicle's emission of CO₂.

The `efcExhaustEmissionValues` component, if present, shall specify the vehicle's emission of CO, HC, NOX and HC plus NOX.

The `efcDieselEmissionValues` component, if present, shall specify the emission of diesel particles and the corrected absorption coefficient.

5.5.1.9 Other components

The `lastOfficialTestData` component, if present, shall specify the data observed during the last official vehicle test, e.g. a periodic motor vehicle test or an intermediate motor vehicle test.

The `lastOfficialTestData` component shall only be present if at least one of its components is present.

NOTE The value of the `EriRegistrationData` has to be signed and therefore, needs a canonical representation.

The `raSpecificVehicleData` component, if present, may contain any additional registration authority-specific data.

5.5.2 Administrative types

```

RegistrationAuthority ::= EntityId
VehicleIdStatus      ::= Text60
DateOfFirstRegistration ::= DATE
DateOfRegistration   ::= DATE
ValidThru            ::= DATE
ChassisNumber        ::= UTF8String (SIZE (1..23)) -- incl. 3 WMI
                      characters
RegistrationNumber    ::= CS4

```

Unless specified otherwise, the definition and assignment of the values for the types defined in this subclause are at the discretion of the registration authority and/or local legislation (see [5.5.1](#)).

The `RegistrationAuthority` type shall be used to identify a registration authority and shall be of type `EntityId`.

The `VehicleIdStatus` type shall be used to specify the status of a vehicle identifier.

The `VehicleIdStatus` type shall not be used for a VIN-based vehicle identifier.

EXAMPLE Possible values are, e.g. ordinary, authority assigned, the identifier of the authority that assigned the `vehicleId`, etc.

The `DateOfFirstRegistration` type shall be used to specify the date of the first registration of a vehicle with its current registration authority.

The value of a `DateOfFirstRegistration` type shall at least contain the year and optionally the month and/or day.

The `DateOfRegistration` type shall be used to specify the date of the registration to which this ERI data refers.

The `ValidThru` type shall be used to specify the last day the ERI data is valid. If not present, the validity period may be assumed to be unlimited.

The `ChassisNumber` type shall be used to specify the chassis number of a vehicle.

The `RegistrationNumber` type shall be used to specify the vehicle's registration number as assigned by the registration authority.

5.5.3 EU vehicle category code type

The `EuVehicleCategoryCode` type is defined as follows.

```
EuVehicleCategoryCode ::= CHOICE {  
    euVehicleCategoryL      EuVehicleCategoryL,  
-- conforms to EU 2002/24 and UNECE 1999  
    euVehicleCategoryM      EuVehicleCategoryM,  
-- conforms to EU 2001/116 and UNECE 1999  
    euVehicleCategoryN      EuVehicleCategoryN,  
-- conforms to EU 2001/116 and UNECE 1999  
    euVehicleCategoryO      EuVehicleCategoryO,  
-- conforms to EU 2001/116 and UNECE 1999  
    euVehicleCategoryT      NULL,      -- conforms to UNECE 1999  
    euVehicleCategoryG      NULL      -- conforms to EU 2001/116  
and UNECE 1999  
}  
EuVehicleCategoryL ::= ENUMERATED {l1, l2, l3, l4, l5, l6, l7}  
EuVehicleCategoryM ::= ENUMERATED {m1, m2, m3}  
EuVehicleCategoryN ::= ENUMERATED {n1, n2, n3}  
EuVehicleCategoryO ::= ENUMERATED {o1, o2, o3, o4}
```

An `EuVehicleCategoryCode` value may be an `euVehicleCategoryL` value, an `euVehicleCategoryM` value, an `euVehicleCategoryN` value, an `euVehicleCategoryO` value, an `euVehicleCategoryT` value, or an `euVehicleCategoryG` value.

The `euVehicleCategoryL` alternative shall be chosen for a vehicle in the L category according to directive EU2002/24 or UNECE 1999.

The `euVehicleCategoryL` alternative, if chosen, shall have one of the values l1, l2, l3, l4, l5, l6, or l7 for, respectively, the vehicle categories L1, L2, L3, L4, L5, L6, or L7 defined in directive EU2002/24 or UNECE 1999.

NOTE 1 EU Vehicle category L is used for vehicles with less than three wheels.

The `euVehicleCategoryM` alternative shall be chosen for a vehicle in the M category according to directive EU2001/116 or UNECE 1999.

The `euVehicleCategoryM` alternative, if chosen, shall have one of the values m1, m2, or m3 for, respectively, the vehicle categories M1, M2, or M3 defined in directive EU2001/116 or UNECE 1999.

NOTE 2 EU Vehicle category M is used for passenger vehicles with M1 for vehicles with no more than eight seats in addition to the driver seat, M2 for vehicles with more than eight seats, but less than five tons, and M3 for vehicles with more than eight seats and more than five tons.

NOTE 3 The category M1 special purpose vehicles from UNECE 1999 can be described as EU2001/116 body types (see the `euBodyWorkType`).

The `euVehicleCategoryN` alternative shall be chosen for a vehicle in the N category according to directive EU2001/116 or UNECE 1999.

The `euVehicleCategoryN` alternative, if chosen, shall have one of the values `n1`, `n2`, or `n3` for, respectively, the vehicle categories N1, N2, or N3 defined in directive EU 2001/116 or UNECE 1999.

NOTE 4 EU Vehicle category N is used for vehicles carrying goods with N1 for vehicles not exceeding 3,5 tons maximum mass, N2 for vehicles exceeding 3,5 tons maximum mass, but not exceeding 12 tons, and N3 for vehicles exceeding 12 tons maximum mass.

The `euVehicleCategoryO` alternative shall be chosen for a vehicle in the O category according to directive EU2001/116 or UNECE 1999.

The `euVehicleCategoryO` alternative, if chosen, shall have one of the values `o1`, `o2`, `o3`, or `o4` for, respectively, the vehicle categories O1, O2, O3, or O4 defined in directive EU 2001/116 or UNECE 1999.

NOTE 5 EU Vehicle category O is used for (semi-) trailers with O1 for trailers not exceeding 0,75 tons maximum mass, O2 for trailers exceeding 0,75 tons maximum mass, but not exceeding 3,5 tons, O3 for trailers exceeding 3,5 tons maximum mass, but not exceeding 10 tons, and O4 for trailers exceeding 10 tons maximum mass.

The `euVehicleCategoryT` alternative shall be chosen for a vehicle in the T category according to UNECE 1999.

NOTE 6 EU Vehicle category T is used for agricultural and forestry tractors.

The `euVehicleCategoryG` alternative shall be chosen for a vehicle in the G category according to directive EU2001/116 or UNECE 1999.

NOTE 7 EU Vehicle category G is used for off-road vehicles.

5.5.4 Other Vehicle type types

```

VehicleMake                ::= Text60
VehicleType                 ::= Text60
VehicleTypeStatus           ::= Text60
CommercialDescription       ::= Text60
TypeApprovalNumber          ::= UTF8String (SIZE (1..60))
VehicleCategory             ::= Text60
VehicleTaxCategory          ::= Text60
RaSpecificVehicleClass1     ::= Text60
RaSpecificVehicleClass2     ::= Text60
RaSpecificVehicleClass3     ::= Text60
VehicleUse                   ::= Text60
PrivateUse                   ::= BOOLEAN          -- False = commercial use
VehicleColour                ::= Text60

```

Unless specified otherwise, the definition and assignment of the values for the types defined in this subclause are at the discretion of the registration authority and/or local legislation (see [5.5.1](#)).

The `VehicleMake` type shall be used to specify the make of a vehicle as assigned by the vehicle manufacturer.

The `VehicleType` type shall be used to specify the variant, if applicable, and/or the version, if applicable, of a vehicle as assigned by the vehicle manufacturer.

The `VehicleTypeStatus` type shall be used to specify the status of the vehicle type.

EXAMPLE 1 Possible values are, e.g. prototype, prefabricated type, modified type, etc.

The `CommercialDescription` type shall be used for the commercial description(s) of a vehicle.

The `TypeApprovalNumber` type shall be used to specify the type-approval number, if available.

The `VehicleCategory` type shall be used to specify the vehicle category according to local legislation.

The `VehicleTaxCategory` type shall be used to specify the vehicle tax category according to local legislation.

The `RaSpecificVehicleClass1` type shall be used for a registration authority specific vehicle class, category, or code.

The `RaSpecificVehicleClass2` type shall be used for a registration authority specific vehicle class, category, or code.

The `RaSpecificVehicleClass3` type shall be used for a registration authority specific vehicle class, category, or code.

The `VehicleUse` type shall be used to specify the use of a vehicle.

EXAMPLE 2 A registration authority may want to use the `VehicleUse` type to specify the usage of a particular category of a vehicle with values such as, e.g. private or commercial, “school bus” for a vehicle in the bus category, or “rental car” for a private car.

The `PrivateUse` type shall be used to specify whether a vehicle is for private or for commercial use. If for private use, the value shall be `TRUE`. If for commercial use, the value shall be `FALSE`.

The `VehicleColour` type shall be used to specify the colour of a vehicle.

5.5.5 ISO 3833 vehicle type

The `Iso3833VehicleType` type is defined as follows.

```
Iso3833VehicleType ::= INTEGER {
    passengerCar           (0),      -- term No 3.1.1
    saloon                 (1),      -- term No 3.1.1.1 (sedan)
    convertibleSaloon     (2),      -- term No 3.1.1.2
    pullmanSaloon         (3),      -- term No 3.1.1.3
    stationWagon          (4),      -- term No 3.1.1.4
    truckStationWagon    (5),      -- term No 3.1.1.4.1
    coupe                 (6),      -- term No 3.1.1.5 (coupé)
    convertible           (7),      -- term No 3.1.1.6 (open
tourer, roadstar, spider)
    multipurposePassengerCar (8),      -- term No 3.1.1.7
    forwardControlPassengerCar (9), -- term No 3.1.1.8
    specialPassengerCar   (10),     -- term No 3.1.1.9
    bus                   (11),     -- term No 3.1.2
    minibus               (12),     -- term No 3.1.2.1
    urbanBus              (13),     -- term No 3.1.2.2
    interurbanCoach       (14),     -- term No 3.1.2.3
    longDistanceCoach     (15),     -- term No 3.1.2.4
    articulatedBus        (16),     -- term No 3.1.2.5
    trolleyBus            (17),     -- term No 3.1.2.6
    specialBus            (18),     -- term No 3.1.2.7
    commercialVehicle     (19),     -- term No 3.1.3
    specialCommercialVehicle (20),  -- term No 3.1.3.1
    specialVehicle        (21),     -- term No 3.1.4
    trailingTowingVehicle (22),     -- term No 3.1.5 (draw-bar
tractor)
    semiTrailerTowingVehicle (23),  -- term No 3.1.6 (fifth
wheel tractor)
    trailer                (24),     -- term No 3.2.1
    busTrailer             (25),     -- term No 3.2.1.1
    generalPurposeTrailer (26),     -- term No 3.2.1.2
    caravan                (27),     -- term No 3.2.1.3
    specialTrailer        (28),     -- term No 3.2.1.4
    semiTrailer           (29),     -- term No 3.2.2
    busSemiTrailer        (30),     -- term No 3.2.2.1
    generalPurposeSemiTrailer (31), -- term No 3.2.2.2
    specialSemiTrailer    (32),     -- term No 3.2.2.3
    roadTrain             (33),     -- term No 3.3.1
    passengerRoadTrain    (34),     -- term No 3.3.2
    articulatedRoadTrain  (35),     -- term No 3.3.3
    doubleRoadTrain       (36),     -- term No 3.3.4
    compositeRoadTrain    (37),     -- term No 3.3.5
    specialRoadTrain      (38),     -- term No 3.3.6
    moped                 (39),     -- term No 3.4
```



```
motorCycle          (40)    -- term No 3.5
} (0..255)
```

A “term No” in a comment parts refers to the number of the corresponding term and its definition in ISO 3833.

A value of `Iso3833VehicleType` type shall conform the corresponding definition in ISO 3833.

5.5.6 Other vehicle shape types

```
VehicleLength      ::= Millimetre
VehicleWidth       ::= Millimetre
VehicleHeight      ::= Millimetre
Wheelbase          ::= Millimetre
VehicleBodyShape   ::= Text60
EuBodyWorkType     ::= UTF8String (SIZE (2))
                   -- conforms to EU 2001/116
```

Unless specified otherwise, the definition and assignment of the values for the types defined in this subclause are at the discretion of the registration authority and/or local legislation (see [5.5.1](#)).

The `VehicleLength` type shall be used to specify the length of a vehicle in millimetres.

Unless local legislation specifies otherwise, ISO 612:1978, 6.1 applies and the length includes draw gear.

The `vehicleWidth` type shall be used to specify the width of a vehicle in millimetres.

Unless local legislation specifies otherwise, ISO 612:1978, 6.2 applies.

The `VehicleHeight` type shall be used to specify the height of a vehicle in millimetres.

Unless local legislation specifies otherwise, ISO 612:1978, 6.3 applies.

The `Wheelbase` type shall be used to specify the wheelbase of a vehicle in millimetres.

Unless local legislation specifies otherwise, ISO 612:1978, 6.4 (wheel space) applies and for vehicles with three or more axles (or semi-trailers with two or more axles) the distance is taken from the foremost wheel (the fifth wheel kingpin for semi-trailers) to the rearmost wheel.

The `VehicleBodyShape` type shall be used to specify the shape of the body of a vehicle.

The `EuBodyWorkType` type shall be used to specify the type of body work of a vehicle according to EU 2001/116.

NOTE 1 The EU bodywork type (two printable characters) is a refinement of ISO 3833.

NOTE 2 The EU bodywork type is also used for the designation of the special purpose vehicles as defined in UNECE 1999 (see EU2001/116).

5.5.7 Number of passenger, axles, and mass types

```
NumberOfSeats      ::= INTEGER    -- including the driver seat
NumberOfStandingPlaces ::= INTEGER
```

```
MaxNumberOfPassengers ::= INTEGER    -- including the driver
UnladenWeight         ::= Kilogram
MaxDesignLadenMass    ::= Kilogram
MaxAuthorizedLadenMass ::= Kilogram
MaxAuthorizedTrainMass ::= Kilogram
MaxAuthorizedPayload  ::= Kilogram
```

```
NumberOfAxles          ::= INTEGER
AxlesPerAxleGroup     ::= SEQUENCE OF Int1    -- from front to rear
axle group
AuthorizedAxleLadenMass ::= SEQUENCE OF Kilogram    -- from front to
rear axle
AuthorizedAxleGroupsLadenMass ::= SEQUENCE OF Kilogram -- from front to
rear axle group
MaxTowableMassBrakedTrailer ::= Kilogram
MaxTowableMassUnbrakedTrailer ::= Kilogram
```

Unless specified otherwise, the definition and assignment of the values for the types defined in this subclause are at the discretion of the registration authority and/or local legislation (see [5.5.1](#)).

The `NumberOfSeats` type shall be used to specify the number of seats, including the driver seat.

The `NumberOfStandingPlaces` type shall be used to specify the number of standing places.

The `MaxNumberOfPassenger` type shall be used to specify the maximum permissible number of passengers (including the driver) that may use a vehicle.

The `UnladenWeight` type shall be used to specify the nominal unladen mass of a vehicle with bodywork in kilograms.

Unless local legislation specifies otherwise, ISO 1176:1990, 4.6 (complete vehicle kerb mass) applies.

The `MaxDesignLadenMass` type shall be used to specify the maximum technically permissible total mass of a vehicle including payload (but excluding the weight of trailers) in kilograms.

Unless local legislation specifies otherwise, ISO 1176:1990, 4.7 (maximum design total mass) applies.

The `MaxAuthorizedLadenMass` type shall be used to specify the maximum permissible total mass of a vehicle including payload (but excluding the mass of trailers) in kilograms when in service in the jurisdiction of the registration authority.

Unless local legislation specifies otherwise, ISO 1176:1990, 4.8 (maximum authorized total mass) applies.

The `MaxAuthorizedTrainMass` type shall be used to specify the maximum permissible total mass in kilograms of a whole vehicle including payload (and including trailers and the payload of trailers) when in service in the jurisdiction of the registration authority.

Unless local legislation specifies otherwise, ISO 1176:1990, 4.19 (maximum authorized mass of vehicle combination) applies.

The `MaxAuthorizedPayload` type shall be used to specify the maximum permissible payload of a vehicle (but excluding the payload of trailers) in kilograms.

Unless local legislation specifies otherwise, ISO 1176:1990, 4.10 (maximum authorized pay mass) applies.

The `NumberOfAxles` type shall be used to specify the number of axles of a vehicle (including lifted axles).

The `AxlesPerAxleGroup` type shall be used to specify the number of axles of each axle group of a vehicle (including lifted axles).

The `AuthorizedAxleLadenMass` type shall be used to specify the maximum laden mass on each axle in kilograms.

The first value in the list shall specify the maximum laden mass on the front axle, the second on the axle next to the front axle (including lifted axles), and so on.

Unless local legislation specifies otherwise, ISO 1176:1990, 4.11 (maximum design axle load) applies.

The `AuthorizedAxleGroupsLadenMass` type shall be used to specify the maximum laden mass on each axle group in kilograms.

The `MaxTowableMassBrakedTrailer` type shall be used to specify the technically permissible maximum braked towable mass of a trailer in kilograms.

Unless local legislation specifies otherwise, ISO 1176:1990, 4.18 (maximum design towed mass) applies.

The `MaxTowableMassUnbrakedTrailer` type shall be used to specify the technically permissible maximum unbraked towable mass of a trailer in kilograms.

Unless local legislation specifies otherwise, ISO 1176:1990, 4.18 (maximum design towed mass) applies.

5.5.8 Engine and power source types

```

EngineId                ::= UTF8String (SIZE (1..60))
PrimeEngineType         ::= Text60
EnginePowerSources     ::= SEQUENCE OF PowerSource      -- primary
source first
PrimePowerSource        ::= PowerSource
EngineMaxNetPower       ::= Kilowatt
EngineDisplacement     ::= Millilitre
RatedEngineSpeed        ::= PerMinute
PowerWeightRatio        ::= KilowattPerKilogram
MaxSpeed                ::= KilometrePerHour
FuelTanksCapacity       ::= Litre

```

```

PowerSource ::= INTEGER {
    notPowered          (0),
    humanPowered        (1),
    animalPowered       (2),
    unleadedPetrol      (3),
    leadedPetrol        (4),
    diesel               (5),
    bioDiesel           (6),
    alcohol              (7),
    otherFuel           (8),
    lpg                  (9),
    hydrogen             (10),
    externalElectricPower (11),
    battery              (12),
    sun                  (13),
    other                (14)
} (0..255)

```

Unless specified otherwise, the definition and assignment of the values for the types defined in this subclause are at the discretion of the registration authority and/or local legislation (see [5.5.1](#)).

The `EngineId` type shall be used to specify the engine identification number.

The `PrimeEngineType` type shall be used to specify type of the prime engine of a vehicle as assigned by the manufacturer.

The `EnginePowerSources` type shall be used to specify the power source(s) of a vehicle (see below). In case of a hybrid vehicle, the primary power source is mentioned first.

The `PrimePowerSource` type shall be used to specify the power source of the prime engine.

The `EngineMaxNetPower` type shall be used to specify the nominal (maximum net) power of the engine in kW.

The `EngineDisplacement` type shall be used to specify the displacement of the engine in millilitres (cm³).

The `RatedEngineSpeed` type shall be used to specify the rated speed in min⁻¹.

The `RowerWeightRatio` type shall be used to specify the power/weight ratio of a vehicle in kW/kg.

The `MaxSpeed` type shall be used to specify the maximum speed of a vehicle in km/h.

The `FuelTankCapacity` type shall be used to specify the capacity of the fuel tank(s) in litres.

The `PowerSource` type shall be used to specify a power source and shall have one of the values: `notPowered`, `humanPowered`, `animalPowered`, `unleadedPetrol`, `leadedPetrol`, `diesel`, `bioDiesel`, `alcohol`, `otherFuel`, `lpg`, `hydrogen`, `externalElectricPower`, `battery`, `sun`, or `other`.

5.5.9 Environmental types

<code>StationarySoundLevel</code>	::= DB
<code>EngineSpeed</code>	::= PerMinute
<code>DriveBySoundLevel</code>	::= DB
<code>EmissionCO</code>	::= MgpkmOrMgpkwh
<code>EmissionHC</code>	::= MgpkmOrMgpkwh
<code>EmissionNOx</code>	::= MgpkmOrMgpkw
<code>EmissionHCandNOx</code>	::= MilligramPerKilometre
<code>ParticulatesForDiesel</code>	::= MicrogrampkmOrMicrogrampkwh
<code>CorrectedAbsorptionCoefficient</code>	::= PerKmMetre
<code>EmissionCO2</code>	::= GramPerKilometre
<code>CombinedFuelConsumption</code>	::= MillilitrePerKilometre
<code>EnvironmentalCategory</code>	::= Text60

```
EuroType ::= INTEGER{
    non-euro          (0),
    euro-1           (1),
    euro-2           (2),
    euro-3           (3),
    euro-4           (4),
    euro-5           (5),
    euro-6           (6)
    (0..255)}
```

Unless specified otherwise, the definition and assignment of the values for the types defined in this subclause are at the discretion of the registration authority and/or local legislation (see [5.5.1](#)).

The `StationarySoundLevel` type shall be used to specify the stationary sound level of the vehicle in dB(A).

The `EngineSpeed` type shall be used to specify the engine speed in min⁻¹.

The `DriveBySoundLevel` type shall be used to specify the drive-by sound level of the vehicle in dB(A).

The `EmissionCO` type shall be used to specify the CO exhaust emission in mg/km or mg/kWh.

The `EmissionHC` type shall be used to specify the HC exhaust emission in mg/km or mg/kWh.

The `EmissionNOx` type shall be used to specify the NOx exhaust emission in mg/km or mg/kWh.

The `EmissionHCandNOx` type shall be used to specify the HC plus COx exhaust emission in mg/km.

The `ParticulatesForDiesel` type shall be used to specify the exhaust emission of particulates for diesel in µg/km or µg/kWh.

The `CorrectedAbsorptionCoefficient` type shall be used to specify the corrected absorption coefficient for diesel in km⁻¹.

The `EmissionCO2` type shall be used to specify the CO2 exhaust emission in g/km.

The `CombinedFuelConsumption` type shall be used to specify the combined fuel consumption of a vehicle in millilitre/km (=litre/1 000km).

The `EnvironmentalCategory` type shall be used to be of type `EnvironmentalCategory` and shall specify the environmental category of a vehicle.

The `EuroType` type shall be used to specify for light duty vehicles the environmental category Euro 1...6 according to EU directive 70/220/EEC (repealed with effect from 2 January 20013) and EU Regulation 715/2007 and for heavy duty vehicles the category Euro I...VI according to EU Directive 2005/55 (repealed with effect from 31 December 2013) and EU Regulation 595/2009.

5.5.10 Official test data type

The type `OfficialVehicleTestData` shall be used for the results of an official roadworthiness test of the vehicle, e.g. a periodic motor vehicle test or an intermediate test and is defined as follows.

```
OfficialVehicleTestData ::= SEQUENCE {
    date                DATE OPTIONAL,
    location            NameAndAddress OPTIONAL,
    odometerValue      Kilometre OPTIONAL,
    emissionCO         MgpkmOrMgpkwh OPTIONAL,
    emissionHC         MgpkmOrMgpkwh OPTIONAL,
    remarks            Text60 OPTIONAL,
    ...
}
```

The `date` component, if present, shall specify the date of a vehicle test.

The `location` component, if present, shall be of type `NameAndAddress` and shall specify the name and address of the vehicle test facility.

The `odometerValue` component, if present, shall specify the reading of the odometer in kilometres.

The `emissionCOx` component, if present, shall specify the CO_x exhaust emission in mg/km or mg/kWh.

The `emissionHC` component, if present, shall specify the HC exhaust emission in mg/km or mg/kWh.

The `remarks` component, if present, shall specify any additional remarks.

5.5.11 Types used for EFC

5.5.11.1 General

Vehicle data is exchanged also for electronic fee collection (EFC) purposes.

[5.5.11](#) contains a number of additional vehicle data types used for EFC. These types may be used for other applications or may be supported by a registration authority as well.

NOTE 1 A reason for use may be a more compact encoding and/or the compatibility with ISO 14906:2011.

The units of data to be exchanged are the values of the EFC attributes listed in ISO 14906:2011, Table 36. The types defined in [5.5.11](#) are equivalent to the types listed in this table.

NOTE 2 Not all EFC vehicle data attributes can be used for ERI. Some EFC attributed contain dynamic date, i.e. data that is not suitable for a vehicle registration certificate. Some EFC attributes contain values for two registered vehicles: a towing one and a trailer. Therefore, it requires both vehicle registration certificates and, consequently, two `EriData` types to represent these two values. Some attributes contain data that is specific for a third party called "service provider" (for details, see Annex C).

NOTE 3 The ASN.1 specification of enumerated types is simplified by removing the numbers from named numbers. With PER encoding, these numbers are only used to order the enumeration before assigning an index number for each enumerated item. Then, the index number is used for the encoding (see ISO/IEC 8825-2:2008, Clause 14 for details).

5.5.11.2 Vehicle dimensions type

The `VehicleDimensions` type shall be used to specify the vehicle's overall length, height, and width in decimetres and rounded to the next decimetre.

The `VehicleDimensions` type is defined as follows.

```
VehicleDimensions ::= SEQUENCE {  
    vehicleLengthOverall      Int1,  
    vehicleHeightOverall      Int1,  
    vehicleWidthOverall       Int1  
}
```

The `vehicleLengthOverall` component shall specify the nominal maximum overall length of the vehicle in accordance with ISO 612.

The `vehicleHeightOverall` component shall specify the nominal overall unladen height in accordance with ISO 612.

The `vehicleWidthOverall` component shall specify the nominal overall width in accordance with ISO 612.

NOTE The `VehicleDimensions` type corresponds to the combined use of the `VehicleLength`, the `VehicleHeight`, and the `VehicleWidth` types with values rounded to the next decimetre.

5.5.11.3 Passenger capacity type

The `VehicleCapacity` type shall be used to specify both the number of seats and the number standing places.

The `VehicleCapacity` type is defined as follows.

```
PassengerCapacity ::= SEQUENCE{  
    numberOfSeats              Int1,  
    numberOfStandingPlaces     Int1  
}
```

The `numberOfSeats` component shall specify the number of seats of the vehicle including the driver's seat.

The `numberOfStandingPlaces` component shall specify the number of standing places of the vehicle.

NOTE The `VehicleDimensions` type corresponds to the combined use of the `NumberOfSeats` type and the `NumberOfStandingPlaces` type with the maximum values restricted to 255.

5.5.11.4 Vehicle weight limits type

The `VehicleWeightLimits` type shall be used to specify the maximum weight for the laden vehicle, the vehicle train, and the unladen vehicle weight.

The `VehicleWeightLimits` type is defined as follows.

```
VehicleWeightLimits ::= SEQUENCE {  
    vehicleMaxLadenWeight      Int2,  
    vehicleTrainMaximumWeight  Int2,  
    vehicleWeightUnladen       Int2  
}
```

The `vehicleMaxLadenWeight` component shall specify the maximum permissible total weight including payload in accordance with ISO 1176.

The `vehicleTrainMaximumWeight` component shall specify the maximum authorized mass of vehicle combination in accordance with ISO 1176 Code ISO-M19.

The `vehicleWeightUnladen` component shall specify the nominal unladen weight in accordance with ISO 1176.

All weight values are expressed in units of 10 kg and rounded down to the next 10 kg unit.

NOTE The type of the `vehicleMaxLadenWeight`, `vehicleTrainMaximumWeight`, and `vehicleWeightUnladen` corresponds the combined use of the `MaxAuthorizedLadenMass`, `MaxAuthorizedTrainMass`, and `UnladenWeight` types rounded down to 10 kilogram units and with values limited to 655 350 kilogram.

5.5.11.5 Axle weight limits type

The `AxleWeightLimits` type shall be used to specify the maximum laden weight on the vehicle's axles.

The `AxleWeightLimits` type is defined as follows.

```
AxleWeightLimits ::= SEQUENCE{
    maxLadenweightOnAxle1      Int2,
    maxLadenweightOnAxle2      Int2,
    maxLadenweightOnAxle3      Int2,
    maxLadenweightOnAxle4      Int2,
    maxLadenweightOnAxle5      Int2
}
```

The `maxLadenweightOnAxle1`, `maxLadenweightOnAxle2`, `maxLadenweightOnAxle3`, `maxLadenweightOnAxle4`, and `maxLadenweightOnAxle5` components shall be used to specify the technically permissible maximum laden weight on respectively the first, second, third, fourth, and fifth axle in 10 kg units and rounded down to the next 10 kg unit.

NOTE The `AxleWeightLimits` type differs from the `AuthorizedAxleLadenMass`. First, the authorized maximum may be less than the technically permissible maximum. Second, the value is rounded down to units of 10 kg and third, the number axle is limited to five.

5.5.11.6 Vehicle specific characteristics type

5.5.11.6.1 Vehicle specific characteristics type

The `VehicleSpecificCharacteristics` type shall be used to specify the vehicle's environmental characteristics, engine characteristics, descriptive characteristics, and future characteristics.

The `VehicleSpecificCharacteristics` type is defined as follows.

```
VehicleSpecificCharacteristics ::= SEQUENCE {
    environmentalCharacteristics      EnvironmentalCharacteristics,
    engineCharacteristics              EngineCharacteristics,
    descriptiveCharacteristics         DescriptiveCharacteristics,
    futureCharacteristics              FutureCharacteristics
}
```

The `environmentalCharacteristics` component shall specify the environmental characteristics.

The `engineCharacteristics` component shall specify the engine characteristics

The `descriptiveCharacteristics` component shall specify the descriptive characteristics

The `futureCharacteristics` component shall specify the vehicle's future characteristics.

5.5.11.6.2 Environmental characteristics type

The `EnvironmentalCharacteristics` type shall be used to specify the vehicles environmental characteristics.

The `EnvironmentalCharacteristics` type is defined as follows.

```
EnvironmentalCharacteristics ::= SEQUENCE {
    euroValue                        EuroValue,
    copValue                          CopValue
}
```

```
EuroValue ::= INTEGER{
    noEntry                (0),
    euro-1                  (1),
    euro-2                  (2),
    euro-3                  (3),
    euro-4                  (4),
    euro-5                  (5),
}
```

```
euro-6 (6),  
} (0..15) -- 4 bits, EURO-Classes as defined in EC directive  
88/77/EEC, annex 1  
-- and in 91/542/EEC, 96/1/EC, 1999/96/EC, 2001/27/EC
```

```
CopValue ::= INTEGER {  
noEntry (0),  
co2class1 (1), -- below 101 g/km  
co2class2 (2), -- 101 to 120 g/km  
co2class3 (3), -- 121 to 140 g/km  
co2class4 (4), -- 141 to 160 g/km  
co2class5 (5), -- 161 to 200 g/km  
co2class6 (6), -- 201 to 250 g/km  
co2class (7)7 -- above 250 g/km  
} (0..15) -- 4 bits, reserved for carbon dioxide pollution  
values as defined in  
-- EC directive 2003/127/EC
```

The `euroValue` component shall specify the vehicle's environmental category in accordance with EU directives 88/77/EEC, Annex 1, 91/542/EEC, 96/1/EC, 1999/96/EC, and 2001/27/EC.

NOTE 1 This specification is in accordance with ISO 14906:2011. However, see NOTES 2 and 3.

NOTE 2 All these directives are repealed in Annex IX part A of the newer EU directive 2005/55/EC which, in turn, is repealed with effect from 31 December 2013 (see EU Regulation 715/2007). EU Regulation 715/2007 stipulates also that references made to the repealed Directives shall be construed as being made to this regulation

NOTE 3 For light duty vehicles, EU Regulation 715/2007 applies.

The `copValue` component shall specify vehicle's emission of CO₂ using the values of the `CopValue` type.

NOTE 4 The `EnvironmentalCharacteristics` type corresponds to the combined use of the `EuroType` and `EmissionCO2` types with the `EmissionCO2` values expressed in g/km and divided into seven intervals/classes.

5.5.11.6.3 Engine characteristics type

The `EngineCharacteristics` type shall be used specify the vehicle's power source.

The `EngineCharacteristics` type is defined as follows.

```
EngineCharacteristics ::= INTEGER {  
noEntry (0),  
noEngine (1),  
petrolUnleaded (2),  
petrolLeaded (3),  
diesel (4),  
LPG (5),  
battery (6),  
solar (7)  
-- (8-255) are reserved for future CEN use  
} (0..255)
```

NOTE The `EngineCharacteristics` type corresponds with the `PrimePowerSource` type, but has a more limited set of values.

5.5.11.6.4 Descriptive characteristics type

The `DescriptiveCharacteristics` type shall be used to specify the vehicle's descriptive characteristics.

The `DescriptiveCharacteristics` type is defined as follows.

```
DescriptiveCharacteristics ::= INTEGER {  
noEntry (0),  
vehicleShape1 (1),  
vehicleShape2 (2),  
vehicleShape3 (3),  
vehicleShape4 (4),
```

```

vehicleShape5           (5),
vehicleShape6           (6),
vehicleShape7           (7),
vehicleShape8           (8),
vehicleShape9           (9),
vehicleShape10          (10),
vehicleShape11          (11),
vehicleShape12          (12),
vehicleShape13          (13),
vehicleShape14          (14),
vehicleShape15          (15),
vehicleShape16          (16),
vehicleShape17          (17),
vehicleShape18          (18),
vehicleShape19          (19),
vehicleShape20          (20),
vehicleShape21          (21),
vehicleShape22          (22),
vehicleShape23          (23),
vehicleShape24          (24),
vehicleShape25          (25),
vehicleShape26          (26),
vehicleShape27          (27),
vehicleShape28          (28),
vehicleShape29          (29),
vehicleShape30          (30),
vehicleShape31          (31),
vehicleShape32          (32),
vehicleShape33          (33),
vehicleShape34          (34),
vehicleShape35          (35),
vehicleShape36          (36),
vehicleShape37          (37),
vehicleShape38          (38),
vehicleShape39          (39),
vehicleShape40          (40),
vehicleShape41          (41),
vehicleShape42          (42),
vehicleShape43          (43),
vehicleShape44          (44),
vehicleShape45          (45),
vehicleShape46          (46),
vehicleShape47          (47),
vehicleShape48          (48),
vehicleShape49          (49),
vehicleShape50          (50),
-- (1..50) are reserved for future CEN ISO use
-- (51..255) are reserved for private use
} (0..255)

```

NOTE The DescriptiveCharacteristics type does not correspond to any other ERI type.

5.5.11.6.5 Future characteristics type

The FutureCharacteristics type shall be used to specify the vehicle's suspension, if applicable.

```

FutureCharacteristics ::= INTEGER {
    noEntry           (0),
    airSuspension    (1)
    -- (2..255) are reserved for future CEN use
} (0..255)

```

The airSuspension value shall be used to specify the presence of air suspension.

The noEntry value shall be used in case the vehicle is not equipped with air suspension or in case no suspension data is to be provided.

5.5.11.7 Trailer characteristics type

The `TrailerCharacteristics` type shall be used to specify for a trailer its type, the number of axles, the maximum permissible total weight, and the unladen weight.

The `TrailerCharacteristics` type is defined as follows.

```
TrailerCharacteristics ::= SEQUENCE {
    trailerDetails          TrailerDetails,
    trailerMaxLadenWeight  Int2,
    trailerWeightUnladen   Int2
}

TrailerDetails ::= SEQUENCE {
    trailerType          TrailerType,
    trailerAxles         TrailerAxles
}

TrailerType ::= INTEGER{
    notPresent (0),          -- trailer not attached or only
    one trailer attached, see information -- VehicleAxlesNumber for more
    trailer (1),            -- also known as pull-bar
    semitrailer (2)        -- also known as articulate trailer
    -- (3..31) reserved for future CEN/ISO use
} (0..31)
TrailerAxles ::= INTEGER (0..7) -- number of axles of the trailer when available
```

The `trailerDetails` component shall specify the trailer type and its number of axles.

The `trailerType` component shall specify the type of the trailer. Defined values are `notPresent`, `trailer` (also known as pull-bar trailer), and `semi-trailer` (a trailer without a front axle).

When used as part of the ERI data (i.e. as part of a trailer registration certificate data), the value `notPresent` shall not be used.

The `trailerAxles` component shall specify the number of axles of the trailer.

The `trailerMaxLadenWeight` component shall specify the maximum permissible total weight of the trailer including payload in accordance with ISO 1176, in 10 kg units, and rounded down to the next 10 kg unit.

The `trailerWeightUnladen` component shall specify the nominal unladen weight of the trailer which shall be according to ISO 1176, in 10 kg units, and rounded down to the next 10 kg unit.

NOTE The `TrailerCharacteristics` type corresponds to the combined use of the following types for a trailer: `NumberOfAxles`, `MaxAuthorizedLadenMass`, and `UnladenWeight`.

5.5.11.8 Engine type

The `Engine` type shall be used to specify the engine's capacity and power.

The `Engine` type is defined as follows.

```
Engine ::= SEQUENCE{
    engineCapacity          Int2,
    enginePower             Int2
}
```

The `engineCapacity` component shall specify the capacity of the vehicle's engine in millilitres.

The `engineCapacity` component shall specify the maximum net power of the vehicle's engine, in kilowatt.

NOTE The `Engine` type corresponds to the combined use of the `EngineDisplacement` and `EngineMaxNetPower` types with their values limited to 65535 cm³ and 65535 kW respectively.

5.5.11.9 Sound level type

The `SoundLevel` type shall be used to specify the vehicle's stationary and drive-by soundlevels.

The `SoundLevel` type is defined as follows.

```
SoundLevel ::= SEQUENCE{
    soundstationary          Int1,
    sounddriveby             Int1
}
```

The `soundstationary` component shall specify the stationary sound level of the vehicle according to its registration certificate in dB(A).

The `sounddriveby` component shall specify the drive-by sound of the vehicle according to its registration certificate in dB(A).

NOTE The `SoundLevel` type corresponds to the combined use of the `StationarySoundLevel` and `DriveBySoundLevel` types with their values limited to 255 dB.

5.5.11.10 CO₂ emission value type

The `CO2EmissionValue` type shall be used to specify the vehicle's emission of CO₂.

The `CO2EmissionValue` type is defined as follows.

```
CO2EmissionValue ::= Int2
```

The value of the `CO2EmissionValue` type shall be in g/km and according to the vehicle registration certificate.

NOTE The `CO2EmissionValue` type corresponds to the `EmissionCO2` type with its values limited to 65 535 g/km.

5.5.11.11 Exhaust emission values type

The `ExhaustEmissionValues` type shall be used to specify the vehicle's emission of CO, HC, NO_x, and HC plus NO_x.

The `ExhaustEmissionValues` type is defined as follows.

```
ExhaustEmissionValues ::= SEQUENCE {
    unitType                UnitType,
    emissionCO              INTEGER (0..32766),
    emissionHC              Int2,
    emissionNOX             Int2,
    emissionHCNOX           Int2
}
```

```
UnitType ::= ENUMERATED {
    mg-km,
    mg-kWh
}
```

The `unitType` component shall specify the unit for the `emissionCO`, `emissionHC`, `emissionNOX`, `emissionHCNOX` components. The defined values are mg/km and mg/kWh.

The `emissionCO` component shall specify the CO exhaust emission in the units specified by the `unitType` component and according to the vehicle registration certificate.

The `emissionHC` component shall specify the HC exhaust emission in the units specified by the `unitType` component and according to the vehicle registration certificate.

The `emissionNOx` component shall specify the NO_x exhaust emission in the units specified by the `unitType` component and according to the vehicle registration certificate.

The `emissionHCNOx` component shall specify the HC plus NO_x exhaust emission in the units specified by the `unitType` component and according to the vehicle registration certificate.

The value of the `emissionHCNOx` component should be the sum of the `emissionHC` and `emissionHCNOx` components values.

NOTE The `ExhaustEmissionValues` corresponds to the combined use of the `EmissionCO`, `EmissionHC`, `EmissionNOx`, and `EmissionHCandNOx` types with their values limited to 32 766 (for the CO emission) or to 65 535 (for the other exhaust emissions).

5.5.11.12 Diesel emission values type

The `DieselEmissionValues` type shall be used to specify the emission of diesel particles and the absorption coefficient.

```
DieselEmissionValues ::= SEQUENCE {  
    unitType          UnitType,  
    particulate       INTEGER (0.. 32767),  
    absorptionCoeff   Int2  
}
```

```
UnitType ::= ENUMERATED {  
    mg-km,  
    mg-kWh  
}
```

The `unitType` component shall specify the unit for the particulate component. The defined values are `mg/km` and `mg/kWh`.

The `particulate` component shall specify the particulates for diesel in the units specified by the `unitType` component and according to vehicle registration certificate.

The `absorptionCoeff` component shall specify the Corrected absorption coefficient for diesel, according to vehicle registration documents, in 10⁻³ m⁻¹ (= per km).

NOTE The `DieselEmissionValues` type corresponds to the combined use of the `ParticulatesForDiesel` and `CorrectedAbsorptionCoefficient` types with the unit of the particles changed from µg/km or µg/kWh to mg/km or mg/kWh, with value of the particulates limited to 32 766, with the unit of the corrected absorption coefficient changed from m⁻¹ to km⁻¹ and its values limited to 65 535.

5.5.12 Other types

5.5.12.1 Registration authority specific data

```
RaSpecificData ::= Text60
```

The `raSpecificVehicleData` component, if present, may contain any additional registration authority-specific data.

5.5.12.2 Measurement units

Measurement unit types to describe a vehicle are defined as follows.

```
MgpkmOrMgpkwh ::= CHOICE {  
    milligramPerKilometre      MilligramPerKilometre,  
    milligramPerKilowattHour    MilligramPerKilowattHour  
}
```

```

MicrogrampkmOrMicrogrampkwh ::= CHOICE {
    microgramPerKilometre      MicrogramPerKilometre,
    microgramPerKilowattHour   MicrogramPerKilowattHour
}
Kilogram ::= INTEGER (0..MAX)
Kilometre ::= INTEGER (0..MAX)
Millimetre ::= INTEGER (0..MAX)
PerKm ::= INTEGER (0..MAX)
Litre ::= INTEGER (0..MAX)
Millilitre ::= INTEGER (0..MAX)
Kilowatt ::= INTEGER (0..MAX)
KilometrePerHour ::= INTEGER (0..MAX)
PerMinute ::= INTEGER (0..MAX)
DB ::= INTEGER (0..MAX)
GramPerKilometre ::= INTEGER (0..MAX)
MilligramPerKilometre ::= INTEGER (0..MAX)
MicrogramPerKilometre ::= INTEGER (0..MAX)
MilligramPerKilowattHour ::= INTEGER (0..MAX)
MicrogramPerKilowattHour ::= INTEGER (0..MAX)
KilowattPerKilogram ::= INTEGER (0..MAX)
MillilitrePerKilometre ::= INTEGER (0..MAX)

```

-- = litre per 1 000 km

The `MgpkmOrMgpkwh` type shall be used to specify a value in milligrams per kilometre or in milligrams per kilowatt-hour. The type shall only be used when a user may choose between either of these values.

The `MicrogrampkmOrMicrogrampkwh` type shall be used to specify a value in micrograms per kilometre or in micrograms per kilowatt-hour. The type shall only be used when a user may choose between either of these values.

5.5.12.3 Entity identifier

The type `EntityId` is used for a global identification of entities and is defined as follows.

```
EntityId ::= OBJECT IDENTIFIER
```

5.5.12.4 Name and address

The `NameAndAddress` type shall be used to specify a name and address and is defined as follows.

```

NameAndAddress ::= SEQUENCE {
    name                Text60,
    otherNamesOrInitials Text60 OPTIONAL,
    address              Text60
}

```

The `name` component shall specify the surname or business name of a natural or artificial person.

The `otherNamesOrInitials` component, if present, shall specify other name(s) or initial(s). The `otherNamesOrInitials` component shall be present, where appropriate, and absent if not.

The `address` component shall specify the address of the natural or artificial person.

NOTE The `NameAndAddress` type is compliant with EU 2003/127 which also specifies a maximum length of 60 characters.

5.5.12.5 Text

The `Text60` type is used for textual ERI data and defined as follows.

```
Text60 ::= UTF8String (SIZE (1..60))
```

The value is a UTF8 string, according to ISO 8824, not exceeding 60 characters.

5.6 Attributes

5.6.1 Introduction

An attribute is a type with an associated identifier.

NOTE 1 Attributes are often used to retrieve or to set a number of parameters of some type.

EXAMPLE In order to get the value of some parameters, one sends their identifiers to receive a list with the values of these parameters together with their identifiers.

NOTE 2 As several parameters can be of the same type, i.e. share the same set of values, the same type may be used more than one attribute.

Using ASN.1 terms, an attribute is an information object from an information object class called ATTRIBUTE.

The attributes can be grouped into sets. This allows for a precise control over the attributes to be used (or not to be used) for a particular application.

This part of ISO 24534 defines some useful sets and some useful types based of these sets.

5.6.2 Useful types

Annex A defines the following useful types for use in other ERI applications:

- a) EriAttributeIdList and EriAttributeList;
- b) EriBasicAttributeIdList and EriBasicAttributeList;
- c) EriEuAttributeIdList and EriEuAttributeList;
- d) EriEfcAttributeIdList and EriEfcAttributeList.

EriAttributeIdList and EriAttributeList are defined as follows.

```
EriAttributeIdList ::= SEQUENCE OF EriAttributeId
EriAttributeList ::= SEQUENCE OF EriAttribute
EriAttributeId ::= ATTRIBUTE.&id ({EriAttributes })
EriAttribute ::= SEQUENCE {
    id                ATTRIBUTE.&id ({EriAttributes }),
    value             ATTRIBUTE.&Type ({EriAttributes } {@.id})
}
```

The EriAttributeIdList type is defined as a sequence of EriAttributeId values.

The EriAttributeList type is defined as a sequence of EriAttribute values.

The EriAttributeId type is defined as an id of an attribute from the set of attributes EriAttributes.

The EriAttribute type is defined as an id and a value of the identified type of an attribute from the set of attributes EriAttributes.

The EriBasicAttributeIdList and EriBasicAttributeList type are defined in the same way as EriAttributeIdList type and the EriAttributeList type, but with the attributes from the attribute set EriBasicAttributes.

EriEuAttributeIdList and EriEuAttributeList are defined in the same way as EriAttributeIdList type and the EriAttributeList type, but with the attributes from the attribute set EriEuAttributes.

`EriEfcAttributeIdList` and `EriEfcAttributeList` are defined in the same way as `EriAttributeIdList` type and the `EriAttributeList` type, but with the attributes from the attribute set `EriEfcAttributes`.

NOTE 1 See Annex A for the details of these definitions.

NOTE 2 By using ANS.1 notation above, it can be guaranteed with ASN.1 tools that an attribute is an attribute from a given set of attributes and that for each id the correct type is used.

5.6.3 Useful sets of attributes

Annex A defines the following useful sets of attributes for use in other ERI applications:

- a) `EriAttributes`;
- b) `EriBasicAttributes`;
- c) `EriEuAttributes`;
- d) `EriEfcAttributes`.

`EriAttributes` is the set of all attributes defined in Annex A.

`EriBasicAttributes` is the set of attributes in `EriAttributes` but not in `EriEfcAttributes`.

`EriEuAttributes` is the set of all the attributes used in EU registration certificates, i.e. for the ERI types listed in [Table B.1](#).

`EriEfcAttributes` is the set of attributes as used for EFC purposes.

5.6.4 Information object class ATTRIBUTES

The information object class `ATTRIBUTE` is defined as follows.

```
ATTRIBUTE ::= CLASS {
    &Type,
    &id                Int2 UNIQUE
}
```

WITH SYNTAX {&Type IDENTIFIED BY &id}

The `&Type` field shall be used for the identified type.

The `&id` field shall be used for a unique identifier of type `Int2`, i.e. with a value between 0 and 65 535 (inclusive).

The "WITH SYNTAX" provides for easy readable attribute definitions (see [5.6.5](#)).

5.6.5 Attribute definitions

In Annex A, attributes are defined for the vehicle identifiers and for the alternatives of the `AdditionalEriRegistrationData` type.

The attributes `vin` and `vehicleId` are defined as follows.

```
vin ATTRIBUTE ::=
    {VIN IDENTIFIED BY vinId}
vinId INTEGER ::= 15
vehicleId ATTRIBUTE ::=
    {VehicleId IDENTIFIED BY vehicleIdId}
vehicleIdId INTEGER ::= 129
```

The `vin` attribute is of type `VIN` and is identified by the value 15.

The `vehicleId` attribute is of type `VehicleID` and is identified by the value 129.

Other attributes are defined in the same way.

The use of identifiers is consistent with ISO 14906:2011. Values between 0 and 127 are only used for types used for EFC and, if used, also with the same value.

NOTE This allows for future combinations (unions) of sets of ERI attributes and EFC attributes without conflicts, i.e. while preserving the uniqueness of the identifiers.

5.7 Encoding

When exchanged between an ERT and an ERI reader or writer, ERI data shall be encoded according to the canonical packed encoding rules (CANONICAL-PER) UNALIGNED variant as defined in ISO 8825-2.

Annex A (normative)

ASN.1 Modules

A.1 General

This Annex contains the following ASN.1 modules:

- the ElectronicRegistrationIdentificationVehicleDataModule in [A.2](#);
- the ElectronicRegistrationIdentificationEfcVehicleDataModule in [A.3](#);
- the ElectronicRegistrationIdentificationVehicleDataAttributesModule in [A.4](#).

In case the ASN.1 specifications given in this Annex are not compliant with illustrations or specifications provided elsewhere in this part of ISO 24534, the specifications given in this Annex shall prevail.

The ASN.1 modules contained in this Annex will be published on <http://standards.iso.org/iso/24534/-3>.

A.2 Module ElectronicRegistrationIdentificationVehicleDataModule

In all definitions

```
fill BIT STRING (SIZE(x))
```

each bit of the BIT STRING shall be set to the value '0'b.

```
ElectronicRegistrationIdentificationVehicleDataModule {iso(1) standard(0) iso24534 (24534)
vehicleData (1) version1 (1)}
```

```
-- This version is upwards compatible with the previous version 0 in the sense that:
-- any receiver can successfully receive data of either version
-- But:
-- a receiver using version 0 will not be able to decode the version 1 extensions
-- The units of the environmental values should be interpreted differently
-- See Annex I of ISO 8824-1:2008 for details
```

```
DEFINITIONS AUTOMATIC TAGS ::= BEGIN
```

```
-- Electronic Registration Identification (ERI)- Vehicle Data
```

```
-- EXPORTS everything;
```

```
IMPORTS
```

```
CS4, CS5 FROM AVIAEINumberingAndDataStructures {iso(1) standard(0) iso14816(14816)
asnml(1) version1(1)}
```

```
VehicleDimensions, PassengerCapacity, VehicleWeightLimits, AxleWeightLimits,
VehicleSpecificCharacteristics, TrailerCharacteristics, Engine,
CO2EmissionValue, SoundLevel, ExhaustEmissionValues, DieselEmissionValues FROM
ElectronicRegistrationIdentificationEfcVehicleDataModule {iso(1) standard(0) iso24534
(24534) efcVehicleData (3) version1 (1)}
;
```

-- Vehicle Identifier

```
VehicleId ::= CHOICE {  
    vin                VIN, -- preferred choice / 17 characters  
    raSpecificVehicleId RaSpecificVehicleId,  
    ...  
}
```

VIN ::= CS5

```
RaSpecificVehicleId ::= SEQUENCE {  
    wmi                UTF8String (SIZE(3)),  
    nonIsoStandardId  UTF8String (SIZE (1..20))  
}
```

-- ERI data

```
EriData ::= SEQUENCE {  
    vehicleId          VehicleId,  
    additionalEriData  AdditionalEriData OPTIONAL  
}
```

```
AdditionalEriData ::= CHOICE {  
    additionalEriRegistrationData AdditionalEriRegistrationData, -- preferred choice  
    ...,  
    raSpecificAdditionalEriData  OCTET STRING (SIZE (0..1024))  
    -- only to be used if AdditionalEriRegistrationData is not supported  
}
```

-- Additional ERI registration data

```
AdditionalEriRegistrationData ::= SEQUENCE {  
    -- Administrative data  
    registrationAuthority  RegistrationAuthority OPTIONAL,  
    vehicleIdStatus        VehicleIdStatus OPTIONAL,  
    dateOfFirstRegistration DateOfFirstRegistration OPTIONAL,  
    dateOfRegistration     DateOfRegistration OPTIONAL,  
    validThru              ValidThru OPTIONAL,  
    chassisNumber          ChassisNumber (SIZE (1..23)) OPTIONAL,  
    registrationNumber     RegistrationNumber OPTIONAL,
```

```
    -- Vehicle type  
    vehicleMake            VehicleMake OPTIONAL,  
    vehicleType            VehicleType OPTIONAL,  
    vehicleTypeStatus     VehicleTypeStatus OPTIONAL,  
    commercialDescription  CommercialDescription OPTIONAL,  
    typeApprovalNumber     TypeApprovalNumber OPTIONAL,  
    vehicleCategory       VehicleCategory OPTIONAL,  
    vehicleTaxCategory     VehicleTaxCategory OPTIONAL,  
    euVehicleCategoryCode  EuVehicleCategoryCode OPTIONAL,  
    raSpecificVehicleClass1 RaSpecificVehicleClass1 OPTIONAL,  
    raSpecificVehicleClass2 RaSpecificVehicleClass2 OPTIONAL,  
    raSpecificVehicleClass3 RaSpecificVehicleClass3 OPTIONAL,  
    vehicleUse             VehicleUse OPTIONAL,  
    privateUse             PrivateUse OPTIONAL,  
    colour                 VehicleColour OPTIONAL,
```

```
    -- Vehicle shape  
    length                 VehicleLength OPTIONAL,  
    width                  VehicleWidth OPTIONAL,
```



```

height                VehicleHeight OPTIONAL,
wheelbase             Wheelbase OPTIONAL,
bodyShape             VehicleBodyShape OPTIONAL,
euBodyWorkType       EuBodyWorkType OPTIONAL,
iso3833VehicleType   Iso3833VehicleType OPTIONAL,

-- Vehicle number of passengers, axles, and mass
numberOfSeats        NumberOfSeats OPTIONAL, -- including the driver seat
numberOfStandingPlaces NumberOfStandingPlaces OPTIONAL,
maxNumberOfPassengers MaxNumberOfPassengers OPTIONAL, -- including the driver
unladenWeight        UnladenWeight OPTIONAL,
maxDesignLadenMass   MaxDesignLadenMass OPTIONAL,
maxAuthorizedLadenMass MaxAuthorizedLadenMass OPTIONAL,
maxAuthorizedTrainMass MaxAuthorizedTrainMass OPTIONAL,
maxAuthorizedPayload MaxAuthorizedPayload OPTIONAL,

numberOfAxles        NumberOfAxles OPTIONAL,
authorizedAxleLadenMass AuthorizedAxleLadenMass OPTIONAL, -- from front to rear
axle
maxTowableMassBrakedTrailer MaxTowableMassBrakedTrailer OPTIONAL,
maxTowableMassUnbrakedTrailer MaxTowableMassUnbrakedTrailer OPTIONAL,

-- Vehicle engine and power source
engineId             EngineId (SIZE (1..60)) OPTIONAL,
primeEngineType      PrimeEngineType OPTIONAL,
enginePowerSources   EnginePowerSources OPTIONAL,
primePowerSource      PrimePowerSource OPTIONAL,
engineMaxNetPower     EngineMaxNetPower OPTIONAL,
engineDisplacement    EngineDisplacement OPTIONAL,
ratedEngineSpeed      RatedEngineSpeed OPTIONAL,
powerWeightRatio      PowerWeightRatio OPTIONAL,
maxSpeed             MaxSpeed OPTIONAL,
fuelTanksCapacity     FuelTanksCapacity OPTIONAL,

-- Environmental characteristics
stationarySoundLevel StationarySoundLevel OPTIONAL,
engineSpeed          EngineSpeed OPTIONAL,
driveBySoundLevel    DriveBySoundLevel OPTIONAL,
emissionCO           DriveBySoundLevel OPTIONAL,
emissionHC           EmissionHC OPTIONAL,
emissionNOx          EmissionNOx OPTIONAL,
emissionHCandNOx     EmissionHCandNOx OPTIONAL,
particulatesForDiesel ParticulatesForDiesel OPTIONAL,
correctedAbsorptionCoefficient CorrectedAbsorptionCoefficient OPTIONAL,
emissionCO2          EmissionCO2 OPTIONAL,
combinedFuelConsumption CombinedFuelConsumption OPTIONAL,
environmentalCategory EnvironmentalCategory OPTIONAL,
euroType             EuroType OPTIONAL,

-- Others
lastOfficialTestData OfficialVehicleTestData OPTIONAL,
...,
raSpecificData       RaSpecificData OPTIONAL,
axlesPerAxleGroup    AxlesPerAxleGroup OPTIONAL,
-- from front to rear axle group
authorizedAxleGroupLadenMass AuthorizedAxleGroupsLadenMass OPTIONAL,
-- from front to rear axle group

-- ERI data used for EFC (types imported from
ElectronicRegistrationIdentificationEfcVehicleData
efcVehicleDimensions VehicleDimensions,
efcPassengerCapacity PassengerCapacity,
efcVehicleWeightLimits VehicleWeightLimits,
efcAxleWeightLimits AxleWeightLimits,

```

```
    efcVehicleSpecificCharacteristics
    VehicleSpecificCharacteristics,
    efcTrailerCharacteristics TrailerCharacteristics,
    efcEngine Engine,
    efcSoundLevel SoundLevel,
    efcCO2EmissionValue CO2EmissionValue,
    efcExhaustEmissionValues ExhaustEmissionValues,
    efcDieselEmissionValues DieselEmissionValues
  }

-- Administrative data
RegistrationAuthority ::= EntityId
VehicleIdStatus ::= Text60
DateOfFirstRegistration ::= DATE
DateOfRegistration ::= DATE
ValidThru ::= DATE
ChassisNumber ::= UTF8String (SIZE (1..23)) -- incl. 3 WMI characters
RegistrationNumber ::= CS4

-- Vehicle type
VehicleMake ::= Text60
VehicleType ::= Text60
VehicleTypeStatus ::= Text60
CommercialDescription ::= Text60
TypeApprovalNumber ::= UTF8String (SIZE (1..60))
VehicleCategory ::= Text60
VehicleTaxCategory ::= Text60
RaSpecificVehicleClass1 ::= Text60
RaSpecificVehicleClass2 ::= Text60
RaSpecificVehicleClass3 ::= Text60
VehicleUse ::= Text60
PrivateUse ::= BOOLEAN -- False = commercial use
VehicleColour ::= Text60

EuVehicleCategoryCode ::= CHOICE {
  euVehicleCategoryL EuVehicleCategoryL, -- conforms to EU 2002/24 and UNECE 1999
  euVehicleCategoryM EuVehicleCategoryM, -- conforms to EU 2001/116 and UNECE 1999
  euVehicleCategoryN EuVehicleCategoryN, -- conforms to EU 2001/116 and UNECE 1999
  euVehicleCategoryO EuVehicleCategoryO, -- conforms to EU 2001/116 and UNECE 1999
  euVehilcleCategoryT NULL, -- conforms to UNECE 1999
  euVehilcleCategoryG NULL -- conforms to EU 2001/116 and UNECE 1999
}

EuVehicleCategoryL ::= ENUMERATED {11, 12, 13, 14, 15, 16, 17}

EuVehicleCategoryM ::= ENUMERATED {m1, m2, m3}

EuVehicleCategoryN ::= ENUMERATED {n1, n2, n3}

EuVehicleCategoryO ::= ENUMERATED {o1, o2, o3, o4}

-- Vehicle shape
VehicleLength ::= Millimetre
VehicleWidth ::= Millimetre
VehicleHeight ::= Millimetre
Wheelbase ::= Millimetre
VehicleBodyShape ::= Text60
EuBodyWorkType ::= UTF8String (SIZE (2)) -- conforms to EU 2001/116

Iso3833VehicleType ::= ENUMERATED {
  passengerCar, -- term No 3.1.1
```

```

    saloon, -- term No 3.1.1.1 (sedan)
    convertibleSaloon, -- term No 3.1.1.2
    pullmanSaloon, -- term No 3.1.1.3
    stationWagon, -- term No 3.1.1.4
    truckStationWagon, -- term No 3.1.1.4.1
    coupe, -- term No 3.1.1.5 (coupé)
    convertible, -- term No 3.1.1.6 (open tourer, roadstar, spider)
    multipurposePassengerCar, -- term No 3.1.1.7
    forwardControlPassengerCar, -- term No 3.1.1.8
    specialPassengerCar, -- term No 3.1.1.9
    bus, -- term No 3.1.2
    minibus, -- term No 3.1.2.1
    urbanBus, -- term No 3.1.2.2
    interurbanCoach, -- term No 3.1.2.3
    longDistanceCoach, -- term No 3.1.2.4
    articulatedBus, -- term No 3.1.2.5
    trolleyBus, -- term No 3.1.2.6
    specialBus, -- term No 3.1.2.7
    commercialVehicle, -- term No 3.1.3
    specialCommercialVehicle, -- term No 3.1.3.1
    specialVehicle, -- term No 3.1.4
    trailingTowingVehicle, -- term No 3.1.5 (draw-bar tractor)
    semiTrailerTowingVehicle, -- term No 3.1.6 (fifth wheel tractor)
    trailer, -- term No 3.2.1
    busTrailer, -- term No 3.2.1.1
    generalPurposeTrailer, -- term No 3.2.1.2
    caravan, -- term No 3.2.1.3
    specialTrailer, -- term No 3.2.1.4
    semiTrailer, -- term No 3.2.2
    busSemiTrailer, -- term No 3.2.2.1
    generalPurposeSemiTrailer, -- term No 3.2.2.2
    specialSemiTrailer, -- term No 3.2.2.3
    roadTrain, -- term No 3.3.1
    passengerRoadTrain, -- term No 3.3.2
    articulatedRoadTrain, -- term No 3.3.3
    doubleRoadTrain, -- term No 3.3.4
    compositeRoadTrain, -- term No 3.3.5
    specialRoadTrain, -- term No 3.3.6
    moped, -- term No 3.4
    motorCycle -- term No 3.5
}

-- Vehicle number of passengers, axles, and mass
NumberOfSeats ::= INTEGER -- including the driver seat
NumberOfStandingPlaces ::= INTEGER
MaxNumberOfPassengers ::= INTEGER -- including the driver
UnladenWeight ::= Kilogram
MaxDesignLadenMass ::= Kilogram
MaxAuthorizedLadenMass ::= Kilogram
MaxAuthorizedTrainMass ::= Kilogram
MaxAuthorizedPayload ::= Kilogram

NumberOfAxles ::= INTEGER
AxlesPerAxleGroup ::= SEQUENCE OF Intl -- from front to rear axle group
AuthorizedAxleLadenMass ::= SEQUENCE OF Kilogram -- from front to rear axle
AuthorizedAxleGroupsLadenMass ::= SEQUENCE OF Kilogram -- from front to rear axle group
MaxTowableMassBrakedTrailer ::= Kilogram
MaxTowableMassUnbrakedTrailer ::= Kilogram

-- Vehicle engine and power source
EngineId ::= UTF8String (SIZE (1..60))
PrimeEngineType ::= Text60
EnginePowerSources ::= SEQUENCE OF PowerSource -- primary source first
PrimePowerSource ::= PowerSource
EngineMaxNetPower ::= Kilowatt
EngineDisplacement ::= Millilitre
RatedEngineSpeed ::= PerMinute
PowerWeightRatio ::= KilowattPerKilogram

```

MaxSpeed ::= KilometrePerHour
FuelTanksCapacity ::= Litre

PowerSource ::= INTEGER {
 notPowered (0),
 humanPowered (1),
 animalPowered (2),
 unleadedPetrol (3),
 leadedPetrol (4),
 diesel (5),
 bioDiesel (6),
 alcohol (7),
 otherFuel (8),
 lpg (9),
 hydrogen (10),
 externalElectricPower (11),
 battery (12),
 sun (13),
 other (14)
} (0..15)

-- Environmental characteristics

StationarySoundLevel ::= DB
EngineSpeed ::= PerMinute
DriveBySoundLevel ::= DB
EmissionCO ::= MgpkmOrMgpkwh
EmissionHC ::= MgpkmOrMgpkwh
EmissionNOx ::= MgpkmOrMgpkwh
EmissionHCandNOx ::= MilligramPerKilometre
ParticulatesForDiesel ::= MicrogrampkOrMicrogrampkwh
CorrectedAbsorptionCoefficient ::= PerKm
EmissionCO2 ::= GramPerKilometre
CombinedFuelConsumption ::= MillilitrePerKilometre
EnvironmentalCategory ::= Text60

EuroType ::= INTEGER {
 non-euro (0),
 euro-1 (1),
 euro-2 (2),
 euro-3 (3),
 euro-4 (4),
 euro-5 (5),
 euro-6 (6)
} (0..15)

-- Others

OfficialVehicleTestData ::= SEQUENCE {
 date DATE OPTIONAL,
 location NameAndAddress OPTIONAL,
 odometerValue Kilometre OPTIONAL,
 emissionCO MgpkmOrMgpkwh OPTIONAL,
 emissionHC MgpkmOrMgpkwh OPTIONAL,
 remarks Text60 OPTIONAL,
 ...
}

RaSpecificData ::= Text60

--Measurement units

```

MgpkmOrMgpkwh ::= CHOICE {
    milligramPerKilometre    MilligramPerKilometre,
    milligramPerKilowattHour MilligramPerKilowatthour
}

MicrogrampkmOrMicrogrampkwh ::= CHOICE {
    microgramPerKilometre    MicrogramPerKilometre,
    microgramPerKilowattHour MicrogramPerKilowatthour
}

Kilogram ::= INTEGER (0..MAX)
Kilometre ::= INTEGER (0..MAX)
Millimetre ::= INTEGER (0..MAX)
PerKm ::= INTEGER (0..MAX)
Litre ::= INTEGER (0..MAX)
Millilitre ::= INTEGER (0..MAX)
Kilowatt ::= INTEGER (0..MAX)
KilometrePerHour ::= INTEGER (0..MAX)
PerMinute ::= INTEGER (0..MAX)
DB ::= INTEGER (0..MAX)
GramPerKilometre ::= INTEGER (0..MAX)
MilligramPerKilometre ::= INTEGER (0..MAX)
MicrogramPerKilometre ::= INTEGER (0..MAX)
MilligramPerKilowatthour ::= INTEGER (0..MAX)
MicrogramPerKilowatthour ::= INTEGER (0..MAX)
KilowattPerKilogram ::= INTEGER (0..MAX)
MillilitrePerKilometre ::= INTEGER (0..MAX) -- = litre per 1000 km

--EntityId, names and addresses

EntityId ::= OBJECT IDENTIFIER

NameAndAddress ::= SEQUENCE {
    name Text60,
    otherNamesOrInitials Text60 OPTIONAL,
    address Text60
}

--Text

Text60 ::= UTF8String (SIZE (1..60))

--Integers

Int1 ::= INTEGER (0..255)

END

```

A.3 ElectronicRegistrationIdentificationEfcVehicleDataModule

```

ElectronicRegistrationIdentificationEfcVehicleDataModule {iso(1) standard(0) iso24534
(24534) efcVehicleData (3) version1 (1)} DEFINITIONS AUTOMATIC TAGS ::= BEGIN

IMPORTS
CountryCode FROM AVIAEINumberingAndDataStructures {iso(1) standard(0) iso14816(14816)

```

```
asnml(1) version1(1)
;

-- Vehicle dimensions

VehicleDimensions ::= SEQUENCE {
    vehicleLengthOverall    Int1,
    vehicleHeigthOverall    Int1,
    vehicleWidthOverall     Int1
}

-- Passengers capicity

PassengerCapacity ::= SEQUENCE{
    numberOfSeats           Int1,
    numberOfStandingPlaces Int1
}

-- Vehicle weight limits

VehicleWeightLimits ::= SEQUENCE {
    vehicleMaxLadenWeight    Int2,
    vehicleTrainMaximumWeight Int2,
    vehicleWeightUnladen     Int2
}

-- Axle weight limits

AxleWeightLimits ::= SEQUENCE{
    maxLadenweightOnAxle1    Int2,
    maxLadenweightOnAxle2    Int2,
    maxLadenweightOnAxle3    Int2,
    maxLadenweightOnAxle4    Int2,
    maxLadenweightOnAxle5    Int2
}

-- Vehicle Specific Characteristics

VehicleSpecificCharacteristics ::= SEQUENCE {
    environmentalCharacteristics EnvironmentalCharacteristics,
    engineCharacteristics       EngineCharacteristics,
    descriptiveCharacteristics   DescriptiveCharacteristics,
    futureCharacteristics        FutureCharacteristics
}

EnvironmentalCharacteristics ::= SEQUENCE {
    euroValue    EuroValue,
    copValue     CopValue
}

EuroValue ::= INTEGER {
    noEntry      (0),
    euro-1       (1),
    euro-2       (2),
    euro-3       (3),
    euro-4       (4),
    euro-5       (5),
}
```

```
euro-6 (6)
} (0..15) -- 4 bits, EURO-Classes as defined in EC directive 88/77/EEC, annex 1
-- and in 91/542/EEC, 96/1/EC, 1999/96/EC, 2001/27/EC
```

```
CopValue ::= INTEGER {
  noEntry (0),
  co2class1 (1), -- below 101 g/km
  co2class2 (2), -- 101 to 120 g/km
  co2class3 (3), -- 121 to 140 g/km
  co2class4 (4), -- 141 to 160 g/km
  co2class5 (5), -- 161 to 200 g/km
  co2class6 (6), -- 201 to 250 g/km
  co2class7 (7) -- above 250 g/km
} (0..15) -- 4 bits, reserved for carbon dioxide pollution values as defined in
-- EC directive 2003/127/EC
```

```
EngineCharacteristics ::= INTEGER {
  noEntry (0),
  noEngine (1),
  petrolUnleaded (2),
  petrolLeaded (3),
  diesel (4),
  LPG (5),
  battery (6),
  solar (7)
  -- (8-255) are reserved for future CEN use
} (0..255)
```

```
DescriptiveCharacteristics ::= INTEGER {
  noEntry (0),
  vehicleShape1 (1),
  vehicleShape2 (2),
  vehicleShape3 (3),
  vehicleShape4 (4),
  vehicleShape5 (5),
  vehicleShape6 (6),
  vehicleShape7 (7),
  vehicleShape8 (8),
  vehicleShape9 (9),
  vehicleShape10 (10),
  vehicleShape11 (11),
  vehicleShape12 (12),
  vehicleShape13 (13),
  vehicleShape14 (14),
  vehicleShape15 (15),
  vehicleShape16 (16),
  vehicleShape17 (17),
  vehicleShape18 (18),
  vehicleShape19 (19),
  vehicleShape20 (20),
  vehicleShape21 (21),
  vehicleShape22 (22),
  vehicleShape23 (23),
  vehicleShape24 (24),
  vehicleShape25 (25),
  vehicleShape26 (26),
  vehicleShape27 (27),
  vehicleShape28 (28),
  vehicleShape29 (29),
  vehicleShape30 (30),
  vehicleShape31 (31),
  vehicleShape32 (32),
  vehicleShape33 (33),
  vehicleShape34 (34),
  vehicleShape35 (35),
  vehicleShape36 (36),
  vehicleShape37 (37),
  vehicleShape38 (38),
```

```
vehicleShape39      (39),  
vehicleShape40      (40),  
vehicleShape41      (41),  
vehicleShape42      (42),  
vehicleShape43      (43),  
vehicleShape44      (44),  
vehicleShape45      (45),  
vehicleShape46      (46),  
vehicleShape47      (47),  
vehicleShape48      (48),  
vehicleShape49      (49),  
vehicleShape50      (50)  
-- (1..50) are reserved for future CEN ISO use  
-- (51..255) are reserved for private use  
} (0..255)
```

```
FutureCharacteristics ::= INTEGER {  
  noEntry            (0),  
  airSuspension      (1)  
  -- (2..255) are reserved for future CEN use  
} (0..255)
```

-- Trailer Characteristics

```
TrailerCharacteristics ::= SEQUENCE {  
  trailerDetails      TrailerDetails,  
  trailerMaxLadenWeight Int2,  
  trailerWeightUnladen Int2  
}
```

```
TrailerDetails ::= SEQUENCE {  
  trailerType          TrailerType,  
  trailerAxles          TrailerAxles  
}
```

```
TrailerType ::= INTEGER{  
  notPresent      (0), -- trailer not attached or only one trailer attached, see  
                   -- VehicleAxlesNumber for more information  
  Trailer         (1), -- also known as pull-bar trailer  
  semitrailer     (2)  -- also known as articulate trailer  
  -- (3..31) reserved for future CEN/ISO use  
} (0..31)
```

TrailerAxles ::= INTEGER (0..7) -- number of axles of the trailer when available

-- Engine

```
Engine ::= SEQUENCE{  
  engineCapacity      Int2,  
  enginePower         Int2  
}
```

-- Environmental characteristics

```
SoundLevel ::= SEQUENCE{  
  soundstationary      Int1,  
  sounddriveby        Int1  
}
```



```
CO2EmissionValue ::= Int2
```

```
ExhaustEmissionValues ::= SEQUENCE {
    unitType          UnitType,
    emissionCO        INTEGER (0..32766),
    emissionHC        Int2,
    emissionNOX       Int2,
    emissionHCNOX     Int2
}
```

```
DieselEmissionValues ::= SEQUENCE {
    unitType          UnitType,
    particulate       INTEGER (0.. 32767),
    absorptionCoeff   Int2
}
```

```
UnitType ::= ENUMERATED {
    mg-km,
    mg-kWh
}
```

```
Int1 ::= INTEGER(0..255)
```

```
Int2 ::= INTEGER(0..65535)
```

```
Int4 ::= INTEGER(0..4294967295)
```

```
END
```

A.4 ElectronicRegistrationIdentificationVehicleDataAttributesModule

```
ElectronicRegistrationIdentificationVehicleDataAttributesModule {iso(1) standard(0)
iso24534 (24534) vehicleDataAttributes (4) version1 (1)}
DEFINITIONS AUTOMATIC TAGS ::= BEGIN
```

```
IMPORTS
```

```
CountryCode FROM AVIAEINumberingAndDataStructures {iso(1) standard(0) iso14816(14816)
asnml(1) version1(1)}
```

```
VehicleId , VIN, RegistrationAuthority, VehicleIdStatus, DateOfFirstRegistration,
DateOfRegistration, ValidThru, ChassisNumber, RegistrationNumber, VehicleMake,
VehicleType, VehicleTypeStatus, CommercialDescription, TypeApprovalNumber,
VehicleCategory, VehicleTaxCategory, EuVehicleCategoryCode, RaSpecificVehicleClass1,
RaSpecificVehicleClass2, RaSpecificVehicleClass3, VehicleUse, PrivateUse, VehicleColour,
VehicleLength, VehicleWidth, VehicleHeight, Wheelbase, VehicleBodyShape,
EuBodyWorkType, Iso3833VehicleType, NumberOfSeats, NumberOfStandingPlaces,
MaxNumberOfPassengers, UnladenWeight, MaxDesignLadenMass, MaxAuthorizedLadenMass,
MaxAuthorizedTrainMass, MaxAuthorizedPayload, NumberOfAxles, AuthorizedAxleLadenMass,
MaxTowableMassBrakedTrailer, MaxTowableMassUnbrakedTrailer, EngineId, PrimeEngineType,
EnginePowerSources, PrimePowerSource, EngineMaxNetPower, EngineDisplacement,
RatedEngineSpeed, PowerWeightRatio, MaxSpeed, FuelTanksCapacity, StationarySoundLevel,
EngineSpeed, DriveBySoundLevel, DriveBySoundLevel, EmissionHC, EmissionNOx,
EmissionHCandNOx, ParticulatesForDiesel, CorrectedAbsorptionCoefficient, EmissionCO2,
CombinedFuelConsumption, EnvironmentalCategory, EuroType, OfficialVehicleTestData,
RaSpecificData, AxlesPerAxleGroup, AuthorizedAxleGroupsLadenMass FROM
ElectronicRegistrationIdentificationVehicleDataModule {iso(1) standard(0) iso24534 (24534)
vehicleData (1) version1 (1)}
```

```
VehicleDimensions, PassengerCapacity, VehicleWeightLimits, AxleWeightLimits,  
VehicleSpecificCharacteristics, TrailerCharacteristics, Engine,  
CO2EmissionValue, SoundLevel, ExhaustEmissionValues, DieselEmissionValues FROM  
ElectronicRegistrationIdentificationEfcVehicleDataModule {iso(1) standard(0) iso24534  
(24534) efcVehicleData (3) version1 (1)};
```

```
-- Usefull types
```

```
EriAttributeIdList ::= SEQUENCE OF EriAttributeId
```

```
EriAttrubuteList ::= SEQUENCE OF EriAttribute
```

```
EriAttributeId ::= ATTRIBUTE.&id ({EriAttributes })
```

```
EriAttribute ::= SEQUENCE {  
    id ATTRIBUTE.&id ({EriAttributes }),  
    value ATTRIBUTE.&Type ({EriAttributes } {@.id})  
}
```

```
EriBasicAttributeIdList ::= SEQUENCE OF EriBasicAttributeId
```

```
EriBasicAttrubuteList ::= SEQUENCE OF EriBasicAttribute
```

```
EriBasicAttributeId ::= ATTRIBUTE.&id ({EriBasicAttributes })
```

```
EriBasicAttribute ::= SEQUENCE {  
    id ATTRIBUTE.&id ({EriBasicAttributes }),  
    value ATTRIBUTE.&Type ({EriBasicAttributes } {@.id})  
}
```

```
EriEuAttributeIdList ::= SEQUENCE OF EriEuAttributeId
```

```
EriEuAttrubuteList ::= SEQUENCE OF EriEuAttribute
```

```
EriEuAttributeId ::= ATTRIBUTE.&id ({EriEuAttributes})
```

```
EriEuAttribute ::= SEQUENCE {  
    id ATTRIBUTE.&id ({EriEuAttributes}),  
    value ATTRIBUTE.&Type ({EriEuAttributes} {@.id})  
}
```

```
EriEfcAttributeIdList ::= SEQUENCE OF EriEfcAttributeId
```

```
EriEfcAttrubuteList ::= SEQUENCE OF EriEfcAttribute
```

```
EriEfcAttributeId ::= ATTRIBUTE.&id ({EriEfcAttributes})
```

```
EriEfcAttribute ::= SEQUENCE {  
    id ATTRIBUTE.&id ({EriEfcAttributes}),  
    value ATTRIBUTE.&Type ({EriEfcAttributes} {@.id})  
}
```

```
-- The Attribute information object class
```

```
ATTRIBUTE ::= CLASS {  
    &Type,  
    &id Int2 UNIQUE  
}
```

```
WITH SYNTAX {&Type IDENTIFIED BY &id}
```

```
EriAttributes ATTRIBUTE ::= {(EriBasicAttributes UNION EriEfcAttributes)}
```

```
EriBasicAttributes ATTRIBUTE ::= {vehicleId | vin | registrationAuthority | vehicleIdStatus |
dateOfFirstRegistration | dateOfRegistration | validThru | chassisNumber |
registrationNumber | vehicleMake | vehicleType | vehicleTypeStatus | commercialDescription |
typeApprovalNumber | vehicleCategory | vehicleTaxCategory | euVehicleCategoryCode |
raSpecificVehicleClass1 | raSpecificVehicleClass2 | raSpecificVehicleClass3 |
vehicleUse | privateUse | colour | length | width | height | wheelbase | bodyShape |
euBodyWorkType | iso3833VehicleType | numberOfSeats | numberOfStandingPlaces |
maxNumberOfPassengers | unladenWeight | maxDesignLadenMass | maxAuthorizedLadenMass |
maxAuthorizedTrainMass | maxAuthorizedPayload | numberOfAxles | authorizedAxleLadenMass |
maxTowableMassBrakedTrailer | maxTowableMassUnbrakedTrailer | engineId | primeEngineType |
enginePowerSources | primePowerSource | engineMaxNetPower | engineDisplacement |
ratedEngineSpeed | powerWeightRatio | maxSpeed | fuelTanksCapacity | stationarySoundLevel |
engineSpeed | driveBySoundLevel | emissionCO | emissionHC | emissionNOx |
emissionHCandNOx | particulatesForDiesel | correctedAbsorptionCoefficient | emissionCO2 |
combinedFuelConsumption | environmentalCategory | euroType | lastOfficialTestData |
raSpecificData | axlesPerAxleGroup | authorizedAxleGroupLadenMass, ...}
```

```
EriEuAttributes ATTRIBUTE ::= { registrationNumber | dateOfFirstRegistration |
vehicleMake | vehicleType | commercialDescription | vin | maxDesignLadenMass |
maxAuthorizedLadenMass | maxAuthorizedTrainMass | unladenWeight | validThru |
dateOfRegistration | vehicleCategory | euVehicleCategoryCode | typeApprovalNumber |
numberOfAxles | wheelbase | authorizedAxleLadenMass | maxTowableMassBrakedTrailer |
maxTowableMassUnbrakedTrailer | engineDisplacement | engineMaxNetPower |
enginePowerSources | ratedEngineSpeed | engineId | powerWeightRatio | colour |
numberOfSeats | numberOfStandingPlaces | maxSpeed | stationarySoundLevel | engineSpeed |
driveBySoundLevel | emissionCO | emissionHC | emissionNOx | emissionHCandNOx |
particulatesForDiesel | correctedAbsorptionCoefficient | emissionCO2 |
combinedFuelConsumption | euroType | fuelTanksCapacity, ...}
```

```
EriEfcAttributes ATTRIBUTE ::= { efcVehicleLicencePlateNumber |
efcTrailerLicencePlateNumber | efcVehicleDimensions | efcPassengerCapacity |
efcVehicleWeightLimits | efcAxleWeightLimits | efcVehicleSpecificCharacteristics |
efcTrailerCharacteristics | efcEngine | efcSoundLevel | efcCO2EmissionValue |
efcExhaustEmissionValues | efcDieselEmissionValues, ...}
```

-- Vehicle Identification and administrative data

```
vehicleId ATTRIBUTE ::= {VehicleId IDENTIFIED BY vehicleIdId}
```

```
vin ATTRIBUTE ::= {VIN IDENTIFIED BY vinId}
```

```
registrationAuthority ATTRIBUTE ::= {RegistrationAuthority IDENTIFIED BY
registrationAuthorityId}
```

```
vehicleIdStatus ATTRIBUTE ::= {VehicleIdStatus IDENTIFIED BY vehicleIdStatusId}
```

```
dateOfFirstRegistration ATTRIBUTE ::= {DateOfFirstRegistration IDENTIFIED BY
dateOfFirstRegistrationId}
```

```
dateOfRegistration ATTRIBUTE ::= {DateOfRegistration IDENTIFIED BY dateOfRegistrationId}
```

```
validThru ATTRIBUTE ::= {ValidThru IDENTIFIED BY validThruId}
```

```
chassisNumber ATTRIBUTE ::= { ChassisNumber IDENTIFIED BY chassisNumberId}
```

```
registrationNumber ATTRIBUTE ::= { RegistrationNumber IDENTIFIED BY registrationNumberId }

-- Vehicle type

vehicleMake ATTRIBUTE ::= { VehicleMake IDENTIFIED BY vehicleMakeId }

vehicleType ATTRIBUTE ::= { VehicleType IDENTIFIED BY vehicleTypeId }

vehicleTypeStatus ATTRIBUTE ::= { VehicleTypeStatus IDENTIFIED BY vehicleTypeStatusId }

commercialDescription ATTRIBUTE ::= { CommercialDescription IDENTIFIED BY
commercialDescriptionId }

typeApprovalNumber ATTRIBUTE ::= { TypeApprovalNumber IDENTIFIED BY typeApprovalNumberId }

vehicleCategory ATTRIBUTE ::= { VehicleCategory IDENTIFIED BY vehicleCategoryId }

vehicleTaxCategory ATTRIBUTE ::= { VehicleTaxCategory IDENTIFIED BY vehicleTaxCategoryId }

euVehicleCategoryCode ATTRIBUTE ::= { EuVehicleCategoryCode IDENTIFIED BY
euVehicleCategoryCodeId }

raSpecificVehicleClass1 ATTRIBUTE ::= { RaSpecificVehicleClass1 IDENTIFIED BY
raSpecificVehicleClass1Id }

raSpecificVehicleClass2 ATTRIBUTE ::= { RaSpecificVehicleClass2 IDENTIFIED BY
raSpecificVehicleClass2Id }

raSpecificVehicleClass3 ATTRIBUTE ::= { RaSpecificVehicleClass3 IDENTIFIED BY
raSpecificVehicleClass3Id }

vehicleUse ATTRIBUTE ::= { VehicleUse IDENTIFIED BY vehicleUseId }

privateUse ATTRIBUTE ::= { PrivateUse IDENTIFIED BY privateUseId }

colour ATTRIBUTE ::= { VehicleColour IDENTIFIED BY colourId }

-- Vehicle shape

length ATTRIBUTE ::= { VehicleLength IDENTIFIED BY lengthId }

width ATTRIBUTE ::= { VehicleWidth IDENTIFIED BY widthId }

height ATTRIBUTE ::= { VehicleHeight IDENTIFIED BY heightId }

wheelbase ATTRIBUTE ::= { Wheelbase IDENTIFIED BY wheelbaseId }
```

```
bodyShape ATTRIBUTE ::= {VehicleBodyShape IDENTIFIED BY bodyShapeId}

euBodyWorkType ATTRIBUTE ::= {EuBodyWorkType IDENTIFIED BY euBodyWorkTypeId}

iso3833VehicleType ATTRIBUTE ::= {Iso3833VehicleType IDENTIFIED BY iso3833VehicleTypeId}

-- Vehicle number of passengers, axles and mass

numberOfSeats ATTRIBUTE ::= {NumberOfSeats IDENTIFIED BY numberOfSeatsId}

numberOfStandingPlaces ATTRIBUTE ::= {NumberOfStandingPlaces IDENTIFIED BY
numberOfStandingPlacesId}

maxNumberOfPassengers ATTRIBUTE ::= {MaxNumberOfPassengers IDENTIFIED BY
maxNumberOfPassengersId}

unladenWeight ATTRIBUTE ::= {UnladenWeight IDENTIFIED BY unladenWeightId}

maxDesignLadenMass ATTRIBUTE ::= {MaxDesignLadenMass IDENTIFIED BY maxDesignLadenMassId}

maxAuthorizedLadenMass ATTRIBUTE ::= {MaxAuthorizedLadenMass IDENTIFIED BY
maxAuthorizedLadenMassId}

maxAuthorizedTrainMass ATTRIBUTE ::= {MaxAuthorizedTrainMass IDENTIFIED BY
maxAuthorizedTrainMassId}

maxAuthorizedPayload ATTRIBUTE ::= {MaxAuthorizedPayload IDENTIFIED BY
maxAuthorizedPayloadId}

numberOfAxles ATTRIBUTE ::= {NumberOfAxles IDENTIFIED BY numberOfAxlesId}

authorizedAxleLadenMass ATTRIBUTE ::= {AuthorizedAxleLadenMass IDENTIFIED BY
authorizedAxleLadenMassId}

maxTowableMassBrakedTrailer ATTRIBUTE ::= {MaxTowableMassBrakedTrailer IDENTIFIED BY
maxTowableMassBrakedTrailerId}

maxTowableMassUnbrakedTrailer ATTRIBUTE ::= {MaxTowableMassUnbrakedTrailer IDENTIFIED BY
maxTowableMassUnbrakedTrailerId}

-- Vehicle engine and power source

engineId ATTRIBUTE ::= {EngineId (SIZE (1..60)) IDENTIFIED BY engineIdId}

primeEngineType ATTRIBUTE ::= {PrimeEngineType IDENTIFIED BY primeEngineTypeId}

enginePowerSources ATTRIBUTE ::= {EnginePowerSources IDENTIFIED BY enginePowerSourcesId}
```

```
primePowerSource ATTRIBUTE ::= {PrimePowerSource IDENTIFIED BY primePowerSourceId}

engineMaxNetPower ATTRIBUTE ::= {EngineMaxNetPower IDENTIFIED BY engineMaxNetPowerId}

engineDisplacement ATTRIBUTE ::= {EngineDisplacement IDENTIFIED BY engineDisplacementId}

ratedEngineSpeed ATTRIBUTE ::= {RatedEngineSpeed IDENTIFIED BY ratedEngineSpeedId}

powerWeightRatio ATTRIBUTE ::= {PowerWeightRatio IDENTIFIED BY powerWeightRatioId}

maxSpeed ATTRIBUTE ::= {MaxSpeed IDENTIFIED BY maxSpeedId}

fuelTanksCapacity ATTRIBUTE ::= {FuelTanksCapacity IDENTIFIED BY fuelTanksCapacityId}

-- Environmental characteristics

stationarySoundLevel ATTRIBUTE ::= {StationarySoundLevel IDENTIFIED BY
stationarySoundLevelId}

engineSpeed ATTRIBUTE ::= {EngineSpeed IDENTIFIED BY engineSpeedId}

driveBySoundLevel ATTRIBUTE ::= {DriveBySoundLevel IDENTIFIED BY driveBySoundLevelId}

emissionCO ATTRIBUTE ::= {DriveBySoundLevel IDENTIFIED BY emissionCOId}

emissionHC ATTRIBUTE ::= {EmissionHC IDENTIFIED BY emissionHCId}

emissionNOx ATTRIBUTE ::= {EmissionNOx IDENTIFIED BY emissionNOxId}

emissionHCandNOx ATTRIBUTE ::= {EmissionHCandNOx IDENTIFIED BY emissionHCandNOxId}

particulatesForDiesel ATTRIBUTE ::= {ParticulatesForDiesel IDENTIFIED BY
particulatesForDieselId}

correctedAbsorptionCoefficient ATTRIBUTE ::= {CorrectedAbsorptionCoefficient IDENTIFIED BY
correctedAbsorptionCoefficientId}

emissionCO2 ATTRIBUTE ::= {EmissionCO2 IDENTIFIED BY emissionCO2Id}

combinedFuelConsumption ATTRIBUTE ::= {CombinedFuelConsumption IDENTIFIED BY
combinedFuelConsumptionId}

environmentalCategory ATTRIBUTE ::= {EnvironmentalCategory IDENTIFIED BY
environmentalCategoryId}

euroType ATTRIBUTE ::= {EuroType IDENTIFIED BY euroTypeId}
```

-- Others

lastOfficialTestData ATTRIBUTE ::= { OfficialVehicleTestData IDENTIFIED BY
lastOfficialTestDataId }

raSpecificData ATTRIBUTE ::= { RaSpecificData IDENTIFIED BY raSpecificDataId }

axlesPerAxleGroup ATTRIBUTE ::= { AxlesPerAxleGroup IDENTIFIED BY axlesPerAxleGroupId }

authorizedAxleGroupLadenMass ATTRIBUTE ::= { AuthorizedAxleGroupsLadenMass IDENTIFIED BY
authorizedAxleGroupLadenMassId }

-- Attribute for ERI data used for EFC

efcVehicleLicencePlateNumber ATTRIBUTE ::= { RegistrationNumber IDENTIFIED BY
efcVehicleLicencePlateNumberId }

efcTrailerLicencePlateNumber ATTRIBUTE ::= { RegistrationNumber IDENTIFIED BY
efcTrailerLicencePlateNumberId }

efcVehicleDimensions ATTRIBUTE ::= { VehicleDimensions IDENTIFIED BY
efcVehicleDimensionsId }

efcPassengerCapacity ATTRIBUTE ::= { PassengerCapacity IDENTIFIED BY
efcPassengerCapacityId }

efcVehicleWeightLimits ATTRIBUTE ::= { VehicleWeightLimits IDENTIFIED BY
efcVehicleWeightLimitsId }

efcAxleWeightLimits ATTRIBUTE ::= { AxleWeightLimits IDENTIFIED BY
efcAxleWeightLimitsId }

efcVehicleSpecificCharacteristics ATTRIBUTE
::= { VehicleSpecificCharacteristics IDENTIFIED BY efcVehicleSpecificCharacteristicsId }

efcTrailerCharacteristics ATTRIBUTE ::= { TrailerCharacteristics IDENTIFIED BY
efcTrailerCharacteristicsId }

efcEngine ATTRIBUTE ::= { Engine IDENTIFIED BY efcEngineId }

efcSoundLevel ATTRIBUTE ::= { SoundLevel IDENTIFIED BY efcSoundLevelId }

efcCO2EmissionValue ATTRIBUTE ::= { CO2EmissionValue IDENTIFIED BY
efcCO2EmissionValueId }

efcExhaustEmissionValues ATTRIBUTE ::= { ExhaustEmissionValues IDENTIFIED BY
efcExhaustEmissionValuesId }

efcDieselEmissionValues ATTRIBUTE ::= { DieselEmissionValues IDENTIFIED BY
efcDieselEmissionValuesId }

-- Type identifiers

-- The type identifiers 0 .. 127 are compatible with ISO 14906:2011

-- Types used as well in ISO 14906:2011 have the same identifier

-- Identifiers for types used in ISO 14906:2011 but in this International Standard are not used

vinId	INTEGER ::=	15
efcVehicleLicencePlateNumberId	INTEGER ::=	16
efcVehicleDimensionsId	INTEGER ::=	18
efcVehicleWeightLimitsId	INTEGER ::=	20
efcVehicleSpecificCharacteristicsId	INTEGER ::=	22
efcAxleWeightLimitsId	INTEGER ::=	37
efcPassengerCapacityId	INTEGER ::=	38
efcEngineId	INTEGER ::=	39
efcSoundLevelId	INTEGER ::=	40
efcExhaustEmissionValuesId	INTEGER ::=	41
efcDieselEmissionValuesId	INTEGER ::=	42
efcCO2EmissionValueId	INTEGER ::=	43
efcTrailerLicencePlateNumberId	INTEGER ::=	45
efcTrailerCharacteristicsId	INTEGER ::=	46

vehicleIdId	INTEGER ::=	129
registrationAuthorityId	INTEGER ::=	130
vehicleIdStatusId	INTEGER ::=	131
dateOfFirstRegistrationId	INTEGER ::=	132
dateOfRegistrationId	INTEGER ::=	133
validThruId	INTEGER ::=	134
chassisNumberId	INTEGER ::=	135
registrationNumberId	INTEGER ::=	136
vehicleMakeId	INTEGER ::=	137
vehicleTypeId	INTEGER ::=	138
vehicleTypeStatusId	INTEGER ::=	139
commercialDescriptionId	INTEGER ::=	140
typeApprovalNumberId	INTEGER ::=	141
vehicleCategoryId	INTEGER ::=	142
vehicleTaxCategoryId	INTEGER ::=	143
euVehicleCategoryCodeId	INTEGER ::=	144
raSpecificVehicleClass1Id	INTEGER ::=	145
raSpecificVehicleClass2Id	INTEGER ::=	146
raSpecificVehicleClass3Id	INTEGER ::=	147
vehicleUseId	INTEGER ::=	148
privateUseId	INTEGER ::=	149
colourId	INTEGER ::=	150
lengthId	INTEGER ::=	151
widthId	INTEGER ::=	152
heightId	INTEGER ::=	153
wheelbaseId	INTEGER ::=	154
bodyShapeId	INTEGER ::=	155
euBodyWorkTypeId	INTEGER ::=	156
iso3833VehicleTypeId	INTEGER ::=	157
numberOfSeatsId	INTEGER ::=	158
numberOfStandingPlacesId	INTEGER ::=	159
maxNumberOfPassengersId	INTEGER ::=	160
unladenWeightId	INTEGER ::=	161
maxDesignLadenMassId	INTEGER ::=	162
maxAuthorizedLadenMassId	INTEGER ::=	163
maxAuthorizedTrainMassId	INTEGER ::=	164
maxAuthorizedPayloadId	INTEGER ::=	165
numberOfAxlesId	INTEGER ::=	166
authorizedAxleLadenMassId	INTEGER ::=	167
maxTowableMassBrakedTrailerId	INTEGER ::=	168
maxTowableMassUnbrakedTrailerId	INTEGER ::=	169
engineIdId	INTEGER ::=	170
primeEngineTypeId	INTEGER ::=	171
enginePowerSourcesId	INTEGER ::=	172

primePowerSourceId	INTEGER ::=	173
engineMaxNetPowerId	INTEGER ::=	174
engineDisplacementId	INTEGER ::=	175
ratedEngineSpeedId	INTEGER ::=	176
powerWeightRatioId	INTEGER ::=	177
maxSpeedId	INTEGER ::=	178
fuelTanksCapacityId	INTEGER ::=	179
stationarySoundLevelId	INTEGER ::=	180
engineSpeedId	INTEGER ::=	181
driveBySoundLevelId	INTEGER ::=	182
emissionCOId	INTEGER ::=	183
emissionHCId	INTEGER ::=	184
emissionNOxId	INTEGER ::=	185
emissionHCandNOxId	INTEGER ::=	186
particulatesForDieselId	INTEGER ::=	187
correctedAbsorptionCoefficientId	INTEGER ::=	188
emissionCO2Id	INTEGER ::=	189
combinedFuelConsumptionId	INTEGER ::=	190
environmentalCategoryId	INTEGER ::=	191
euroTypeId	INTEGER ::=	192
lastOfficialTestDataId	INTEGER ::=	193
raSpecificDataId	INTEGER ::=	194
axlesPerAxleGroupId	INTEGER ::=	195
authorizedAxleGroupLadenMassId	INTEGER ::=	196

Int2 ::= INTEGER(0..65535)

END

Annex B (informative)

Combined ERI data and local registrations

B.1 General

This Annex provides some examples of a mapping from registration certificate data in some countries to the ERI data components as defined in this part of ISO 24534.

The following examples are presented:

- EU registration certificates;
- Japanese certificates for private cars.

B.2 EU registration certificates and ERI data components

Within the EU, a harmonized community code is assigned to each data element of a registration certificate (see directive EU 1999/37 and EU 2003/127).

[Table B.1](#) provides for each harmonized community code as assigned in the directive EU 1999/37 and EU 2003/127 the corresponding ERI data component.

For privacy reasons, there is no personal data stored in an ERT and, therefore, the personal data elements are not supported.

Table B.1 — Harmonized community codes and ERI data components

Harmonized community code	EU registration certificate part 1 data element	Part 1 ^a	ERI data component
A	Registration number	M	registrationNumber
B	Date of first registration of the vehicle	M	dateOfFirstRegistration
C	Personal data		
C.1	Holder of the registration certificate	M	(not supported)
C.2	Owner of the vehicle (repeated as many times as there are owners)	O	(not supported)
C.3	Natural or legal person who may use the vehicle by virtue of a legal right other than ownership.	O	(not supported)
C.4	Where the particulars of C.2 are not included, reference is made to the fact that the holder (a) is the vehicle owner, (b) is not the vehicle owner, (c) is not identified by the registration certificate as being the vehicle owner.	M	(not supported)
^a Legend Part 1 column: M Mandatory O Optional Blank Not applicable (see detailed data elements).			

Table B.1 (continued)

Harmonized community code	EU registration certificate part 1 data element	Part 1 ^a	ERI data component
C.5, C.6, C.7, C.8	Where a change in the personal data given in points C.1, C.2 and/or C.3 does not give rise to the issue of a new registration certificate, the new personal data corresponding to these points may be included under codes C.5, C.6, C.7, or C.8; they are then broken down in accordance with the references in C.1, C.2, C.3, and C.4.	O	(not supported)
D	Vehicle		
D.1	Make	M	vehicleMake
D.2	Type - variant (if applicable), - version (if applicable)	M	VehicleType
D.3	Commercial description(s)	M	commercialDescription
E	Vehicle identification number	M	vin
F	Mass		
F.1	Maximum technically permissible laden mass (except for motorcycles)	M	maxDesignLadenMass
F.2	Maximum permissible laden mass of the vehicle in service in the member state of registration	O	maxAuthorizedLadenMass
F.3	Maximum permissible laden mass of the whole vehicle in service in the member state of registration	O	maxAuthorizedTrainMass
G	Mass of the vehicle in service with bodywork and with coupling device in the case of a towing vehicle in service from any category other than M1	M	UnladenWeight
H	Period of validity, if not unlimited	M	ValidThru
I	Date of registration to which this certificate refers	M	dateOfRegistration
J	Vehicle category	O	vehicleCategory or euVehicleCategoryCode
K	Type approval number (if applicable)	M	typeApprovalNumber
L	Number of axles	O	NumberOfAxles
M	Wheelbase (in mm)	O	Wheelbase
N	For vehicles with a total exceeding 3 500 kg, distribution of the technically permissible maximum laden mass among the axles		
N.1	Axle 1 (in kg)	O	authorizedAxleLadenMass, first list value
N.2	Axle 2 (in kg), where appropriate	O	authorizedAxleLadenMass, second list value
N.3	Axle 3 (in kg), where appropriate	O	authorizedAxleLadenMass, third list value
N.4	Axle 4 (in kg), where appropriate	O	authorizedAxleLadenMass, fourth list value
^a Legend Part 1 column: M Mandatory O Optional Blank Not applicable (see detailed data elements).			

Table B.1 (continued)

Harmonized community code	EU registration certificate part 1 data element	Part 1 ^a	ERI data component
N.5	Axle 5 (in kg), where appropriate	0	authorizedAxleLaden-Mass, fifth list value
	Technically permissible maximum towable mass of the trailer		
0.1	Braked (in kg)	0	maxTowableMassBraked Trailer
0.2	Unbraked (in kg)	0	maxTowableMassUn-braked Trailer
P	Engine		
P.1	Capacity (displacement) (in cm ³)	M	engineDisplacement
P.2	Maximum net Power (nominal power) (in kW), if available	M	engineMaxNetPower
P.3	Type of fuel or power source	M	enginePowerSource
P.4	Rated speed (in min ⁻¹)	0	ratedEngineSpeed
P.5	Engine identification number	0	engineId
Q	Power/weight ratio (in kW/kg) (only motorcycles)	M	powerWeightRatio
R	Colour of the vehicle	0	colour
S	Seating capacity:		
S.1	Number of seats, including the driver's seat	M	numberOfSeats
S.2	Number of standing places (where appropriate)	M	numberOfStanding-Places
T	Maximum speed (in km/h)	0	maxSpeed
U	Sound level:		
U.1	Stationary [in db(A)]	0	stationarySoundLevel
U.2	Engine speed (in min ⁻¹)	0	engineSpeed
U.3	Drive by [in db(A)]	0	driveBySoundLevel
V	Exhaust emissions:		
V.1	CO (in g/km or g/kWh)	0	emissionCO
V.2	HC (in g/km or g/kWh)	0	emissionHC
V.3	NO _x (in g/km or g/kWh)	0	emissionNOx
V.4	HC + NO _x (in g/km)	0	emissionHCandNOx
V.5	Particulates (in g/km or g/kWh)	0	particulatesForDiesel
V.6	Corrected absorption coefficient for diesel (in min ⁻¹)	0	correctedAbsorption Coefficient
V.7	CO ₂ (in g/km)	0	emissionCO2
V.8	Combined fuel consumption (in l/100 km)	0	combinedFuelCon-sumption
V.9	Indication of the environmental category of EC type-approval	0	euroType
W	Fuel tank(s) capacity (in litres)	0	fuelTanksCapacity

^a Legend Part 1 column:

M Mandatory

0 Optional

Blank Not applicable (see detailed data elements).

B.3 Japanese registration certificates and ERI data components

Table B.2 shows the data elements in a Japanese registration certificate for a vehicle with the corresponding ERI data component.

For privacy reasons, there is no personal data stored in an ERT and, therefore, the personal data elements are not supported.

Table B.2 — Japanese registration certificates and ERI data components

Japanese registration certificate data element	ERI data component
Vehicle ID	vehicleId
Licence plate number	registrationNumber
Vehicle discrimination code	vehicleTaxCategory
Registration date or issue date	dateOfRegistration
First year registration date	dateOfFirstRegistration
Classification of the vehicle	vehicleCategory
Purpose of use	vehicleUse
Private use or commercial use	privateUse
Shape of the body	bodyShape
Make and type of motor vehicle	vehicleMake and vehicleType
Riding capacity	maxNumberOfPassengers
Maximum payload	maxAuthorizedPayload
Vehicle weight	unladenWeight
Gross vehicle weight	maxDesignLadenMass
Length	length
Width	width
Height	height
Front axle capacity	authorizedAxleLadenMass, first list value
Second front axle capacity	authorizedAxleLadenMass, second list value
Second rear axle capacity	authorizedAxleLadenMass, second last list value
Rear axle capacity	authorizedAxleLadenMass, last list value
Type of motor vehicle	vehicleType
Supplementary code for the motor vehicle type	vehicleTypeStatus
Supplementary code for the vehicle chassis number	vehicleIdStatus
Type of prime mover (engine)	primeEngineType
Engine displacement or rated output	engineDisplacement
Kind of fuel	primePowerSource
Classification number of motor vehicle	raSpecificVehicleClass1
Classification number of kind	raSpecificVehicleClass2
Name or designation of owner	(not supported)
Address of owner	(not supported)
Name or designation of user	(not supported)
Address of user	(not supported)

Annex C (informative)

Correspondance with EFC attributes

[Table C.1](#) shows the correspondance between the attributes for vehicle data in ISO 14906:2011 and the ones for EFC purposes in this part of ISO 24534.

Table C.1 — Correspondance with the attributes in ISO 14906

ISO 14906:2011 attribute type	ERI part 3 attribute	Equivalence/Explanation
VehicleIdentificationNumber	vin	Equal
VehicleLicencePlateNumber	efcVehicleLicencePlateNumber	Equal ¹⁾
VehicleClass	None	In ISO 14906, the Vehicle class type is toll service provider specific.
VehicleDimensions	efcVehicleDimensions	Equal
VehicleAxles	None	The VehicleAxles type uses values from two vehicle registration certificates: the one for the towing vehicle and the one for the trailer. Consequently, these values are part of two distinguished EriDate type values.
VehicleWeightLimits	efcVehicleWeightLimits	Equal
VehicleWeightLaden	None	A registration authority cannot specify the actual weight of a vehicle.
VehicleSpecificCharacteristics	efcVehicleSpecificCharacteristics	Equal
VehicleAuthenticator	None	The value depends on the actual data to be exchanged.
AxleWeightLimits	efcAxleWeightLimits	Equal
PassengerCapacity	efcPassengerCapacity	Equal
Engine	efcEngine	Equal
SoundLevel	efcSoundLevel	Equal
ExhaustEmissionValues	efcExhaustEmissionValues	Equal
DieselEmissionValues	egcDieselEmissionValues	Equal
CO2EmissionValue	efcCO2EmissionValue	Equal

Table C.1 (continued)

ISO 14906:2011 attribute type	ERI part 3 attribute	Equivalence/Explanation
VehicleTotalDistance	None	A registration authority cannot specify the actual total distance driven.
TrailerLicencePlateNumber	efcTrailerLicencePlateNumber	Equal ¹⁾
TrailerCharacteristics	efcTrailerCharacteristics	Equal

NOTE 1 All three attributes registrationNumber, vehicleLicencePlateNumber, and TrailerLicencePlateNumber identify the same registrationnumber type which is equal to the LPN type used in ISO 14906-201. They only have different identifiers.

Bibliography

- [1] ISO 24534-1, *Automatic vehicle and equipment identification — Electronic registration identification (ERI) for vehicles — Part 1: Architecture*
- [2] ISO 24534-2, *Automatic vehicle and equipment identification — Electronic registration identification (ERI) for vehicles — Part 2: Operational requirements*
- [3] ISO 24534-4, *Automatic vehicle and equipment identification — Electronic registration identification (ERI) for vehicles — Part 4: Secure communications using asymmetrical techniques*
- [4] ISO 24534-5, *Intelligent transport systems — Automatic vehicle and equipment identification — Electronic Registration Identification (ERI) for vehicles — Part 5: Secure communications using symmetrical techniques*
- [5] ISO/IEC 7498-2:1989, *Information technology — Security techniques — Entity authentication — Part 2: Security Architecture*
- [6] ISO/IEC 9798-1:2010, *Information technology — Security techniques — Entity authentication — Part 1: General*
- [7] EU 1970/156:1970, *Council directive 70/156/EEC of 6 February 1970 on the approximation of the laws of the Member States relating to the type-approval of motor vehicles and their trailers. (OJ L 42, 23.2.1970, p. 1)*

This directive is adapted to technical progress in EU 2001/116.

- [8] EU 1988/77:1988, *Council directive 88/77/EEC of 3 December 1988 on the approximation of the laws of the Member States relating to the measures to be taken against the emission of gaseous pollutants from diesel engines for use in vehicles. (OJ L 36, 9.2.1988, p. 33)*

This directive has been repealed in article 10 of directive 05/55 which, in turn, is repealed with effect from 31 December 2013 (see regulation 595/2009).

- [9] EU 1992/61:1992, *Council directive 92/61/EEC of 30 June 1992 relating to the type-approval of two or three-wheel motor vehicles (OJ L 225, 10.8.1992, p. 72)*
- [10] EU 1999/37:1999, *Council directive 1999/37/EC of 29 April 1999 on the registration documents for vehicles. (OJ L 138, 1.6.1999, p. 57)*

This relevant annex of this directive is amended in EU 2003/127.

- [11] EU 2001/116:2001, *Commission directive 2001/116/EC of 20 December 2001 adapting to technical progress Council directive 70/156/EEC of 6 February 1970 on the approximation of the laws of the Member States relating to the type-approval of motor vehicles and their trailers. (OJ L 18, 21.1.2002, p. 1)*
- [12] EU 2002/24:2002, *Directive 2002/24/EC of the European Parliament and of the council of 18 March 2002 relating to the type-approval of two or three-wheel motor vehicles and repealing Council Directive 92/61/EEC (Text with EEA relevance) (OJ L 124, 9.5.2002, p. 1)*
- [13] EU 2003/127:2003, *Commission directive 2003/127/EC of 23 December 2003 amending council directive 1999/37/EC on the registration documents for vehicles. (Text with EEA relevance) (OJ L 10, 16.1.2004, p. 29)*
- [14] EU 2005/55, *Directive 2005/55/EC of the European Parliament and of the Council of 28 September 2005 on the approximation of the laws of the Member States relating to the measures to be taken against the emission of gaseous and particulate pollutants from compression-ignition engines for use in vehicles, and the emission of gaseous pollutants from positive-*

ignition engines fuelled with natural gas or liquefied petroleum gas for use in vehicles (OJ L 275, 20.10.2005, p. 1)

This directive is repealed with effect from 31 December 2013 (see regulation 595/2009).

- [15] UNECE 1999:1999, UNECE Consolidated resolution on the construction of vehicle (R.E.3) revision 1 — amendment 2, Annex 7/Rev.2 — Classification and definition of power-driven vehicles and trailers, TRANS/WP.29/78/Rev.1/Amend.2, 16 April 1999
- [16] EU 1970/220, Council Directive of 20 March 1970 on the approximation of the laws of the Member States on measures to be taken against air pollution by emissions from motor vehicles (OJ L 76, 6.4.1970, p. 1)

This directive is repealed with effect from 2 January 2013 (see regulation 715/2007).

- [17] EU 715/2007, *Regulation (EC) No 715/2007 of the European Parliament and of the council of 20 June 2007 on type approval of motor vehicles with respect to emissions from light passenger and commercial vehicles (Euro 5 and Euro 6) and on access to vehicle repair and maintenance information* (OJ L 171, 29.6.2007, p. 1)
- [18] EU 595/2009, *Regulation (EC) No 595/2009 of the European Parliament and of the Council of 18 June 2009 on type-approval of motor vehicles and engines with respect to emissions from heavy duty vehicles (Euro VI) and on access to vehicle repair and maintenance information and amending Regulation (EC) No 715/2007 and Directive 2007/46/EC and repealing Directives 80/1269/EEC, 2005/55/EC and 2005/78/EC* (OJ L 188, 18.7.2009, p. 1)
- [19] ISO 14906:2011, *Electronic fee collection — Application interface definition for dedicated short-range communication*

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK