BS EN 73:2014



## **BSI Standards Publication**

Wood preservatives —
Accelerated ageing of treated wood prior to biological testing — Evaporative ageing procedure



#### National foreword

This British Standard is the UK implementation of EN 73:2014. It supersedes BS 5761-1:1989 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee B/515, Wood preservation.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014. Published by BSI Standards Limited 2014

ISBN 978 0 580 77207 8

ICS 71.100.50

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 October 2014.

Amendments issued since publication

Date

Text affected

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM **EN 73** 

October 2014

ICS 71.100.50

Supersedes EN 73:1988

#### **English Version**

# Wood preservatives - Accelerated ageing of treated wood prior to biological testing - Evaporative ageing procedure

Produits de préservation du bois - Épreuves de vieillissement accéléré des bois traités avant essais biologiques - Épreuve d'évaporation

Holzschutzmittel - Beschleunigte Alterung von behandeltem Holz vor biologischen Prüfungen -Verdunstungsbeanspruchung

This European Standard was approved by CEN on 30 August 2014.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

| Co    | ntents   | Page |
|-------|--|------|
| Fore  | eword  | 3    |
| Intro | oduction   | 4    |
| 1     | Scope  | 5    |
| 2     | Principle  | 5    |
| 3     | Equipment  |      |
| 4     | Test specimens   | 5    |
| 5     | Procedure  | 6    |
| 6     | Destination of the test specimens after the evaporative ageing procedure | 8    |
| 7     | Reference to this standard in biological test reports                    | 8    |
| Ribli | iography   | 9    |

## **Foreword**

This document (EN 73:2014) has been prepared by Technical Committee CEN/TC 38 "Durability of wood and wood-based products", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2015 and conflicting national standards shall be withdrawn at the latest by April 2015.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 73:1988.

Compared to EN 73:1988 the following modifications have been made:

- a) an Introduction has been added;
- b) grids have been introduced in 5.1 to carry the test specimens.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

## Introduction

During its service life, preservative-treated wood can be exposed to conditions which may cause the volatilization and removal of the wood preservative thereby reducing its effectiveness.

This European Standard provides a laboratory based method for ageing test blocks which are to be subject to biological testing.

## 1 Scope

This European Standard specifies an evaporative ageing procedure, applicable to test specimens of wood which have been previously treated with a wood preservative, in order to evaluate any loss of effectiveness when these test specimens are subsequently subjected to biological tests.

## 2 Principle

Test specimens are prepared for biological testing of the effectiveness of wood preservatives against either fungi or insects using the appropriate standards methods. Test specimens are exposed, for a specified period, in a dust-free current of air of a defined velocity and temperature.

## 3 Equipment

**3.1** A wind tunnel which is compartmented and fitted with devices for heating and distributing air.

The air shall be dust-free and shall not be polluted by chemical products which could have an effect on the test results.

The heating and distribution devices shall be such that the temperature and air velocity are maintained constant and uniform in each compartment.

The air leaving the tunnel shall be led away in such a manner that it cannot re-enter the tunnel.

- **3.2** A device which:
- a) controls the temperature within the defined limits stated in 5.2;
- b) measures and records the air temperature within the defined limits as stated in 5.2.
- 3.3 An anemometer capable of measuring air velocity of  $(1 \pm 0.3)$  m/s.

## 4 Test specimens

#### 4.1 Definitions and origin

The test specimens and their preparation are defined in the standards concerning the biological tests to which they are intended to be subjected.

The evaporative ageing procedure shall be carried out no more than 3 months after the end of the conditioning period that follows the treatment of the test specimens described in the relevant biological test standard. An alternative period can be used if specified by the product supplier. This shall be stated in the test report.

## 4.2 Number of test specimens

The number of test specimens shall allow the relevant biological tests to be carried out in accordance with the instructions in the appropriate standards, bearing in mind that the evaporative ageing procedure shall be applied equally to treated test specimens that are subjected to biological agents and to control test specimens.

The control test specimens may be of the following kinds where required by the relevant test standard:

- treated control test specimens that will not be subjected to attack by biological agents after the evaporative ageing procedure. These will serve as controls for changes in mass in those tests in which this factor is taken into consideration;
- untreated control specimens which, after evaporative ageing, are subjected to the test by biological agents, to check any variation in the behaviour of untreated wood.

#### 5 Procedure

## 5.1 Arrangement of the test specimens

Arrange the test specimens in the compartments on grids made from metal or any other inert material which can be decontaminated, resting them with one of their faces on the base so that none of the other faces is less than 10 mm from the side partitions. The faces parallel to the grain of the wood shall be parallel to the general direction of air flow and they shall be at least 10 mm from the corresponding faces of the adjacent test specimens. Do not place in the same compartment either test specimens treated with different products or with different concentrations or loadings of the same product or treated and control specimens. Arrange the test specimens according to type, as follows:

#### Test specimens treated on all surfaces

Rest the test specimens on one of the small faces parallel to the grain of wood with the faces that are perpendicular to the grain of the wood at least 20 mm away from the corresponding faces of adjacent test pieces.

For example, specimens intended for testing in accordance with EN 113 (basidiomycetes).

## Test specimens for which the faces perpendicular to the grain of wood are sealed before treatment

Arrange the test specimens as above. The sealed faces may, however, be brought closer together.

For example, specimens intended for testing in accordance with EN 118 (termites).

#### Test specimens with one treated face only

Rest the test specimens on the opposite face to that which has been treated.

For example, test specimens intended for the test determining preventive action against termites (EN 118) and the larvae of *Hylotrupes bajulus*.

## 5.2 Starting and adjustment of the apparatus

With the test specimens in position, establish an air current controlled at a temperature of  $(40 \pm 2)$  °C which enters the compartments at a speed of  $(1 \pm 0.3)$  m/s.


## 5.3 Procedure

Maintain the test specimens in the arrangement specified in 5.1 and under the conditions specified in 5.2 for two weeks (14 days).


In order to obtain homogeneous evaporation from all the treated faces of a test specimen, rotate the test specimens through an angle of 180° on its small horizontal axis every two week (14 days) period (see Figure 2).

Test specimens with only one treated surface shall be rotated through an angle of 180° on their vertical axis every two weeks (14 days) period (see Figure 3).


If a compartment contains more than one test specimen, at the same time as rotating the test specimens, change the position of the specimens within this compartment, the method depending on the number of test specimens which it contains and on the duration of the procedure (see Figure 1).



## a) Position of test specimens in 1st week




## b) Position of test specimens in 2nd week



c) Position of test specimens in 3rd week

Each progressive move is associated with a rotation (see Figures 2 and 3).

Figure 1 — Movement of test specimens in a compartment containing more than one test specimen








Figure 2 — Rotation of test specimen with 4 or 6 treated surfaces through an angle of 180° on its small horizontal axis





NOTE The specimen rests on the untreated surface that is opposite the treated surface.

Figure 3 — Rotation of test specimen with only one treated surface through an angle of 180° on its vertical axis

## 5.4 Exposure period in the tunnel

The duration of the exposure period is 12 weeks.

For certain specific applications alternative periods of ageing may be used, in which case the ageing period should be mentioned in the report of the biological test concerned.

## 6 Destination of the test specimens after the evaporative ageing procedure

After completion of the ageing procedure and the post exposure conditioning period the test specimens shall be subject to biological tests within 3 months.

## 7 Reference to this standard in biological test reports

Quote the evaporative ageing procedure by giving the number of this European Standard (i.e. EN 73), the duration of evaporative ageing period and the date of the start of the biological tests in the test report for each biological test.

The duration and conditions of storage of the test specimen between initial preparation and the start of the ageing procedure shall also be reported.

Any deviation from the method described in this standard shall be reported in the test report.

## **Bibliography**

- [1] EN 113:1996, Wood preservatives Test method for determining the protective effectiveness against wood destroying basidiomycetes Determination of the toxic values
- [2] EN 117, Wood preservatives Determination of toxic values against Reticulitermes species (European termites) (Laboratory method)
- [3] EN 118, Wood preservatives Determination of preventive action against Reticulitermes species (European termites) (Laboratory method)
- [4] EN 599-1, Durability of wood and wood-based products Efficacy of preventive wood preservatives as determined by biological tests Part 1: Specification according to Use Class

# British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

#### About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards -based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

#### Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

## **Buying standards**

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

## **Subscriptions**

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

**PLUS** is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

## **BSI Group Headquarters**

389 Chiswick High Road London W4 4AL UK

#### Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

#### Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

#### **Useful Contacts:**

#### **Customer Services**

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com
Email (enquiries): cservices@bsigroup.com

#### Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

#### **Knowledge Centre**

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

#### **Copyright & Licensing**

**Tel:** +44 20 8996 7070

Email: copyright@bsigroup.com

