BS EN 480-15:2013



BSI Standards Publication

Admixtures for concrete, mortar and grout — Test methods

Part 15: Reference concrete and method for testing viscosity modifying admixtures



BS EN 480-15:2013 BRITISH STANDARD

National foreword

This British Standard is the UK implementation of EN 480-15:2013.

The UK participation in its preparation was entrusted to Technical Committee B/517/3, Admixtures.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2013. Published by BSI Standards Limited 2013

ISBN 978 0 580 76349 6

ICS 91.100.30

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 March 2013.

Amendments issued since publication

Date Text affected

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 480-15

March 2013

ICS 91.100.30

English Version

Admixtures for concrete, mortar and grout - Test methods - Part 15: Reference concrete and method for testing viscosity modifying admixtures

Adjuvant pour béton, mortier et coulis - Méthodes d'essai -Partie 15: Béton de référence et méthode d'essai des adjuvants modificateurs de viscosité Zusatzmittel für Beton, Mörtel und Einpressmörtel -Prüfverfahren - Teil 15: Referenzbeton und Prüfverfahren zur Prüfung von viskositätsmodifizierenden Zusatzmitteln

This European Standard was approved by CEN on 19 January 2013.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Cor	Contents		
Fore	Foreword		
1	Scope	4	
2	Normative references	4	
3	Constituent materials	4	
3.1	Cement	4	
3.2	Aggregate	4	
3.3	Aggregate Mixing water	5	
4	Reference concrete	5	
5	Preparation of reference concrete	6	
5.1	Mix proportions	6	
5.2	Mixing and testing	6	
6	Test report	7	

Foreword

This document (EN 480-15:2013) has been prepared by Technical Committee CEN/TC 104 "Concrete and related products", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2013, and conflicting national standards shall be withdrawn at the latest by September 2013.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document has been drafted by Subcommittee 3 (SC 3) of CEN/TC 104 "Admixtures for concrete, mortar and grout".

This draft European Standard is part of the series EN 480, *Admixtures for concrete, mortar and grout — Test methods* which is comprised of the following parts:

- Part 1: Reference concrete and reference mortar for testing
- Part 2: Determination of setting time
- Part 4: Determination of bleeding of concrete
- Part 5: Determination of capillary absorption
- Part 6: Infrared analysis
- Part 8: Determination of the conventional dry material content
- Part 10: Determination of water soluble chloride content
- Part 11: Determination of air void characteristics in hardened concrete
- Part 12: Determination of the alkali content of admixtures
- Part 13: Reference masonry mortar for testing mortar admixtures
- Part 14: Determination of the effect on corrosion susceptibility of reinforcing steel by potentiostatic electro-chemical test
- Part 15: Reference concrete and method for testing viscosity modifying admixtures (the present document)

This European Standard is applicable together with the other standards of the EN 480 series and for testing admixtures in accordance with the EN 934 series of standards.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1 Scope

This European Standard specifies the constituent materials, the composition and the mix procedure to produce a reference concrete with a prescribed consistency and segregated portion for testing viscosity modifying admixtures as defined in EN 934-2. It also describes how to determine the requirements for the test mix in comparison with the control mix.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 196-2, Methods of testing cement — Part 2: Chemical analysis of cement

EN 196-6, Methods of testing cement — Part 6: Determination of fineness

EN 197-1, Cement — Part 1: Composition, specifications and conformity criteria for common cements

EN 934-2, Admixtures for concrete, mortar and grout — Part 2: Concrete admixtures — Definitions, requirements, conformity, marking and labelling

EN 1008, Mixing water for concrete — Specification for sampling, testing and assessing the suitability of water, including water recovered from processes in the concrete industry, as mixing water for concrete

EN 12350-7, Testing fresh concrete — Part 7: Air content — Pressure methods

EN 12350-8, Testing fresh concrete — Part 8: Self-compacting concrete — Slump-flow test

EN 12350-11, Testing fresh concrete — Part 11: Self-compacting concrete — Sieve segregation test

EN 12390-1, Testing hardened concrete — Part 1: Shape, dimensions and other requirements for specimens and moulds

EN 12390-2, Testing hardened concrete — Part 2: Making and curing specimens for strength tests

EN 12620, Aggregates for concrete

3 Constituent materials

3.1 Cement

The reference concrete shall be made with a CEM I cement of strength class 42,5 or 52,5 conforming to EN 197-1.

The cement used shall have a C_3A content of 7 % to 11 % by mass calculated from chemical analysis according to EN 196-2 and a specific surface of 3 200 cm²/g to 4 600 cm²/g determined according to EN 196-6.

3.2 Aggregate

A natural normal weight aggregate conforming to EN 12620 with low water absorption (\leq 2 % by mass) shall be used. The grading shall conform to Table 1.

Table 1 — Aggregate for reference concrete

Aperture size - mm	Percentage by mass passing the test sieve
16	95 to 100
12	85 to 100
8	62 to 74
4	42 to 52
2	28 to 38
1	19 to 29
0,500	11 to 21
0,250	4 to 14
0,125	2 to 6
0,063	0 to 2

3.3 Mixing water

Water according to EN 1008, or distilled or de-ionised water shall be used as mixing water.

Wash water from concrete production shall not be used.

4 Reference concrete

Unless otherwise specified, tests on the reference concrete are performed as comparative tests. That is, the performance of the admixtures is determined by comparing the reference concrete containing the viscosity modifying admixture (test mix) with the reference concrete made without the viscosity modifying admixture (control mix) but otherwise with the same aggregate/cement ratio and constituents from the same delivery.

The requirements for the reference concrete are given in Table 2. The fresh concrete shall be fully compacted. The air content of the control mix shall not exceed 2 % by volume.

Table 2 — Requirements for reference concrete

Constituent / test	Requirement
Reference Cement	(400 ± 10) kg/m ³
Aggregate	According to 3.2. The aggregate: cement ratio shall be recorded
Superplasticizer to EN 934-2	Within manufacturers normal range
Water	≤ 230 kg/m ³
Slump flow (SF) to EN 12350-8	Control mix 660 mm to 750 mm
	Test mix ≥ control mix
Sieve segregation (SR) to EN 12350-11	Control mix 15 % ≤ SR ≤ 30 %
Air content to EN 12350-7	Control mix ≤ 2 %

5 Preparation of reference concrete

5.1 Mix proportions

The mix proportions shall be in accordance with Table 2.

The aggregate shall be used in an oven dry condition (≥ 105 °C) to remove doubts on moisture content variation. If the aggregate is not oven dry, its moisture content shall be determined and the aggregate and water content shall be corrected accordingly. In the case of dispute, oven dry aggregates shall be used.

The dosage of the superplasticizer and the quantity of water in the control mix shall be such as to obtain an initial slump flow (SF) and sieve segregation (SR) in accordance with Table 2.

The test mix containing the viscosity modifying admixture shall have the same water content, cement content and the same aggregate: cement ratio as the control mix but the dosage of superplasticizer shall be adjusted if necessary to give a consistence not less than that of the control mix.

5.2 Mixing and testing

Prior to mixing, each of the constituents shall be conditioned to a temperature of (20 ± 2) °C.

The following mixing technique shall be adopted to ensure repeatability of results and eliminate initial moisture absorption effects on consistence.

- Use a forced action pan mixer to a minimum of 50 % and a maximum 90 % of capacity.
- Wipe the inside with a damp cloth if dry.
- Add all the aggregates to the pan mixer with half the mixing water. Mix for 2 min then stand for 2 min.
 Cover the pan mixer during the standing period to minimise evaporation effects.
- Restart the mixer for 30 s after or while adding the cement. Over the next 30 s, add the remaining water and admixtures as appropriate to the mix (noting any manufacturer's recommendations with respect to the order and timing). Mix for a further 2 min.
- Determine the slump flow (SF) and start the sieve segregation test (SR) within 10 min of completion of mixing.

- If the slump flow and sieve segregation of the control mix are outside the limits in Table 2, discard the mix and repeat at a revised water or superplasticiser content. If the slump flow of the test mix is not equal to or greater than the slump flow of the control mix, discard the mix and repeat at a revised superplasticiser content.
- Determine the fresh density and air content within 30 min from completion of mixing (if necessary the concrete may be remixed for 10 s).
- If the air content and/or cement content of the control mix calculated from the fresh density are outside the limits in Table 2. discard the mix and test a new mix.
- Take three specimens from each mix for compressive strength testing. The control mix should be held for 60 min to 90 min then remixed for 1 min before taking the specimens to prevent segregation in the cube or cylinder mould. The test mix specimens should not be remixed but be made within 60 min from completion of initial mixing. Prepare and cure the specimens in accordance with EN 12390-2 using moulds conforming to EN 12390-1. If the compressive strength of one of the specimens varies from the average of the set by more than 10 % it shall be discarded and the average recalculated from the remaining two specimens.

6 Test report

The test report shall include the following information for the control and test mixes:

- a) A reference to this standard.
- b) Aggregate:
 - 1) source and type;
 - 2) crushed / uncrushed;
 - 3) grading:
 - 4) moisture content if not oven dry.
- c) Cement:
 - 1) source;
 - 2) notation to EN 197-1 including strength class;
 - C₃A content;
 - 4) specific surface.
- d) Concrete:
 - 1) aggregate: cement ratio of control and test mixes;
 - 2) admixture dose in the control and test mixes (superplasticizer and the viscosity modifying admixture);
 - 3) consistence, slump flow (SF);
 - 4) sieve segregation, segregated portion (SR);
 - 5) air content;
 - 6) fresh bulk density;
 - 7) compressive strength individual and average results.





British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards -based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com
Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070 Email: copyright@bsigroup.com

