

**Chemicals used for
treatment of water
intended for human
consumption —
Aluminium chloride
(monomeric),
aluminium chloride
hydroxide (monomeric)
and aluminium
chloride hydroxide
sulfate (monomeric)**

The European Standard EN 881:2004 has the status of a
British Standard

ICS 71.100.80

National foreword

This British Standard is the official English language version of EN 881:2004. It supersedes BS EN 881:1997 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee CII/59, Chemicals for drinking water treatment, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the *BSI Catalogue* under the section entitled “International Standards Correspondence Index”, or by using the “Search” facility of the *BSI Electronic Catalogue* or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the EN title page, pages 2 to 18, an inside back cover and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

Amendments issued since publication

Amd. No.	Date	Comments

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 2 December 2004

© BSI 2 December 2004

ISBN 0 580 44942 4

English version

Chemicals used for treatment of water intended for human consumption - Aluminium chloride (monomeric), aluminium chloride hydroxide (monomeric) and aluminium chloride hydroxide sulfate (monomeric)

Produits chimiques utilisés pour le traitement de l'eau destinée à la consommation humaine - Chlorure d'aluminium, hydroxychlorure d'aluminium et hydroxychlorosulfate d'aluminium (monomères)

Produkte zur Aufbereitung von Wasser für den menschlichen Gebrauch - Aluminiumchlorid (monomer), Aluminiumhydroxidchlorid (monomer) und Aluminiumhydroxidchloridsulfat (monomer)

This European Standard was approved by CEN on 30 September 2004.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

	Page
Foreword.....	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Description	5
4 Purity criteria.....	8
5 Test methods.....	10
6 Labelling - Transportation - Storage.....	11
Annex A (informative) General information on aluminium chloride (monomeric), aluminium chloride hydroxide (monomeric) and aluminium chloride hydroxide sulfate (monomeric)	14
Annex B (normative) General rules relating to safety.....	17
Bibliography	18

Foreword

This document (EN 881:2004) has been prepared by Technical Committee CEN/TC 164 "Water supply", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by May 2005, and conflicting national standards shall be withdrawn at the latest by May 2005.

This document supersedes EN 881:1997.

Significant technical differences between this edition and EN 881:1997 are as follows:

- a) replacement of the reference to EU Directive 80/778 of 15 July 1980 with the latest Directive in force (see[1]);
- b) introduction of an annex B (normative) giving general rules relating to safety;
- c) expansion of annex A by addition of A.2 "Quality of commercial product".

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

Introduction

In respect of potential adverse effects on the quality of water intended for human consumption, caused by the product covered by this document:

- a) this document provides no information as to whether the product may be used without restriction in any of the Member States of the EU or EFTA;
- b) it should be noted that, while awaiting the adoption of verifiable European criteria, existing national regulations concerning the use and/or the characteristics of this product remain in force.

NOTE Conformity with this document does not confer or imply acceptance or approval of the product in any of the Member States of the EU or EFTA. The use of the product covered by this document is subject to regulation or control by National Authorities.

1 Scope

This document is applicable to aluminium chloride (monomeric), aluminium chloride hydroxide (monomeric) and aluminium chloride hydroxide sulfate (monomeric) used for treatment of water intended for human consumption. It describes the characteristics and specifies the requirements of aluminium chloride, aluminium chloride hydroxide and aluminium chloride hydroxide sulfate (monomeric) and refers to the corresponding analytical methods. This document does not apply to any polymeric form of these salts (see EN 883). It also gives information for their use in water treatment. It also determines the rules relating to safe handling and use of these aluminium salts (see Annex B).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 883, *Chemicals used for treatment of water intended for human consumption - Polyaluminium chloride hydroxide and polyaluminium chloride hydroxide sulfate.*

EN 1302, *Chemicals used for treatment of water intended for human consumption - Aluminium based coagulants - Analytical methods.*

ISO 3165, *Sampling of chemical products for industrial use - Safety in sampling.*

ISO 6206, *Chemical products for industrial use - Sampling – Vocabulary.*

ISO 8213, *Chemical products for industrial use - Sampling techniques - Solid chemical products in the form of particles varying from powders to coarse lumps.*

3 Description

3.1 Identification

3.1.1 Chemical name

- a) aluminium chloride (monomeric);
- b) aluminium chloride hydroxide (monomeric);
- c) aluminium chloride hydroxide sulfate (monomeric).

3.1.2 Synonym or common names

- a) aluminium chloride;
- b) aluminium chloride hydroxide;
- c) aluminium chloride hydroxide sulfate.

3.1.3 Relative molecular mass

133,3 for AlCl_3 .

3.1.4 Empirical formula

- a) AlCl_3 ;
- b) $\text{Al(OH)}_a\text{Cl}_b$ with $(a + b) = 3$ and a less than or equal to 1,05;
- c) $\text{Al(OH)}_a\text{Cl}_b(\text{SO}_4)_c$ with $(a + b + 2c) = 3$ and a less than or equal to 1,05.

3.1.5 Chemical formula

Variable (see 3.1.4).

3.1.6 CAS Registry Number¹⁾

- a) 7446-70-0;
- b)
 - 1) a and b variable: 1327-41-9 with a less than or equal to 1,05;
 - 2) $a = 1, b = 2$: 14215-15-7;
- c) a, b and c variable: 39290-78-3 with a less than or equal to 1,05.

3.1.7 EINECS reference²⁾

- a) 231-208-1;
- b)
 - 1) 215-477-2;
 - 2) 238-071-7;
- c) 254-400-7.

3.2 Commercial forms

Aluminium chloride in the form of hexahydrate is available as crystals.

Liquid forms of aluminium chloride, aluminium chloride hydroxide and aluminium chloride hydroxide sulfate (monomeric) are available as solutions or suspensions.

3.3 Physical properties

3.3.1 Appearance

The product is colourless to yellow.

1) Chemical Abstracts Service Registry Number.
2) European Inventory of Existing Commercial Chemical Substances.

3.3.2 Density

The density depends on the particular composition, especially the aluminium ion content, expressed as mass fraction of aluminium (Al) in %.

Typical values for solutions:

- a) aluminium chloride: 1,3 g/ml for 5,8 % Al;
- b) aluminium chloride hydroxide: 1,35 g/ml to 1,40 g/ml for 9,5 % Al ;
- c) aluminium chloride hydroxide sulfate:
 - 1,18 g/ml to 1,22 g/ml for 5,3 % Al;
 - 1,18 g/ml for 4,2 % Al .

3.3.3 Solubility

Aluminium chloride, aluminium chloride hydroxide and aluminium chloride hydroxide sulfate (monomeric) are fully miscible with water.

NOTE Depending on the particular product, dilute solutions can hydrolyze and form a precipitate.

3.3.4 Vapour pressure

Not known.

3.3.5 Boiling point at 100 kPa³⁾

Not known.

3.3.6 Crystallization point

Typical values for solutions:

- a) aluminium chloride: - 20 °C for 5,8 %Al ;
- b) aluminium chloride hydroxide:
 - ≤ - 20 °C for 9,5 %Al;
 - ≈ - 20 °C for 12,4 % Al;
- c) aluminium chloride hydroxide sulfate:
 - 10 °C to - 15 °C for 5,3 % Al ;
 - 5 °C for 4,2 %Al .

3.3.7 Specific heat

Not known.

3) 100 kPa = 1 bar.

3.3.8 Viscosity (dynamic)

Typical values for solutions at 20 °C:

- a) aluminium chloride solution: ≈ 10 mPa.s for 5,8 %Al ;
- b) aluminium chloride hydroxide:
 - 10 mPa.s to 50 mPa.s for 9,5 %Al;
- c) aluminium chloride hydroxide sulfate:
 - 3 mPa.s to 10 mPa.s for 5,3 % Al .

3.3.9 Critical temperature

Not applicable.

3.3.10 Critical pressure

Not applicable.

3.3.11 Physical hardness

Not applicable.

3.4 Chemical properties

Aluminium chloride, aluminium chloride hydroxide and aluminium chloride hydroxide sulfate (monomeric) are acidic liquids which hydrolyse and form a precipitate of aluminium hydroxide when diluted beyond a particular level.

NOTE Since aluminium compounds are amphoteric in nature, the solubility of aluminium depends on the pH value and the products should be used within an appropriate pH range.

4 Purity criteria

4.1 General

This document specifies the minimum purity requirements for aluminium chloride (monomeric), aluminium chloride hydroxide (monomeric) and aluminium chloride hydroxide sulfate (monomeric) used for the treatment of water intended for human consumption. Limits are given for impurities commonly present in the product. Depending on the raw material and the manufacturing process other impurities may be present and, if so, this shall be notified to the user and when necessary to relevant authorities.

NOTE Users of these products should check the national regulations in order to clarify whether it is of appropriate purity for treatment of water intended for human consumption, taking into account raw water quality, required dosage, contents of other impurities and additives used in the products not stated in this document.

Limits have been given for impurities and chemicals parameters where these are likely to be present in significant quantities from the current production process and raw materials. If the production process or raw materials lead to significant quantities of impurities, by-products or additives being present, this shall be notified to the user.

4.2 Composition of commercial product

The concentration of active matter (aluminium ion content) in the commercial product expressed as grams per kilogram of product shall be within $\pm 3\%$ of the manufacturer's declared values.

NOTE The concentration of water-soluble aluminium in commercial products varies. Typical values of aluminium content in products can be between 42 g/kg and 124 g/kg.

The commercial products vary in the proportions of chloride and sulfate ions.

The relative basicity of these products expressed as the mole ratio OH/3Al shall be less than or equal to 0,35.

4.3 Impurities and main by-products

Impurities derived from the manufacturing or extraction process include insoluble matter, trace metals and organic compounds.

Note If iron is present, it will usually be removed in the treatment process.

4.4 Chemical parameters

The products shall conform to the requirements specified in Table 1.

Table 1 — Chemical parameters

Parameter		Limit mg/kg of Al		
		type 1	type 2	type 3
Arsenic (As)	max.	14	40	100
Cadmium (Cd)	max.	3	50	100
Chromium (Cr)	max.	30	700	1 000
Mercury (Hg)	max.	4	10	20
Nickel (Ni)	max.	20	700	1 000
Lead (Pb)	max.	40	200	800
Antimony (Sb)	max.	20	40	120
Selenium (Se)	max.	20	40	120

NOTE Cyanide (CN⁻) is usually not relevant because of the acidity of the product. Pesticides and polycyclic aromatic hydrocarbons are not relevant since the raw materials used in the manufacturing process are free of them. For maximum impact of these products on trace metal content in drinking water see A.2

5 Test methods

5.1 Sampling

5.1.1 General

Observe the general recommendations of ISO 3165 and take into account ISO 6206.

5.1.2 Solid

Prepare the laboratory sample(s) required by the relevant procedure described in ISO 8213.

5.1.3 Liquid

5.1.3.1 Sampling from drums and bottles

5.1.3.1.1 General

5.1.3.1.1.1 Mix the contents of each container to be sampled by shaking the container, by rolling it or by rocking it from side to side, taking care not to damage the container or spill any of the liquid.

5.1.3.1.1.2 If the design of the container is such (for example, a narrow-necked bottle) that it is impracticable to use a sampling implement, take a sample by pouring after the contents have been thoroughly mixed. Otherwise, proceed as described in 5.1.3.1.1.3.

5.1.3.1.1.3 Examine the surface of the liquid. If there are signs of surface contamination, take samples from the surface as described in 5.1.3.1.2; otherwise, take samples as described in 5.1.3.1.3.

5.1.3.1.2 Surface sampling

Take a sample using a suitable ladle. Lower the ladle into the liquid until the rim is just below the surface, so that the surface layer runs into it. Withdraw the ladle just before it fills completely and allow any liquid adhering to the ladle to drain off. If necessary, repeat this operation so that, when the other selected containers have been sampled in a similar manner, the total volume of sample required for subsequent analysis is obtained.

5.1.3.1.3 Bottom sampling

Take a sample using an open sampling tube, or a bottom-valve sampling tube, suited to the size of container and the viscosity of the liquid.

When using an open sampling tube, close it at the top and then lower the bottom end to the bottom of the container. Open the tube and move it rapidly so that the bottom of the tube traverses the bottom of the container before the tube is filled. Close the tube, withdraw it from the container and allow any liquid adhering to the outside of the tube to drain off.

When using a bottom-valve sampling tube, close the valve before lowering the tube into the container and then proceed in a similar manner to that when using an open sampling tube.

5.1.3.2 Sampling from tanks and tankers

From each access point, take samples as follows:

- a) from the surface of the liquid, using a ladle as described in 5.1.3.1.2;
- b) from the bottom of the tank or tanker, using a sampling tube as described in 5.1.3.1.3 or using specially designed bottom-sampling apparatus;
- c) from one or more positions, depending on the overall depth, between the bottom and the surface using a weighted sampling can.

5.2 Analyses

Use the relevant methods for analysis described in EN 1302.

6 Labelling - Transportation - Storage

6.1 Means of delivery

Solids (aluminium chloride): the product shall be delivered in suitable packages, paper or plastics bags, or by rubber or plastics-lined bulk truck (20 t to 35 t depending on transport regulations if applicable).

Bulk liquids: the product shall be delivered in tankers of corrosion-resistant materials suitable for the purpose.

NOTE The manufacturer can provide advice on suitable materials.

In order that the purity of the product is not affected, the means of delivery shall not have been used previously for any different product or it shall have been specially cleaned and prepared before use.

6.2 Risk and safety labelling in accordance with the EU-Directives⁴⁾

One of the two following labelling requirements shall apply to aluminium chloride (monomeric), aluminium chloride hydroxide (monomeric) and aluminium chloride hydroxide (monomeric) depending on the relative basicity, composition and concentration at the date of the publication of this document.

a) solid forms:

- symbols and indications of danger:
 - Xi: irritant;
- nature of special risks attributed to dangerous substances:
 - R 36/38: irritating to eyes and skin;
- safety advice concerning dangerous substances:
 - S 26: in case of contact with eyes, rinse immediately with plenty of water and seek medical advice;
 - S 28: after contact with skin, wash immediately with plenty of water;

b) solutions:

- symbols and indications of danger:
 - C: corrosive;
- nature of special risks attributed to dangerous substances:
 - R 34: causes burns;
- safety advice concerning dangerous substances:
 - S 26: in case of contact with eyes, rinse immediately with plenty of water and seek medical advice;
 - S 27: take off immediately all contaminated clothing;
 - S 37/39: wear suitable gloves and eye/face protection.

NOTE Annex I of the Directive 67/548/EEC on Classification, packaging and labelling of dangerous substances and its amendments and adaptations in the European Union contains a list of substances classified by the EU. Substances not in this annex I should be classified on the basis of their intrinsic properties according to the criteria in the Directive by the person responsible for the marketing of the substance.

4) See [2].

6.3 Transportation regulations and labelling

Depending on the composition, the commercial product can be subject to transportation regulations and, if so, these products are listed as UN⁵⁾ number 1760 (corrosive liquid not otherwise specified)

- RID⁶⁾: class 8, classification code C9;packing group I;
- ADR⁷⁾: class 8, classification code C9;packing group I;
- IMDG⁸⁾: class 8;
- IATA⁹⁾: class 8.

UN number 2581 or UN number 3264 (corrosive acidic inorganic liquid):

- RID⁶⁾: class 8, classification code C1;packing group III;
- ADR⁷⁾: class 8, classification code C1;packing group III;
- IMDG⁸⁾: class 8;
- IATA⁹⁾: class 8.

6.4 Marking

The marking shall include the following:

- the name:
 - 1) "aluminium chloride (monomeric)"; or
 - 2) "aluminium chloride hydroxide (monomeric)"; or
 - 3) "aluminium chloride hydroxide sulfate (monomeric)"
- the trade name, grade and type;
- the net mass;
- the name and the address of the supplier and/or manufacturer;
- the statement "This product conforms to EN 881".

5) United Nations Number.

6) Regulations concerning International carriage of Dangerous goods by rail.

7) European Agreement concerning the international carriage of Dangerous goods by Road.

8) International Maritime transport of Dangerous Goods.

9) International Air Transport Association.

6.5 Storage

6.5.1 General

Storage tanks shall be of corrosion- resistant material suitable for the purpose

NOTE 1 The manufacturer can provide advice on suitable materials.

NOTE 2 Storage tanks located outside can require protection against extreme temperature, depending on freezing point and maximum storage temperature: refer to manufacturer's information on permissible temperatures.

6.5.2 Long term stability

Aluminium chloride, aluminium chloride hydroxide and aluminium chloride hydroxide sulfate (monomeric) are usually stable.

6.5.3 Storage incompatibilities

Avoid contact with chlorites, hypochlorites and sulfites.

The products react aggressively with some metal surfaces (e.g. galvanized metal, aluminium, copper, zinc and alloys of these metals).

These products are incompatible with iron salts and aluminium sulfate.

Annex A (informative)

General information on aluminium chloride (monomeric), aluminium chloride hydroxide (monomeric) and aluminium chloride hydroxide sulfate (monomeric)

A.1 Origin

A.1.1 Raw materials

Depending on product and manufacturer, the aluminium chloride, the aluminium chloride hydroxide and the aluminium chloride hydroxide sulfate (monomeric) are manufactured from:

- aluminium hydroxide;
- aluminium chloride;
- aluminium metal;
- bauxite or clay;
- hydrochloric acid;
- sulfuric acid.


A.1.2 Manufacturing process

Aluminium chloride, aluminium chloride hydroxide and aluminium chloride hydroxide sulfate (monomeric) are the results of a complex manufacturing process from producers and should not be, in any case, the result of a mixture of available commercial products (see 3.1.4).

A typical manufacturing process is the digestion of e.g. aluminium hydroxide in suitable acid(s) with or without addition of aluminium chloride, in a substoichiometric amount of acidic material.

A.2 Quality of commercial product

The three types of product specified in Table 1 reflect the quality of commercially available products. Figures A.1 to A.3 show the maximum concentrations of trace metals that would be added to the raw water by the addition of products corresponding to the purity levels specified in Table 1. It can be seen that the concentrations of metal added are well below the Parametric Values given in the EU Directive 98/83/EC (see [1]) at typical product doses. Furthermore, the figures overstate the concentrations of metals that would be present in the treated water since a substantial proportion of the trace metals will be incorporated in the sludge. Users of this product should select an appropriate type to enable them to achieve treated water quality targets taking into account raw water characteristics, required dosage, process plant conditions and other relevant factors.




A	B
As	10
Cd	5
Cr	50
Hg	1
Ni	20
Pb	10
Sb	5
Se	10

Key

- 1 Maximum addition to water µg/l metal
- 2 Product dosage mg/l Al - Typical dose
- A Element
- B Drinking water limit µg/l

Figure A.1 — Maximum impact of aluminium salts, type 1, on trace metal content of water




A	B
As	10
Cd	5
Cr	50
Hg	1
Ni	20
Pb	10
Sb	5
Se	10

Key

- 1 Maximum addition to water µg/l metal
- 2 Product dosage mg/l Al - Typical dose
- A Element
- B Drinking water limit µg/l

Figure A.2 — Maximum impact of aluminium salts, type 2, on trace metal content of water



A	B
As	10
Cd	5
Cr	50
Hg	1
Ni	20
Pb	10
Sb	5
Se	10

Key

- 1 Maximum addition to water µg/l metal
- 2 Product dosage mg/l Al - Typical dose
- A Element
- B Drinking water limit µg/l

Figure A.3 — Maximum impact of aluminium salts, type 3, on trace metal content of water

A.3 Use

A.3.1 Function

The products are used as coagulants, and sometimes simultaneously as precipitants.

A.3.2 Form in which the products are used

The products are used either as delivered or prediluted according to the manufacturer's recommendations.

A.3.3 Treatment dose

The treatment dose is generally in the range of 1 mg/l to 5 mg/l, expressed as Al, depending on raw water quality.

A.3.4 Means of application

The solutions are usually applied using a positive displacement metering pump. Sufficient turbulence should be provided at the point of addition to promote rapid dispersion. Injection of dosed products by means of carrier water can be advantageous.

A.3.5 Secondary effects

- reduction of pH value and alkalinity;
- increase of respective anion concentration.

A.3.6 Removal of excess product

The water purification process should be operated under conditions (e.g. pH) in which aluminium ions in the system are precipitated and reduced below the maximum allowable concentration.

Annex B (normative)

General rules relating to safety

B.1 Rules for safe handling and use

The supplier shall provide current safety instructions.

B.2 Emergency procedures

B.2.1 Accident

In case of contact with skin, take off immediately all contaminated clothing; wash immediately with plenty of water.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of ingestion, do not vomit. Seek medical advice immediately.

B.2.2 Spillage

Refer to 6.3.5 for incompatibilities.

Put on protective clothing. Collect and dispose of solid spillage carefully.

Dilute small liquid spillages with plenty of water and flush to sewer.

Neutralize and dispose of large spillages of liquids.

NOTE 1 Local regulations might apply to the disposal of these products.

NOTE 2 Suitable neutralizing chemicals are diluted sodium hydroxide or sodium carbonate.

B.2.3 Fire

The products are non-flammable liquids. Any extinguishing media can be used. The products can liberate hydrogen chloride (or sulfur oxides) when boiled to dryness or heated above 200 °C.

Bibliography

- [1] 98/83/EC: Council Directive of 3 November 1998 on the Quality of Water intended for Human Consumption.
- [2] 67/548/EEC: Council Directive of 27th June 1967 on the approximation of the laws, regulations and administrative provisions relating to the classification, packaging and labelling of dangerous substances and its amendments and adaptations.

BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover.
Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001.
Fax: +44 (0)20 8996 7001. Email: orders@bsi-global.com. Standards are also available from the BSI website at <http://www.bsi-global.com>.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre.
Tel: +44 (0)20 8996 7111. Fax: +44 (0)20 8996 7048. Email: info@bsi-global.com.

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration.
Tel: +44 (0)20 8996 7002. Fax: +44 (0)20 8996 7001.
Email: membership@bsi-global.com.

Information regarding online access to British Standards via British Standards Online can be found at <http://www.bsi-global.com/bsonline>.

Further information about BSI is available on the BSI website at <http://www.bsi-global.com>.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright & Licensing Manager.
Tel: +44 (0)20 8996 7070. Fax: +44 (0)20 8996 7553.
Email: copyright@bsi-global.com.