Door leaves — Determination of the resistance to hard body impact

The European Standard EN 950:1999 has the status of a British Standard

ICS 91.060.50



National foreword

This British Standard is the English language version of EN 950:1999.

The UK participation in its preparation was entrusted by Technical Committee B/538, Doors, windows, shutters, hardware and curtain walling, to Subcommittee B/538/2, Doors, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this subcommittee can be obtained on request to its secretary.

This British Standard forms part of a package of standards on doors which will not become fully effective until all standards in the package have been published and any superseded standards have been withdrawn. The date of withdrawal for national standards will be agreed within CEN and will be notified.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the BSI Standards Catalogue under the section entitled "International Standards Correspondence Index", or by using the "Find" facility of the BSI Standards Electronic Catalogue.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the EN title page, pages 2 to 4, an inside back cover and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

This British Standard, having been prepared under the direction of the Sector Committee for Building and Civil Engineering, was published under the authority of the Standards Committee and comes into effect on 15 December 1999

© BSI 12-1999

Amendments issued since publication

Amd. No.	Date	Comments

ISBN 0 580 35905 0

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 950

August 1999

ICS 91.060.50 Supersedes EN 85:1980

English version

Door leaves — Determination of the resistance to hard body impact

Vantaux de portes — Détermination de la résistance au choc de corps dur

Türblätter — Ermittlung der Widerstandsfähigkeit gegen harten Stoß

This European Standard was approved by CEN on 21 July 1999.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

CEN

European Committee for Standardization Comité Européen de Normalisation Europäisches Komitee für Normung

Central Secretariat: rue de Stassart 36, B-1050 Brussels

Page 2 EN 950:1999

Foreword

This European Standard has been prepared by Technical Committee CEN/TC 33, Doors, windows, shutters and building hardware, the Secretariat of which is held by AFNOR.

This European Standard supersedes EN 85:1980.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by February 2000, and conflicting national standards shall be withdrawn at the latest by February 2000.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

This standard is one of a series of standards for doors.

This standard has been prepared taking into account ISO 8271 and EN 85.

1 Scope

This standard applies to all door leaves.

The standard specifies the method to be used to determine the damage caused to a door leaf by the impact of a hard body.

NOTE Such impacts, that might reasonably be expected from contact with small objects or parts of larger objects such as corners on furniture or footwear, can produce local surface failures affecting both strength and appearance. The kind of damage caused by impact can vary with the material used in the door construction.

2 Apparatus

2.1 Supports

Rigid supports, to support the longer edges of the door leaf in a stable manner, when mounted horizontally.

2.2 Impact Equipment

 $A~(50\pm1)~mm~diameter~steel~ball,~of~known~weight,~and~appropriate~release~tower.$

2.3 Measuring equipment

A dial or digital gauge, accurate to 0,01 mm mounted at the centre of a 50 mm long and 12 mm wide reference bar.

A steel ruler, accurate to 0,5 mm.

3 Test specimens

Test specimens shall be stored and tested in a non-destructive environment within the ranges of 15 $^{\circ}{\rm C}$ to 30 $^{\circ}{\rm C}$ and 25 % to 75 % relative humidity.

4 Procedure

Mount the door leaf horizontally, with rigid supports under the long edges resting on a solid base.

Select one of the four aiming patterns shown in Figure 1 such that the theoretically weakest point is included, and mark the 15 impact points on the surface of the door leaf. Any glazed area shall be omitted from the test, thereby reducing the number of impact points.

Impact points in the topmost row or rows of the aiming pattern shall also be omitted where the height of the door leaf is less than 2 000 mm. The test area is not extended where the height is more than 2 000 mm.

NOTE 1 To facilitate the setting out of the aiming pattern, templates can be made for standard sized door leaves in accordance with Figure 1. Holes of approximately 8 mm diameter are drilled in the centres of the numbered rectangles so that a marker pen can be used to indicate the selected aiming pattern onto the face of the door leaf.

Position the release tower vertically over each of the impact points in turn, and drop the steel ball from a height, measured from its underside to the surface of the door leaf, which corresponds to the required impact energy.

Where a permanent imprint is left by any impact, after 30 min measure the maximum depth of the indentation to the nearest 0,1 mm, the maximum diameter of the indentation to the nearest 1,0 mm and the maximum diameter of the cracking area to the nearest 1,0 mm.

NOTE 2 Where impacts occur at points where the surface is uneven, e.g. at mouldings, a more general assessment of damage is permitted.

Repeat the procedure for the other face of the door leaf only if the door construction is not symmetrical.

5 Expression of results


Record:

- the measurement of indentation depth and diameter, and the diameter of cracking at each impact point;
- calculation of the mean values and the coefficient of variation of the depths of indentations;
- calculation of the mean values and the coefficient of variation of the diameters of cracks.

6 Test report

The test report shall contain the following information:

- a) reference to this standard;
- b) all necessary details to identify the door leaf;
- c) all relevant details concerning the type, specified dimensions, materials, form and construction of the door leaf;
- d) position and size of any glazed areas omitted from the test;
- e) laboratory storage and testing conditions;
- f) the number and position of impact points used;
- g) the impact energy in joules applied in the test;
- h) the results expressed as in clause 5;
- i) the nature of any damage;
- j) name of testing laboratory.
- k) date of test.



- 1 Width of door: 10 columns
- 2 Total of 15 rows
- 3 Bottom of door
- 4 Main area 10 Equal divisions
- 5 Base area 150 mm: 5 Equal divisions
- 6 2 000 mm

Figure 1 — Four different aiming patterns for hard body impact test, marked 1, 2, 3 or 4 respectively

BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: 020 8996 9000. Fax: 020 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: 020 8996 9001. Fax: 020 8996 7001.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre. Tel: 020 8996 7111. Fax: 020 8996 7048.

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration. Tel: 020 8996 7002. Fax: 020 8996 7001.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

If permission is granted, the terms may include royalty payments or a licensing agreement. Details and advice can be obtained from the Copyright Manager. Tel: 020 8996 7070.

BSI 389 Chiswick High Road London W4 4AL