BS EN 1367-7:2014



BSI Standards Publication

Tests for thermal and weathering properties of aggregates

Part 7: Determination of resistance to freezing and thawing of Lightweight aggregates



BS EN 1367-7:2014 BRITISH STANDARD

National foreword

This British Standard is the UK implementation of EN 1367-7:2014.

The UK participation in its preparation was entrusted to Technical Committee B/502/6, Test methods.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014. Published by BSI Standards Limited 2014

ISBN 978 0 580 80003 0

ICS 91.100.15

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 April 2014.

Amendments issued since publication

Date Text affected

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 1367-7

April 2014

ICS 91.100.15

English Version

Tests for thermal and weathering properties of aggregates - Part 7: Determination of resistance to freezing and thawing of Lightweight aggregates

Essais pour déterminer les propriétés thermiques et l'altérabilité des granulats - Partie 7: Détermination de la résistance au gel-dégel des granulats légers

Prüfverfahren für thermische Eigenschaften und Verwitterungsbeständigkeit von Gesteinskörnungen - Teil 7: Bestimmung des Widerstandes von leichten Gesteinskörnungen gegen Frost-Tau-Wechsel

This European Standard was approved by CEN on 16 February 2014.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents Page Foreword 3 Scope 4 Normative references4 2 Terms and definitions4 3 4 Principle......4 Apparatus and materials.....5 5 6 Sampling......5 7 Test specimens5 7.1 Size of test specimens5 7.2 Preparation of test specimens6 7.3 Procedure _____6 8 8.1 Soaking 6 8.2 Freezing in air and thawing in water......6 Calculation and expression of results......6 9 Test report7 10 10.1 Mandatory data7 10.2 Bibliography8

Foreword

This document (EN 1367-7:2014) has been prepared by Technical Committee CEN/TC 154 "Aggregates", the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2014, and conflicting national standards shall be withdrawn at the latest by October 2014.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

EN 1367 "Tests for thermal and weathering properties of aggregates" consists of the following parts:

- Part 1: Determination of resistance to freezing and thawing
- Part 2: Magnesium sulfate test
- Part 3: Boiling test for "Sonnenbrand Basalt"
- Part 4: Determination of drying shrinkage
- Part 5: Determination of resistance to thermal shock
- Part 6: Determination of resistance to freezing and thawing in the presence of salt (NaCl)
- Part 7: Determination of resistance to freezing and thawing of Lightweight Aggregates (the present document)
- Part 8: Determination of resistance to disintegration of Lightweight Aggregates

Test methods for other properties of aggregates are covered by parts of the following European Standards:

- EN 932, Tests for general properties of aggregates
- EN 933, Tests for geometrical properties of aggregates
- EN 1097, Tests for mechanical and physical properties of aggregates
- EN 1744, Tests for chemical properties of aggregates
- EN 13179, Tests for filler aggregate used in bituminous mixtures

NOTE This document supersedes the test methods described in EN 13055–1:2002, Annex C and EN 13055-2:2004, Annex B.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1 Scope

This European Standard specifies the reference test method used for type testing, and in case of dispute, for determining the resistance to freezing and thawing of lightweight aggregates (LWA) in accordance with EN 13055. For other purposes, in particular for factory production control, other methods may be used provided that an appropriate working relationship with the reference method has been established. The test is applicable to LWA with particle size not less than 4 mm and up to a maximum size of 32 mm.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 932-1, Tests for general properties of aggregates - Part 1: Methods for sampling

EN 932-2, Tests for general properties of aggregates - Part 2: Methods for reducing laboratory samples

EN 932-5, Tests for general properties of aggregates - Part 5: Common equipment and calibration

EN 933-2, Tests for geometrical properties of aggregates - Part 2: Determination of particle size distribution - Test sieves, nominal size of apertures

EN 13055-1, Lightweight aggregates - Part 1: Lightweight aggregates for concrete, mortar and grout

EN 13055-2, Lightweight aggregates - Part 2: Lightweight aggregates for bituminous mixtures and surface treatments and for unbound and bound applications

3 Terms and definitions

For the purpose of this document, the terms and definitions given in EN 13055-1, EN 13055-2 and the following apply.

3.1

test specimen

sample used as in single determination when a test method requires more than one determination of a property

3.2

constant mass

mass determined by successive weighings performed 1 h apart and not differing by more than 0,1 %

Note 1 to entry: In many cases constant mass can be achieved after a test portion has been dried for a predetermined period in a specified oven at (110 ± 5) °C. Test laboratories can determine the time required to achieve constant mass for specific types and sizes of sample dependent upon the drying capacity of the oven used.

4 Principle

Three test specimens of lightweight aggregates, having been soaked in water at atmospheric pressure, are subjected to 20 freeze—thaw cycles. This involves cooling down to -17,5 °C in air and then thawing in a water bath at about 20 °C. After completion of the freeze—thaw cycles, the loss of mass of the lightweight aggregates is recorded.

5 Apparatus and materials

- **5.1** All apparatus, unless otherwise stated, shall conform to the general requirements of EN 932-5.
- **5.2** Ventilated drying oven, with forced circulation of adequate capacity. The oven shall be capable of being maintained at (110 ± 5) °C.
- **5.3** Balance, capable of weighing test specimens up to $400 \, \mathrm{g}$ with an accuracy of $\pm \, 0.04 \, \mathrm{g}$ and test specimens above $400 \, \mathrm{g}$ with an accuracy of $0.1 \, \mathrm{g}$.
- **5.4** Low temperature cabinet, (upright or chest) with air circulation. The cabinet shall be capable of being maintained at (-17.5 ± 2.5) °C.
- **5.5** Test sieves, conforming to EN 933-2 shall be used.
- **5.6** Water, distilled or deionised.
- **5.7** Container, made from corrosion resistant material with a base area of approximate 0,02 m² and a height not less than 0,1 m.
- **5.8** Grid, of a suitable size and aperture to prevent the lightweight aggregates floating out of the container and to prevent any loss of whole aggregates.
- **5.9** Water bath, thermostatically controlled to maintain a temperature of (20 ± 3) °C.

6 Sampling

Sampling and sample reduction shall be carried out in accordance with EN 932-1 and EN 932-2.

7 Test specimens

7.1 General

Three individual test specimens shall be used. The test specimens shall be obtained in accordance with EN 932-2 by sample reduction. Particles of oversize (>D) and undersize (<d) shall be removed.

7.2 Size of test specimens

The quantities for each of the three individual test specimens shall be chosen according to the upper size of the aggregates as shown in Table 1. Deviations of \pm 5 % in the volume of test specimens are permissible.

Table 1 — Test specimen volumes required

Approximate volume

Maximum aggregate size (mm)	Approximate volume of the test specimen
8	0,5
16	1,0
32	1,5

7.3 Preparation of test specimens

Wash the test specimens on the lower (d) test sieve. Dry the test specimens to constant mass. Allow to cool to ambient temperature and weigh immediately (M_1 , see Clause 9).

Weighing shall be carried out to the following accuracies:

- Test specimens up to 400 g: to ± 0,04 g.
- Test specimens above 400 g: to ± 0,1 g.

8 Procedure

8.1 Soaking

Store the test specimens at atmospheric pressure for (240 ± 15) min in the containers specified in 5.7 at (20 ± 3) °C in distilled or deionised water, ensuring that the water covers the test specimens by at least 10 mm. In order to prevent the test specimens floating, the specimens are kept submerged by a grid as specified in 5.8.

8.2 Freezing in air and thawing in water

Remove the test specimens from the containers and allow them to drain on a sieve with a maximum size of 2 mm for about 1 min. Then place them back into the containers spreading them out evenly.

Place the containers in the low temperature cabinet, ensuring that the heat is extracted as uniformly as possible from all sides of all test specimens. The distance between each container, and between the containers and the sidewalls of the cabinet, shall not be less than 50 mm. After placing the containers in the cabinet, hold the air temperature in the cabinet at (-17.5 ± 2.5) °C.

The containers with the test specimens shall remain in the cabinet for minimum of 240 min.

After completion of the freezing cycle, remove the containers from the cabinet, add water to the containers with the test specimens and store for at least 60 min in a water bath at a temperature of (20 ± 3) °C. In order to prevent the test specimens floating, the specimens are kept submerged by a grid as specified in 5.8.

Pour off the water from the containers carefully and allow the test specimens to drain for about 1 min. Then start the next freezing cycle. In total 20 freeze—thaw cycles shall be performed.

If it is necessary to interrupt the test, the test specimens should remain in the cabinet at (−17,5 ± 2,5) °C.

On completion of the 20th freezing and thawing cycle, pour the contents of each container into a sieve having an aperture size that is half the lower size sieve used to prepare the test specimen (e.g. in case of the 8 mm to 16 mm fraction, pour into a test sieve of 4 mm aperture size). Wash and sieve the test specimen on the specified sieve by hand. Dry the residue remaining on the sieve at (110 ± 5) °C to constant mass, cool at ambient temperature and weigh immediately (M_2 , see Clause 9).

9 Calculation and expression of results

Calculate the loss in mass (FL_i) of each test specimen in accordance with the following formula:

$$FL_1 = [(M_1 - M_2)/M_1] \times 100$$

where

- FLi is the percentage loss in mass of the test specimen;
- M_1 is the initial dry mass of the test specimen before freeze–thaw cycling, in grams;
- M_2 is the final dry mass of the test specimen after freeze–thaw cycling, that is retained on the specified sieve, in grams. Express FL_i to the nearest 0,01 %.

Calculate FL as the mean of the three individual test results to the nearest 0,1 %.

10 Test report

10.1 Mandatory data

The test report shall include the following information:

- · reference to this European Standard;
- identification of the test sample, including identification of the source, aggregate size and date of sampling;
- · sample reception date if different from sampling date;
- · identification of the laboratory;
- percentage of mass loss after freezing and thawing FL, expressed to the nearest 0,1 %;
- deviations from the reference method, if any.

10.2 Optional data

The test report can include the following information:

- · date of test;
- · reference to the chosen sampling procedure;
- reference to the chosen sample reduction procedure;
- percentage of the mass loss after freezing and thawing of the individual test specimens *FL*_i, expressed to the nearest 0,01 %.

Bibliography

[1] EN 1097-5, Tests for mechanical and physical properties of aggregates - Part 5: Determination of the water content by drying in a ventilated oven



British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards -based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com
Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070 Email: copyright@bsigroup.com

