

**Aerospace series  
— Nuts, hexagonal,  
plain, normal height,  
normal across flats, in  
steel, cadmium plated,  
left hand thread —  
Classification: 1 100  
MPa (at ambient  
temperature) / 235 °C**

ICS 49.030.30

## National foreword

This British Standard is the UK implementation of EN 3227:2010.

The UK participation in its preparation was entrusted to Technical Committee ACE/12, Aerospace fasteners and fastening systems.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 March 2010

© BSI 2010

ISBN 978 0 580 70737 7

### Amendments/corrigenda issued since publication

Date	Comments

EUROPEAN STANDARD

**EN 3227**

NORME EUROPÉENNE

EUROPÄISCHE NORM

February 2010

ICS 49.030.30

English Version

**Aerospace series - Nuts, hexagonal, plain, normal height,  
normal across flats, in steel, cadmium plated, left hand thread -  
Classification: 1 100 MPa (at ambient temperature) / 235 °C**

Série aérospatiale - Écrous hexagonaux ordinaires, hauteur normale, surplats normaux, en acier, cadmiés, filetage à gauche - Classification : 1 100 MPa (à température ambiante) / 235 °C

Luft- und Raumfahrt - Sechskantmuttern mit normaler Schlüsselweite, aus Stahl, verkadmet, Linksgewinde - Klasse: 1 100 MPa (bei Raumtemperatur) / 235 °C

This European Standard was approved by CEN on 11 December 2009.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**Management Centre: Avenue Marnix 17, B-1000 Brussels**

## Contents

Page

Foreword.....	3
1 <b>Scope</b> .....	4
2 <b>Normative references</b> .....	4
3 <b>Required characteristics</b> .....	5
4 <b>Designation</b> .....	7
5 <b>Marking</b> .....	8
6 <b>Technical specification</b> .....	8

.....

## Foreword

This document (EN 3227:2010) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by August 2010, and conflicting national standards shall be withdrawn at the latest by August 2010.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

## 1 Scope

This standard specifies the characteristics of plain, hexagonal nuts, normal height, normal across flats, with left hand thread, in steel, cadmium plated.

Classification : 1 100 MPa <sup>1)</sup> / 235 °C <sup>2)</sup>.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 2133, *Aerospace series — Cadmium plating of steels with specified tensile strength  $\leq 1\,450$  MPa, copper, copper alloys and nickel alloys*

EN 2205, *Aerospace series — Steel FE-PL1502 (25CrMo4) —  $900\text{ MPa} \leq R_m \leq 1\,100\text{ MPa}$  — Bars —  $D_e \leq 40\text{ mm}$*

EN 2424, *Aerospace series — Marking of aerospace products*

EN 2438, *Aerospace series — Steel FE-PL2102 (35NiCr6) —  $900\text{ MPa} \leq R_m \leq 1\,100\text{ MPa}$  — Bars —  $D_e \leq 40\text{ mm}$*

EN 2448, *Aerospace series — Steel FE-PL1503 (35CrMo4) —  $900\text{ MPa} \leq R_m \leq 1\,100\text{ MPa}$  — Bars —  $D_e \leq 40\text{ mm}$*

EN 3513, *Aerospace series — Steel FE-PL711 — Hardened and tempered —  $900\text{ MPa} \leq R_m \leq 1\,100\text{ MPa}$  — Bar and wire —  $D_e \leq 45\text{ mm}$  <sup>3)</sup>*

EN 9100, *Quality Management Systems — Requirements for Aviation, Space and Defense Organizations*

ISO 5855-2, *Aerospace — MJ threads — Part 2: Limit dimensions for bolts and nuts*

ISO 8279, *Aerospace — Nuts, hexagonal, plain, normal height, normal across flats, with MJ threads, classifications: 600 MPa (at ambient temperature)/120 °C, 600 MPa (at ambient temperature)/235 °C, 900 MPa (at ambient temperature)/425 °C, 1 100 MPa (at ambient temperature)/235 °C, 1 100 MPa (at ambient temperature)/315 °C, 1 100 MPa (at ambient temperature)/650 °C, 1 210 MPa (at ambient temperature)/730 °C, 1 250 MPa (at ambient temperature)/235 °C and 1 550 MPa (at ambient temperature)/600 °C — Dimensions*

ISO 8788, *Aerospace — Nuts, metric — Tolerances of form and position*

ISO 9139, *Aerospace — Nuts, plain or slotted (castellated) — Procurement specification*

TR 3823, *Aerospace series — Materials for plain and slotted hexagonal nuts* <sup>4)</sup>

---

1) Corresponds to strength class of the associated bolt, the 100 % load of which it is able to withstand, when tested at ambient temperature, without breaking or cracking.

2) Maximum temperature that the nut is able to withstand, without permanent alteration to its original characteristics, after ambient temperature has been restored. The maximum temperature is conditioned by the surface treatment.

3) Published as ASD-STAN Prestandard at the date of publication of this standard.

4) Published as ASD-STAN Technical Report at the date of publication of this standard.

### **3 Required characteristics**

#### **3.1 Configuration — Dimensions — Masses**

See Figure 1 and Table 1.


Dimensions and tolerances are in conformity with ISO 8279, expressed in millimetres and apply after surface treatment.

#### **3.2 Materials**

EN 2205, EN 2438, EN 3513, EN 2448 or TR 3823.

#### **3.3 Surface treatment**


EN 2133, 5 µm minimum on threads and all surfaces which can be contacted by a 20 mm diameter ball. On all other surfaces, a continuous cadmium plating shall be present.



These values in micrometres apply before surface treatment. The values do not apply to threads the surface texture of which will be achieved by usual manufacturing methods.

Break sharp edges 0,1 to 0,4.

Details of form not stated are at the manufacturer's option.



**Key**

- 1 Thread
  - 2 Two holes  $\varnothing U$  optional
  - 3 Marking
  - 4  $r = 0,2$  to  $0,5$
  - 5 The groove bottom shall not extend completely across the flats
  - 6 Marking for left hand thread
- a From either face
  - b Diameter  $M$  may be tangential to, but shall not intrude on the flats.
  - c Applicable to both faces
  - d All forms of entry (chamfer or radius) option within these limiting dimensions.

Tolerances of form and position shall be in conformity with ISO 8788.

**Figure 1**




Table 1

Diameter code	Left hand thread <sup>a</sup>	<i>E</i>		<i>F</i>		<i>H</i>		<i>L</i>		<i>M</i>		<i>N</i>		<i>U</i>	<i>V</i>	<i>W</i>	Mass kg/1 000 pieces approx.
		min.				h14		min.	max.	min.	H13	± 0,2	min.				
020	MJ2×0,4-4H6H-LH	4,2	4	h12	1,6	2,2	+0,6 0	3,4	0,4	0,2	b	b	b				0,15
025	MJ2,5×0,45-4H6H-LH	5,3	5		2	2,7		4,4									0,3
030	MJ3×0,5-4H6H-LH	6,5	6		2,4	3,2		5,4									0,5
040	MJ4×0,7-4H6H-LH	7,6	7		3,2	4,2		6,4									0,85
050	MJ5×0,8-4H6H-LH	8,7	8		4	5,2		7,4									1,3
060	MJ6×1-4H5H-LH	10,9	10	h13	4,8	6,3	+0,8 0	9,3	0,5	0,3	1	3,9	2				2,4
070	MJ7×1-4H5H-LH	12	11		5,6	7,3		10,2									3,2
080	MJ8×1-4H5H-LH	14,3	13		6,4	8,3		12,2									5,2
100	MJ10×1,25-4H5H-LH	18,9	17		8	10,3		16									11,5
120	MJ12×1,25-4H5H-LH	21,1	19		9,6	12,3		18									16,1
140	MJ14×1,5-4H5H-LH	24,5	22	11,2	14,4	21	25										
160	MJ16×1,5-4H5H-LH	26,8	24	12,8	16,4	23	33										
180	MJ18×1,5-4H5H-LH	30,2	27	14,4	18,4	26	46										
200	MJ20×1,5-4H5H-LH	33,6	30	16	20,4	29	62										
220	MJ22×1,5-4H5H-LH	35,8	32	17,6	22,4	30,9	75										
240	MJ24×2-4H5H-LH	40,4	36	19,2	24,5	34,9	108										

<sup>a</sup> In accordance with ISO 5855-2.  
<sup>b</sup> Lockwire holes not provided for these diameters.

## 4 Designation

EXAMPLE



NOTE If necessary the originator code I9005 shall be placed between the description block and the identity block.

Table 2

Option	Code
Lockwire holes	H
No hole	— (hyphen)

## 5 Marking

See Table 3.

Table 3

Diameter code	EN 2424 Style
020 to 030	F
040 to 070	N
080 to 160	C
180 to 240	A

## 6 Technical specification

ISO 9139, except for approval of manufacturers: see EN 9100.

.....

---

## BSI - British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

### Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

### Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001. Fax: +44 (0)20 8996 7001 Email: [orders@bsigroup.com](mailto:orders@bsigroup.com) You may also buy directly using a debit/credit card from the BSI Shop on the Website <http://www.bsigroup.com/shop>

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

### Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact Information Centre. Tel: +44 (0)20 8996 7111 Fax: +44 (0)20 8996 7048 Email: [info@bsigroup.com](mailto:info@bsigroup.com)

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration. Tel: +44 (0)20 8996 7002 Fax: +44 (0)20 8996 7001 Email: [membership@bsigroup.com](mailto:membership@bsigroup.com)

Information regarding online access to British Standards via British Standards Online can be found at <http://www.bsigroup.com/BSOL>

Further information about BSI is available on the BSI website at <http://www.bsigroup.com>.

### Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright and Licensing Manager. Tel: +44 (0)20 8996 7070 Email: [copyright@bsigroup.com](mailto:copyright@bsigroup.com)