



BSI Standards Publication

Flat products made of steels for pressure purposes

Part 7: Stainless steels

National foreword

This British Standard is the UK implementation of EN 10028-7:2016. It supersedes BS EN 10028-7:2007 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee ISE/107, Steels for Pressure Purposes.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2016.
Published by BSI Standards Limited 2016

ISBN 978 0 580 84032 6

ICS 77.140.20; 77.140.30; 77.140.50

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 July 2016.

Amendments/corrigenda issued since publication

| Date | Text affected |
|------|---------------|
|------|---------------|

**EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM**

EN 10028-7

July 2016

ICS 77.140.30; 77.140.50

Supersedes EN 10028-7:2007

English Version

**Flat products made of steels for pressure purposes - Part
7: Stainless steels**

Produits plats en aciers pour appareils à pression -
Partie 7: Aciers inoxydables

Flacherzeugnisse aus Druckbehälterstählen - Teil 7:
Nichtrostende Stähle

This European Standard was approved by CEN on 15 April 2016.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

| | Page |
|-----------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| European foreword | 4 |
| Introduction | 5 |
| 1 Scope..... | 6 |
| 2 Normative references..... | 6 |
| 3 Terms and definitions | 6 |
| 4 Tolerances on dimensions..... | 6 |
| 5 Calculation of mass..... | 7 |
| 6 Classification and designation | 7 |
| 7 Information to be supplied by the purchaser..... | 7 |
| 7.1 Mandatory information | 7 |
| 7.2 Options..... | 7 |
| 7.3 Example for ordering..... | 7 |
| 8 Requirements..... | 7 |
| 8.1 Steelmaking process | 7 |
| 8.2 Delivery condition | 7 |
| 8.3 Chemical composition and chemical corrosion properties..... | 7 |
| 8.4 Mechanical properties | 8 |
| 8.5 Surface condition | 8 |
| 8.6 Internal soundness..... | 8 |
| 8.7 Physical properties | 8 |
| 8.8 Weldability | 8 |
| 9 Inspection | 9 |
| 9.1 Types of inspection and inspection documents | 9 |
| 9.2 Tests to be carried out | 9 |
| 9.3 Re-tests, sorting and reprocessing | 9 |
| 10 Sampling..... | 9 |
| 10.1 Frequency of testing | 9 |
| 10.2 Selection and preparation of samples and test pieces | 9 |
| 11 Test methods | 9 |
| 12 Marking | 9 |
| Annex A (informative) Guidelines for further treatment (including heat treatment in fabrication) | 34 |
| Annex B (informative) Post weld heat treatment | 39 |
| Annex C (informative) Preliminary reference data for the tensile strength of austenitic-ferritic steels at elevated temperatures | 41 |
| Annex D (informative) Reference data of strength values for 1 % (plastic) creep strain and creep rupture | 42 |
| Annex E (informative) Reference data on mechanical properties of austenitic steels at room temperature and at low temperatures..... | 51 |

| | |
|----------------------------------------------------------------------------------------------------------------------------------------|-----------|
| Annex F (informative) Significant changes to the version EN 10028-7:2007 | 52 |
| Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of Directive 2014/68/EU | 53 |
| Bibliography | 54 |

European foreword

This document (EN 10028-7:2016) has been prepared by Technical Committee ECISS/TC 107 "Steels for pressure purposes", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by January 2017, and conflicting national standards shall be withdrawn at the latest by January 2017.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 10028-7:2007.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive, see informative Annex ZA, which is an integral part of this document.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

The European Committee for Standardisation (CEN) draws attention to the fact that it is claimed that compliance with this document may involve the use of patents concerning eight steel grades.

Outokumpu Oyj

FI-02200 Espoo, Finland

for steel grades 1.4420, 1.4622, 1.4162 (but also consider footnote c in Table 4) and 1.4662

Industeel

F-71200 Creusot,

56 Rue Clemenceau, France

for steel grade 1.4062

Acciai Speciali Terni S.p.A.

I-05100 Terni, Italy

for steel grades 1.4646, 1.4611 and 1.4613

1 Scope

This European Standard specifies requirements for flat products for pressure purposes made of stainless steels, including austenitic creep resisting steels, in thicknesses as indicated in Tables 7 to 10.

The requirements of EN 10028-1 also apply.

NOTE 1 The steel grades covered by this European Standard have been selected from EN 10088-1.

NOTE 2 Once this European Standard is published in the Official Journal of the European Union (OJEU) under Directive 2014/68/EU, presumption of conformity to the Essential Safety Requirements (ESRs) of Directive 2014/68/EU is limited to technical data of materials in this European Standard (Part 1 and Part 7) and does not presume adequacy of the material to a specific item of equipment. Consequently, the assessment of the technical data stated in this material standard against the design requirements of this specific item of equipment to verify that the ESRs of the Pressure Equipment Directive are satisfied, needs to be done.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 10028-1, *Flat products made of steels for pressure purposes — Part 1: General requirements*

EN 10088-1:2014, *Stainless steels — Part 1: List of stainless steels*

EN ISO 3651-2, *Determination of resistance to intergranular corrosion of stainless steels — Part 2: Ferritic, austenitic and ferritic-austenitic (duplex) stainless steels — Corrosion test in media containing sulfuric acid (ISO 3651-2)*

EN ISO 9444-2, *Continuously hot-rolled stainless steel — Tolerances on dimensions and form — Part 2: Wide strip and sheet/plate (ISO 9444-2)*

EN ISO 9445-2, *Continuously cold-rolled stainless steel — Tolerances on dimensions and form — Part 2: Wide strip and plate/sheet (ISO 9445-2)*

EN ISO 18286, *Hot-rolled stainless steel plates — Tolerances on dimensions and shape (ISO 18286)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 10028-1 and the following apply.

3.1

cryogenic temperature

temperature lower than -75 °C used in the liquefaction of gases

4 Tolerances on dimensions

Shall be according to the following standards:

- EN ISO 9445-2 for product form C;
- EN ISO 9444-2 for product form H;
- EN ISO 18286 for product form P.

5 Calculation of mass

For density values, shall be according to EN 10088-1:2014, Annex E.

6 Classification and designation

Shall be according to EN 10028-1.

7 Information to be supplied by the purchaser

7.1 Mandatory information

Shall be according to EN 10028-1.

7.2 Options

The relevant options of EN 10028-1 apply. If the purchaser does not indicate a wish to implement any of these options at the time of enquiry and order, the products shall be supplied in accordance with the basic specification (see EN 10028-1).

7.3 Example for ordering

10 plates made of a steel grade with the name X5CrNi18-10 and the number 1.4301 as specified in EN 10028-7 with nominal dimensions, thickness = 8 mm, width = 2 000 mm, length = 5 000 mm; tolerances on dimensions, shape and mass as specified in EN ISO 18286 with thickness tolerance class B and "normal" flatness tolerance according to process route 1D (see Table 6), inspection document 3.1 as specified in EN 10204:

10 plates- EN ISO 18286:—, 8x2000x5000 B-steel EN 10028-7-X5CrNi18-10+1D-inspection document 3.1

or

10 plates- EN ISO 18286:—, 8x2000x5000 B-steel EN 10028-7-1+1D-inspection document 3.1

8 Requirements

8.1 Steelmaking process

Shall be according to EN 10028-1.

8.2 Delivery condition

The products shall be supplied in the delivery condition specified in the order by reference to the process route given in Table 6 and, where alternatives exist, to the treatment conditions given in Tables 7 to 10. Guidelines for further treatment including heat treatment are given in Annex A.

8.3 Chemical composition and chemical corrosion properties

8.3.1 The chemical composition requirements given in Tables 1 to 4 shall apply in respect of the chemical composition according to the cast analysis.

8.3.2 The product analysis may deviate from the limiting values for the cast analysis given in Tables 1 to 4 by the values listed in Table 5.

8.3.3 The specifications in Tables 7, 9 and 10 shall apply in respect to resistance to intergranular corrosion as defined in EN ISO 3651-2, for ferritic, austenitic and austenitic-ferritic steels.

NOTE 1 EN ISO 3651-2 is not applicable for testing martensitic steels.

NOTE 2 The corrosion resistance of stainless steels is very dependent on the type of environment and can therefore not always be clearly ascertained through laboratory tests. It is therefore advisable to draw on the available experience of the use of the steels.

8.4 Mechanical properties

8.4.1 The tensile properties at room temperature and the impact energy at 20 °C and at low temperatures as specified in Tables 7 to 10 apply for the relevant specified heat treatment condition.

NOTE Austenitic stainless steels are insensitive to brittle fracture in the solution annealed condition. As they have a good resistance to shock loads, due to their high impact energy, also at very low (cryogenic) temperatures, they are useful for applications at such temperatures (see also the NOTE to Tables 9 and 10).

8.4.2 The values in Tables 11 to 14 apply for the 0,2 % and 1,0 % proof strength at elevated temperatures. Additionally, the values in Table 15 apply for the tensile strength at elevated temperatures for austenitic steels.

8.4.3 Tensile strength values at elevated temperatures for austenitic-ferritic steels are given for guidance in Annex C.

8.4.4 Annex D gives mean values as preliminary data for the purchaser about strength for 1 % (plastic) creep strain and creep rupture. These data apply for the solution annealed condition only (see Table A.3).

8.4.5 In Annex E preliminary data on mechanical properties at low temperatures of austenitic steels are listed.

8.5 Surface condition

Shall be according to EN 10028-1 and Table 6.

8.6 Internal soundness

Shall be according to EN 10028-1.

8.7 Physical properties

For reference data on physical properties, see EN 10088-1:2014, Annex E.

8.8 Weldability

8.8.1 General

The choice of the appropriate welding method and welding parameters is under the responsibility of the equipment manufacturer.

8.8.2 Post weld heat treatment

Guidelines for the purchaser on post weld heat treatment are given in Annex B.

9 Inspection

9.1 Types of inspection and inspection documents

Shall be according to EN 10028-1.

9.2 Tests to be carried out

Shall be according to Table 16 and EN 10028-1.

9.3 Re-tests, sorting and reprocessing

Shall be according to EN 10028-1.

10 Sampling

10.1 Frequency of testing

Shall be according to Table 16 and EN 10028-1.

10.2 Selection and preparation of samples and test pieces

Shall be according to EN 10028-1.

11 Test methods

Shall be according to EN 10028-1.

12 Marking

Shall be according to EN 10028-1.

Table 1 — Chemical composition (cast analysis)^a of ferritic steels

| Steel grade | Steel name | Steel number | % by mass | | | | | | | Ti | |
|---------------------|------------|--------------|-----------|---------|---------|--------|--------|--------|--------------|--------------|------------------------------------------|
| | | | C max. | Si max. | Mn max. | P max. | S max. | N max. | Cr | Mo | |
| X2CrNi12 | | 1.4003 | 0,030 | 1,00 | 1,50 | 0,040 | 0,015 | 0,030 | 10,5 to 12,5 | — | 0,30 to 1,00 |
| X2CrTiNb18 | | 1.4509 | 0,030 | 1,00 | 1,00 | 0,040 | 0,015 | — | 17,5 to 18,5 | — | 0,10 to 0,60 |
| X3CrTi17 | | 1.4510 | 0,050 | 1,00 | 1,00 | 0,040 | 0,015 | — | 16,0 to 18,0 | — | [$(4x(C+N)+0,15)$ to 0,80] ^b |
| X2CrMoTi17-1 | | 1.4513 | 0,025 | 1,00 | 1,00 | 0,040 | 0,015 | 0,020 | 16,0 to 18,0 | 0,80 to 1,40 | — |
| X6CrNiTi12 | | 1.4516 | 0,080 | 0,70 | 1,50 | 0,040 | 0,015 | — | 10,5 to 12,5 | — | 0,50 to 1,50 |
| X2CrTi17 | | 1.4520 | 0,025 | 0,50 | 0,50 | 0,040 | 0,015 | 0,015 | 16,0 to 18,0 | — | [$(4x(C+N)+0,15)$ to 0,60] ^b |
| X2CrMoTi18-2 | | 1.4521 | 0,025 | 1,00 | 1,00 | 0,040 | 0,015 | 0,030 | 17,0 to 20,0 | 1,80 to 2,50 | — |
| X6CrMoNb17-1 | | 1.4526 | 0,080 | 1,00 | 1,00 | 0,040 | 0,015 | 0,040 | 16,0 to 18,0 | 0,80 to 1,40 | [$7x(C+N)+0,10$] to 1,00 |
| X2CrTi21 c,d | | 1.4611 | 0,030 | 1,00 | 1,00 | 0,050 | 0,05 | — | 19,0 to 22,0 | ≤ 0,50 | ≤ 0,50 |
| X2CrTi24 c,d | | 1.4613 | 0,030 | 1,00 | 1,00 | 0,050 | 0,05 | — | 22,0 to 25,0 | ≤ 0,50 | ≤ 0,50 |
| X2CrCuNbTiV22-1 d,e | | 1.4622 | 0,030 | 1,00 | 0,80 | 0,040 | 0,015 | 0,030 | 20,0 to 24,0 | — | 0,10 to 0,70 |
| | | | | | | | | | | — | 0,10 to 0,70 |

^a Elements not listed in this table shall not be intentionally added to the steel without the agreement of the purchaser except for finishing of the cast. All appropriate precautions are to be taken to avoid the addition of such elements from scrap and other materials used in production which would impair mechanical properties and the suitability of the steel.

^b The stabilization may be made by use of titanium and/or niobium and/or zirconium. According to the atomic mass of these elements and the content of carbon and nitrogen, the equivalence shall be the following, in % by mass:

$$Nb \approx Zr \approx \frac{7}{4} Ti$$

^c Other elements: Cu < 0,5 % and Al < 0,05 %.

^d Patented steel.

^e Other elements: V: 0,03 to 0,50 %; Cu: 0,30 to 0,80 %; Ti + Nb: 8x(C+N) to 0,80 %.

Table 2 — Chemical composition (cast analysis)^a of martensitic steels

| Steel grade Steel name | Steel number | % by mass | | | | | | N min. | | |
|---------------------------|--------------|-----------|------------|------------|-----------|-----------|--------------|--------------|------------|-------|
| | | C max. | Si max. | Mn max. | P max. | S max. | Cr | | | |
| X3CrNiMo13-4 | 1.4313 | 0,05 | 0,70 | 1,50 | 0,040 | 0,015 | 12,0 to 14,0 | 0,30 to 0,70 | 3,5 to 4,5 | 0,020 |
| X4CrNiMo16-5-1 | 1.4418 | 0,06 | 0,70 | 1,50 | 0,040 | 0,015 | 15,0 to 17,0 | 0,80 to 1,50 | 4,0 to 6,0 | 0,020 |

^a Elements not quoted in this table shall not be intentionally added to the steel without the agreement of the purchaser except for finishing the cast. All appropriate precautions are to be taken to avoid the addition of such elements from scrap and other materials used in production which would impair mechanical properties and the suitability of the steel.

Table 3 — Chemical composition (cast analysis)^a of austenitic steels

| Steel grade | Steel name | Steel number | C | Si | Mn | P max. | S max. | N | Cr | Cu | Mo | Nb | Ni | Ti | Others |
|----------------------------------------------|------------|--------------|-------------|---------------|------------|--------|--------|--------------|--------------|--------------|----------------|----|----|--------------|---------------|
| Austenitic corrosion resisting grades | | | | | | | | | | | | | | | |
| % by mass | | | | | | | | | | | | | | | |
| X5CrNi18-10 | | 1.4301 | ≤ 0,07 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | ≤ 0,10 | 17,5 to 19,5 | — | — | — | — | 8,0 to 10,5 | — |
| X2CrNi19-11 | | 1.4306 | ≤ 0,03 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | ≤ 0,10 | 18,0 to 20,0 | — | — | — | — | 10,0 to 12,0 | — |
| X2CrNi18-9 | | 1.4307 | ≤ 0,03 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | ≤ 0,10 | 17,5 to 19,5 | — | — | — | — | 8,0 to 10,5 | — |
| X2CrNiN18-10 | | 1.4311 | ≤ 0,03 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | 0,12 to 0,22 | 17,5 to 19,5 | — | — | — | — | 8,5 to 11,5 | — |
| X5CrNiN19-9 | | 1.4315 | ≤ 0,06 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | 0,12 to 0,22 | 18,0 to 20,0 | — | — | — | — | 8,0 to 11,0 | — |
| X2CrNiN18-7 | | 1.4318 | ≤ 0,03 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | 0,10 to 0,20 | 16,5 to 18,5 | — | — | — | — | 6,0 to 8,0 | — |
| X1CrNi25-21 | | 1.4335 | ≤ 0,02 | ≤ 0,25 | ≤ 2,00 | 0,025 | 0,010 | ≤ 0,10 | 24,0 to 26,0 | — | ≤ 0,20 | — | — | 20,0 to 22,0 | — |
| X1CrNiSi18-15-4 | | 1.4361 | ≤ 0,01 5 | 3,7 to 4,5 | ≤ 2,00 | 0,025 | 0,010 | ≤ 0,10 | 16,5 to 18,5 | — | ≤ 0,20 | — | — | 14,0 to 16,0 | — |
| X2CrMnNiN17-7,5 | | 1.4371 | ≤ 0,03 | ≤ 1,00 | 6,0 to 8,0 | 0,045 | 0,015 | 0,15 to 0,20 | 16,0 to 17,0 | — | — | — | — | 3,5 to 5,5 | — |
| X12CrMnNi17-7,5 | | 1.4372 | ≤ 0,15 | ≤ 1,00 | 5,5 to 7,5 | 0,045 | 0,015 | 0,05 to 0,25 | 16,0 to 18,0 | — | — | — | — | 3,5 to 5,5 | — |
| X5CrNiMo17-12-2 | | 1.4401 | ≤ 0,07 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | ≤ 0,10 | 16,5 to 18,5 | — | 2,00 to 2,50 | — | — | 10,0 to 13,0 | — |
| X2CrNiMo17-12-2 | | 1.4404 | ≤ 0,03 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | ≤ 0,10 | 16,5 to 18,5 | — | 2,00 to 2,50 | — | — | 10,0 to 13,0 | — |
| X2CrNiMo17-11-2 | | 1.4406 | ≤ 0,03 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | 0,12 to 0,22 | 16,5 to 18,5 | — | 2,00 to 2,50 | — | — | 10,0 to 12,5 | — |
| X2CrNiMo17-9-1 ^b | | 1.4420 | ≤ 0,03 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | 0,14 to 0,25 | 19,5 to 21,5 | ≤ 1,00 | 0,50 to 1,50 | — | — | 8,0 to 9,5 | — |
| X2CrNiMo17-13-3 | | 1.4429 | ≤ 0,03 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | 0,12 to 0,22 | 16,5 to 18,5 | — | 2,50 to 3,00 | — | — | 11,0 to 14,0 | — |
| X2CrNiMo17-12-3 | | 1.4432 | ≤ 0,03 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | ≤ 0,10 | 16,5 to 18,5 | — | 2,50 to 3,00 | — | — | 10,5 to 13,0 | — |
| X2CrNiMo18-12-4 | | 1.4434 | ≤ 0,03 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | 0,10 to 0,20 | 16,5 to 19,5 | — | 3,0 to 4,0 | — | — | 10,5 to 14,0 | — |
| X2CrNiMo18-14-3 | | 1.4435 | ≤ 0,03 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | ≤ 0,10 | 17,0 to 19,0 | — | 2,50 to 3,00 | — | — | 12,5 to 15,0 | — |
| X3CrNiMo17-13-3 | | 1.44436 | ≤ 0,05 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | ≤ 0,10 | 16,5 to 18,5 | — | 2,50 to 3,00 | — | — | 10,5 to 13,0 | — |
| X2CrNiMo18-15-4 | | 1.44438 | ≤ 0,03 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | ≤ 0,10 | 17,5 to 19,5 | — | 3,0 to 4,0 | — | — | 13,0 to 16,0 | — |
| X2CrNiMo17-13-5 | | 1.44439 | ≤ 0,03 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | 0,12 to 0,22 | 16,5 to 18,5 | — | 4,0 to 5,0 | — | — | 12,5 to 14,5 | — |
| X1CrNiMoN25-22-2 | | 1.44466 | ≤ 0,02 | ≤ 0,70 | ≤ 2,00 | 0,025 | 0,010 | 0,10 to 0,16 | 24,0 to 26,0 | — | 2,00 to 2,50 | — | — | 21,0 to 23,0 | — |
| X1NiCrMoCuN25-20-7 | | 1.4529 | ≤ 0,02 | ≤ 0,50 | ≤ 1,00 | 0,030 | 0,010 | 0,15 to 0,25 | 19,0 to 21,0 | 0,50 to 1,50 | 6,0 to 7,0 | — | — | 24,0 to 26,0 | — |
| X1CrNiMoCuN25-25-5 | | 1.4537 | ≤ 0,02 | ≤ 0,70 | ≤ 2,00 | 0,030 | 0,010 | 0,17 to 0,25 | 24,0 to 26,0 | 1,00 to 2,00 | 4,7 to 5,7 | — | — | 24,0 to 27,0 | — |
| X1NiCrMoCu25-20-5 | | 1.4539 | ≤ 0,02 | ≤ 0,70 | ≤ 2,00 | 0,030 | 0,010 | ≤ 0,15 | 19,0 to 21,0 | 1,20 to 2,00 | 4,0 to 5,0 | — | — | 24,0 to 26,0 | — |
| X6CrNiTi18-10 | | 1.4541 | ≤ 0,08 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | — | 17,0 to 19,0 | — | — | — | — | 9,0 to 12,0 | 5 x C to 0,70 |
| X1CrNiMoCuN20-18-7 | | 1.4547 | ≤ 0,02 | ≤ 0,70 | ≤ 1,00 | 0,030 | 0,010 | 0,18 to 0,25 | 19,5 to 20,5 | 0,50 to 1,00 | 6,0 to 7,0 | — | — | 17,5 to 18,5 | — |
| X6CrNiNb18-10 | | 1.4550 | ≤ 0,08 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | — | 17,0 to 19,0 | — | 10 x C to 1,00 | — | — | 9,0 to 12,0 | — |
| X1NiCrMoCu31-27-4 | | 1.4563 | ≤ 0,02 | ≤ 0,70 | ≤ 2,00 | 0,030 | 0,010 | ≤ 0,10 | 26,0 to 28,0 | 0,70 to 1,50 | 3,0 to 4,0 | — | — | 30,0 to 32,0 | — |

(to be continued)

| Steel grade | | % by mass | | | | | | | | | | | | |
|------------------------------------------|--------------|--------------|--------------|--------------|--------|--------|--------------|--------------|--------------|--------------|----------------|--------------|---------------|------------------------------------------------------------------------|
| Steel name | Steel number | C | Si | Mn | P max. | S max. | N | Cr | Cu | Mo | Nb | Ni | Ti | Others |
| X6CrNiMoTi17-12-2 | 1.4571 | ≤ 0,08 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | — | 16,5 to 18,5 | — | 2,00 to 2,50 | — | 10,5 to 13,5 | 5 × C to 0,70 | — |
| X6CrNiMoNb17-12-2 | 1.4580 | ≤ 0,08 | ≤ 1,00 | ≤ 2,00 | 0,045 | 0,015 | — | 16,5 to 18,5 | — | 2,00 to 2,50 | 10 × C to 1,00 | 10,5 to 13,5 | — | — |
| X9CrMnNiCu17-8-5-2 | 1.4618 | ≤ 0,10 | ≤ 1,00 | 5,5 to 9,5 | 0,070 | 0,010 | ≤ 0,15 | 16,5 to 18,5 | 1,00 to 2,50 | — | — | 4,5 to 5,5 | — | — |
| X6CrMnNiCu18-2-4-2 ^b | 1.4646 | 0,02 to 0,10 | 1,0 | 10,5 to 12,5 | 0,05 | 0,015 | 0,2 to 0,3 | 17 to 19 | 1,5 to 3,0 | < 0,5 | — | 3,5 to 4,5 | — | Al < 0,05 |
| Austenitic creep resisting grades | | | | | | | | | | | | | | |
| X3CrNiMoBN17-13-3 | 1.4910 | ≤ 0,04 | ≤ 0,75 | ≤ 2,00 | 0,035 | 0,015 | 0,10 to 0,18 | 16,0 to 18,0 | — | 2,00 to 3,00 | — | 12,0 to 14,0 | — | B: 0,0015 to 0,0050 |
| X6CrNiTiB18-10 | 1.4941 | 0,04 to 0,08 | ≤ 1,00 | ≤ 2,00 | 0,035 | 0,015 | — | 17,0 to 19,0 | — | — | — | 9,0 to 12,0 | 5 × C to 0,80 | B: 0,0015 to 0,0050 |
| X6CrNi18-10 | 1.4948 | 0,04 to 0,08 | ≤ 1,00 | ≤ 2,00 | 0,035 | 0,015 | ≤ 0,10 | 17,0 to 19,0 | — | — | — | 8,0 to 11,0 | — | — |
| X6CrNi23-13 | 1.4950 | 0,04 to 0,08 | ≤ 0,70 | ≤ 2,00 | 0,035 | 0,015 | ≤ 0,10 | 22,0 to 24,0 | — | — | — | 12,0 to 15,0 | — | — |
| X6CrNi25-20 | 1.4951 | 0,04 to 0,08 | ≤ 0,70 | ≤ 2,00 | 0,035 | 0,015 | ≤ 0,10 | 24,0 to 26,0 | — | — | — | 19,0 to 22,0 | — | — |
| X5NiCrAlTi31-20 (+RA) | 1.4958 (+RA) | 0,03 to 0,08 | ≤ 0,70 | ≤ 1,50 | 0,015 | 0,010 | ≤ 0,030 | 19,0 to 22,0 | ≤ 0,50 | — | ≤ 0,10 | 30,0 to 32,5 | 0,20 to 0,50 | Al: 0,20 to 0,50 Al+Ti: ≤ 0,70 Co: ≤ 0,50 Ni+Co: 30,0 to 32,5 |
| X8NiCrAlTi32-21 | 1.4959 | 0,05 to 0,10 | ≤ 0,70 | ≤ 1,50 | 0,015 | 0,010 | ≤ 0,030 | 19,0 to 22,0 | ≤ 0,50 | — | — | 30,0 to 34,0 | 0,25 to 0,65 | Al: 0,25 to 0,65 Co: ≤ 0,50 Ni+Co: 30,0 to 34,0 |
| X8CrNiNb16-13 | 1.4961 | 0,04 to 0,10 | 0,30 to 0,60 | ≤ 1,50 | 0,035 | 0,015 | — | 15,0 to 17,0 | — | — | 10 × C to 1,20 | 12,0 to 14,0 | — | — |

a Elements not listed in this table shall not be intentionally added to the steel without the agreement of the purchaser except for finishing of the cast. All appropriate precautions are to be taken to avoid the addition of such elements from scrap and other materials used in production which would impair mechanical properties and the suitability of the steel.

b Patented steel

Table 4 — Chemical composition (cast analysis)^a of austenitic-ferritic steels

| Steel grade | | % by mass | | | | | | | | | | |
|------------------------------------|--------------|-----------|---------|-------------|--------|--------|--------------|--------------|--------------|--------------|---------------------------|--------------|
| Steel name | Steel number | C max. | Si max. | Mn | P max. | S max. | N | Cr | Cu | Mo | Ni | W |
| X2CrNiN22-2 ^b | 1.4062 | 0,030 | 1,00 | ≤ 2,00 | 0,040 | 0,010 | 0,16 to 0,28 | 21,5 to 24,0 | — | ≤ 0,45 | 1,00 to 2,90 | — |
| X2CrMnNiN21-5-1 ^b | 1.4162 | 0,040 | 1,00 | 4,0 to 6,0 | 0,035 | 0,005 | 0,20 to 0,25 | 21,0 to 22,0 | 0,10 to 0,80 | 0,10 to 0,80 | 1,35 to 1,90 ^c | — |
| X2CrNiN23-4 | 1.4362 | 0,030 | 1,00 | ≤ 2,00 | 0,035 | 0,015 | 0,05 to 0,20 | 22,0 to 24,0 | 0,10 to 0,60 | 0,10 to 0,60 | 3,5 to 5,5 | — |
| X2CrNiMoN25-7-4 | 1.4410 | 0,030 | 1,00 | ≤ 2,00 | 0,035 | 0,015 | 0,24 to 0,35 | 24,0 to 26,0 | — | 3,0 to 4,5 | 6,0 to 8,0 | — |
| X2CrNiMoN22-5-3 | 1.4462 | 0,030 | 1,00 | ≤ 2,00 | 0,035 | 0,015 | 0,10 to 0,22 | 21,0 to 23,0 | — | 2,50 to 3,5 | 4,5 to 6,5 | — |
| X2CrMnNiMoN21-5-3 | 1.4482 | 0,030 | 1,00 | 4,0 to 6,0 | 0,035 | 0,030 | 0,05 to 0,20 | 19,5 to 21,5 | ≤ 1,00 | 0,10 to 0,60 | 1,50 to 3,50 | — |
| X2CrNiMoCuWN25-7-4 | 1.4501 | 0,030 | 1,00 | ≤ 1,00 | 0,035 | 0,015 | 0,20 to 0,30 | 24,0 to 26,0 | 0,50 to 1,00 | 3,0 to 4,0 | 6,0 to 8,0 | 0,50 to 1,00 |
| X2CrNiMoCuN25-6-3 | 1.4507 | 0,030 | 0,70 | ≤ 2,00 | 0,035 | 0,015 | 0,20 to 0,30 | 24,0 to 26,0 | 1,00 to 2,50 | 3,0 to 4,0 | 6,0 to 8,0 | — |
| X2CrNiMnMoCuN24-4-3-2 ^b | 1.4662 | 0,030 | 0,70 | 2,50 to 4,0 | 0,035 | 0,005 | 0,20 to 0,30 | 23,0 to 25,0 | 0,10 to 0,80 | 1,00 to 2,00 | 3,0 to 4,5 | — |

^a Elements not quoted in this table shall not be intentionally added to the steel without the agreement of the purchaser except for finishing the cast. All appropriate precautions are to be taken to avoid the addition of such elements from scrap and other materials used in production which would impair mechanical properties and the suitability of the steel.

^b Patented steel

^c Steel grade 1.4162 is patented steel up to a max. limit of Ni of 1,70 %.

Table 5 — Permissible product analysis tolerances on the limiting values given in Tables 1 to 4 for the cast analysis

| Element | Specified limits, cast analysis % by mass | | Permissible tolerance ^a % by mass |
|------------|----------------------------------------------|----------|----------------------------------------------------|
| Carbon | | ≤ 0,030 | + 0,005 |
| | > 0,030 | ≤ 0,10 | ± 0,01 |
| Silicon | | ≤ 1,00 | + 0,05 |
| | > 1,00 | ≤ 3,00 | ± 0,10 |
| | > 3,00 | ≤ 4,50 | ± 0,15 |
| Manganese | | ≤ 1,00 | + 0,03 |
| | > 1,00 | ≤ 2,00 | ± 0,04 |
| | > 2,00 | ≤ 12,50 | ± 0,10 |
| Phosphorus | | ≤ 0,045 | + 0,005 |
| | > 0,045 | ≤ 0,070 | + 0,010 |
| Sulfur | | ≤ 0,015 | + 0,003 |
| Nitrogen | | ≤ 0,35 | ± 0,01 |
| Aluminium | | ≤ 0,65 | ± 0,10 |
| Boron | ≥ 0,0015 | ≤ 0,0050 | ± 0,0003 |
| Chromium | ≥ 10,5 | < 15,0 | ± 0,15 |
| | ≥ 15,0 | ≤ 20,0 | ± 0,20 |
| | > 20,0 | ≤ 28,0 | ± 0,25 |
| Copper | | ≤ 1,00 | ± 0,07 |
| | > 1,00 | ≤ 2,50 | ± 0,10 |
| Molybdenum | | ≤ 0,60 | ± 0,03 |
| | > 0,60 | < 1,75 | ± 0,05 |
| | ≥ 1,75 | ≤ 7,0 | ± 0,10 |
| Niobium | | ≤ 1,20 | ± 0,05 |
| Nickel | | ≤ 1,00 | ± 0,03 |
| | > 1,00 | ≤ 5,0 | ± 0,07 |
| | > 5,0 | ≤ 10,0 | ± 0,10 |
| | > 10,0 | ≤ 20,0 | ± 0,15 |
| | > 20,0 | ≤ 34,0 | ± 0,20 |
| Cobalt | | ≤ 0,50 | + 0,05 |
| Titanium | | ≤ 1,00 | ± 0,05 |
| Tungsten | | ≤ 1,00 | ± 0,05 |
| Vanadium | ≥ 0,030 | ≤ 0,50 | - 0,01 + 0,03 |

^a If several product analyses are carried out on one cast and the contents of an individual element determined lie outside the permissible range of the chemical composition specified for the cast analysis, then it is only allowed to exceed the permissible maximum value or to fall short of the permissible minimum value, but not both for one cast.

Table 6 — Type of process route of sheet, plate and strip^a

| | Abbreviation ^b | Type of treatment ^c | Surface finish | Notes |
|------------------|---------------------------|-----------------------------------------------------------|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hot rolled | 1C | Hot rolled, heat treated, not descaled | Covered with the rolling scale | Suitable for parts which will be descaled or machined in subsequent production or for certain heat-resisting applications. |
| | 1E | Hot rolled, heat treated, mechanically descaled | Free of scale | The type of mechanical descaling, e.g. coarse grinding or shot blasting, depends on the steel grade and the product, and is left to the manufacturer's discretion, unless otherwise agreed. |
| | 1D | Hot rolled, heat treated, pickled | Free of scale | Usually standard for most steel types to ensure good corrosion resistance; also common finish for further processing. It is permissible for grinding marks to be present. Not as smooth as 2D or 2B. |
| Cold rolled | 2C | Cold rolled, heat treated, not descaled | Smooth with scale from heat treatment | Suitable for parts which will be descaled or machined in subsequent production or for certain heat-resisting applications. |
| | 2E | Cold rolled, heat treated, mechanically descaled | Free of scale ^g | Usually applied to steels with a scale which is very resistant to pickling solutions. May be followed by pickling. |
| | 2D | Cold rolled, heat treated, pickled | Smooth | Finish for good ductility, but not as smooth as 2B or 2R. |
| | 2B | Cold rolled, heat treated, pickled, skin passed | Smoother than 2D | Most common finish for most steel types to ensure good corrosion resistance, smoothness and flatness. Also common finish for further processing. Tension levelling may be used as an alternative to skin passing. |
| | 2R | Cold rolled, bright annealed ^d | Smooth, bright, reflective | Smoother and brighter than 2B. Also common finish for further processing. |
| Special finishes | 1G or 2G | Ground ^e | See footnote ^f | Grade of grit or surface roughness can be specified. Unidirectional texture, not very reflective. |
| | 1J or 2J | Brushed ^e or dull polished ^e | Smoother than ground. See footnote ^f | Grade of brush or surface roughness can be specified. Unidirectional texture, not very reflective. |
| | 1K or 2K | Satin polished ^e | See footnote ^f | Additional specific requirements to a "J" type finish, in order to achieve adequate corrosion resistance for marine and external architectural applications. Transverse Ra < 0,5 µm with clean cut surface finish. |
| | 1P or 2P | Bright polished ^e | See footnote ^f | Mechanical polishing. Process or surface roughness can be specified. Non-directional finish, reflective with high degree of image clarity. |
| | 2F | Cold rolled, heat treated, skin passed on roughened rolls | Uniform non-reflective matt surface | Heat treatment by bright annealing or by annealing and pickling. |

^a Not all process routes and surface finishes are available for all steels.

^b First digit, 1 = hot rolled, 2 = cold rolled.

^c The basic heat treatment condition specified in the relevant Table 7, 8, 9 or 10 applies.

^d May be skin passed.

^e One surface only, unless specifically agreed at the time of enquiry and order.

^f Within each finish description the surface characteristics can vary, and more specific requirements may need to be agreed between manufacturer and purchaser (e.g. grade of grit or surface roughness).

^g Different methods of mechanical descaling may be used. Shot blasting will result in a rough and dull surface while brushing may result in a smooth surface.

Table 7 — Mechanical properties at room temperature for ferritic steels in the annealed condition (see Table A.1), impact energy at 20 °C and resistance to intergranular corrosion

| Steel grade | | Product form ^a | Thickness <i>t</i> mm max. | 0,2 % proof strength | | Tensile strength <i>R_m</i> MPa | Elongation after fracture | | Resistance to intergranular corrosion ^d | | Impact energy (ISO-V) <i>KV₂</i> min. <i>J</i> (long. + tr.) |
|-----------------|--------------|---------------------------|-------------------------------------|--------------------------------|-------|-------------------------------------------------|---------------------------------------------------------------------------|--------------------------------------------------------|----------------------------------------------------|-------------------------|-------------------------------------------------------------------------------------|
| Steel name | Steel number | | | <i>R_{p0,2}</i> MPa | min. | | <i>A_{80 mm}</i> ^b <i>t < 3 mm</i> thick % | <i>A</i> ^c <i>t ≥ 3 mm</i> thick % | in the delivery condition | In the welded condition | |
| | | | | (long.) | (tr.) | | (long. + tr.) | (long. + tr.) | | | |
| X2CrNi12 | 1.4003 | C | 8 | 280 | 320 | 450 to 650 | 20 | | no | no | 50 |
| | | H | 13,5 | | | | 18 | | | | |
| | | P | 25 | 250 | 280 | | 18 | | yes | yes | |
| X2CrTiNb18 | 1.4509 | C | 4 | 230 | 250 | 430 to 630 | 23 | | yes | yes | 27 |
| X3CrTi17 | 1.4510 | C | 4 | 230 | 240 | 420 to 600 | 20 | | yes | yes | 27 |
| X2CrMoTi17-1 | 1.4513 | C | 8 | 260 | 260 | 400 to 550 | 23 | | yes | yes | 27 |
| X6CrNiTi12 | 1.4516 | C | 8 | 280 | 320 | 450 to 650 | 23 | | no | no | 50 |
| | | H | 13,5 | | | | 20 | | | | |
| | | P | 25 | 250 | 280 | | 24 | | yes | yes | |
| X2CrTi17 | 1.4520 | C | 4 | 180 | 200 | 380 to 530 | 20 | | yes | yes | 27 |
| X2CrMoTi18-2 | 1.4521 | C | 4 | 300 | 320 | 420 to 640 | 25 | | yes | yes | 27 |
| X6CrMoNb17-1 | 1.4526 | C | 4 | 280 | 300 | 480 to 560 | 18 | | yes | yes | 27 |
| X2CrTi21 | 1.4611 | C | 8 | 230 | 250 | 430 to 630 | 18 | | yes | yes | 27 |
| X2CrTi24 | 1.4613 | C | 8 | 230 | 250 | 430 to 630 | 18 | | yes | yes | 27 |
| X2CrCuNbTiV22-1 | 1.4622 | C | 4 | 280 | 300 | 430 to 630 | 22 | | yes | yes | 27 |

^a C = cold rolled strip; H = hot rolled strip; P = hot rolled plate.

^b The values are related to test pieces with a gauge length of 80 mm and a width of 20 mm. Test pieces with a gauge length of 50 mm and a width of 12,5 mm may also be used.

^c The values are related to test pieces with a gauge length of $5,65\sqrt{S_0}$.

^d When tested according to EN ISO 3651-2.

Table 8 — Mechanical properties at room temperature and impact energy at -20 °C for martensitic steels in the quenched and tempered condition (see Table A.2)

| Steel grade | | Product form ^a | Thickness <i>t</i> mm max. | 0,2 % proof strength <i>R_{p0,2}</i> MPa min. | Tensile strength <i>R_m</i> MPa | Elongation after fracture <i>A</i> ^b ≥ 3 mm thick % min. (long. + tr.) | Impact energy (ISO-V) | |
|----------------|--------------|---------------------------|-------------------------------------|----------------------------------------------------------------|-------------------------------------------------|--------------------------------------------------------------------------------------------------|-------------------------------------------|-----------|
| Steel name | Steel number | | | | | | <i>KV₂</i> <i>J</i> min. | at -20 °C |
| (long. + tr.) | | | | | | | | |
| X3CrNiMo13-4 | 1.4313 | P | 75 | 650 | 780 to 980 | 14 | 70 | 40 |
| X4CrNiMo16-5-1 | 1.4418 | P | 75 | 680 | 840 to 980 | 14 | 55 | 40 |

^a *P* = hot rolled plate.

^b The values apply for test pieces with a gauge length of $5,65 \sqrt{S_0}$.

Table 9 — Mechanical properties at room temperature and impact energy at 20 °C and –196 °C of austenitic steels in the solution annealed condition^a and resistance to intergranular corrosion

| Steel grade | | Pro- duct- form ^b | Thick- ness <i>t</i> mm max | 0,2 % proof strength | 1,0 % proof strength | Tensile strength | Elongation after fracture | | Impact energy (ISO-V) <i>KV</i> ₂ J min. | | | Resistance to intergranular corrosion ^f | |
|----------------------------------------------|----------------------|---------------------------------------|-----------------------------------------|---------------------------------------------------------------|---------------------------------|------------------------------|----------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-----------------------------------------------------------------|---------------------------|---------------------------------|----------------------------------------------------------|-----------------|
| Steel name | Steel num- ber | | | <i>R</i> _{p0,2} MPa min. (tr.) ^c | <i>R</i> _{p1,0} MPa | <i>R</i> _m MPa | <i>A</i> _{80mm^d} < 3 mm thick % min. (long+tr.) ^e <i>c</i> | <i>A</i> ≥ 3 mm thick % min. (long+tr.) ^e <i>c</i> | at 20 °C (long.) | at –196 °C (tr.) | in the delivery condition | in the sensitized condition | |
| Austenitic corrosion resisting grades | | | | | | | | | | | | | |
| X5CrNi18-10 | 1.4301 | C | 8 | 230 | 260 | 540 to 750 | 45 ^g | 45 ^g | 100 | 60 | 60 | yes ^h | no ⁱ |
| | | H | 13,5 | 210 | 250 | 520 to 720 | | | | | | | |
| | | P | 75 | 210 | 250 | | 45 | 45 | | | | | |
| X2CrNi19-11 | 1.4306 | C | 8 | 220 | 250 | 520 to 700 | 45 | 45 | 100 | 60 | 60 | yes | yes |
| | | H | 13,5 | 200 | 240 | 500 to 700 | | | | | | | |
| | | P | 75 | 200 | 240 | | | | | | | | |
| X2CrNi18-9 | 1.4307 | C | 8 | 220 | 250 | 520 to 700 | 45 | 45 | 100 | 60 | 60 | yes | yes |
| | | H | 13,5 | 200 | 240 | 500 to 700 | | | | | | | |
| | | P | 75 | 200 | 240 | | | | | | | | |
| X2CrNiN18-10 | 1.4311 | C | 8 | 290 | 320 | 550 to 750 | 40 | 40 | 100 | 60 | 60 | yes | yes |
| | | H | 13,5 | 270 | 310 | 550 to 750 | | | | | | | |
| | | P | 75 | 270 | 310 | | | | | | | | |
| X5CrNiN19-9 | 1.4315 | C | 8 | 290 | 320 | 550 to 750 | 40 | 40 | 100 | 60 | 60 | yes ^h | no ⁱ |
| | | H | 13,5 | 270 | 310 | 550 to 750 | | | | | | | |
| | | P | 75 | 270 | 310 | | | | | | | | |
| X2CrNiN18-7 | 1.4318 | C | 8 | 350 | 380 | 650 to 850 | 35 | 40 | 90 | 60 | 60 | yes | yes |
| | | H | 13,5 | 330 | 370 | 650 to 850 | | | | | | | |
| | | P | 75 | 330 | 370 | | | | | | | | |
| X1CrNi25-21 | 1.4335 | P | 75 | 200 | 240 | 470 to 670 | 40 | 40 | 100 | 60 | 60 | yes | yes |
| X1CrNiSi18-15-4 | 1.4361 | P | 75 | 220 | 260 | 530 to 730 | 40 | 40 | 100 | 60 | — | yes | yes |
| X2CrMnNiN 17-7-5 | 1.4371 | C | 8 | 330 | 380 | 650 to 850 | 40 | 45 | 100 | 60 | 60 | yes | yes |
| | | H | 13,5 | 300 | 370 | | | | | | | | |
| | | P | 75,0 | 300 | 370 | | | | | | | | |
| X12CrMnNiN 17-7-5 | 1.4372 | C | 8 | 350 | 380 | 680 to 880 | 45 | 45 | 100 | 60 | — | yes | no |
| | | H | 13,5 | 330 | 370 | | | | | | | | |
| | | P | 75 | 330 | 370 | | 40 | 40 | | | | | |
| <i>(to be continued)</i> | | | | | | | | | | | | | |

| Steel grade | | Product-form ^b | Thickness <i>t</i> mm max. | 0,2 % proof strength | 1,0 % proof strength | Tensile strength <i>R_m</i> MPa | Elongation after fracture | | Impact energy (ISO-V) <i>KV₂</i> <i>J</i> min. | | | Resistance to intergranular corrosion ^f | |
|------------------------------|-----------------|---------------------------|-------------------------------------|-----------------------------------|----------------------------|----------------------------------------------------|------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-----------------------------------------------------------------------|----------------------------|---------------------------------|----------------------------------------------------------|-----------------|
| | | | | <i>R_{p0,2}</i> | <i>R_{p1,0}</i> | | <i>A_{80mm^d}</i> < 3 mm thick % min. (long+tr.) ^c | <i>A^e ≥ 3 mm thick %</i> min. (long+tr.) ^c | | | | | |
| Steel name | Steel number | | | MPa min. (tr.) ^c | | | | | at 20 °C (long.) | at - 196 °C (tr.) | in the delivery condition | in the sensi- tized condition | |
| X5CrNiMo17-12-2 | 1.4401 | C | 8 | 240 | 270 | 530 to 680 | 40 | 40 | 100 | 60 | 60 | yes ^h | no ⁱ |
| | | H | 13,5 | 220 | 260 | | 45 | 45 | | | | | |
| | | P | 75 | 220 | 260 | 520 to 670 | 45 | 45 | | | | | |
| X2CrNiMo17-12-2 ^k | 1.4404 | C | 8 | 240 | 270 | 530 to 680 | 40 | 40 | 100 | 60 | 60 | yes | yes |
| | | H | 13,5 | 220 | 260 | | 45 | 45 | | | | | |
| | | P | 75 | 220 | 260 | 520 to 670 | 45 | 45 | | | | | |
| X2CrNiMoN17-11-2 | 1.4406 | C | 8 | 300 | 330 | 580 to 780 | 40 | 40 | 100 | 60 | 60 | yes | yes |
| | | H | 13,5 | 280 | 320 | | 40 | 40 | | | | | |
| | | P | 75 | 280 | 320 | | 45 | 45 | | | | | |
| X2CrNiMoN21-9-1 | 1.4420 | C | 8 | 350 | 380 | 650 to 850 | 35 | 35 | 100 | 60 | 60 | yes | yes |
| | | H | 13,5 | 350 | 380 | | 40 | 40 | | | | | |
| | | P | 75 | 320 | 350 | 630 to 830 | 40 | 40 | | | | | |
| X2CrNiMoN17-13-3 | 1.4429 | C | 8 | 300 | 330 | 580 to 780 | 35 | 35 | 100 | 60 | 60 | yes | yes |
| | | H | 13,5 | 280 | 320 | | 40 | 40 | | | | | |
| | | P | 75 | 280 | 320 | | 45 | 45 | | | | | |
| X2CrNiMo17-12-3 | 1.4432 | C | 8 | 240 | 270 | 550 to 700 | 40 | 40 | 100 | 60 | 60 | yes | yes |
| | | H | 13,5 | 220 | 260 | | 45 | 45 | | | | | |
| | | P | 75 | 220 | 260 | 520 to 670 | 45 | 45 | | | | | |
| X2CrNiMoN18-12-4 | 1.4434 | C | 8 | 290 | 320 | 570 to 770 | 35 | 35 | 100 | 60 | 60 | yes | yes |
| | | H | 13,5 | 270 | 310 | | 40 | 40 | | | | | |
| | | P | 75 | 270 | 310 | 540 to 740 | 40 | 40 | | | | | |
| X2CrNiMo18-14-3 | 1.4435 | C | 8 | 240 | 270 | 550 to 700 | 40 | 40 | 100 | 60 | 60 | yes | yes |
| | | H | 13,5 | 220 | 260 | | 45 | 45 | | | | | |
| | | P | 75 | 220 | 260 | 520 to 670 | 40 | 40 | | | | | |
| X3CrNiMo17-13-3 | 1.4436 | C | 8 | 240 | 270 | 550 to 700 | 40 | 40 | 100 | 60 | 60 | yes ^h | no ⁱ |
| | | H | 13,5 | 220 | 260 | | 45 | 45 | | | | | |
| | | P | 75 | 220 | 260 | 530 to 730 | 40 | 40 | | | | | |
| X2CrNiMo18-15-4 | 1.4438 | C | 8 | 240 | 270 | 550 to 700 | 35 | 35 | 100 | 60 | 60 | yes | yes |
| | | H | 13,5 | 220 | 260 | | 40 | 40 | | | | | |
| | | P | 75 | 220 | 260 | 520 to 720 | 40 | 40 | | | | | |

(to be continued)

| Steel grade | | Pro- duct- form ^b | Thick- ness <i>t</i> mm max. | 0,2 % proof strength | 1,0 % proof strength | Tensile strength <i>R_m</i> MPa | Elongation after fracture | | Impact energy (ISO-V) <i>KV₂</i> <i>J</i> min. | | Resistance to intergranular corrosion ^f | | | | | | | |
|----------------------|-----------------|------------------------------------|------------------------------------------|--------------------------------------------------------------|--------------------------------------------------------------|--------------------------------------------------------|------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|---------------------------------------------------------------------------|-------------------------------|----------------------------------------------------------|----------------------------------------|-----|--|--|--|--|--|
| | | | | <i>R_{p0,2}</i> MPa min. (tr.) ^c | <i>R_{p1,0}</i> MPa min. (tr.) ^c | | <i>A_{80mm^d}</i> < 3 mm thick % min. (long+tr.) ^c | <i>A^e ≥ 3 mm thick %</i> min. (long+tr.) ^c | | | | | | | | | | |
| Steel name | Steel number | | | | | | | | at 20 °C | at - 196 °C (tr.) | in the delivery condition | in the sensi- tized condition | | | | | | |
| | | | | | | | | | (long) | (tr.) | | | | | | | | |
| X2CrNiMoN17-13-5 | 1.4439 | C | 8 | 290 | 320 | 580 to 780 | 35 | 35 | 100 | 60 | 60 | yes | yes | | | | | |
| | | H | 13,5 | 270 | 310 | | 40 | 40 | | | | | | | | | | |
| | | P | 75 | 270 | 310 | | | | | | | | | | | | | |
| X1CrNiMoN25-22-2 | 1.4466 | P | 75 | 250 | 290 | 540 to 740 | 40 | 40 | 100 | 60 | 60 | yes | yes | | | | | |
| X1NiCrMoCuN25-20-7 | 1.4529 | C | 7 | 300 | 340 | 650 to 850 | 40 | 40 | 120 | 100 | - | yes | yes | | | | | |
| | | H | 13 | 300 | 340 | 650 to 850 | 40 | 40 | 120 | 100 | - | yes | yes | | | | | |
| | | P | 75 | 300 | 320 | 650 to 850 | 40 | 40 | 100 | 60 | - | yes | yes | | | | | |
| X1CrNiMoCuN25-25-5 | 1.4537 | P | 75 | 290 | 330 | 600 to 800 | 40 | 40 | 100 | 60 | 60 | yes | yes | | | | | |
| X1NiCrMoCu25-20-5 | 1.4539 | C | 8 | 240 | 270 | 530 to 730 | 35 | 35 | 100 | 60 | 60 | yes | yes | | | | | |
| | | H | 13,5 | 220 | 260 | | | | | | | | | | | | | |
| | | P | 75 | 220 | 260 | | | | | | | | | | | | | |
| X6CrNiTi18-10 | 1.4541 | C | 8 | 220 | 250 | 520 to 720 | 40 | 40 | 100 | 60 | 60 | yes | yes | | | | | |
| | | H | 13,5 | 200 | 240 | | | | | | | | | | | | | |
| | | P | 75 | 200 | 240 | | | | | | | | | | | | | |
| X1CrNiMoCuN20-18-7 | 1.4547 | C | 8 | 320 | 350 | 650 to 850 | 35 | 35 | 100 | 60 | 60 | yes | yes | | | | | |
| | | H | 13,5 | 300 | 340 | | 40 | 40 | | | | | | | | | | |
| | | P | 75 | 300 | 340 | | | | | | | | | | | | | |
| X6CrNiNb18-10 | 1.4550 | H | 13,5 | 200 | 240 | 520 to 720 | 40 | 40 | 100 | 60 | 40 | yes | yes | | | | | |
| | | P | 75 | 200 | 240 | 500 to 700 | | | | | | | | | | | | |
| X1NiCrMoCu31-27-4 | 1.4563 | P | 75 | 220 | 260 | 500 to 700 | 40 | 40 | 100 | 60 | 60 | yes | yes | | | | | |
| X6CrNiMoTi17-12-2 | 1.4571 | C | 8 | 240 | 270 | 540 to 690 | 40 | 40 | 100 | 60 | 60 | yes | yes | | | | | |
| | | H | 13,5 | 220 | 260 | | | | | | | | | | | | | |
| | | P | 75 | 220 | 260 | | | | | | | | | | | | | |
| X6CrNiMoNb17-12-2 | 1.4580 | P | 75 | 220 | 260 | 520 to 720 | 40 | 40 | 100 | 60 | - | yes | yes | | | | | |
| X9CrMnNiCu17-8-5-2 | 1.4618 | C | 8,0 | 230 | 250 | 540 to 850 | 45 | 45 | 100 | 60 | 60 | yes | yes | | | | | |
| | | H | 13,5 | 230 | 250 | | | | | | | | | | | | | |
| | | P | 75,0 | 210 | 240 | | | | | | | | | | | | | |
| X6CrMnNiCuN18-12-4-2 | 1.4646 | C | 8 | 380 | 400 | 650 to 850 | 30 | 30 | 100 | 60 | - | yes | yes | | | | | |

(to be continued)

| Steel grade | | Pro- duct- form ^b | Thick- ness <i>t</i> mm max. | 0,2 % proof strength | 1,0 % proof strength | Tensile strength <i>R_m</i> MPa | Elongation after fracture | | Impact energy (ISO-V) <i>KV₂</i> <i>J</i> min. | | Resistance to intergranular corrosion ^f | | | | | | | | | |
|------------------------------------------|-----------------|------------------------------------|------------------------------------------|-----------------------------------|----------------------------|--------------------------------------------------------|------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|---------------------------------------------------------------------------|-------------------------------|----------------------------------------------------------|----------------------------------------|-----|--|--|--|--|--|--|--|
| | | | | <i>R_{p0,2}</i> | <i>R_{p1,0}</i> | | <i>A_{80mm}^d</i> < 3 mm thick % min. (long+tr.) ^c | <i>A^e</i> ≥ 3 mm thick % min. (long+tr.) ^c | | | | | | | | | | | | |
| Steel name | Steel number | | | MPa min. (tr.) ^c | | | | at 20 °C | | at - 196 °C (tr.) | in the delivery condition | in the sensi- tized condition | | | | | | | | |
| | | | | (long.) | (tr.) | | | | | | | | | | | | | | | |
| Austenitic creep resisting grades | | | | | | | | | | | | | | | | | | | | |
| X3CrNiMoBN17-13-3 | 1.4910 | C | 8 | 300 | 330 | 580 to 780 | 35 | 40 | 100 | 60 | - | yes | yes | | | | | | | |
| | | H | 13,5 | 260 | 300 | 550 to 750 | | | | | | | | | | | | | | |
| | | P | 75 | 260 | 300 | | | | | | | | | | | | | | | |
| X6CrNiTiB18-10 | 1.4941 | C | 8 | 220 | 250 | 510 to 710 | 40 | 40 | 100 | 60 | - | yes | yes | | | | | | | |
| | | H | 13,5 | 200 | 240 | | | | | | | | | | | | | | | |
| | | P | 75 | 200 | 240 | 490 to 690 | | | | | | | | | | | | | | |
| X6CrNi18-10 | 1.4948 | C | 8 | 230 | 260 | 530 to 740 | 45 ^g | 45 ^g | 100 | 60 | - | no | no | | | | | | | |
| | | H | 13,5 | 210 | 250 | 510 to 710 | | | | | | | | | | | | | | |
| | | P | 75 | 190 | 230 | | | | | | | | | | | | | | | |
| X6CrNi23-13 | 1.4950 | C | 8 | 220 | 250 | 530 to 730 | 35 | 35 | 100 | 60 | - | no | no | | | | | | | |
| | | H | 13,5 | 200 | 240 | 510 to 710 | | | | | | | | | | | | | | |
| | | P | 75 | 200 | 240 | | | | | | | | | | | | | | | |
| X6CrNi25-20 | 1.4951 | C | 8 | 220 | 250 | 530 to 730 | 35 | 35 | 100 | 60 | - | no | no | | | | | | | |
| | | H | 13,5 | 200 | 240 | 510 to 710 | | | | | | | | | | | | | | |
| | | P | 75 | 200 | 240 | | | | | | | | | | | | | | | |
| X5NiCrAlTi31-20 | 1.4958 | P | 75 | 170 | 200 | 500 to 750 | 30 | 30 | 120 | 80 | - | yes | no | | | | | | | |

(to be continued)

| Steel grade | | Pro- duct- form b | Thick- ness t mm max. | 0,2 % proof strength h | 1,0 % proof strength $R_{p1,0}$ | Tensile strength h R_m MPa | Elongation after fracture | | Impact energy (ISO-V) KV_2 J min. | | Resistance to intergranular corrosion ^f | | |
|---------------------------------|------------------------|----------------------------|-------------------------------------|---------------------------------|------------------------------------------|------------------------------------------|------------------------------------------------------------------------|----------------------------------------------------------|-------------------------------------------------|----|----------------------------------------------------------|-----|-----|
| Steel name | Steel number | | | $R_{p0,2}$ | MPa min. (tr.) ^c | | $A_{80\text{mm}}^d$ < 3 mm thick % min. (long+tr.) c | A^e ≥ 3 mm thick % min. (long+tr.) c | | | | | |
| X5NiCrAlTi31-20+RA ^j | 1.4958+RA ^j | P | 75 | 210 | 240 | 500 to 750 | 30 | 30 | 120 | 80 | - | yes | no |
| X8NiCrAlTi32-21 | 1.4959 | P | 75 | 170 | 200 | 500 to 750 | 30 | 30 | 120 | 80 | - | yes | no |
| X8CrNiNb16-13 | 1.4961 | P | 75 | 200 | 240 | 510 to 690 | 35 | 35 | 100 | 60 | - | yes | yes |

NOTE Austenitic steels always have adequate toughness and do not need to be impact tested. In contrast, austenitic-ferritic steels need to be tested to the impact energy requirements in Table 10 to ensure that toughness is adequate.

^a See Table A.3.
^b C = cold rolled strip; H = hot rolled strip; P = hot rolled plate.
^c If, in the case of strip in rolling widths < 300 mm, longitudinal test pieces are taken, the minimum values are reduced as follows:
 - proof strength $R_{p0,2}$: minus 15 MPa
 - elongation for constant gauge length A80 mm: minus 5 %
 - elongation for proportional gauge length A: minus 2 %.
^d The values are related to test pieces with a gauge length of 80 mm and a width of 20 mm; test pieces with a gauge length of 50 mm and a width of 12,5 mm can also be used.
^e The values are related to test pieces with a gauge length of $5,65\sqrt{S_0}$.
^f When tested according to EN ISO 3651-2.
^g For stretcher levelled material, the minimum value is 5 % lower.
^h Normally for thicknesses up to 6 mm.
ⁱ Resistance to intergranular corrosion is given for thicknesses up to 6 mm in the welded condition.
^j +RA = recrystallizing annealed condition.
^k For steel grade 1.4404 supplementary data considering mechanical properties may be agreed at time of enquiry and order.

Table 10 — Mechanical properties at room temperature and impact energy at 20 °C and –40 °C of austenitic-ferritic steels in the solution annealed condition (see Table A.4) and resistance to intergranular corrosion

| Steel grade | | Product form ^a | Thickness ^t | 0,2 % proof strength $R_{p0,2}$ MPa min. width | | Tensile strength R_m MPa | Elongation after fracture | | Impact energy (ISO-V) KV_2 J min. | | | Resistance to intergranular corrosion ^d | |
|-----------------------|--------------|---------------------------|------------------------|------------------------------------------------------------|-------------------------|----------------------------------|---------------------------|---------|----------------------------------------------------------------|--------------------------------------------------------------|----------|----------------------------------------------------|-----------------------------|
| | | | | mm max. | (long.) < 300 m m | | (tr.) ≥ 300 mm | (tr.) | $A_{80\text{mm}} < 3$ mm thick ^b % min. | $A \geq 3 \text{ m}$ m thick ^c % min. | at 20 °C | at –40 °C | |
| Steel name | Steel number | | | | (long. + tr.) | | (long. + tr.) | (long.) | (tr.) | (tr.) | (tr.) | in the delivery condition | in the sensitized condition |
| X2CrNiN22-2 | 1.4062 | C | 6,4 | 515 | 530 | 700 to 900 | 20 | 30 | 80 | 80 | 50 | yes | yes |
| | | H | 10 | 465 | 480 | 680 to 900 | 30 | 30 | | | | | |
| | | P | 75 | 435 | 450 | 650 to 850 | 30 | 30 | | 60 | 60 | 27 ^e | |
| X2CrMnNiN21-5-1 | 1.4162 | C | 6,4 | 515 | 530 | 700 to 900 | 25 | 30 | 80 | 80 | 50 | yes | yes |
| | | H | 10 | 465 | 480 | 680 to 900 | 30 | 30 | 80 | 80 | 50 | | |
| | | P | 75 | 435 | 450 | 650 to 850 | 30 | 30 | 60 | 40 | 27 | | |
| X2CrNiN23-4 | 1.4362 | C | 8 | 405 | 420 | 630 to 850 | 20 | 20 | 120 | 90 | 40 | yes | yes |
| | | H | 13,5 | 385 | 400 | | 25 | 25 | | | | | |
| | | P | 50 | 385 | 400 | 600 to 800 | 25 | 25 | | | | | |
| X2CrNiMoN25-7-4 | 1.4410 | C | 8 | 535 | 550 | 750 to 1 000 | 20 | 20 | 150 | 90 | 40 | yes | yes |
| | | H | 13,5 | 515 | 530 | | 25 | 25 | | | | | |
| | | P | 50 | 515 | 530 | 730 to 930 | 20 | 20 | | | | | |
| X2CrNiMoN22-5-3 | 1.4462 | C | 8 | 485 | 500 | 700 to 950 | 20 | 20 | 150 | 100 | 40 | yes | yes |
| | | H | 13,5 | 445 | 460 | | 25 | 25 | | | | | |
| | | P | 75 | 445 | 460 | 640 to 840 | 25 | 25 | | | | | |
| X2CrMnNiMoN21-5-3 | 1.4482 | C | 6,4 | 485 | 500 | 700 to 900 | 20 | 30 | 100 | 60 | 40 | yes | yes |
| | | H | 10 | 465 | 480 | 660 to 900 | 30 | 30 | 100 | 60 | 40 | yes | yes |
| | | P | 75 | 435 | 450 | 650 to 850 | - | 30 | 100 | 60 | 40 | yes | yes |
| X2CrNiMoCuWN25-7-4 | 1.4501 | C | 8 | 535 | 550 | 750 to 1 000 | 20 | 20 | 150 | 90 | 40 | yes | yes |
| | | H | 13,5 | 515 | 530 | | 25 | 25 | | | | | |
| | | P | 50 | 515 | 530 | 730 to 930 | 25 | 25 | | | | | |
| X2CrNiMoCuN25-6-3 | 1.4507 | C | 8 | 495 | 510 | 690 to 940 | 20 | 20 | 150 | 90 | 40 | yes | yes |
| | | H | 13,5 | 475 | 490 | | 25 | 25 | | | | | |
| | | P | 50 | 475 | 490 | 690 to 890 | - | 25 | | | | | |
| X2CrNiMnMoCuN24-4-3-2 | 1.4662 | C | 6,4 | 550 | 550 | 750 to 900 | 20 | 25 | 80 | 80 | 40 | yes | yes |
| | | H | 13 | 550 | 550 | 750 to 900 | - | 25 | 80 | 80 | 40 | | |
| | | P | 50 | 480 | 480 | 680 to 900 | - | 25 | 60 | 60 | 40 | | |

NOTE Austenitic-ferritic steels need to be tested to the above impact energy requirements to ensure that toughness is adequate. In contrast, austenitic steels always have adequate toughness and do not need to be impact tested.

a C = cold rolled strip; H = hot rolled strip; P = hot rolled plate.

b The values are related to test pieces with a gauge length of 80 mm and a width of 20 mm; test pieces with a gauge length of 50 mm and a width of 12,5 mm may also be used.

c The values are related to test pieces with a gauge length of $5,65\sqrt{S_0}$.

d When tested according to EN ISO 3651-2.

e For thicknesses ≤ 12 mm.

Table 11 — Minimum values for the 0,2 % proof strength of ferritic steels at elevated temperatures in the annealed condition (see Table A.1)^a

| Steel grade | | Minimum 0,2 % proof strength $R_{p0,2}$, MPa at a temperature (in °C) of | | | | | | | |
|-----------------|--------------|------------------------------------------------------------------------------|-----|-----|-----|-----|-----|-----|-----|
| Steel name | Steel number | 50 ^b | 100 | 150 | 200 | 250 | 300 | 350 | 400 |
| X2CrNi12 | 1.4003 | 265 | 240 | 235 | 230 | 220 | 215 | - | - |
| X6CrNiTi12 | 1.4516 | - | 300 | 270 | 250 | 245 | 225 | 215 | - |
| X2CrTi17 | 1.4520 | 198 | 195 | 180 | 170 | 160 | 155 | - | - |
| X3CrTi17 | 1.4510 | 223 | 195 | 190 | 185 | 175 | 165 | 155 | - |
| X2CrMoTi17-1 | 1.4513 | - | 250 | 240 | 230 | 220 | 210 | 205 | 200 |
| X2CrMoTi18-2 | 1.4521 | 294 | 250 | 240 | 230 | 220 | 210 | 205 | - |
| X6CrMoNb17-1 | 1.4526 | 289 | 270 | 265 | 250 | 235 | 215 | 205 | - |
| X2CrTiNb18 | 1.4509 | 242 | 230 | 220 | 210 | 205 | 200 | 180 | - |
| X2CrTi21 | 1.4611 | - | 230 | 220 | 210 | 205 | 200 | 180 | - |
| X2CrTi24 | 1.4613 | - | 230 | 220 | 210 | 205 | 200 | 180 | - |
| X2CrCuNbTiV22-1 | 1.4622 | 260 | 240 | 230 | 220 | 205 | 200 | 180 | 170 |

^a The values apply to longitudinal and transversal direction.
^b Value determined by linear interpolation.

Table 12 — Minimum values for the 0,2 % proof strength of martensitic steels at elevated temperatures in the quenched and tempered condition (see Table A.2)^a

| Steel grade | | Minimum 0,2 % proof strength Rp0,2, MPa | | | | | | |
|----------------|--------------|-----------------------------------------|-----|-----|-----|-----|-----|-----|
| Steel name | Steel number | at a temperature (in °C) of | | | | | | |
| | | 50 ^b | 100 | 150 | 200 | 250 | 300 | 350 |
| X3CrNiMo13-4 | 1.4313 | 627 | 590 | 575 | 560 | 545 | 530 | 515 |
| X4CrNiMo16-5-1 | 1.4418 | 672 | 660 | 640 | 620 | 600 | 580 | — |

^a The values apply to longitudinal and transversal direction.
^b Value determined by linear interpolation.

Table 13 — Minimum values for the 0,2 % and 1,0 % proof strength of austenitic steels at elevated temperatures in the solution annealed condition (see Table A.3)^a

| Steel grade | Steel number | Minimum 0,2 % proof strength $R_{p0,2}$, MPa | | | | | | | | | | | | Minimum 1,0 % proof strength $R_{p1,0}$, MPa | | | | | | | | | | | | |
|----------------------------------------------|--------------|-----------------------------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----------------------------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|---|
| | | 50 ^b | 100 | 150 | 200 | 250 | 300 | 350 | 400 | 450 | 500 | 550 | 600 | 50 ^b | 100 | 150 | 200 | 250 | 300 | 350 | 400 | 450 | 500 | 550 | 600 | |
| Austenitic corrosion resisting grades | | | | | | | | | | | | | | | | | | | | | | | | | | |
| X5CrNi18-10 | | | | | | | | | | | | | | | | | | | | | | | | | | |
| X5CrNi19-11 | 1.43006 | 180 | 147 | 132 | 118 | 108 | 100 | 94 | 89 | 85 | 81 | 80 | - | 218 | 181 | 162 | 147 | 137 | 127 | 121 | 116 | 112 | 109 | 108 | - | |
| X2CrNi18-9 | 1.43007 | 180 | 147 | 132 | 118 | 108 | 100 | 94 | 89 | 85 | 81 | 80 | - | 218 | 181 | 162 | 147 | 137 | 127 | 121 | 116 | 112 | 109 | 108 | - | |
| X2CrNi18-10 | 1.43111 | 246 | 205 | 175 | 157 | 145 | 136 | 130 | 125 | 121 | 119 | 118 | - | 284 | 240 | 210 | 187 | 175 | 167 | 161 | 156 | 152 | 149 | 147 | - | |
| X5CrNi19-9 | 1.43115 | 246 | 205 | 175 | 157 | 145 | 136 | 130 | 125 | 121 | 119 | 118 | - | 284 | 240 | 210 | 187 | 175 | 167 | 161 | 156 | 152 | 149 | 147 | - | |
| X2CrNi18-7 | 1.43118 | 309 | 265 | 200 | 185 | 180 | 170 | 165 | - | - | - | - | - | - | - | - | 235 | 215 | 210 | 200 | 195 | - | - | - | - | |
| X1CrNi25-21 | 1.43335 | 181 | 150 | 140 | 130 | 120 | 115 | 110 | 105 | - | - | - | - | - | 217 | 180 | 170 | 160 | 150 | 140 | 135 | 130 | - | - | - | |
| X1CrNiSi18-15-4 | 1.43611 | 205 | 185 | 160 | 145 | 135 | 125 | 120 | 115 | - | - | - | - | - | 240 | 210 | 190 | 175 | 165 | 155 | 150 | - | - | - | - | |
| X2CrMnNi17-7-5 | 1.43711 | 246 | 205 | 175 | 127 | 120 | 110 | 104 | 100 | 95 | 92 | 90 | - | 284 | 240 | 210 | 157 | 145 | 135 | 129 | 125 | 122 | 120 | 120 | - | |
| X12CrMnNi17-7-5 | 1.43722 | 330 | 295 | 260 | 230 | 220 | 205 | 185 | - | - | - | - | - | 360 | 325 | 295 | 265 | 250 | 230 | 205 | - | - | - | - | - | - |
| X5CrNiMo17-12-2 | 1.44011 | 204 | 177 | 162 | 147 | 137 | 127 | 120 | 115 | 112 | 110 | 108 | - | 242 | 211 | 191 | 177 | 167 | 156 | 150 | 144 | 141 | 139 | 137 | - | |
| X2CrNiMo17-12-2 | 1.44044 | 200 | 166 | 152 | 137 | 127 | 118 | 113 | 108 | 103 | 100 | 98 | - | 237 | 199 | 181 | 167 | 157 | 145 | 139 | 135 | 130 | 128 | 127 | - | |
| X2CrNiMoN17-11-2 | 1.44066 | 254 | 211 | 185 | 167 | 155 | 145 | 140 | 135 | 131 | 128 | 127 | - | 292 | 246 | 218 | 198 | 183 | 175 | 169 | 164 | 160 | 158 | 157 | - | |
| X2CrNiMoN21-9-1 | 1.44200 | 280 | 230 | 210 | 190 | 180 | 170 | 165 | 160 | 155 | 150 | 147 | - | 320 | 270 | 250 | 225 | 210 | 195 | 190 | 185 | 180 | 170 | 167 | - | |
| X2CrNiMoN17-13-3 | 1.44229 | 254 | 211 | 185 | 167 | 155 | 145 | 140 | 135 | 131 | 129 | 127 | - | 292 | 246 | 218 | 198 | 183 | 175 | 169 | 164 | 160 | 158 | 157 | - | |
| X2CrNiMo17-12-3 | 1.44322 | 200 | 166 | 152 | 137 | 127 | 118 | 113 | 108 | 103 | 100 | 98 | - | 237 | 199 | 181 | 167 | 157 | 145 | 139 | 135 | 130 | 128 | 127 | - | |
| X2CrNiMoN18-12-4 | 1.44344 | 248 | 211 | 185 | 167 | 155 | 145 | 140 | 135 | 131 | 129 | 127 | - | 286 | 246 | 218 | 198 | 183 | 175 | 169 | 164 | 160 | 158 | 157 | - | |
| X2CrNiMo18-14-3 | 1.44355 | 199 | 165 | 150 | 137 | 127 | 119 | 113 | 108 | 103 | 100 | 98 | - | 237 | 200 | 180 | 165 | 153 | 145 | 139 | 135 | 130 | 128 | 127 | - | |
| X3CrNiMo17-13-3 | 1.44366 | 204 | 177 | 162 | 147 | 137 | 127 | 120 | 115 | 112 | 110 | 108 | - | 252 | 211 | 191 | 177 | 167 | 156 | 150 | 144 | 141 | 139 | 137 | - | |
| X2CrNiMo18-15-4 | 1.44388 | 202 | 172 | 157 | 147 | 137 | 127 | 120 | 115 | 112 | 110 | 108 | - | 240 | 206 | 188 | 177 | 167 | 156 | 148 | 144 | 140 | 138 | 136 | - | |
| X2CrNiMoN17-13-5 | 1.44399 | 253 | 225 | 200 | 185 | 175 | 165 | 155 | 150 | - | - | - | - | 289 | 255 | 230 | 210 | 190 | 180 | 175 | - | - | - | - | - | |

(to be continued)

| Steel grade | Steel name | Minimum 0,2 % proof strength $R_{p0,2}$, MPa | | | | | | | | | | Minimum 1,0 % proof strength $R_{p1,0}$, MPa | | | | | | | | | | | | | | | |
|------------------------------------------|------------|-----------------------------------------------|-----------------|-----|-----|-----|-----|-----|-----|-----|-----|-----------------------------------------------|-----|-----|-----------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|---|
| | | Steel number | 50 ^b | 100 | 150 | 200 | 250 | 300 | 350 | 400 | 450 | 500 | 550 | 600 | 50 ^b | 100 | 150 | 200 | 250 | 300 | 350 | 400 | 450 | 500 | 550 | 600 | |
| X1CrNiMoN25-22-2 | 1.4466 | 229 | 195 | 170 | 160 | 150 | 140 | 135 | - | - | - | - | - | - | 266 | 225 | 205 | 190 | 180 | 170 | 165 | - | - | - | - | - | |
| X1NiCrMoCuN25-20-7 | 1.4529 | 274 | 230 | 210 | 190 | 180 | 170 | 165 | 160 | 130 | 120 | 105 | - | - | 314 | 270 | 245 | 225 | 215 | 205 | 195 | 190 | 160 | 150 | 135 | - | |
| X1CrNiMoCuN25-25-5 | 1.4537 | 271 | 240 | 220 | 200 | 190 | 180 | 175 | 170 | - | - | - | - | - | 307 | 270 | 250 | 230 | 220 | 210 | 205 | 200 | - | - | - | - | - |
| X1NiCrMoCu25-20-5 | 1.4539 | 214 | 205 | 190 | 175 | 160 | 145 | 135 | 125 | 115 | 110 | 105 | - | - | 251 | 235 | 220 | 205 | 190 | 175 | 165 | 155 | 145 | 140 | 135 | - | |
| X6CrNiTi18-10 | 1.4541 | 191 | 176 | 167 | 157 | 147 | 136 | 130 | 125 | 121 | 119 | 118 | - | - | 228 | 208 | 196 | 186 | 177 | 167 | 161 | 156 | 152 | 149 | 147 | - | |
| X1CrNiMoCuN20-18-7 | 1.4547 | 274 | 230 | 205 | 190 | 180 | 170 | 165 | 160 | 153 | 148 | - | - | - | 314 | 270 | 245 | 225 | 212 | 200 | 195 | 190 | 184 | 180 | - | - | |
| X6CrNiNb18-10 | 1.4550 | 191 | 177 | 167 | 157 | 147 | 136 | 130 | 125 | 121 | 119 | 118 | - | - | 229 | 211 | 196 | 186 | 177 | 167 | 161 | 156 | 152 | 149 | 147 | - | |
| X1NiCrMoCu31-27-4 | 1.4563 | 209 | 190 | 175 | 160 | 155 | 150 | 145 | 135 | 125 | 120 | 115 | - | - | 245 | 220 | 205 | 190 | 185 | 180 | 175 | 165 | 155 | 150 | 145 | - | |
| X6CrNiMoTi17-12-2 | 1.4571 | 207 | 185 | 177 | 167 | 157 | 145 | 140 | 135 | 131 | 129 | 127 | - | - | 244 | 218 | 206 | 196 | 186 | 175 | 169 | 164 | 160 | 158 | 157 | - | |
| X6CrNiMoNb17-12-2 | 1.4580 | 207 | 185 | 177 | 167 | 157 | 145 | 140 | 135 | 131 | 129 | 127 | - | - | 244 | 218 | 206 | 196 | 186 | 175 | 169 | 164 | 160 | 158 | 157 | - | |
| X9CrMnNiCu17-8-5-2 | 1.4618 | 190 | 160 | 150 | 125 | 120 | 110 | 104 | 100 | 95 | 92 | 90 | - | - | 230 | 200 | 180 | 157 | 145 | 135 | 129 | 125 | 122 | 120 | 120 | - | |
| X6CrMnNiCuN18-2-4-2 | 1.4646 | - | 295 | 260 | 230 | 220 | 205 | 180 | - | - | - | - | - | - | 325 | 295 | 265 | 250 | 230 | 205 | - | - | - | - | - | | |
| Austenitic creep resisting grades | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| X3CrNiMoBN17-13-3 | 1.4910 | 239 | 205 | 187 | 170 | 159 | 148 | 141 | 134 | 130 | 127 | 124 | 121 | 277 | 240 | 220 | 200 | 189 | 178 | 171 | 164 | 160 | 157 | 154 | 151 | | |
| X6CrNiTiB18-10 | 1.4941 | 186 | 162 | 152 | 142 | 137 | 132 | 127 | 123 | 118 | 113 | 108 | 103 | 225 | 201 | 191 | 181 | 176 | 172 | 167 | 162 | 157 | 152 | 147 | 142 | | |
| X6CrNi18-10 | 1.4948 | 178 | 157 | 142 | 127 | 117 | 108 | 103 | 98 | 93 | 88 | 83 | 78 | 215 | 191 | 172 | 157 | 147 | 137 | 132 | 127 | 122 | 118 | 113 | 108 | | |
| X6CrNi23-13 | 1.4950 | 177 | 140 | 128 | 116 | 108 | 100 | 94 | 91 | 86 | 85 | 84 | 82 | 219 | 185 | 167 | 154 | 146 | 139 | 132 | 126 | 121 | 118 | 114 | - | | |
| X6CrNi25-20 | 1.4951 | 177 | 140 | 128 | 116 | 108 | 100 | 94 | 91 | 86 | 85 | 84 | 82 | 219 | 185 | 167 | 154 | 146 | 139 | 132 | 126 | 123 | 121 | 118 | 114 | | |
| X5NiCrAlTi31-20 | 1.4958 | 159 | 140 | 127 | 115 | 105 | 95 | 90 | 85 | 82 | 80 | 75 | 75 | 185 | 160 | 147 | 135 | 125 | 115 | 110 | 105 | 102 | 100 | 95 | 95 | | |

(to be continued)

| Steel grade | Steel name | Minimum 0,2 % proof strength $R_{p0,2}$, MPa | | | | | | | | | | Minimum 1,0 % proof strength $R_{p1,0}$, MPa | | | | | | | | | | | | | |
|--------------------|---------------|-----------------------------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----------------------------------------------|-----|-----------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| | | 50 ^b | 100 | 150 | 200 | 250 | 300 | 350 | 400 | 450 | 500 | 550 | 600 | 50 ^b | 100 | 150 | 200 | 250 | 300 | 350 | 400 | 450 | 500 | 550 | 600 |
| X5NiCrAlTi31-20+RA | 1.4958+ RA | 199 | 180 | 170 | 160 | 152 | 145 | 137 | 130 | 125 | 120 | 115 | 110 | 227 | 205 | 193 | 180 | 172 | 165 | 160 | 155 | 150 | 145 | 140 | 135 |
| X8NiCrAlTi32-21 | 1.4959 | 159 | 140 | 127 | 115 | 105 | 95 | 90 | 85 | 82 | 80 | 75 | 75 | 185 | 160 | 147 | 135 | 125 | 115 | 110 | 105 | 102 | 100 | 95 | 95 |
| X8CrNiNb16-13 | 1.4961 | 191 | 175 | 166 | 157 | 147 | 137 | 132 | 128 | 123 | 118 | 118 | 113 | 227 | 205 | 195 | 186 | 176 | 167 | 162 | 157 | 152 | 147 | 147 | 142 |

a The values apply to longitudinal and transversal direction.

b Value determined by linear interpolation.

Table 14 — Minimum values for the 0,2 % proof strength of austenitic-ferritic steels at elevated temperatures in the solution annealed condition (see Table A.4)^a

| Steel grade | | Minimum 0,2 % proof strength $R_{p0,2}$, MPa | | | | |
|------------------------------------|--------------|-----------------------------------------------|-----|-----|-----|-----|
| Steel name | Steel number | at a temperature (in °C) of | | | | |
| | | 50 ^b | 100 | 150 | 200 | 250 |
| X2CrNiN22-2 ^c | 1.4062 | - | 380 | 350 | 330 | 315 |
| X2CrMnNiN21-5-1 ^{c,d} | 1.4162 | 430 | 380 | 350 | 330 | 320 |
| X2CrNiN23-4 | 1.4362 | 374 | 330 | 300 | 280 | 265 |
| X2CrNiMoN25-7-4 | 1.4410 | 500 | 450 | 420 | 400 | 380 |
| X2CrNiMoN22-5-3 | 1.4462 | 422 | 360 | 335 | 315 | 300 |
| X2CrMnNiMoN21-5-3 | 1.4482 | 390 | 340 | 315 | 300 | 280 |
| X2CrNiMoCuWN25-7-4 | 1.4501 | 500 | 450 | 420 | 400 | 380 |
| X2CrNiMoCuN25-6-3 | 1.4507 | 475 | 450 | 420 | 400 | 380 |
| X2CrNiMnMoCuN24-4-3-2 ^c | 1.4662 | - | 385 | 345 | 325 | 315 |

^a The values apply to longitudinal and transversal direction.
^b Value determined by linear interpolation.
^c Patented steel
^d The values in table are valid only for product forms C and H. Corresponding values for quarto plate P are: 430, 380, 340, 310 and 290 MPa for thicknesses $t \leq 15$ mm; 415, 365, 325, 295 and 275 MPa for thicknesses 15 mm < $t \leq 40$ mm; and 400, 350, 310, 280 and 260 MPa for thicknesses 40 mm < $t \leq 75$ mm.

Table 15 — Minimum values for the tensile strength of austenitic steels at elevated temperatures in the solution annealed condition (see Table A.3)^a

| Steel grade | | Minimum tensile strength R_m , MPa | | | | | | | | | | | |
|---------------------------------------|--------------|--------------------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Steel name | Steel number | at a temperature (in °C) of | | | | | | | | | | | |
| | | 50 ^b | 100 | 150 | 200 | 250 | 300 | 350 | 400 | 450 | 500 | 550 | 600 |
| Austenitic corrosion resisting grades | | | | | | | | | | | | | |
| X5CrNi18-10 | 1.4301 | 494 | 450 | 420 | 400 | 390 | 380 | 380 | 380 | 370 | 360 | 330 | - |
| X2CrNi19-11 | 1.4306 | 466 | 410 | 380 | 360 | 350 | 340 | 340 | - | - | - | - | - |
| X2CrNi18-9 | 1.4307 | 466 | 410 | 380 | 360 | 350 | 340 | 340 | - | - | - | - | - |
| X2CrNiN18-10 | 1.4311 | 527 | 490 | 460 | 430 | 420 | 410 | 410 | - | - | - | - | - |
| X5CrNiN19-9 | 1.4315 | 527 | 490 | 460 | 430 | 420 | 410 | 410 | - | - | - | - | - |
| X2CrNiN18-7 | 1.4318 | 605 | 530 | 490 | 460 | 450 | 440 | 430 | - | - | - | - | - |
| X1CrNi25-21 | 1.4335 | 459 | 440 | 425 | 410 | 390 | 385 | 380 | - | - | - | - | - |
| X1CrNiSi18-15-4 | 1.4361 | 515 | 490 | 470 | 450 | 435 | 420 | 410 | 400 | - | - | - | - |
| X2CrMnNiN17-7-5 | 1.4371 | 527 | 490 | 460 | 430 | 420 | 410 | 400 | 380 | 370 | 360 | 330 | - |
| X12CrMnNiN17-7-5 | 1.4372 | 640 | 560 | 520 | 500 | 480 | 470 | 460 | - | - | - | - | - |
| X5CrNiMo17-12-2 | 1.4401 | 486 | 430 | 410 | 390 | 385 | 380 | 380 | - | - | - | - | - |
| X2CrNiMo17-12-2 | 1.4404 | 486 | 430 | 410 | 390 | 385 | 380 | 380 | 380 | - | 360 | - | - |
| X2CrNiMoN17-11-2 | 1.4406 | 557 | 520 | 490 | 460 | 450 | 440 | 435 | - | - | - | - | - |
| X2CrNiMoN21-9-1 | 1.4420 | 615 | 565 | 535 | 505 | 495 | 480 | 475 | 465 | 455 | 445 | 425 | - |
| X2CrNiMoN17-13-3 | 1.4429 | 557 | 520 | 490 | 460 | 450 | 440 | 435 | 435 | - | 430 | - | - |
| X2CrNiMo17-12-3 | 1.4432 | 486 | 430 | 410 | 390 | 385 | 380 | 380 | 380 | - | 360 | - | - |
| X2CrNiMoN18-12-4 | 1.4434 | 525 | 500 | 470 | 440 | 430 | 420 | 415 | 415 | 415 | 410 | 390 | - |
| X2CrNiMo18-14-3 | 1.4435 | 482 | 420 | 400 | 380 | 375 | 370 | 370 | - | - | - | - | - |
| X3CrNiMo17-13-3 | 1.4436 | 504 | 460 | 440 | 420 | 415 | 410 | 410 | 410 | - | 390 | - | - |
| X2CrNiMo18-15-4 | 1.4438 | 486 | 430 | 410 | 390 | 385 | 380 | 380 | - | - | - | - | - |
| X2CrNiMoN17-13-5 | 1.4439 | 557 | 520 | 490 | 460 | 450 | 440 | 435 | - | - | - | - | - |
| X1CrNiMoN25-22-2 | 1.4466 | 521 | 490 | 475 | 460 | 450 | 440 | 435 | - | - | - | - | - |
| X1NiCrMoCuN25-20-7 | 1.4529 | 612 | 550 | 535 | 520 | 500 | 480 | 475 | - | - | - | - | - |
| X1CrNiMoCuN25-25-5 | 1.4537 | 581 | 550 | 535 | 520 | 500 | 480 | 475 | - | - | - | - | - |
| X1NiCrMoCu25-20-5 | 1.4539 | 512 | 500 | 480 | 460 | 450 | 440 | 435 | - | - | - | - | - |
| X6CrNiTi18-10 | 1.4541 | 477 | 440 | 410 | 390 | 385 | 375 | 375 | 375 | 370 | 360 | 330 | - |
| X1CrNiMoCuN20-18-7 | 1.4547 | 637 | 615 | 587 | 560 | 542 | 525 | 517 | 510 | 502 | 495 | - | - |
| X6CrNiNb18-10 | 1.4550 | 476 | 435 | 400 | 370 | 350 | 340 | 335 | 330 | 320 | 310 | 300 | - |
| X1NiCrMoCu31-27-4 | 1.4563 | 485 | 460 | 445 | 430 | 410 | 400 | 395 | - | - | - | - | - |
| X6CrNiMoTi17-12-2 | 1.4571 | 490 | 440 | 410 | 390 | 385 | 375 | 375 | 375 | 370 | 360 | 330 | - |
| X6CrNiMoNb17-12-2 | 1.4580 | 490 | 440 | 410 | 390 | 385 | 375 | 375 | 375 | 370 | 360 | 330 | - |
| X9CrMnNiCu17-8-5-2 | 1.4618 | 500 | 450 | 420 | 400 | 390 | 380 | 380 | 380 | 370 | 360 | 330 | - |
| Austenitic creep resisting grades | | | | | | | | | | | | | |
| X3CrNiMoBN17-13-3 | 1.4910 | 529 | 495 | 472 | 450 | 440 | 430 | 425 | 420 | 410 | 400 | 385 | 365 |
| X6CrNiTiB18-10 | 1.4941 | 460 | 410 | 390 | 370 | 360 | 350 | 345 | 340 | 335 | 330 | 320 | 300 |
| X6CrNi18-10 | 1.4948 | 484 | 440 | 410 | 390 | 385 | 375 | 375 | 375 | 370 | 360 | 330 | 300 |
| X6CrNi23-13 | 1.4950 | 495 | 470 | 450 | 430 | 420 | 410 | 405 | 400 | 385 | 370 | 350 | 320 |
| X6CrNi25-20 | 1.4951 | 495 | 470 | 450 | 430 | 420 | 410 | 405 | 400 | 385 | 370 | 350 | 320 |
| X5NiCrAlTi31-20 ^c | 1.4958 | 487 | 465 | 445 | 435 | 425 | 420 | 418 | 415 | 415 | 415 | - | - |
| X8NiCrAlTi32-21 | 1.4959 | 487 | 465 | 445 | 435 | 425 | 420 | 418 | 415 | 415 | 415 | - | - |
| X8CrNiNb16-13 | 1.4961 | 493 | 465 | 440 | 420 | 400 | 385 | 375 | 370 | 360 | 350 | 340 | 320 |

(to be continued)

- a The values apply to longitudinal and transversal direction.
- b Value determined by linear interpolation
- c The tensile strength values also apply for the recrystallizing annealed condition (+RA).

Table 16 — Tests to be carried out, test units and extent of testing

| Test | Test status ^a | Test unit | Product form | | Number of test pieces per test sample | |
|---------------------------------------------------|------------------------------------------------------------------|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|--|
| | | | Strip and sheet cut from strip in rolling width (C, H) | Rolled plate (P) | | |
| Chemical analysis | m | Cast | Cast analysis ^b | | | |
| Tensile test at room temperature | m Cast, thickness $\pm 10\%$, heat treatment batch | 1 test sample from each coil | a) Plates $\leq 20\text{ mm}$ ($\leq 15\text{ mm}^{\text{c}}$) thickness: Plates processed under identical conditions may be collected into a batch comprising not more than 20 plates. One test sample per batch shall be taken from heat treated plates up to 15 m in length. One test sample shall be taken from each end of the longest plate in the batch where heat treated plates are longer than 15 m. | b) Plates $> 20\text{ mm}$ ($> 15\text{ mm}^{\text{c}}$) thickness: Each single plate; one test sample shall be taken from heat treated plates up to 15 m long and one sample shall be taken from each end of heat treated plates longer than 15 m. | 1 | |
| Tensile test at elevated temperature ^d | | | | | | |
| Impact test at 20 °C | m ^e | | To be agreed at the time of enquiry and order. | | 1 | |
| Impact test at low temperature | o | | To be agreed at the time of enquiry and order. | | 3 | |
| Resistance to intergranular corrosion | o | | To be agreed at the time of enquiry and order. | | 1 | |
| Other tests | o | See EN 10028-1. | | | | |

^a Tests marked with an 'm' (mandatory) shall be carried out as acceptance tests. In all cases, those marked with an 'o' (optional) shall be carried out as acceptance tests only if agreed at the time of enquiry and order.

^b A product analysis may be agreed at the time of enquiry and order (see EN 10028-1).

^c Limit value for martensitic, ferritic and austenitic-ferritic steels.

^d See EN 10028-1.

^e For ferritic, martensitic and austenitic-ferritic grades $\geq 6\text{ mm}$ thickness and for austenitic grades for cryogenic service $> 20\text{ mm}$ thickness, optional for austenitic grades for other applications (see EN 10028-1).

Annex A (informative)

Guidelines for further treatment (including heat treatment in fabrication)

A.1 The guidelines given in Tables A.1 to A.4 are intended for hot forming and heat treatment.

Table A.1 — Guidelines on the temperatures for hot forming and heat treatment^a of ferritic stainless steels

| Steel grade | | Hot forming | | Heat treatment symbol ^b | Annealing | |
|------------------|--------------|----------------|-----------------|------------------------------------|-----------------------------|-----------------|
| Steel name | Steel number | Temperature °C | Type of cooling | | Temperature ^c °C | Type of cooling |
| X2CrNi12 | 1.4003 | 1 100 to 800 | air | +A | 700 to 750 | air, water |
| X2CrTiNb18 | 1.4509 | | | | 870 to 930 | |
| X3CrTi17 | 1.4510 | | | | 770 to 830 | |
| X2CrMoTi17-1 | 1.4513 | | | | 790 to 850 | |
| X6CrNiTi12 | 1.4516 | | | | 790 to 850 | |
| X2CrTi17 | 1.4520 | | | | 820 to 880 | |
| X2CrMoTi18-2 | 1.4521 | | | | 820 to 880 | |
| X6CrMoNb17-1 | 1.4526 | | | | 800 to 860 | |
| X2CrTi21 | 1.4611 | | | | 870 to 930 | |
| X2CrTi24 | 1.4613 | | | | 870 to 930 | |
| X2CrCuNbTiV2 2-1 | 1.4622 | | | | 870 to 930 | |

^a The temperatures of annealing should be agreed for simulated heat treated test pieces.
^b +A = annealed.
^c If heat treatment is carried out in a continuous furnace, the upper part of the range specified is usually preferred, or even exceeded.

Table A.2 — Guidelines on the temperatures for hot forming and heat treatment^a of martensitic stainless steels

| Steel grade | | Hot forming | | Heat treatment symbol ^b | Quenching | | Tempering |
|----------------|--------------|----------------|-----------------|------------------------------------|----------------|--------------------|----------------|
| Steel name | Steel number | Temperature °C | Type of cooling | | Temperature °C | Type of cooling | Temperature °C |
| X3CrNiMo13-4 | 1.4313 | 1 150 to 900 | air | +QT | 950 to 1 050 | oil, air, water | 560 to 640 |
| X4CrNiMo16-5-1 | 1.4418 | | | +QT | 900 to 1 000 | | 570 to 650 |

^a The temperatures of annealing should be agreed for simulated heat treated test pieces.
^b +QT = quenched and tempered.
^c If heat treatment is carried out in a continuous furnace, the upper part of the range specified is usually preferred, or even exceeded.

Table A.3 — Guidelines on the temperatures for hot forming and heat treatment^a of austenitic stainless steels

| Steel grade | | Hot forming | | Heat treatment symbol ^b | Solution annealing ^c (but see footnote g) | |
|----------------------------------------------|--------------|----------------|-----------------|------------------------------------|------------------------------------------------------|-------------------------|
| Steel name | Steel number | Temperature °C | Type of cooling | | Temperature ^{d,e} °C | Type of cooling |
| Austenitic corrosion resisting grades | | | | | | |
| X5CrNi18-10 | 1.4301 | 1 150 to 850 | air | +AT | 1 000 to 1 100 | water, air ^f |
| X2CrNi19-11 | 1.4306 | | | | 1 000 to 1 100 | |
| X2CrNi18-9 | 1.4307 | | | | 1 000 to 1 100 | |
| X2CrNiN18-10 | 1.4311 | | | | 1 000 to 1 100 | |
| X5CrNiN19-9 | 1.4315 | | | | 1 000 to 1 100 | |
| X2CrNiN18-7 | 1.4318 | | | | 1 020 to 1 100 | |
| X1CrNi25-21 | 1.4335 | | | | 1 030 to 1 110 | |
| X1CrNiSi18-15-4 | 1.4361 | | | | 1 100 to 1 160 | |
| X2CrMnNiN17-7-5 | 1.4371 | | | | 1 000 to 1 100 | |
| X12CrMnNiN17-7-5 | 1.4372 | | | | 1 000 to 1 100 | |
| X5CrNiMo17-12-2 | 1.4401 | | | | 1 030 to 1 110 | |
| X2CrNiMo17-12-2 | 1.4404 | | | | 1 030 to 1 110 | |
| X2CrNiMoN17-11-2 | 1.4406 | | | | 1 030 to 1 110 | |
| X2CrNiMoN17-13-3 | 1.4429 | | | | 1 030 to 1 110 | |
| X2CrNiMoN21-9-1 | 1.4420 | | | | 1 030 to 1 110 | |
| X2CrNiMo17-12-3 | 1.4432 | | | | 1 030 to 1 110 | |
| X2CrNiMoN18-12-4 | 1.4434 | | | | 1 070 to 1 150 | |
| X2CrNiMo18-14-3 | 1.4435 | | | | 1 030 to 1 110 | |
| X3CrNiMo17-13-3 | 1.4436 | | | | 1 030 to 1 110 | |
| X2CrNiMo18-15-4 | 1.4438 | | | | 1 070 to 1 150 | |
| X2CrNiMoN17-13-5 | 1.4439 | | | | 1 060 to 1 140 | |
| X1CrNiMoN25-22-2 | 1.4466 | | | | 1 070 to 1 150 | |
| X1NiCrMoCuN25-20-7 | 1.4529 | | | | 1 120 to 1 180 | |
| X1CrNiMoCuN25-25-5 | 1.4537 | | | | 1 120 to 1 180 | |
| X1NiCrMoCu25-20-5 | 1.4539 | | | | 1 060 to 1 140 | |
| X6CrNiTi18-10 | 1.4541 | | | | 1 000 to 1 100 | |
| X1CrNiMoCuN20-18-7 | 1.4547 | | | | 1 140 to 1 200 | |
| X6CrNiNb18-10 | 1.4550 | | | | 1 020 to 1 120 | |
| X1NiCrMoCu31-27-4 | 1.4563 | | | | 1 070 to 1 150 | |
| X6CrNiMoTi17-12-2 | 1.4571 | | | | 1 030 to 1 110 | |
| X6CrNiMoNb17-12-2 | 1.4580 | | | | 1 030 to 1 110 | |
| X9CrMnNiCu17-8-5-2 | 1.4618 | | | | 1 000 to 1 100 | |
| X6CrMnNiCuN18-12-4-2 | 1.4646 | | | | 1 000 to 1 100 | |
| Austenitic creep resisting grades | | | | | | |
| X3CrNiMoBN17-13-3 | 1.4910 | 1 150 to 850 | air | +AT | 1 020 to 1 100 | water, air ^f |
| X6CrNiTiB18-10 | 1.4941 | | | | 1 050 to 1 110 | |
| X6CrNi18-10 | 1.4948 | | | | 1 050 to 1 110 | |
| X6CrNi23-13 | 1.4950 | | | | 1 050 to 1 150 | |

| | | | | | |
|--------------------|--------------|--|--|----------------|-----------------------------|
| X6CrNi25-20 | 1.4951 | | | 1 050 to 1 150 | |
| X5NiCrAlTi31-20 | 1.4958 | | | 1 100 to 1 200 | |
| X5NiCrAlTi31-20+RA | 1.4958 (+RA) | | | +RA | 920 to 1 000 ^g |
| X8NiCrAlTi32-21 | 1.4959 | | | +AT | 1 100 to 1 200 ^h |
| X8CrNiNb16-13 | 1.4961 | | | | 1 050 to 1 110 |

^a The temperatures of annealing should be agreed for simulated heat treated test pieces.
^b +AT = solution annealed, +RA = re-crystallizing annealed.
^c The solution treatment may be omitted if the conditions for hot working and subsequent cooling are such that the requirements for the mechanical properties of the product and the resistance to intergranular corrosion as defined in EN ISO 3651-2 are obtained and provided these requirements are met even after appropriate subsequent solution annealing.
^d If heat treatment is carried out in a continuous furnace, the upper part of the range specified is usually preferred, or even exceeded.
^e The lower end of the range specified for solution annealing should be aimed at for heat treatment as part of further processing, because otherwise the mechanical properties might be affected. If the temperature of hot forming does not drop below the lower temperature for solution annealing, a temperature of 980 °C is adequate as a lower limit for Mo-free steels, a temperature of 1000 °C for steels with Mo contents up to 3 % and a temperature of 1 020 °C for steels with Mo contents exceeding 3 %.
^f Cooling sufficiently rapid.
^g Re-crystallizing annealing.
^h After solution annealing the grain size according to EN ISO 643 shall be 1 to 5.

Table A.4 — Guidelines on the temperatures for hot forming and heat treatment^a of austenitic-ferritic stainless steels

| Steel grade | | Hot forming | | Heat treatment | Solution annealing ^c | |
|--------------------|--------------|----------------|-----------------|----------------|---------------------------------|-----------------|
| | | Temperature °C | Type of cooling | | Temperature ^d °C | Type of cooling |
| Steel name | Steel number | | | | | |
| X2CrNiN22-2 | 1.4062 | 1 100 to 950 | air | +AT | 980 to 1 100 | water, air |
| X2CrMnNiN21-5-1 | 1.4162 | 1 100 to 900 | air | +AT | 1 020 to 1 100 | water, air |
| X2CrNiN23-4 | 1.4362 | 1 150 to 950 | air | +AT | 950 to 1 050 | water, air |
| X2CrNiMoN25-7-4 | 1.4410 | 1 150 to 1 000 | air | +AT | 1 040 to 1 120 | water, air |
| X2CrNiMoN22-5-3 | 1.4462 | 1 150 to 950 | air | +AT | 1 020 to 1 100 | water, air |
| X2CrMnNiMoN21-5-3 | 1.4482 | 1 150 to 950 | air | +AT | 900 to 1 050 | water, air |
| X2CrNiMoCuWN25-7-4 | 1.4501 | 1 150 to 1 000 | air | +AT | 1 040 to 1 120 | water, air |
| X2CrNiMoCuN25-6-3 | 1.4507 | | | | | |

^a The temperatures of annealing, should be agreed for simulated heat treated test pieces.
^b +AT = Solution annealed.
^c Solution annealing in the range specified followed by sufficiently rapid cooling to avoid precipitation of deleterious phases is essential after hot forming these steels.
^d If heat treatment is carried out in a continuous furnace, the upper part of the range specified is usually preferred, or even exceeded.

A.2 Flame cutting may adversely affect edge areas; they should be machined.

A.3 Scale and annealing colours produced during hot forming, heat treatment or welding may adversely affect the corrosion resistance. They should be removed as far as possible before use, e.g. by pickling.

A.4 For further information see EN 1011-3 [1].

Annex B (informative)

Post weld heat treatment

B.1 In general, welded assemblies of stainless steels covered by this European Standard are not subjected to any heat treatment with the following exceptions:

- martensitic grades are retempered and
- ferritic grades are reannealed

if there is any risk of residual martensite in the heat affected zone; for appropriate temperatures see Tables A.1 and A.2.

B.2 During heating of high chromium and molybdenum austenitic-ferritic or austenitic steel weldments containing some ferrite, intermetallic phases may be formed which need to be re-dissolved during post weld heat treatment. As most filler metals are overalloyed in comparison with the equivalent basic grades, minimum solution temperatures higher than those given in Tables A.3 and A.4 may be necessary.

In the case of fully austenitic weld structures it should be verified that mechanical properties of heat treated weldments conform to this European Standard.

Oxidation of surfaces which necessitates pickling, and possible distortion of the welded construction may raise further difficulties.

Consequently post weld heat treatment of duplex and austenitic steels should be avoided, and therefore welding be planned carefully.

B.3 In special cases, e.g. for parts with greater wall thickness, requirements concerning stress-relief and resistance to intergranular corrosion, in order to avoid failure by stress corrosion cracking or corrosion fatigue, may prove the necessity for post weld heat treatment. This should be carried out according to Table B.1 by holding at an intermediate stage below the usual solution temperature (see Table A.3) and is defined as stabilizing annealing for the niobium or titanium bearing grades and as stress-relieving for the un-stabilized low carbon grades.

In some cases post weld heat treatment may also be performed as solution annealing according to Table A.3 or at a temperature below the precipitation range of carbides and intermetallic phases; however, the latter reduces only peak stresses.

B.4 Preheating of austenitic-ferritic steels is a very effective precaution against stress increase by shrinkage of thicker welded cross-sections, because temperatures of 200 °C to 250 °C bring down room temperature yield strength by about 50 %. Thus preheating is often more appropriate to avoid high stress levels in those weldments than any post weld heat treatment, and a preheating temperature between 120 °C and 200 °C according to the particular steel and thickness should be applied.

The same is advisable for complex welds of austenitic steels.

Table B.1 — Guideline on post weld heat treatment of austenitic steels

| Steel grade | | Temperature ^a °C | Type of cooling |
|---------------------------------------------------------|--------------|--------------------------------|-----------------|
| Steel name | Steel number | | |
| Stabilized steels | | | |
| X6CrNiTi18-10 | 1.4541 | 900 to 940 | air |
| X6CrNiNb18-10 | 1.4550 | | |
| X6CrNiMoTi17-12-2 | 1.4571 | not recommended | - |
| X6CrNiMoNb17-12-2 | 1.4580 | | |
| Steels with ≤ 0,07 % C | | | |
| X5CrNi18-10 | 1.4301 | not recommended | - |
| X5CrNiN19-9 | 1.4315 | | |
| X5CrNiMo17-12-2 | 1.4401 | | |
| X3CrNiMo17-13-3 | 1.4436 | | |
| X9CrMnNiCu17-8-5-2 | 1.4618 | | |
| Steels with ≤ 0,03 % C | | | |
| X2CrNi19-11 | 1.4306 | 900 to 940 | air |
| X2CrNi18-9 | 1.4307 | | |
| X2CrNiN18-10 | 1.4311 | | |
| X2CrNiN18-7 | 1.4318 | | |
| X2CrMnNiN17-7-5 | 1.4371 | | |
| X2CrNiMo17-12-2 | 1.4404 | 960 to 1 040 ^c | forced air |
| X2CrNiMoN17-11-2 | 1.4406 | | |
| X2CrNiMoN21-9-1 | 1.4420 | | |
| X2CrNiMoN17-13-3 | 1.4429 | | |
| X2CrNiMo17-12-3 | 1.4432 | | |
| X2CrNiMoN18-12-4 | 1.4434 | | |
| X2CrNiMo18-14-3 | 1.4435 | | |
| X2CrNiMo18-15-4 | 1.4438 | | |
| X2CrNiMoN17-13-5 | 1.4439 | | |
| X1CrNiSi18-15-4 | 1.4361 | | |
| Steels with ≤ 0,15 % C | | | |
| X12CrMnNiN17-7-5 | 1.4372 | not recommended | - |
| Higher alloyed austenitic steels with ≤ 0,02 % C | | | |
| X1CrNi25-21 | 1.4335 | not recommended | - |
| X1CrNiMoN25-22-2 | 1.4466 | | |
| X1NiCrMoCuN25-20-7 | 1.4529 | | |
| X1CrNiMoCuN25-25-5 | 1.4537 | | |
| X1NiCrMoCu25-20-5 | 1.4539 | | |
| X1CrNiMoCuN20-18-7 | 1.4547 | | |
| X1NiCrMoCu31-27-4 | 1.4563 | | |
| Creep resisting steels | | | |
| X3CrNiMoBN17-13-3 | 1.4910 | 900 to 950 ^b | air |
| X6CrNiTiB18-10 | 1.4941 | | |
| X6CrNi18-10 | 1.4948 | not recommended | |
| X6CrNi23-13 | 1.4950 | | |
| X6CrNi25-20 | 1.4951 | | |
| X5NiCrAlTi31-20 (+RA) | 1.4958 (+RA) | | |
| X8NiCrAlTi32-21 | 1.4959 | 900 to 950 ^b | air |
| X8CrNiNb16-13 | 1.4961 | | |

^a Minimum holding time: 30 min.

^b Recommended for components with greater wall thickness.

^c Recommended if welded with stabilized filler metal.

Annex C
(informative)

Preliminary reference data for the tensile strength of austenitic-ferritic steels at elevated temperatures

Table C.1 — Minimum values for the tensile strength of austenitic-ferritic steels at elevated temperatures in the solution annealed condition (see Table A.4)

| Steel name | Steel number | Minimum tensile strength, MPa at a temperature (in °C) of | | | | |
|--------------------|--------------|--------------------------------------------------------------|-----|-----|-----|-----|
| | | 50 | 100 | 150 | 200 | 250 |
| X2CrNiN22-2 | 1.4062 | 630 | 590 | 560 | 540 | 540 |
| X2CrMnNiN21-5-1 | 1.4162 | 630 | 590 | 560 | 540 | 540 |
| X2CrNiN23-4 | 1.4362 | 577 | 540 | 520 | 500 | 490 |
| X2CrNiMoN25-7-4 | 1.4410 | 711 | 680 | 660 | 640 | 630 |
| X2CrNiMoN22-5-3 | 1.4462 | 621 | 590 | 570 | 550 | 540 |
| X2CrMnNiMoN21-5-3 | 1.4482 | 620 | 580 | 540 | 520 | 500 |
| X2CrNiMoCuWN25-7-4 | 1.4501 | 711 | 680 | 660 | 640 | 630 |
| X2CrNiMoCuN25-6-3 | 1.4507 | 679 | 660 | 640 | 620 | 610 |
| X2CrCuNbTiV22-1 | 1.4622 | 655 | 615 | 590 | 575 | 560 |

Annex D
(informative)

Reference data of strength values for 1 % (plastic) creep strain and creep rupture

NOTE 1 The values given in Tables D.1 and D.2 are mean values of the scatter band considered until now. If these are referred to in regulations however, they will be binding for calculation purposes. According to experience with long-time creep-testing it seems apparent that scattering of data are about $\pm 20\%$ in the long-range endurance of about 10^5 h up to $700\text{ }^\circ\text{C}$ to $800\text{ }^\circ\text{C}$. Above that temperature, scattering may be gradually more or less enlarged and be summarized with about 35 % to 40 % at $1\ 000\text{ }^\circ\text{C}$ testing temperature. However, individual deviations need to be presumed.

NOTE 2 The strength values for 1 % (plastic) creep strain and creep rupture given up to the elevated temperatures listed in Tables D.1 and D.2 do not mean that the steels can be used in continuous duty up to these temperatures. The governing factor is the total stressing during operation. Where relevant it is important that the oxidation conditions are taken into account.

Table D.1 — Strength for 1 % (plastic) creep strain of austenitic creep resisting steels in the solution annealed condition (see Table A.3)

| Steel grade | | Temperature | Strength for 1 % (plastic) creep strain ^a in MPa for | |
|-----------------------------|--------------|-------------|-----------------------------------------------------------------------|-----------|
| Steel name | Steel number | °C | 10 000 h | 100 000 h |
| X6CrNi18-10 ^b | 1.4948 | 500 | 147 | 114 |
| | | 510 | 142 | 111 |
| | | 520 | 137 | 108 |
| | | 530 | 132 | 104 |
| | | 540 | 127 | 100 |
| | | 550 | 121 | 96 |
| | | 560 | 116 | 92 |
| | | 570 | 111 | 88 |
| | | 580 | 106 | 84 |
| | | 590 | 100 | 79 |
| | | 600 | 94 | 74 |
| | | 610 | 88 | 69 |
| | | 620 | 82 | 63 |
| | | 630 | 75 | 56 |
| X6CrNi23-13 ^c | 1.4950 | 640 | 68 | 49 |
| | | 650 | 61 | 43 |
| | | 660 | 55 | 37 |
| | | 670 | 49 | 32 |
| | | 680 | 44 | 28 |
| | | 690 | 39 | 25 |
| | | 700 | 35 | 22 |
| | | 710 | (31) | (15) |
| | | 720 | (28) | (14) |
| | | 730 | (26) | (13) |
| X5NiCrAlTi31-2 ^b | 1.4958 | 740 | (25) | (12) |
| | | 750 | (24) | (11) |
| | | 550 | 107 | 60 |
| | | 600 | 80 | 35 |
| | | 650 | 50 | 22 |
| | | 700 | 25 | 12 |
| | | 750 | - | - |
| | | 800 | 10 | - |
| | | 600 | 115 | (85) |
| | | 610 | 109 | (79) |
| | | 620 | 102 | (74) |
| | | 630 | 96 | (69) |
| | | 640 | 90 | (64) |
| | | 650 | 84 | (59) |
| | | 660 | 78 | (55) |
| | | 670 | 73 | (51) |
| | | 680 | 68 | (47) |
| | | 690 | 63 | (43) |
| | | 700 | 58 | (40) |

| | | | | |
|-------------------------------------|-------------|------|------|-------|
| X5NiCrAlTi31-20 +RA ^b | 1.4958 + RA | 550 | 164 | (132) |
| | | 560 | 154 | (122) |
| | | 570 | 144 | (111) |
| | | 580 | 133 | (101) |
| | | 590 | 123 | (92) |
| | | 600 | 113 | (82) |
| | | 610 | 103 | (74) |
| | | 620 | 93 | (65) |
| | | 630 | 84 | (58) |
| | | 640 | 75 | (51) |
| X8NiCrAlTi32-21 ^b | 1.4959 | 650 | 67 | (46) |
| | | 660 | 60 | (41) |
| | | 670 | 55 | (37) |
| | | 680 | 50 | (33) |
| | | 690 | 45 | (30) |
| | | 700 | 41 | (27) |
| | | 700 | 59,0 | 42,0 |
| | | 710 | 55,5 | 38,0 |
| | | 720 | 52,0 | 34,4 |
| | | 730 | 48,5 | 31,3 |
| X8CrNiNb16-13 ^b | 1.4961 | 740 | 45,0 | 28,4 |
| | | 750 | 41,7 | 26,0 |
| | | 760 | 38,4 | 23,5 |
| | | 770 | 35,6 | 21,3 |
| | | 780 | 32,9 | 19,3 |
| | | 790 | 30,5 | 17,6 |
| | | 800 | 28,2 | 16,0 |
| | | 810 | 26,2 | 14,7 |
| | | 820 | 24,2 | 13,4 |
| | | 830 | 22,4 | 12,1 |
| | | 840 | 20,8 | 11,1 |
| | | 850 | 19,1 | 10,0 |
| | | 860 | 17,6 | 9,1 |
| | | 870 | 16,1 | 8,2 |
| | | 880 | 14,7 | 7,3 |
| | | 890 | 13,4 | 6,5 |
| | | 900 | 12,1 | 5,7 |
| | | 910 | 10,9 | 5,0 |
| | | 920 | 9,8 | 4,4 |
| | | 930 | 8,8 | 3,9 |
| | | 940 | 7,8 | 3,4 |
| | | 950 | 6,9 | 2,9 |
| | | 960 | 6,1 | 2,5 |
| | | 970 | 5,3 | 2,1 |
| | | 980 | 4,6 | 1,8 |
| | | 990 | 4,0 | 1,6 |
| | | 1000 | 3,5 | 1,4 |
| | | 580 | 127 | 91 |
| | | 590 | 120 | 84 |
| | | 600 | 113 | 78 |
| | | 610 | 106 | 73 |
| | | 620 | 99 | 67 |
| | | 630 | 92 | 61 |
| | | 640 | 85 | 55 |
| | | 650 | 78 | 49 |

| | | |
|-----|----|----|
| 660 | 72 | 44 |
| 670 | 66 | 39 |
| 680 | 59 | 34 |
| 690 | 54 | 30 |
| 700 | 49 | 26 |
| 710 | 45 | 24 |
| 720 | 42 | 21 |
| 730 | 39 | 19 |
| 740 | 36 | 17 |
| 750 | 34 | 16 |

a Values in parentheses involved extended time and/or stress extrapolation.
b Values were taken from DIN 17460 [3]
c Those preliminary values were taken from NF A 36-209 [4].

Table D.2 — Creep rupture strength of austenitic creep-resisting steels in the solution annealed condition (see Table A.3)

| Steel grade | | Tempe- rature | Strength for rupture ^a in MPa for | | | | | | |
|------------------------------------|-----------------|------------------|----------------------------------------------|-------------|-------------|--------------|--------------|--------------|-----------|
| Steel name | Steel number | | 10 000 h | 30 000 h | 50 000 h | 100 000 h | 150 000 h | 200 000 h | 250 000 h |
| X3CrNiMoBN17- 13-3 ^b | 1.4910 | 550 | 290 | | | 220 | | 200* | |
| | | 560 | 272 | | | 202 | | 184* | |
| | | 570 | 254 | | | 186 | | 166* | |
| | | 580 | 237 | | | 170 | | 151* | |
| | | 590 | 220 | | | 155 | | 137* | |
| | | 600 | 205 | | | 141 | | 122* | |
| | | 610 | 190 | | | 127 | | 113* | |
| | | 620 | 174 | | | 114 | | 100* | |
| | | 630 | 162 | | | 102 | | 91* | |
| | | 640 | 148 | | | 92 | | 81* | |
| | | 650 | 135 | | | 83 | | 73* | |
| | | 660 | 122 | | | 75 | | 65* | |
| | | 670 | 112 | | | 68 | | 58* | |
| | | 680 | 102 | | | 61 | | 52* | |
| | | 690 | 93 | | | 56 | | 46* | |
| | | 700 | 84 | | | 52 | | 42* | |
| | | 710 | 78 | | | 48 | | 39* | |
| | | 720 | 71 | | | 45 | | 36* | |
| | | 730 | 65 | | | 41 | | 34* | |
| | | 740 | 58 | | | 37 | | 31* | |
| | | 750 | 52 | | | 34 | | 28* | |
| | | 760 | 48 | | | 31 | | 26* | |
| | | 770 | 44 | | | 28 | | 24* | |
| | | 780 | 41 | | | 25 | | 21* | |
| | | 790 | 37 | | | 22 | | 19* | |
| | | 800 | 33 | | | 20 | | 17* | |
| X6CrNiTiB18-10 ^b | 1.4941 | 550 | 223 | | | 170 | | 150 | |
| | | 560 | 210 | | | 154 | | 135 | |
| | | 570 | 196 | | | 140 | | 122 | |
| | | 580 | 182 | | | 127 | | 110 | |
| | | 590 | 170 | | | 114 | | 100 | |
| | | 600 | 156 | | | 102 | | 91 | |
| | | 610 | 142 | | | 92 | | 82 | |
| | | 620 | 130 | | | 84 | | 74 | |
| | | 630 | 119 | | | 76 | | 67 | |
| | | 640 | 108 | | | 68 | | 60 | |
| | | 650 | 98 | | | 62 | | 54 | |
| | | 660 | 89 | | | 56 | | 49 | |
| | | 670 | 80 | | | 50 | | 43 | |
| | | 680 | 73 | | | 44 | | 39 | |
| | | 690 | 66 | | | 39 | | 33 | |
| | | 700 | 60 | | | 35 | | 29 | |

(to be continued)

| Steel grade | | Temper- ature °C | Strength for rupture ^a in MPa for | | | | | | |
|--------------------------|-----------------|------------------------|----------------------------------------------|-------------|-------------|--------------|--------------|--------------|-----------|
| Steel name | Steel number | | 10 000 h | 30 000 h | 50 000 h | 100 000 h | 150 000 h | 200 000 h | 250 000 h |
| X6CrNi18-10 ^b | 1.4948 | 500 | 250 | | | 192 | | 176 | |
| | | 510 | 239 | | | 182 | | 166 | |
| | | 520 | 227 | | | 172 | | 156 | |
| | | 530 | 215 | 165 | 155 | 162 | | 146 | |
| | | 540 | 203 | | | 151 | | 136 | |
| | | 550 | 191 | | | 140 | | 125 | |
| | | 560 | 177 | 154 | 145 | 128 | | 114 | |
| | | 570 | 165 | 144 | 136 | 117 | | 104 | |
| | | 580 | 154 | 135 | 126 | 107 | | 95 | |
| | | 590 | 143 | 126 | 118 | 98 | | 86 | |
| | | 600 | 132 | 117 | 110 | 89 | | 78 | |
| | | 610 | 122 | 109 | 102 | 81 | | 70 | |
| | | 620 | 113 | 101 | 94 | 73 | | 62 | |
| | | 630 | 104 | 94 | 87 | 65 | | 55 | |
| | | 640 | 95 | | | 58 | | 49 | |
| | | 650 | 87 | | | 52 | | 43 | |
| X6CrNi23-13 ^c | 1.4950 | 660 | 80 | | | 47 | | 38 | |
| | | 670 | 73 | | | 42 | | 34 | |
| | | 680 | 67 | | | 37 | | 30 | |
| | | 690 | 61 | | | 32 | | 26 | |
| | | 700 | 55 | | | 28 | | 22 | |
| | | 710 | (45) | | | (22) | | | |
| | | 720 | (41) | | | (20) | | | |
| | | 730 | (38) | | | (18) | | | |
| | | 740 | (36) | | | (16) | | | |
| | | 750 | (34) | | | (15) | | | |
| X6CrNi25-20 ^d | 1.4951 | 550 | 160 | | | 90 | | | |
| | | 600 | 120 | | | 65 | | | |
| | | 650 | 70 | | | 35 | | | |
| | | 700 | 36 | | | 16 | | | |
| | | 750 | - | | | - | | | |
| | | 800 | 18 | | | 7,5 | | | |
| | | 600 | 137 | 113 | 104* | 92* | 89* | 82* | 79* |
| | | 610 | 120 | 98 | 90* | 79* | 74* | 71* | 68* |
| | | 620 | 105 | 85 | 78* | 69* | 64* | 61* | 59* |
| | | 630 | 92 | 75 | 68* | 60* | 56* | 54* | 52* |
| | | 640 | 81 | 66 | 60* | 53* | 50* | 47* | 46* |
| | | 650 | 72 | 58 | 53* | 47* | 44* | 42* | 41* |
| | | 660 | 64 | 52 | 47* | 42* | 39* | 38* | 36* |
| | | 670 | 57 | 46 | 42* | 38* | 35* | 34* | 33* |
| | | 680 | 51 | 42 | 38 | 34* | 32* | 31* | 29* |
| | | 690 | 47 | 38 | 35 | 31* | 29* | 28* | 27* |
| | | 700 | 42 | 34 | 32 | 28* | 26* | 25* | 24* |
| | | 710 | 39 | 31 | 29 | 26* | 24* | 23* | 22* |
| | | 720 | 35 | 29 | 26 | 23,5* | 22* | 21* | 20* |
| | | 730 | 32 | 27 | 24,5* | 22* | 20* | 19,5* | 18,5* |
| | | 740 | 30 | 24,5 | 22,5* | 20* | 18,5* | 18* | 17* |
| | | 750 | 28 | 22,5 | 21* | 18,5* | 17* | 16,5* | 16* |

(to be continued)

| Steel grade | | Tempe- rature | Strength for rupture ^a in MPa for | | | | | | |
|---------------------------------|-----------------|------------------|----------------------------------------------|-------------|-------------|-----------|--------------|-----------|--------------|
| Steel name | Steel number | | 10 000 h | 30 000 h | 50 000 h | 100 000 h | 150 000 h | 200 000 h | 250 000 h |
| X6CrNi25-20 ^d | 1.4951 | 760 | 26 | 21 | 19* | 17* | 16* | 15* | 14,5* |
| | | 770 | 24 | 19,5 | 18* | 15,5* | 14,5* | 14* | 13,5* |
| | | 780 | 22 | 18 | 16,5* | 14,5* | 13,5* | 13* | 12,5* |
| | | 790 | 21 | 17 | 15,5* | 13,5* | 12,5* | 12* | 11,5* |
| | | 800 | 19,5 | 15,5 | 14* | 12,5* | 11,5* | 11* | 10,5* |
| | | 810 | 18 | 14,5 | 13* | 11,5* | 10,5* | 10* | 9,5* |
| | | 820 | 17 | 13,5 | 12* | 10,5* | 10* | 9,5* | 9* |
| | | 830 | 16 | 12,5 | 11,5* | 10* | 9* | | |
| | | 840 | 15 | 12 | 10,5* | 9* | | | |
| | | 850 | 14 | 11 | 10* | | | | |
| | | 860 | 13 | 10 | 9* | | | | |
| | | 870 | 12 | 9,5 | | | | | |
| | | 880 | 11,5 | 9* | | | | | |
| | | 890 | 10,5 | | | | | | |
| | | 900 | 10,0 | | | | | | |
| | | 910 | 9,5 | | | | | | |
| X5NiCrAlTi31-20 | 1.4958 | 500 | 290 | | 215 | | (196) | | |
| | | 510 | 279 | | 205 | | (186) | | |
| | | 520 | 267 | | 195 | | (176) | | |
| | | 530 | 254 | | 184 | | (166) | | |
| | | 540 | 240 | | 172 | | (155) | | |
| | | 550 | 225 | | 160 | | (143) | | |
| | | 560 | 208 | | 147 | | (130) | | |
| | | 570 | 190 | | 133 | | (117) | | |
| | | 580 | 172 | | 119 | | (105) | | |
| | | 590 | 155 | | 106 | | (93) | | |
| | | 600 | 140 | | 95 | | (83) | | |
| | | 610 | 128 | | 85 | | (74) | | |
| | | 620 | 118 | | 78 | | (68) | | |
| | | 630 | 109 | | 72 | | (63) | | |
| | | 640 | 103 | | 67 | | (59) | | |
| | | 650 | 97 | | 63 | | (55) | | |
| X5NiCrAlTi31-20+RA ^b | 1.4958 +RA | 660 | 91 | | 59 | | (52) | | |
| | | 670 | 85 | | 55 | | (48) | | |
| | | 680 | 80 | | 52 | | (45) | | |
| | | 690 | 74 | | 48 | | (41) | | |
| | | 700 | 69 | | 44 | | (38) | | |
| | | 500 | 315 | | 258 | | (242) | | |
| | | 510 | 297 | | 241 | | (225) | | |
| | | 520 | 280 | | 224 | | (207) | | |
| | | 530 | 262 | | 206 | | (190) | | |
| | | 540 | 243 | | 189 | | (172) | | |
| | | 550 | 224 | | 171 | | (155) | | |
| | | 560 | 204 | | 153 | | (138) | | |
| | | 570 | 184 | | 136 | | (122) | | |
| | | 580 | 165 | | 119 | | (106) | | |
| | | 590 | 147 | | 104 | | (92) | | |
| | | 600 | 131 | | 90 | | (80) | | |
| | | 610 | 117 | | 79 | | (70) | | |
| | | 620 | 106 | | 70 | | (62) | | |
| | | 630 | 96 | | 62 | | (55) | | |
| | | 640 | 87 | | 56 | | (49) | | |
| | | 650 | 80 | | 51 | | (44) | | |

(to be continued)

| Steel grade | | Tempe- rature | Strength for rupture ^a in MPa for | | | | | | | |
|-------------------------------------|-----------------|------------------|----------------------------------------------|----------|----------|----------|-----------|-----------|-----------|-----------|
| Steel name | Steel number | | °C | 10 000 h | 30 000 h | 50 000 h | 100 000 h | 150 000 h | 200 000 h | 250 000 h |
| X5NiCrAlTi31- 20+RA ^c | 1.4958 +RA | 660 | 73 | | | | 46 | | (40) | |
| | | 670 | 67 | | | | 42 | | (36) | |
| | | 680 | 61 | | | | 38 | | (33) | |
| | | 690 | 55 | | | | 34 | | (29) | |
| | | 700 | 50 | | | | 30 | | (26) | |
| X8NiCrAlTi32- 21 ^e | 1.4959 | 700 | 73,0 | 58,2 | | | 44,8 | | 38,2* | |
| | | 710 | 67,8 | 54,0 | | | 41,4 | | 35,2* | |
| | | 720 | 63,0 | 50,1 | | | 38,3 | | 32,5* | |
| | | 730 | 58,5 | 46,5 | | | 35,4 | | 30,0* | |
| | | 740 | 54,4 | 43,1 | | | 32,8 | | 27,7* | |
| | | 750 | 50,6 | 40,0 | | | 30,3 | | 25,6* | |
| | | 760 | 47,0 | 37,1 | | | 28,0 | | 23,6* | |
| | | 770 | 43,7 | 34,4 | | | 25,9 | | 21,8* | |
| | | 780 | 40,7 | 31,9 | | | 24,0 | | 20,1* | |
| | | 790 | 37,8 | 29,6 | | | 22,1 | | 18,5* | |
| | | 800 | 35,2 | 27,4 | | | 20,4 | | 17,0* | |
| | | 810 | 32,7 | 25,4 | | | 18,9 | | 15,6* | |
| | | 820 | 30,4 | 23,6 | | | 17,4 | | 14,4* | |
| | | 830 | 28,3 | 21,8 | | | 16,0 | | 13,2* | |
| | | 840 | 26,3 | 20,2 | | | 14,8 | | 12,1* | |
| | | 850 | 24,4 | 18,7 | | | 13,6 | | 11,1* | |
| | | 860 | 22,7 | 17,3 | | | 12,5 | | 10,1* | |
| | | 870 | 21,0 | 16,0 | | | 11,5 | | 9,23* | |
| | | 880 | 19,5 | 14,8 | | | 10,5 | | 8,41* | |
| | | 890 | 18,1 | 13,6 | | | 9,60 | | 7,63* | |
| | | 900 | 16,8 | 12,6 | | | 8,76 | | 6,91* | |
| | | 910 | 15,6 | 11,6 | | | 7,98 | | 6,23* | |
| | | 920 | 14,4 | 10,6 | | | 7,25 | | 5,60* | |
| | | 930 | 13,3 | 9,77 | | | 6,57 | | 5,01* | |
| | | 940 | 12,3 | 8,95 | | | 5,93 | | 4,45* | |
| | | 950 | 11,4 | 8,19 | | | 5,33 | | 3,93* | |
| | | 960 | 10,5 | 7,47 | | | 4,77* | | 3,43* | |
| | | 970 | 9,63 | 6,80 | | | 4,23* | | 2,95* | |
| | | 980 | 8,85 | 6,17 | | | 3,73* | | | |
| | | 990 | 8,11 | 5,57 | | | 3,25* | | | |
| | | 1000 | 7,42 | 5,01 | | | 2,79* | | | |

(to be continued)

| Steel grade | | Temperature °C | Strength for rupture ^a in MPa for | | | | | | |
|----------------------------|-----------------|-------------------|----------------------------------------------|-------------|-------------|--------------|--------------|--------------|--------------|
| Steel name | Steel number | | 10 000 h | 30 000 h | 50 000 h | 100 000 h | 150 000 h | 200 000 h | 250 000 h |
| X8CrNiNb16-13 ^b | 1.4961 | 580 | 182 | | | 129 | | 115 | |
| | | 590 | 170 | | | 119 | | 105 | |
| | | 600 | 157 | | | 108 | | 94 | |
| | | 610 | 145 | | | 98 | | 85 | |
| | | 620 | 134 | | | 89 | | 77 | |
| | | 630 | 124 | | | 80 | | 69 | |
| | | 640 | 113 | | | 72 | | 61 | |
| | | 650 | 103 | | | 64 | | 53 | |
| | | 660 | 93 | | | 57 | | 47 | |
| | | 670 | 84 | | | 50 | | 41 | |
| | | 680 | 76 | | | 44 | | 36 | |
| | | 690 | 70 | | | 39 | | 31 | |
| | | 700 | 64 | | | 34 | | 27 | |
| | | 710 | 59 | | | 30 | | 25 | |
| | | 720 | 55 | | | 27 | | 22 | |
| | | 730 | 51 | | | 25 | | 19 | |
| | | 740 | 47 | | | 22 | | 17 | |
| | | 750 | 44 | | | 20 | | 15 | |

^a Values in parentheses involved time and/or stress extrapolation; values with asterisk involved time extrapolation.
^b Values were taken from DIN 17460 [3].
^c Those preliminary values were taken from NF A 36-209 [3].
^d Values were taken from BS PD 6525 Part 1 [4].
^e Values were prepared by ECCC, WG 3.3 [5].

Annex E
(informative)

Reference data on mechanical properties of austenitic steels at room temperature and at low temperatures

Table E.1 — Tensile properties at room temperature and at low temperatures

| Steel grade | 20 °C | | | | -80 °C | | | | -150 °C | | | | -196 °C | | | | | |
|---------------|------------------------------------------|------------------------------------------|---------------------------------|-----------------------------------------|------------------------------------------|------------------------------------------|---------------------------------|-----------------------------------------|------------------------------------------|------------------------------------------|---------------------------------|-----------------------------------------|------------------------------------------|------------------------------------------|---------------------------------|-----------------------------------------|-------|----|
| | 0,2 % proof strength $R_{p0,2}$ min. MPa | 1,0 % proof strength $R_{p1,0}$ min. MPa | Tensile strength R_m min. MPa | Elongation on after fracture A min. % | 0,2 % proof strength $R_{p1,0}$ min. MPa | 1,0 % proof strength $R_{p0,2}$ min. MPa | Tensile strength R_m min. MPa | Elongation on after fracture A min. % | 0,2 % proof strength $R_{p1,0}$ min. MPa | 1,0 % proof strength $R_{p0,2}$ min. MPa | Tensile strength R_m min. MPa | Elongation on after fracture A min. % | 0,2 % proof strength $R_{p1,0}$ min. MPa | 1,0 % proof strength $R_{p0,2}$ min. MPa | Tensile strength R_m min. MPa | Elongation on after fracture A min. % | | |
| Steel name | Steel number | | | | | | | | | | | | | | | | | |
| X5CrNi18-10 | 1.4301 | 210 | 250 | 520 | 45 | 270 | 350 | 860 | 35 | 315 | 415 | 1 100 | 30 | 300 | 400 | 1 250 | 30 | |
| X2CrNi18-9 | 1.4307 | 200 | 240 | 500 | 45 | 220 | 290 | 830 | 35 | 225 | 325 | 1 070 | 30 | 300 | 400 | 1 200 | 30 | |
| X2CrNi18-10 | 1.4311 | 270 | 310 | 550 | 40 | 350 | 420 | 850 | 40 | 450 | 550 | 1 050 | 35 | 550 | 650 | 1 250 | 35 | |
| X5CrNi19-9 | 1.4315 | 270 | 310 | 550 | 40 | 385 | 455 | 890 | 40 | 450 | 550 | 1 180 | 35 | 550 | 650 | 1 350 | 35 | |
| X2CrNi18-7 | 1.4318 | 330 | 370 | 650 | 35 | 380 | 410 | 1 040 | 25 | 420 | 450 | 1 320 | 20 | 450 | 490 | 1 500 | 15 | |
| X2CrMnNi17- | 7-5 | 1.4371 | 300 | 370 | 650 | 40 | 400 | 450 | 1 000 | 35 | 430 | 500 | 1 300 | 30 | 500 | 600 | 1 350 | 25 |
| X12CrMnNi17- | 7-5 | 1.4372 | 330 | 370 | 680 | 45 | 420 | 500 | 950 | 35 | 500 | 580 | 1 150 | 20 | - | - | - | - |
| X2CrNiMo17- | 12-2 | 1.4404 | 220 | 260 | 520 | 45 | 275 | 355 | 840 | 40 | 315 | 415 | 1 070 | 40 | 350 | 450 | 1 200 | 35 |
| X2CrNiMo17- | 11-2 | 1.4406 | 280 | 320 | 580 | 40 | 380 | 450 | 800 | 35 | 500 | 600 | 1 000 | 35 | 600 | 700 | 1 150 | 30 |
| X2CrNiMoN21- | 9-1 | 1.4420 | 350 | 380 | 650 | 35 | 430 | 520 | 900 | 35 | 530 | 620 | 1 080 | 35 | 600 | 700 | 1 200 | 30 |
| X2CrNiMoN17- | 13-3 | 1.4429 | 280 | 320 | 580 | 35 | 380 | 450 | 800 | 30 | 500 | 600 | 1 000 | 30 | 600 | 700 | 1 150 | 30 |
| X6CrNiTi18-10 | 1.4541 | 200 | 240 | 500 | 40 | 260 | 290 | 855 | 35 | 350 | 420 | 1 100 | 35 | 390 | 470 | 1 200 | 30 | |

NOTE For any temperature between 20 °C and -196 °C, mechanical properties may be estimated by linear interpolation.

Annex F
(informative)

Significant changes to the version EN 10028-7:2007

Some significant changes to the version EN 10028-7:2007 are:

- a) Normative references revised;
- b) Technical data on steel grades 1.4062 (X2CrNiN22-2), 1.4162 (X2CrMnNiN21-5-1) and 1.4662 (X2CrNiMnMoCuN24-4-3-2) as patented steels generally revised;
- c) Steel grades 1. 4420 (X2CrNiMoN21-9-1), 1.4371 (X2CrMnNiN17-7-5), 1.4372 (X12CrMnNiN17-7-5), 1.4482 (X2CrMnNiMoN21-5-3), 1.4611 (X2CrTi21), 1.4618 (X9CrMnNiCu17-8-5-2), 1.4613 (X2CrTi24), 1.4622 (X2CrCuNbTiV22-1), 1.4646 (X6CrMnNiCuN18-2-4-2) and 1.4361 (X1CrNiSi18-15-4) new added and the correspondence tables updated;
- d) Table 1, footnote b) has been updated for a better clarification;
- e) Chemical composition generally revised for some steel grades e.g. 1.4618; 1.4062 or 1.4162;
- f) Data for Mn in Table 5 “Product analysis” updated for the range 1 % to 2 % and completed with value for the range 2 % to 10,5 %; Table 5 generally revised;
- g) New formulations for the surface finishes 2B and 2E in Table 6;
- h) Example of ordering has been updated;
- i) Supplementary statements in chapter 8 considering “Weldability” (in correlation with Annex B);
- j) Mechanical properties in Tables 7 to 15 and in Annexes A to E updated;
- k) Annex F new in the European Standard;
- l) Table ZA.1 revised; New relationship to the PED Directive 2014/68/EU;
- m) “Bibliography” new added.

Annex ZA (informative)

Relationship between this European Standard and the Essential Requirements of Directive 2014/68/EU

This European Standard has been prepared under a Commission's standardization request M/071 to provide one voluntary means of conforming to Essential Requirements of Directive 2014/68/EU.

Once this standard is cited in the Official Journal of the European Union under that Directive, compliance with the normative clauses of this standard given in Table ZA.1 confers, within the limits of the scope of this standard, a presumption of conformity with the corresponding Essential Requirements of Directive 2014/68/EU, and associated EFTA regulations.

Table ZA.1 — Correspondence between this European Standard and Annex I of Directive 2014/68/EU

| Requirements of Directive 2014/68/EU | Clause(s)/sub-clause(s) of this EN | Remarks/Notes |
|--------------------------------------|---------------------------------------------------------|----------------------------------------|
| 4.1a | 8.4.1, 8.4.2 and Table 7; Table 8; Table 9 and Table 10 | Appropriate material properties |
| 4.1d | 8.2, 8.5 and 8.6 | Suitable for the processing procedures |
| 4.3 | 9.1 and Table 16 | Inspection documentation |

WARNING 1 — Presumption of conformity stays valid only as long as a reference to this European Standard is maintained in the list published in the Official Journal of the European Union. Users of this standard should consult frequently the latest list published in the Official Journal of the European Union.

WARNING 2 — Other Union legislation may be applicable to the product(s) falling within the scope of this standard.

Bibliography

- [1] EN 1011-3, *Welding — Recommendations for welding of metallic materials — Part 3: Arc welding of stainless steels*
- [2] EN ISO 643, *Steels — Micrographic determination of the apparent grain size (ISO 643)*
- [3] DIN 17460, *High temperature austenitic steel plate and sheet, cold and hot rolled strip, bars and forgings — Technical delivery conditions*
- [4] NF A 36-209, *Iron and steel products — Austenitic stainless steels for boilers and pressure purposes*
- [5] BS PS 625 Part 1:1990, *Elevated temperature properties for steels for pressure purposes: Plates — Part 1: Stress rupture properties*
- [6] *Results of investigations of the European Creep Collaborative Committee (ECCC, WG 3.3)*

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit, or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than 1 device provided that it is accessible by the sole named user only and that only 1 copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than 1 copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright & Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email subscriptions@bsigroup.com.

Rewrites

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK