BS EN 13038:2011



BSI Standards Publication

Soil improvers and growing media — Determination of electrical conductivity



BS EN 13038:2011 BRITISH STANDARD

National foreword

This British Standard is the UK implementation of EN 13038:2011. It supersedes BS EN 13038:2000 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee AW/20, Top soil and other growing media.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© BSI 2011

ISBN 978 0 580 68880 5

ICS 65.080

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 November 2011.

Amendments issued since publication

Date Text affected

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 13038

November 2011

ICS 65.080

Supersedes EN 13038:1999

English Version

Soil improvers and growing media - Determination of electrical conductivity

Amendements du sol et supports de culture -Détermination de la conductivité électrique Bodenverbesserungsmittel und Kultursubstrate -Bestimmung der elektrischen Leitfähigkeit

This European Standard was approved by CEN on 17 September 2011.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents		
Fore	word	3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Principle	4
5	Reagents	4
6	Apparatus	5
7	Preparation	5
8 8.1 8.2 8.3 8.4 8.5 8.6	Procedure Test samples passing through a 20 mm sieve Test samples passing through a 40 mm sieve Filtration Blank Measuring conductivity Measurement of the specific electrical conductivity of the filtrates	5 5 6 6
9	Precision	
10	Test report	7
Anne	ex A (informative) Results of an interlaboratory trial to determine specific electrical conductivity	8
Bibli	ography	9

Foreword

This document (EN 13038:2011) has been prepared by Technical Committee CEN/TC 223 "Soil improvers and growing media", the secretariat of which is held by ASI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by May 2012, and conflicting national standards shall be withdrawn at the latest by May 2012.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 13038:1999.

The main change to the previous is the change of the scope.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

1 Scope

This European Standard specifies an instrumental method for the routine determination of electrical conductivity in a water extract of a soil improver or growing medium. The determination is carried out to obtain an indication of the content of water soluble electrolytes in either soil improvers or growing media.

This method is not applicable to liming materials and preformed materials such as mineral wool slabs and foam slabs.

NOTE The requirements of the standard may differ from the national legal requirements for the declaration of the products concerned.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13040:2007, Soil improvers and growing media – Sample preparation for chemical and physical tests, determination of dry matter content, moisture content and laboratory compacted bulk density

EN ISO 3696, Water for analytical laboratory use – Specification and test methods (ISO 3696:1987)

ISO 1770, Solid-stem general purposes thermometers

3 Terms and definitions

For the purposes of this document the terms and definitions given in EN 13040:2007 and the following apply.

3.1

electrical conductivity

ability of an aqueous extract of the sample to conduct electricity as a function of the ion concentration

4 Principle

A test portion is extracted with water at (22 ± 3.0) °C in an extraction ratio of 1 : 5 (1 V sample + 5 V water) to dissolve the electrolytes. The specific electrical conductivity of the extract is measured and the result is adjusted to a measurement temperature of 25 °C.

5 Reagents

5.1 Water having an electrical conductivity not higher than 0,2 mS/m at 25 °C and a pH >5,6 (grade 2 water according to EN ISO 3696).

5.2 Potassium chloride solution, c(KCI) = 0.100 mol/l

Dissolve 7,456 g potassium chloride, (KCI), previously dried for 2 h at 105 °C, in water (see 5.1) and dilute to 1000 ml. The specific electrical conductivity of this solution at 25 °C is 1290 mS/m.

5.3 Potassium chloride solution, c(KCI) = 0.0100 mol/l

Add 100,0 ml of potassium chloride solution (see 5.2) into a 1000 ml volumetric flask and dilute to the mark with water (see 5.1) at 20 °C. The specific electrical conductivity of this solution at 25 °C is 141 mS/m.

Commercially available solutions may also be used.

NOTE All potassium chloride solutions used for calibration should be stored in tightly sealed glass bottles which do not release alkali metal or alkali earth cations.

6 Apparatus

- **6.1 Conductivity meter** fitted with a conductivity cell and equipped with adjustable measuring range setting and (automatic) temperature correction and having a resolution not greater than 1 mS/m at 25 °C. Preferably, the conductivity meter should also be equipped with a cell constant control.
- **6.2** Analytical balance with an accuracy of 0,001 g.
- **6.3** Thermometer capable of measuring to the nearest 0,1 °C complying with type C according to ISO 1770.
- **6.4 Plastic or glass containers,** of sufficient capacity to accommodate the volume of the sample, extractant and 10 % air volume.
- **6.5 Shaking or mixing machine,** capable of holding container (see 6.4) and maintaining the sample in suspension without damaging the structure of the sample.
- **6.6 Filter paper**, with low ash content and high retentive properties.

7 Preparation

Prepare the sample in accordance with Clause 8 of EN 13040:2007 and determine the compacted laboratory bulk density of the sample in accordance with Annex A of EN 13040:2007.

8 Procedure

8.1 Test samples passing through a 20 mm sieve

Take a weight equivalent 60 ml of the sample volume to the nearest 1 g and transfer to the container (see 6.4). Add 300 ml of water (see 5.1) secure the cap and shake for 1 h on the shaking machine (see 6.5) at (22 ± 3) °C.

8.2 Test samples passing through a 40 mm sieve

Take a weight equivalent 250 ml of the sample volume to the nearest 1 g and transfer to the container (see 6.4). Add 1250 ml of water (see 5.1), secure the cap and shake for 1 h on the shaking machine (see 6.5) at (22 ± 3) °C.

8.3 Filtration

Filter through filter paper (see 6.6) discarding the first 10 ml. In some cases, paper filtration is too slow or even impossible. In such cases alternative procedures, (e.g. centrifugation, glass fibre filter papers) may be used to obtain a clear supernatant. The technique used shall be reported.

8.4 Blank

Repeat the procedures (see 8.1 to 8.2) but omitting the sample. Any modifications to the filtration procedure should also be repeated.

NOTE Measurement of a blank is introduced to determine the contribution of the water, glassware and filter paper used to the electrical conductivity of the extracts.

8.5 Measuring conductivity

- **8.5.1** Measure the conductance (G) of the potassium chloride solutions (see 5.2 and 5.3) according to the instruction manual of the instrument.
- **8.5.2** Calculate for potassium chloride solution (see 5.3) the cell constant according to:

$$k = \frac{K_{\rm s}}{G} \tag{1}$$

where

- *k* is the cell constant, in reciprocal metres;
- $K_{\rm s}$ is the specific electrical conductance of one of the potassium chloride solutions, in millisiemens per metre:
- G is the measured electrical conductance of the same potassium chloride solution, in millisiemens per metre.

The calculated cell constant shall not differ by more than 5 % from the value given by the manufacturer.

8.5.3 Adjust the cell constant on the conductivity meter.

8.6 Measurement of the specific electrical conductivity of the filtrates

Measure within one hour of extraction the specific electrical conductivity of the filtrates in millisiemens per metre (mS/m) according to the instructions given by the manufacturer of the conductivity meter (see 6.1). Carry out the measurements with the temperature correction set at 25 °C. Note the results to one decimal place.

If the blank exceeds twice the detection limit of the conductivity meter, all the results from this batch are void. All the apparatus and equipment used in the extraction shall be checked and cleaned as required. No results shall be reported until the blank is less than twice the detection limit of the conductivity meter.

NOTE 1 The measured values of the electrical conductivity can be influenced by contamination of the electrodes.

This type of interference is very difficult to recognise. Pollution of the electrodes may change the cell constant, which can be perceived by measuring the electrical conductance of the standard potassium chloride solutions.

NOTE 2 Air bubbles on the electrodes, developed during warming up of solutions disturb the measurements.

9 Precision

The repeatability and reproducibility of the specific electrical conductivity in separately prepared samples should be in accordance with Table A.1.

A summary of the results of an interlaboratory trial to determine the precision of the method in accordance with ISO 5725 are given in Annex A.

The values derived from the interlaboratory trial may not be applicable to concentrations and matrices other than those given.

10 Test report

The test report shall contain the following information:

- a) a reference to this European Standard;
- b) all information necessary for complete identification of the sample;
- c) the results of the determination as whole numbers, expressed in millisiemens per metre;
- d) details of any operations not specified in the European Standard or regarded as optional, as well as any factor which may have affected the results;
- e) compacted laboratory bulk density.

Annex A (informative)

Results of an interlaboratory trial to determine specific electrical conductivity

An interlaboratory trial was organized in 1995 under the auspices of the European Committee for Standardization, to test the procedures specified in this European Standard.

In this trial the number of laboratories given in Table A.1 determined the specific electrical conductivity in three types of samples.

Table A.1 — Summary of the results of an interlaboratory trial for the determination of the specific electrical conductivity

Sample	Unfertilized peat perlite	Composted coarse bark	Sewage sludge composted with straw
Number of laboratories retained after eliminating outliers	16	16	16
Number of outliers (laboratories)	0	0	0
Mean Value (mS/m)	10,18	31,70	126,93
Repeatability standard deviation, $s_{\rm r}$ (mS/m)	0,40	0,98	3,18
Repeatability relative standard deviation (%)	3,93	3,09	2,50
Repeatability limit, $r = 2.8 s_r \text{ (mS/m)}$	1,12	2,73	8,90
Reproducibility standard deviation, s_R (mS/m)	2,02	5,39	11,96
Reproducibility relative standard deviation (%)	19,84	17,00	9,42
Reproducibility limit, $r = 2.8 s_R \text{ (mS/m)}$	5,71	15,11	33,50

Bibliography

EN 27888, Water quality – Determination of electrical conductivity (ISO 7888:1985)

ISO 5725 (all parts), Accuracy (trueness and precision) of measurement methods and results





British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards -based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com
Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070 Email: copyright@bsigroup.com

