Products and systems for the protection and repair of concrete structures — Test methods — Determination of workability —

Part 4: Application of repair mortar overhead

The European Standard EN 13395-4:2002 has the status of a British Standard

 $ICS\ 91.080.40;\ 91.100.30$



National foreword

This British Standard is the official English language version of EN 13395-4:2002.

The UK participation in its preparation was entrusted by Technical Committee B/517, Concrete, to Subcommittee B/517/8, Protection and repair of concrete structures, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed:
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this subcommittee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the $BSI\ Catalogue$ under the section entitled "International Standards Correspondence Index", or by using the "Search" facility of the $BSI\ Electronic\ Catalogue$ or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

This British Standard, having been prepared under the direction of the Building and Civil Engineering Sector Policy and Strategy Committee, was published under the authority of the Standards Policy and Strategy Committee on 16 July 2002

Summary of pages

This document comprises a front cover, an inside front cover, the EN title page, pages 2 to 7 and a back cover.

The BSI copyright date displayed in this document indicates when the document was last issued.

Amendments issued since publication

Amd. No.	Date	Comments

© BSI 16 July 2002

ISBN 0 580 40091 3

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 13395-4

May 2002

ICS 91.080.40; 91.100.30

English version

Products and systems for the protection and repair of concrete structures - Test methods - Determination of workability - Part 4: Application of repair mortar overhead

Produits et systèmes pour la protection et la réparation des structures en béton - Méthodes d'essai - Détermination de la maniabilité - Partie 4: Application de mortier de réparation en sous-face Produkte und Systeme für den Schutz und die Instandsetzung von Betontragwerken - Prüfverfahren -Bestimmung der Verarbeitbarkeit - Teil 4: Überkopfanwendung von Instandsetzungsmörtel

This European Standard was approved by CEN on 4 January 2002.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

		page
Forew	/ord	3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Principle	4
5	Apparatus	4
6	Test procedure	5
7	Test report	5
Annex	x A (normative) Summary of temperatures and humidities for the curing, conditioning and testing of repair products and systems	7

Foreword

This document EN 13395-4:2002 has been prepared by Technical Committee CEN/TC 104 "Concrete and related products", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by November 2002, and conflicting national standards shall be withdrawn at the latest by December 2002.

It is one of a series of inter-related parts dealing with the workability of repair grouts, mortars and concretes. The other parts of this standard are:

- Part 1: Products and systems for the protection and repair of concrete structures Test methods -Determination of workability - Part 1: Test for flow of thixotropic mortars.
- Part 2: Products and systems for the protection and repair of concrete structures Test methods -Determination of workability - Part 2: Test for flow of grout or mortar.
- Part 3: Products and systems for the protection and repair of concrete structures Test methods Determination of workability Part 3: Test for flow of concrete.

Annex A is normative.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

1 Scope

This European Standard specifies a method for determining the applicability overhead of products and systems for the repair of concrete as defined in prEN 1504-3¹ under usual conditions.

NOTE This method can only demonstrate that products are capable of being applied overhead. It cannot take into account the possible effects of the operative's skill on site.

2 Normative references

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text, and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies (including amendments).

EN 196-1, Methods of testing cement - Part 1: Determination of strength.

EN 1542, Products and systems for the repair and protection of concrete structures - Test methods - Measurement of bond strength by pull off.

EN 1504-1, Products and systems for the protection and repair of concrete structures - Definitions, requirements, quality control and evaluation of conformity - Part 1: Definitions.

EN 1766, Products and systems for the protection and repair of concrete structures - Test methods - Reference concretes for testing.

prEN 1504-3¹, Products and systems for the protection and repair of concrete structures - Definitions, requirements, quality control and evaluation of conformity - Part 3: Structural and non-structural repair.

ISO 554, Standard atmospheres for conditioning and/or testing – Specifications.

3 Terms and definitions

For the purposes of this European Standard, the terms and definitions contained in EN 1504-1 apply.

4 Principle

The repair mortar or concrete is applied to overhead face of a prepared concrete substrate. After hardening, the pull-off strength is determined and taken for evaluation of overhead applicability.

5 Apparatus

- **5.1 Standard laboratory climate** of (21 ± 2) °C and $60 \% \pm 10 \%$ RH in accordance with EN 1542 (see annex A).
- **5.2 Concrete slabs** for substrates MC (0,45) according to EN 1766, of dimensions $300 \text{ mm} \times 300 \text{ mm} \times 100 \text{ mm}$, with one grit blasted surface $300 \text{ mm} \times 300 \text{ mm}$.

¹ Under preparation.

- **5.3 Mixer** in accordance with EN 196-1 or **forced action pan mixer** for mixing the constituents of the repair mortar or concrete.
- **5.4** Rigid non absorbent panels for framework.
- **5.5 Trowel and tools** to apply the mortar or concrete to the prepared concrete substrates (**5.2**), and a plasterer's steel float for smoothing the surface.
- **5.6** Core drilling machine with a diamond tool, internal diameter 50 mm according to EN 1542.
- **5.7 Pull-off equipment** for measuring the pull-off strength, according to EN 1542.

6 Test procedure

Two concrete slabs (see **5.2**), conditioned in accordance with the manufacturer's instructions, are mounted with the grit blasted surfaces at the bottom.

NOTE 1 The substrates can be supported by form work on two sides (see **5.4**) to ensure the required uniform thickness of repair mortar or concrete.

The layer thickness shall be (20 ± 2) mm for repair mortars up to 5 mm maximum particle size and (40 ± 4) mm for repair materials with larger maximum particle sizes, unless recommended otherwise by the manufacturer.

All materials shall be conditioned in the standard laboratory climate (5.1) for a period of not less than 24 hours prior to mixing.

The repair mortar or concrete is mixed according to the manufacturer's instructions. If no particular instructions are given, the maximum water content should be applied in the case of CC and PCC.

The repair mortar or concrete is applied to the overhead surface of the prepared substrates according to the manufacturer's instructions.

NOTE 2 If required, the substrates may be pre-wetted and/or a bonding aid used.

After application to the required layer thickness, the surface shall be finished with a steel float (5.5) to provide a smooth surface. The test specimens shall then be cured and stored according to annex A.

After the cure periods (28 days for CC and PCC, 7 days for PC repair mortars – see annex A) the pull off strength shall be determined for each slab according to EN 1542.

7 Test report

The test report shall include the following information:

- a) a reference to this European Standard, including the number, title and date of issue;
- b) name and address of the test laboratory;
- c) identification number and date of the test report;
- d) name and address of the manufacturer or supplier of the product(s);
- e) name and identification marks or batch number of the product(s);
- f) date of supply of the product(s);
- g) date of preparation of the test specimens and any deviation from the prescribed method of preparation, including whether it is a single or multi layer system and whether a bonding agent was used;

EN 13395-4:2002 (E)

- h) conditions of storage of prepared specimens prior to test;
- i) date of test and details of test equipment used including the make, type and capacity and calibration details or identification number of the apparatus;
- j) the test results (single values, mean values and standard deviations) of the pull off test including individual forms of fracture;
- k) precision data;
- I) date of test report and signature.

Annex A

(normative)

Summary of temperatures and humidities for the curing, conditioning and testing of repair products and systems

A.1 Curing

A.1.1 CC (grouts, mortars and concretes)

- Prepare as EN 196-1, cover in film for 24 h;
- Demould after 24 h;
- Cure under water at (21 ± 2) °C for 27 d.

A.1.2 PCC (grouts, mortars and concretes)

- Prepare as EN 196-1, cover in film for 24 h;
- Demould after 24 h and wrap in film for 48 h;
- Unwrap and cure for 25 d in a standard laboratory climate of (21 ± 2) °C and (60 ± 10) % RH.

A.1.3 PC (grouts, mortars and concretes)

- Prepare as ISO 554;
- Cure for 7 d at (21 ± 2) ° C and (60 ± 10) % RH.

A.2 Conditioning and testing

For specific applications, the following requirements apply:

A.2.1 Standard laboratory climate (Dry conditioning)

Take from the curing/storage environment and condition for 7 d in a standard laboratory climate of (21 ± 2) °C and (60 ± 10) % RH.

A.2.2 Wet Conditioning

- Immerse for 48 h at (21 ± 2) °C, or for CC take directly for test after 28 d of immersion;
- Remove all surface water by standing upright for 30 min before using for tests.

BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001. Fax: +44 (0)20 8996 7001. Email: orders@bsi-global.com. Standards are also available from the BSI website at http://www.bsi-global.com.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre. Tel: +44 (0)20 8996 7111. Fax: +44 (0)20 8996 7048. Email: info@bsi-global.com.

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration.

Tel: +44 (0)20 8996 7002. Fax: +44 (0)20 8996 7001.

Email: membership@bsi-global.com.

Information regarding online access to British Standards via British Standards Online can be found at http://www.bsi-global.com/bsonline.

Further information about BSI is available on the BSI website at http://www.bsi-global.com.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means — electronic, photocopying, recording or otherwise — without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright & Licensing Manager. Tel: +44 (0)20 8996 7070. Fax: +44 (0)20 8996 7553. Email: copyright@bsi-global.com.

BSI 389 Chiswick High Road London W4 4AL