

BS EN 14680:2015



BSI Standards Publication

Adhesives for non-pressure thermoplastics piping systems — Specifications

bsi.

...making excellence a habit.™

National foreword

This British Standard is the UK implementation of EN 14680:2015. It supersedes BS EN 14680:2006 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee PRI/52, Adhesives.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2015.
Published by BSI Standards Limited 2015

ISBN 978 0 580 82573 6

ICS 83.180

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 October 2015.

Amendments issued since publication

Date	Text affected
------	---------------

EUROPEAN STANDARD

EN 14680

NORME EUROPÉENNE

EUROPÄISCHE NORM

October 2015

ICS 83.180

Supersedes EN 14680:2006

English Version

Adhesives for non-pressure thermoplastics piping systems - Specifications

Adhésifs pour systèmes de canalisations
thermoplastiques sans pression - Spécifications

Klebstoffe für drucklose thermoplastische
Rohrleitungssysteme - Festlegungen

This European Standard was approved by CEN on 15 August 2015.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents		Page
European foreword.....		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Product characteristics.....	7
4.1	General considerations.....	7
4.2	Resistance to pull out.....	8
4.3	Tightness.....	8
4.4	Resistance for high temperature.....	8
4.5	Shelf life	8
4.6	Release of dangerous substances.....	9
4.7	Durability	9
5	Testing, assessment and sampling methods	9
5.1	Resistance to pull out.....	9
5.2	Tightness and resistance for high temperature.....	9
5.3	Shelf life	9
5.4	Release of dangerous substances.....	10
5.5	Durability	10
6	Assessment and verification of constancy of performance — (AVCP).....	10
6.1	General.....	10
6.2	Type testing.....	10
6.2.1	General.....	10
6.2.2	Test samples, testing and compliance criteria	11
6.2.3	Test reports.....	11
6.3	Factory production control (FPC)	12
6.3.1	General.....	12
6.3.2	Requirements	12
6.3.3	Product specific requirements.....	14
6.3.4	One-off products, pre-production products (e.g. prototypes) and products produced in very low quantity	15
7	Marking, labelling and packaging	16
Annex A (informative) Additional characterization for adhesives for non-pressure thermoplastic piping systems		17
Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation		18
ZA.2	Procedure for AVCP of adhesives for non-pressure thermoplastic piping systems	19
ZA.2.1	System(s) of AVCP	19
ZA.2.2	Declaration of performance (DoP)	19
ZA.2.2.1	General	19
ZA.2.2.2	Content.....	19

ZA.2.2.3 Example of DoP	20
ZA.3 CE marking and labelling	22
Bibliography	25

European foreword

This document (EN 14680:2015) has been prepared by Technical Committee CEN/TC 193 “Adhesives”, the secretariat of which is held by AENOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2016, and conflicting national standards shall be withdrawn at the latest by July 2017.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 14680:2006.

With respect to the previous version, no technical changes have been introduced in this standard, being the only modifications those relevant for its adaptation to the Construction Products Regulation EU n°305/2011.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of basic work requirements of Regulation (EU) 305/2011.

For relationship with Regulation (EU) 305/2011, see informative Annex ZA, which is an integral part of this document.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

This European Standard contains the requirements for adhesives for non-pressure thermoplastic piping systems independent of piping system application. The existing system and application standards which specify parameters for adhesive joints in particular application areas and the test methods specified therein remain unchanged. The requirements referred to in these system standards concern temperature, pressure and standard life span of the piping system, and are applicable to all the components of the piping system for all the relevant dimensions that require specified application.

1 Scope

This European Standard specifies the requirements and test methods for adhesives used for joining the components of unplasticised poly(vinyl chloride) (PVC-U), chlorinated poly(vinyl chloride)(PVC-C), acrylonitrile -butadiene-styrene (ABS) and styrene copolymer blends (PVC+SAN) thermoplastic piping systems for non-pressure applications (e.g. soil and waste discharge), independent of the application area.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 923:2005+A1:2008, *Adhesives — Terms and definitions*

EN 1055, *Plastics piping systems — Thermoplastics piping systems for soil and waste discharge inside buildings — Test method for resistance to elevated temperature cycling*

EN 1329-1, *Plastics piping systems for soil and waste discharge (low and high temperature) within the building structure — Unplasticized poly(vinyl chloride) (PVC-U) — Part 1: Specifications for pipes, fittings and the system*

EN 1401-1, *Plastics piping systems for non-pressure underground drainage and sewerage — Unplasticized poly(vinyl chloride) (PVC-U) — Part 1: Specifications for pipes, fittings and the system*

EN 1453-1, *Plastics piping systems with structured wall-pipes for soil and waste discharge (low and high temperature) inside buildings — Unplasticized poly(vinyl chloride) (PVC-U) — Part 1: Specifications for pipes and the system*

EN 1455-1, *Plastics piping systems for soil and waste discharge (low and high temperature) within the building structure — Acrylonitrile-butadiene-styrene (ABS) — Part 1: Requirements for pipes, fittings and the system*

EN 1565-1, *Plastics piping systems for soil and waste discharge (low and high temperature) within the building structure — Styrene copolymer blends (SAN+PVC) — Part 1: Specifications for pipes, fittings and the system*

EN 1566-1, *Plastics piping systems for soil and waste discharge (low and high temperature) within the building structure — Chlorinated poly(vinyl chloride) (PVC-C) — Part 1: Specifications for pipes, fittings and the system*

EN 13476-2, *Plastics piping systems for non-pressure underground drainage and sewerage — Structured-wall piping systems of unplasticized poly(vinyl chloride) (PVC-U), polypropylene (PP) and polyethylene (PE) — Part 2: Specifications for pipes and fittings with smooth internal and external surface and the system, Type A*

EN 13476-3, *Plastics piping systems for non-pressure underground drainage and sewerage — Structured-wall piping systems of unplasticized poly(vinyl chloride) (PVC-U), polypropylene (PP) and polyethylene (PE) — Part 3: Specifications for pipes and fittings with smooth internal and profiled external surface and the system, Type B*

EN ISO 9311-2, *Adhesives for thermoplastic piping systems — Part 2: Determination of shear strength (ISO 9311-2)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 923:2005+A1:2008 and the following apply.

3.1

diametral clearance

difference between the mean inside diameter (d_{sm}) of the socket and the mean outside diameter (d_{em}) of the pipe

3.2

Batch Release Test

BRT

test performed by the manufacturer on a batch of components, which has to be satisfactorily completed before the batch can be released

3.3

Type Test

TT

tests performed to prove that the material, component, joint or assembly is capable of conforming with the relevant requirements given in the System Standard

4 Product characteristics

4.1 General considerations

The manufacturer of the adhesive shall specify for which non-pressure system the adhesive is intended by reference to the appropriate standard as listed in Table 1.

Table 1 — Intended use standard list

PVC-U	EN 1401-1, EN 1453-1, EN 1329-1, EN 13476-2, EN 13476-3
PVC-C	EN 1566-1
ABS	EN 1455-1
PVC+ABS	EN 1565-1

When not otherwise mentioned, the test pieces shall fulfil the following requirements set in Tables 2 and 3:

Table 2 — Test pieces diametral clearance

PVC-U	$\left(0,6 \begin{smallmatrix} 0 \\ -0,1 \end{smallmatrix}\right)$ mm
PVC-C	$\left(0,6 \begin{smallmatrix} 0 \\ -0,1 \end{smallmatrix}\right)$ mm
ABS	$\left(0,6 \begin{smallmatrix} 0 \\ -0,1 \end{smallmatrix}\right)$ mm
SAN+PVC	$\left(0,6 \begin{smallmatrix} 0 \\ -0,1 \end{smallmatrix}\right)$ mm

Table 3 — Test pieces setting time

	Setting time	Setting conditions
PVC-U	1 h 24 h 480 h	At (23 ± 2) °C and (50 ± 5) % relative humidity
PVC-C	1 h 24 h 480 h	At (23 ± 2) °C and (50 ± 5) % relative humidity
ABS	1 h 24 h 480 h	At (23 ± 2) °C and (50 ± 5) % relative humidity
SAN+PVC	1 h 24 h 480 h	At (23 ± 2) °C and (50 ± 5) % relative humidity

The setting time shall be measured from the start of the application of the adhesive.

4.2 Resistance to pull out

The resistance to pull out is assessed by the measurement of the shear strength.

The resistance to pull out obtained by using adhesives for non-pressure thermoplastic piping systems shall comply with the requirements of 5.1 using pipe and fitting compatible with the claims of the adhesive suitability.

The adhesive joints on the test pieces shall be prepared according to the instructions recommended by the adhesive manufacturer.

4.3 Tightness

The tightness is assessed by the resistance to elevated temperature cycling.

The adhesive joints shall be prepared according to the instructions recommended by the adhesive manufacturer. The setting time of the adhesive joints shall be at least 24 h at (23 ± 2) °C and (50 ± 5) % relative humidity.

The adhesive joints shall be tested against water leakage in accordance with 5.2.

4.4 Resistance for high temperature

The resistance for high temperature is assessed by the resistance to elevated temperature cycling.

The adhesive joints shall be prepared according to the instructions recommended by the adhesive manufacturer. The setting time of the adhesive joints shall be at least 24 h at (23 ± 2) °C and (50 ± 5) % relative humidity.

The adhesive joints shall be tested against water leakage in accordance with 5.2.

4.5 Shelf life

Adhesive producers shall indicate the minimum shelf life of the adhesive when it is stored in unopened containers.

Shelf life of adhesives have to be assessed with the requirements of 5.3.

4.6 Release of dangerous substances

National regulations on dangerous substances may require verification and declaration on release, and sometimes content, when construction products covered by this standard are placed on those markets. In the absence of European harmonized test methods, verification and declaration on release/content should be done taking into account national provisions in the place of use.

NOTE An informative database covering European and national provisions on dangerous substances is available at the Construction website on EUROPA accessed through: http://ec.europa.eu/growth/tools-databases/cp-ds/index_en.htm.

4.7 Durability

The durability of tightness and resistance to high temperature of the adhesive joints shall comply with the requirements of 5.5.

5 Testing, assessment and sampling methods

5.1 Resistance to pull out

The adhesive shall be tested in accordance with EN ISO 9311-2 using pipe and fitting compatible with the claims of the adhesive suitability. The sampling procedure is to be defined by the manufacturer and the number of samples is one. The mean of the test results shall meet the requirements of Table 4.

Table 4 — Requirements for the shear strength

Test temperature (°C)	Setting time (hours)	PVC-U adhesives MPa (N/mm ²)	PVC-C adhesives MPa (N/mm ²)	ABS adhesives (SAN+PVC) adhesives MPa (N/mm ²)
23 ± 2	1	≥ 0,25	≥ 0,25	≥ 0,10
23 ± 2	24	≥ 1,5	≥ 1,5	≥ 1,5
23 ± 2	480	≥ 3,0	≥ 3,0	≥ 3,0

5.2 Tightness and resistance for high temperature

The adhesive shall be tested in accordance with EN 1055 application “B” using pipe and fitting compatible with the claims of the adhesive suitability. The sampling procedure is to be defined by the manufacturer and the number of samples is one.

The test assembly, application “B”, described in EN 1055, shall contain a minimum of six adhesive joints:

- minimum two adhesive joints in pipe of 40 mm or 50 mm diameter, horizontal stack;
- minimum two adhesive joints in pipe of 75 mm ≤ d ≤ 160 mm diameter, vertical stack;
- minimum two adhesive joints in pipe of 75 mm ≤ d ≤ 160 mm diameter, horizontal stack.

When tested in accordance with this method, each adhesive joint shall show no signs of leakage.

5.3 Shelf life

The producer shall recheck the film properties (see Annex A) and the shear strength (setting time 24 h) of the adhesive after the recommended shelf life (minimum 12 months). The adhesive, stored in

unopened containers in accordance with the manufacturer's instructions for the specified shelf life shall still meet the requirements of Table 4.

5.4 Release of dangerous substances

The release of dangerous substances shall comply with the existing national regulation.

5.5 Durability

The durability of tightness and resistance to high temperature of the adhesive joints is assessed by the resistance to elevated temperature cycling test and shall comply with 5.2.

6 Assessment and verification of constancy of performance — (AVCP)

6.1 General

The compliance of adhesives for non-pressure thermoplastic piping systems with the requirements of this standard and with the performances declared by the manufacturer in the DoP shall be demonstrated by:

- determination of the product type;
- factory production control by the manufacturer, including product assessment.

The manufacturer shall always retain the overall control and shall have the necessary means to take responsibility for the conformity of the product with its declared performance(s).

6.2 Type testing

6.2.1 General

All performances related to characteristics included in this standard shall be determined when the manufacturer intends to declare the respective performances unless the standard gives provisions for declaring them without performing tests. (e.g. use of previously existing data, classified without further testing (CWFT) and conventionally accepted performance).

Assessment previously performed in accordance with the provisions of this standard, may be taken into account provided that they were made to the same or a more rigorous test method, under the same AVCP system on the same product or products of similar design, construction and functionality, such that the results are applicable to the product in question.

For the purposes of assessment, the manufacturer's products may be grouped into families, where it is considered that the results for one or more characteristics from any one product within the family are representative for that same characteristics for all products within that same family.

NOTE Products may be grouped in different families for different characteristics. Example: Products/Formulations which only differ in colour or slightly in viscosity can be considered as one product family.

Reference to the assessment method standards should be made to allow the selection of a suitable representative sample.

In addition, the determination of the product type shall be performed for all characteristics included in the standard for which the manufacturer declares the performance:

- at the beginning of the production of a new or modified adhesive for non-pressure thermoplastic piping systems(unless a member of the same product range), or
- at the beginning of a new or modified method of production (where this may affect the stated properties); or

- they shall be repeated for the appropriate characteristic(s), whenever a change occurs in the adhesive for non-pressure thermoplastic piping systems design, in the raw material or in the supplier of the components, or in the method of production (subject to the definition of a family), which would affect significantly one or more of the characteristics.

Where components are used whose characteristics have already been determined, by the component manufacturer, on the basis of assessment methods of other product standards, these characteristics need not be re-assessed. The specifications of these components shall be documented.

Products bearing regulatory marking in accordance with appropriate harmonized European specifications may be presumed to have the performances declared in the DoP, although this does not replace the responsibility on the adhesive for non-pressure thermoplastic piping systems manufacturer to ensure that the adhesive for non-pressure thermoplastic piping systems as a whole is correctly manufactured and its component products have the declared performance values.

6.2.2 Test samples, testing and compliance criteria

The number of samples of adhesives for non-pressure thermoplastic piping systems to be tested/assessed shall be in accordance with Table 5.

Table 5 — Number of samples to be tested and compliance criteria

Characteristic	Requirement	Assessment method	No. of samples	Compliance criteria
Resistance to pull out 1 h setting time (Shear strength)	Clause 4.2	Clause 5.1	One sample	See Table 4
Resistance to pull out 24 h setting time (Shear strength)	Clause 4.2	Clause 5.1	One sample	See Table 4
Resistance to pull out 480 h setting time (Shear strength)	Clause 4.2	Clause 5.1	One sample	See Table 4
Tightness/resistance to high temperature (Resistance to elevated temperature cycling)	Clause 4.3/Clause 4.4	Clause 5.2	One sample	Clause 5.2
Shelf life	Clause 4.5	Clause 5.3	One sample	Clause 5.3 at producer's specified shelf life
Release of dangerous substances	Clause 4.6	Clause 5.4		Shall comply with existing national regulations
Durability	Clause 4.7	Clause 5.5	One sample	Clause 5.5

6.2.3 Test reports

The results of the determination of the product type shall be documented in test reports. All test reports shall be retained by the manufacturer for at least 10 years after the last date of production of the adhesive for non-pressure thermoplastic piping systems to which they relate.

6.3 Factory production control (FPC)

6.3.1 General

The manufacturer shall establish, document and maintain an FPC system to ensure that the products placed on the market comply with the declared performance of the essential characteristics.

The FPC system shall consist of procedures, regular inspections and tests and/or assessments and the use of the results to control raw and other incoming materials or components, equipment, the production process and the product.

All the elements, requirements and provisions adopted by the manufacturer shall be documented in a systematic manner in the form of written policies and procedures.

This factory production control system documentation shall ensure a common understanding of the evaluation of the constancy of performance and enable the achievement of the required product performances and the effective operation of the production control system to be checked. Factory production control therefore brings together operational techniques and all measures allowing maintenance and control of the compliance of the product with the declared performances of the essential characteristics.

6.3.2 Requirements

6.3.2.1 General

The manufacturer is responsible for organizing the effective implementation of the FPC system in line with the content of this product standard. Tasks and responsibilities in the production control organization shall be documented and this documentation shall be kept up-to-date.

The responsibility, authority and the relationship between personnel that manages, performs or verifies work affecting product constancy, shall be defined. This applies in particular to personnel that need to initiate actions preventing product non-constancies from occurring, actions in case of non-constancies and to identify and register product constancy problems.

Personnel performing work affecting the constancy of performance of the product shall be competent on the basis of appropriate education, training, skills and experience for which records shall be maintained.

In each factory the manufacturer may delegate the action to a person having the necessary authority to:

- identify procedures to demonstrate constancy of performance of the product at appropriate stages;
- identify and record any instance of non-constancy;
- identify procedures to correct instances of non-constancy.

The manufacturer shall draw up and keep up-to-date documents defining the factory production control. The manufacturer's documentation and procedures should be appropriate to the product and manufacturing process. The FPC system should achieve an appropriate level of confidence in the constancy of performance of the product. This involves:

- a) the preparation of documented procedures and instructions relating to factory production control operations, in accordance with the requirements of the technical specification to which reference is made;
- b) the effective implementation of these procedures and instructions;
- c) the recording of these operations and their results;

- d) the use of these results to correct any deviations, repair the effects of such deviations, treat any resulting instances of non-conformity and, if necessary, revise the FPC to rectify the cause of non-constancy of performance.

Where subcontracting takes place, the manufacturer shall retain the overall control of the product and ensure that he receives all the information that is necessary to fulfill his responsibilities according to this European Standard.

If the manufacturer has part of the product designed, manufactured, assembled, packed, processed and/or labelled by subcontracting, the FPC of the subcontractor may be taken into account, where appropriate for the product in question.

The manufacturer who subcontracts all of his activities may in no circumstances pass the above responsibilities on to a subcontractor.

NOTE Manufacturers having an FPC system, which complies with EN ISO 9001 standard and which addresses the provisions of the present European Standard are considered as satisfying the FPC requirements of the Regulation (EU) No 305/2011.

6.3.2.2 Equipment

6.3.2.2.1 Testing

All weighing, measuring and testing equipment shall be calibrated and regularly inspected according to documented procedures, frequencies and criteria.

6.3.2.2.2 Manufacturing

All equipment used in the manufacturing process shall be regularly inspected and maintained to ensure use, wear or failure does not cause inconsistency in the manufacturing process. Inspections and maintenance shall be carried out and recorded in accordance with the manufacturer's written procedures and the records retained for the period defined in the manufacturer's FPC procedures.

6.3.2.3 Raw materials and components

The specifications of all incoming raw materials and components shall be documented, as shall the inspection scheme for ensuring their compliance. In case supplied kit components are used, the constancy of performance system of the component shall be that given in the appropriate harmonized technical specification for that component.

6.3.2.4 Traceability and marking

Individual adhesives for non-pressure thermoplastic piping systems shall be identifiable and traceable with regard to their production origin. The manufacturer shall have written procedures ensuring that processes related to affixing traceability codes and/or markings are inspected regularly.

6.3.2.5 Controls during manufacturing process

The manufacturer shall plan and carry out production under controlled conditions.

6.3.2.6 Product testing and evaluation

The manufacturer shall establish procedures to ensure that the stated values of the characteristics he declares are maintained. The characteristics, and the means of control, are:

- Resistance to pull out (shear strength) at 1 h setting time shall be subject to the tests indicated in 5.1, at least once every 10 batches as Batch Release Test and at least once a year;

For the 1 h shear strength test as Batch Release Test, it is permitted to use only one test piece. If the result does not fulfil the specified requirement, this test shall be repeated and increase the number of test pieces to 3.

- Resistance to pull out (shear strength) at 24 h setting time shall be subject to the tests indicated in 5.1, at least once a year;
- Resistance to pull out (shear strength) at 480 h setting time: shall be subject to the tests indicated in 5.1, at least once a year;
- Shelf life: shall be subject to the tests indicated in 5.3, at least for the specified shelf life;

NOTE A list of other possible characterization tests is reviewed in Annex A.

6.3.2.7 Non-complying products

The manufacturer shall have written procedures which specify how non-complying products shall be dealt with. Any such events shall be recorded as they occur and these records shall be kept for the period defined in the manufacturer's written procedures.

Where the product fails to satisfy the acceptance criteria, the provisions for non-complying products shall apply, the necessary corrective action(s) shall immediately be taken and the products or batches not complying shall be isolated and properly identified.

Once the fault has been corrected, the test or verification in question shall be repeated.

The results of controls and tests shall be properly recorded. The product description, date of manufacture, test method adopted, test results and acceptance criteria shall be entered in the records under the signature of the person responsible for the control/test.

With regard to any control result not meeting the requirements of this European Standard, the corrective measures taken to rectify the situation (e.g. a further test carried out, modification of manufacturing process, throwing away or putting right of product) shall be indicated in the records.

6.3.2.8 Corrective action

The manufacturer shall have documented procedures that instigate action to eliminate the cause of non-conformities in order to prevent recurrence.

6.3.2.9 Handling, storage and packaging

The manufacturer shall have procedures providing methods of product handling and shall provide suitable storage areas preventing damage or deterioration.

6.3.3 Product specific requirements

The FPC system shall address this European Standard and ensure that the products placed on the market comply with the declaration of performance.

The FPC system shall include a product specific FPC, which identifies procedures to demonstrate compliance of the product at appropriate stages, i.e.

- a) the controls and tests to be carried out prior to and/or during manufacture according to a frequency laid down in the FPC test plan,

and/or

- b) the verifications and tests to be carried out on finished products according to a frequency laid down in the FPC test plan.

If the manufacturer uses only finished products, the operations under b) shall lead to an equivalent level of compliance of the product as if FPC had been carried out during the production.

If the manufacturer carries out parts of the production himself, the operations under b) may be reduced and partly replaced by operations under a). Generally, the more parts of the production that are carried out by the manufacturer, the more operations under b) may be replaced by operations under a).

In any case the operation shall lead to an equivalent level of compliance of the product as if FPC had been carried out during the production.

NOTE Depending on the specific case, it can be necessary to carry out the operations referred to under a) and b), only the operations under a) or only those under b).

The operations under a) refer to the intermediate states of the product as on manufacturing machines and their adjustment, and measuring equipment etc. These controls and tests and their frequency shall be chosen based on product type and composition, the manufacturing process and its complexity, the sensitivity of product features to variations in manufacturing parameters etc.

The manufacturer shall establish and maintain records that provide evidence that the production has been sampled and tested. These records shall show clearly whether the production has satisfied the defined acceptance criteria and shall be available for at least three years.

6.3.4 One-off products, pre-production products (e.g. prototypes) and products produced in very low quantity

The adhesives for non-pressure thermoplastic piping systems produced as a one-off, prototypes assessed before full production is established, and products produced in very low quantities (less than one ton) per year shall be assessed as follows.

For type assessment, the provisions of 6.2.1, 3rd paragraph apply, together with the following additional provisions:

- in case of prototypes, the test samples shall be representative of the intended future production and shall be selected by the manufacturer;
- on request of the manufacturer, the results of the assessment of prototype samples may be included in a certificate or in test reports issued by the involved third party.

The FPC system of one-off products and products produced in very low quantities shall ensure that raw materials and/or components are sufficient for production of the product. The provisions on raw materials and/or components shall apply only where appropriate. The manufacturer shall maintain records allowing traceability of the product.

For prototypes, where the intention is to move to series production, the initial inspection of the factory and FPC shall be carried out before the production is already running and/or before the FPC is already in practice. The following shall be assessed:

- the FPC-documentation; and
- the factory.

In the initial assessment of the factory and FPC it shall be verified:

- a) that all resources necessary for the achievement of the product characteristics included in this European Standard will be available, and
- b) that the FPC-procedures in accordance with the FPC-documentation will be implemented and followed in practice, and

- c) that procedures are in place to demonstrate that the factory production processes can produce a product complying with the requirements of this European Standard and that the product will be the same as the samples used for the determination of the product type, for which compliance with this European Standard has been verified.

Once series production is fully established, the provisions of 6.3 shall apply.

7 Marking, labelling and packaging

Each container of adhesive shall be clearly marked by the manufacturer either directly on the container or by an adhesive label with at least the following information:

- a) manufacturer's or supplier's name and the trademark or identification mark of the adhesive;
- b) number of this European Standard, EN 14680;
- c) field of application: Adhesives for non-pressure applications;
- d) list of the thermoplastics piping systems standards for which the adhesive is suitable;
- e) instructions for use and storage of the adhesive;
- f) any safety precautions relating to use and storage;
- g) batch number from which the container was filled;
- h) date of manufacturing and a statement to the effect that the adhesive has a shelf life of minimum 12 months or "use before date" when stored in unopened containers in accordance with the manufacturer's instructions;
- i) where regulatory marking provisions require information on some or all items listed in this clause, the provisions of this clause concerning those common items are deemed to be met.

Annex A
(informative)

Additional characterization for adhesives for non-pressure thermoplastic piping systems

Properties declared in Table A.1 may be used for monitoring manufacturing control and characterization of the adhesives for non-pressure thermoplastic piping systems.

Table A.1 — List of additional characterization test methods and a suggested test frequency for adhesives for non-pressure thermoplastic piping systems

Nº	Properties to be assess	Test method	BRT	TT
1	Density	EN 542	o	+
2	Solid content	EN 827	+	o
3	Viscosity	EN 12092	+	o
4	Film properties	EN ISO 9311-1	o	+
(o) not to be performed (+) to be performed				

All test methods mentioned in Table A.1 are suitable for solvent based adhesives.

For non-solvent adhesives the above test methods may be used if the specific test method is suitable. If the specified test methods cannot be used, the non-solvent based adhesive shall be characterized using other tests methods appropriate to the nature of the adhesive.

NOTE In this annex, it is not possible to specify properties and test methods for non-solvent based adhesives because the nature (epoxy, acrylic, hot melt, etc.) of the adhesive is unknown. Depending on the chemical basis of the non-solvent based adhesive, characterizing properties such as epoxy equivalent, open time, pot life, etc., may be necessary.

Annex ZA (informative)

Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation

ZA.1 Scope and relevant characteristics

This European Standard has been prepared under Mandate M 131 “Pipes, tanks and ancillaries not in contact with water intended for human consumption” given to CEN by the European Commission and the European Free Trade Association.

If this European Standard is cited in the Official Journal of the European Union (OJEU), the clauses of this standard, shown in this annex, are considered to meet the provisions of the relevant mandate, under the Regulation (EU) No. 305/2011.

This annex deals with the CE marking of the adhesives for non-pressure thermoplastic piping systems intended for the uses indicated in Table ZA.1 and shows the relevant clauses applicable.

This annex has the same scope as in Clause 1 of this standard related to the aspects covered by the mandate and is defined by Table ZA.1.

Table ZA.1 — Relevant clauses for adhesives for non-pressure thermoplastic piping systems

Product:	Adhesives for thermoplastic piping systems		
Intended use:	Adhesives for non-pressure thermoplastic piping systems in installations for the transport/disposal/storage of water not intended for human consumption		
Essential Characteristics	Requirement and clauses in this European Standard	Regulatory classes	Notes
Resistance to pull out	4.2		Expressed as shear strength at 1 h, 24 h and 480 h setting time
Tightness	4.3		No leakage
Resistance to high temperature	4.4		No leakage
Release of dangerous substances	4.6		
Durability	4.7		No leakage

The declaration of the product performance related to certain essential characteristics is not required in those Member States (MS) where there are no regulatory requirements on these essential characteristics for the intended use of the product.

In this case, manufacturers placing their products on the market of these MS are not obliged to determine nor declare the performance of their products with regard to these essential characteristics and the option “No performance determined” (NPD) in the information accompanying the CE marking and in the declaration of performance (see ZA.3) may be used for those essential characteristics.

ZA.2 Procedure for AVCP of adhesives for non-pressure thermoplastic piping systems

ZA.2.1 System(s) of AVCP

The AVCP system of adhesives for non-pressure thermoplastic piping systems indicated in Table ZA.1, established by EC Decision 1999/472/EC (OJEU L184 of 17.7.1999) as amended by EC Decision 2001/596/EC (OJEU L209 of 2.8.2001) is shown in Table ZA.2 for the indicated intended use and relevant level or class of performance.

Table ZA.2 — System of AVCP

Product	Intended use	Level or class of performance	AVCP system(s)
Adhesives for non pressure thermoplastic piping system	In installations for the transport/disposal/storage of water not intended for human consumption		4
System 4: See Regulation (EU) No. 305/2011 (CPR) Annex V, 1.5.			

The AVCP of the adhesives for non-pressure thermoplastic piping systems in Table ZA.1 shall be according to the AVCP procedures indicated in Table ZA.3 resulting from application of the clauses of this or other European Standard indicated therein. The content of tasks of the notified body shall be limited to those essential characteristics as provided for, if any, in Annex III of the relevant mandate and to those that the manufacturer intends to declare.

Table ZA.3 — Assignment of AVCP tasks for adhesives for non-pressure thermoplastic piping systems under system 4

Tasks		Content of the task	AVCP clauses to apply
Tasks for the manufacturer	Factory production control (FPC)	Parameters related to shear strength of Table ZA.1 relevant for the intended use	6.3
	Determination of the product-type on the basis of type testing, type calculation, tabulated values or descriptive documentation of the product	All relevant characteristics of Table ZA.1 relevant for the intended use which are declared	6.2

ZA.2.2 Declaration of performance (DoP)

ZA.2.2.1 General

The manufacturer draws up the DoP and affixes the CE marking on the basis of the different AVCP systems set out in Annex V of the Regulation (EU) No 305/2011:

- the factory production control carried out by the manufacturer;
- the determination by the manufacturer of the product-type on the basis of type testing, type calculation, tabulated values or descriptive documentation of the product.

ZA.2.2.2 Content

The model of the DoP is provided in Annex III of the Regulation (EU) No 305/2011.

According to this Regulation, the DoP shall contain, in particular, the following information:

- the reference of the product-type for which the declaration of performance has been drawn up;
- the AVCP system or systems of the construction product, as set out in Annex V of the CPR;
- the reference number and date of issue of the harmonized standard which has been used for the assessment of each essential characteristic;
- where applicable, the reference number of the Specific Technical Documentation used and the requirements with which the manufacturer claims the product complies.

The DoP shall in addition contain:

- a) the intended use or uses for the construction product, in accordance with the applicable harmonized technical specification;
- b) the list of essential characteristics, as determined in the harmonized technical specification for the declared intended use or uses;
- c) the performance of at least one of the essential characteristics of the construction product, relevant for the declared intended use or uses;
- d) where applicable, the performance of the construction product, by levels or classes, or in a description, if necessary based on a calculation in relation to its essential characteristics determined in accordance with the Commission determination regarding those essential characteristics for which the manufacturer shall declare the performance of the product when it is placed on the market or the Commission determination regarding threshold levels for the performance in relation to the essential characteristics to be declared;
- e) the performance of those essential characteristics of the construction product which are related to the intended use or uses, taking into consideration the provisions in relation to the intended use or uses where the manufacturer intends the product to be made available on the market;
- f) for the listed essential characteristics for which no performance is declared, the letters “NPD” (No Performance Determined).

Regarding the supply of the DoP, Article 7 of the Regulation (EU) No 305/2011 applies.

The information referred to in Article 31 or, as the case may be, in Article 33 of Regulation (EC) No 1907/2006, (REACH) shall be provided together with the DoP.

ZA.2.2.3 Example of DoP

The following gives an example of a filled-in DoP for adhesives for non-pressure PVC-U piping systems

DECLARATION OF PERFORMANCE

Number (to be given by the manufacturer)

- 1) Unique identification code of the product-type:

TRADE MARK

2) Intended use/es:

Adhesive for non-pressure thermoplastic piping systems in installations for the transport/disposal/storage of water not intended for human consumption

3) Manufacturer:

Trademark

AnyCo SA,

PO Box 21

B-1050 Brussels, Belgium

Tel. +32987654321

Fax: +32123456789

Email: anyco.sa@provider.be

4) Authorized representative (if applicable):

Anyone Ltd

Flower Str. 24

West Hamfordshire

UK-589645 United Kingdom

Tel. +44987654321

Fax: +44123456789

e-mail: anyone.ltd@provider.uk

5) System of assessment and verification of constancy of performance (AVCP):

System 4

6) Harmonized standard:

EN 14680:2015

7) Declared performance (example adapted for PVC-U adhesives for non-pressure applications)

Essential characteristics	Performance	Harmonized technical specification
Resistance to pull out (shear strength at 1 h setting time)	≥ 0,25 MPa	EN 14680:2015
Resistance to pull out (shear strength at 24 h time)	≥ 1,5 MPa	
Resistance to pull out (shear strength at 480 h time)	≥ 3,0 MPa	
Tightness (resistance to elevated temperature cycling)	No leakage	EN 14680:2015
Resistance to high temperature (resistance to elevated temperature cycling)	No leakage	EN 14680:2015
Release of dangerous substances	NPD	
Durability on tightness and resistance to high temperature	No leakage	EN 14680:2015

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

[name]

At [place] on [date of issue]

[signature]

ZA.3 CE marking and labelling

The CE marking symbol shall be in accordance with the general principles set out in Article 30 of Regulation (EC) No 765/2008 and shall be affixed visibly, legibly and indelibly:

to the packaging, together with:

- the last two digits of the year in which it was first affixed;
- the reference number of the declaration of performance;
- the reference to this harmonized European Standard.

Figure ZA.1 gives an example of the information related to adhesives for non-pressure thermoplastic piping systems subject to AVCP to be given on the adhesive packaging.


	<i>CE marking, consisting of the "CE"-symbol</i>
15	<i>Last two digits of the year in which the marking was first affixed</i>
00001-CPR-2013/05/12	<i>Reference number of the DoP</i>
EN 14680	<i>No. of European Standard applied, as referenced in OJEU</i>

Figure ZA.1 — Example CE marking information on adhesive packaging

to the accompanying documents, together with:

- the last two digits of the year in which it was first affixed;
- the name and the registered address of the manufacturer, or the identifying mark allowing identification of the name and address of the manufacturer easily and without any ambiguity;
- the reference number of the declaration of performance;
- the reference to this harmonized European Standard;
- the unique identification code of the product-type;
- the intended use as laid down in the harmonized technical specification applied;
- the level or class of the performance declared.

The CE marking shall be affixed before the construction product is placed on the market. It may be followed by a pictogram or any other mark notably indicating a special risk or use.

Figure ZA.2 gives an example of the information related to adhesives for non-pressure thermoplastic piping systems subject to AVCP to be given on the accompanying commercial documents.


	<i>CE marking, consisting of the "CE"-symbol</i>
15	<i>Last two digits of the year in which the marking was first affixed</i>
AnyCo Ltd, PO Box 21, B-1050, Brussels, Belgium	<i>Name and the registered address of the manufacturer, or identifying mark</i>
00001-CPR-2013/05/12	<i>Reference number of the DoP</i>
EN 14680	<i>No. of European Standard applied, as referenced in OJEU</i>
PVC-U Adhesive for non-pressure thermoplastic piping systems	<i>Unique identification code of the product-type</i>
In installations for the transport/disposal/storage of water not intended for human consumption	<i>Intended use of the product as laid down in the European Standard applied</i>
Resistance to pull out ≥ 0,25 MPa (N/mm²) at 1 h	<i>Level or class of the performance declared</i>
Resistance to pull out ≥ 1,5 MPa (N/mm²) at 24 h	
Resistance to pull out ≥ 3,0 MPa (N/mm²) at 480 h	
Tightness No leakage	
Resistance to high temperature No leakage	
Release of dangerous substances NPD	
Durability No leakage	

Figure ZA.2 — Example CE marking information on accompanying commercial documents

Bibliography

- [1] EN 542: 2003, *Adhesives — Determination of density*
- [2] EN 827:2005, *Adhesives — Determination of conventional solids content and constant mass solids content*
- [3] EN ISO 9001:2008, *Quality management systems — Requirements (ISO 9001:2008)*
- [4] EN 12092:2001, *Adhesives — Determination of viscosity*
- [5] EN ISO 11296-1:2011, *Plastics piping systems for renovation of underground non-pressure drainage and sewerage networks — Part 1: General (ISO 11296-1:2009)*
- [6] EN ISO 9229:2007, *Thermal insulation — Vocabulary (ISO 9229:2007)*
- [7] EN ISO 9311-1, *Adhesives for thermoplastic piping systems — Part 1: Determination of film properties (ISO 9311-1)*

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com



...making excellence a habit.™