

Fixed capacitors for use in electronic equipment —

**Part 11-1: Blank detail specification —
Fixed polyethylene-terephthalate film
dielectric metal foil d.c. capacitors —
Assessment level EZ**

ICS 31.060.30

National foreword

This British Standard is the UK implementation of EN 60384-11-1:2008. It is identical to IEC 60384-11-1:2008. It supersedes BS EN 130101:1998, BS EN 130102:1998 and BS QC 300101:1993, which are withdrawn.

The UK participation in its preparation was entrusted to Technical Committee EPL/40X, Capacitors and resistors for electronic equipment.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 29 August 2008

© BSI 2008

ISBN 978 0 580 57747 5

Amendments/corrigenda issued since publication

Date	Comments

English version

**Fixed capacitors for use in electronic equipment -
Part 11-1: Blank detail specification -
Fixed polyethylene-terephthalate film dielectric metal foil d.c. capacitors -
Assessment level EZ
(IEC 60384-11-1:2008)**

Condensateurs fixes utilisés
dans les équipements électroniques -
Partie 11-1: Spécification
particulière cadre -
Condensateurs fixes pour courant continu
à diélectrique en film de polytéréphtalate
d'éthylène à armatures
en feuilles métalliques -
Niveau d'assurance de la qualité EZ
(CEI 60384-11-1:2008)

Festkondensatoren zur Verwendung
in Geräten der Elektronik -
Teil 11-1: Vordruck
für Bauartspezifikation -
Festkondensatoren mit einem
Dielektrikum aus Polyethylen-Terephthalat
und Belägen aus dünnen Metallfolien
für Gleichspannung -
Bewertungsstufe EZ
(IEC 60384-11-1:2008)

This European Standard was approved by CENELEC on 2008-03-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

The text of document 40/1840/CDV, future edition 2 of IEC 60384-11-1, prepared by IEC TC 40, Capacitors and resistors for electronic equipment, was submitted to the IEC-CENELEC parallel Unique Acceptance Procedure and was approved by CENELEC as EN 60384-11-1 on 2008-03-01.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2008-12-01
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2011-03-01

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 60384-11-1:2008 was approved by CENELEC as a European Standard without any modification.

CONTENTS

Introduction.....	5
1 General data.....	6
1.1 Recommended method(s) of mounting.....	6
1.2 Dimensions.....	6
1.3 Ratings and characteristics.....	7
1.4 Normative references	7
1.5 Marking.....	7
1.6 Ordering information.....	7
1.7 Certified records of released lots.....	8
1.8 Additional information.....	8
1.9 Additional or increased severities or requirements to those specified in the generic and/or sectional specification.....	8
2 Inspection requirements.....	8
2.1 Procedures	8
Annex ZA (normative) Normative references to international publications with their corresponding European publications.....	15
Bibliography.....	14
Table 1 – Case size reference and dimensions.....	6
Table 2 – Values of capacitance and of voltage related to case sizes.....	7
Table 3 – Other characteristics.....	8
Table 4 – Test schedule for quality conformance inspection.....	8

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT –

Part 11-1: Blank detail specification – Fixed polyethylene-terephthalate film dielectric metal foil d.c. capacitors – Assessment level EZ

INTRODUCTION

Blank detail specification

A blank detail specification is a supplementary document to the sectional specification and contains requirements for style and layout and minimum content of detail specifications. Detail specifications not complying with these requirements may not be considered as being in accordance with IEC specifications nor shall they so be described.

In the preparation of detail specifications, the content of 1.4 of the sectional specification shall be taken into account.

The numbers between brackets on the first page correspond to the following information which shall be inserted in the position indicated.

Identification of the detail specification

- [1] The "International Electrotechnical Commission" or the National Standards Organization under whose authority the detail specification is drafted.
- [2] The IEC or National Standards number of the detail specification, date of issue and any further information required by the national system.
- [3] The number and issue number of the IEC or national generic specification.
- [4] The IEC number of the blank detail specification.

Identification of the capacitor

- [5] A short description of the type of capacitor.
- [6] Information on typical construction (when applicable).

NOTE When the capacitor is not designed for use in printed-board applications, this shall be clearly stated in the detail specification in this position.

- [7] Outline drawing with main dimensions which are of importance for interchangeability and/or reference to the national or international documents for outlines. Alternatively, this drawing may be given in an annex to the detail specification.
- [8] Application or group of applications covered and/or assessment level.

NOTE The assessment level(s) to be used in a detail specification are selected from 3.5.4 of the sectional specification. This implies that one blank detail specification may be used in combination with several assessment levels, provided the grouping of the tests does not change.

- [9] Reference data on the most important properties, to allow comparison between the various capacitor types.

	IEC 60384-11-1-XXX [2] QC 300101-XXX
[1]	
ELECTRONIC COMPONENTS OF ASSESSED QUALITY IN ACCORDANCE WITH:	IEC 60384-11-1 [4] QC 300101
[3]	FIXED POLYETHYLENE-TEREPHTHALATE FILM DIELECTRIC METAL FOIL D.C. CAPACITORS [5]
Outline drawing: (see Table 1) [...angle projection]	[6]
[7]	Assessment level(s): EZ [8]
[Other shapes are permitted within the dimensions given.]	
For Notes [1] to [9] see preceding page.	

Information on the availability of components qualified to this detail specification is given in the Qualified Products List.

(9)

1 General data

1.1 Recommended method(s) of mounting (to be inserted)

See IEC 60384-11, 1.4.2.

1.2 Dimensions

Table 1 – Case size reference and dimensions

Case size reference	Dimensions						
	mm						
	\varnothing	<i>L</i>	<i>H</i>	<i>d</i>		

NOTE 1 When there is no case size reference, Table 1 may be omitted and the dimensions shall be given in Table 2, which then becomes Table 1.

NOTE 2 The dimensions shall be given as maximum dimensions or as nominal dimensions with a tolerance.

1.3 Ratings and characteristics

- Capacitance range (see Table 2)
- Tolerance on rated capacitance
- Rated voltage (see Table 2)
- Category voltage (if applicable) (see Table 2)
- Climatic category
- Rated temperature
- Max. a.c. voltage (if applicable)
- Tangent of loss angle ($\tan \delta$)
- Insulation resistance

Table 2 – Values of capacitance and of voltage related to case sizes

Rated voltage				
Category voltage^a				
	Case size	Case size	Case size	Case size
Rated capacitance (in nF and/or μ F)				
^a If different from the rated voltage.				

1.4 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60384-11, *Fixed capacitors for use in electronic equipment – Part 11: Sectional specification – Fixed polyethylene-terephthalate film dielectric metal foil d.c. capacitors*

1.5 Marking

The marking of the capacitor and the package shall be in accordance with the requirements of 1.6 of IEC 60384-11.

The details of the marking of the component and package shall be given in full in the detail specification.

1.6 Ordering information

Orders for capacitors covered by this specification shall contain, in clear or in coded form, the following minimum information:

- a) rated capacitance;
- b) tolerance on rated capacitance;
- c) rated d.c. voltage;
- d) number and issue reference of the detail specification and style reference;
- e) packaging instructions.

1.7 Certified records of released lots

Required/not required.

1.8 Additional information (not for inspection purposes)**1.9 Additional or increased severities or requirements to those specified in the generic and/or sectional specification**

NOTE Additions or increased requirements should be specified only when essential.

Table 3 – Other characteristics

This table is to be used for defining characteristics which are additional to, or more severe than, those given in the sectional specification.

2 Inspection requirements**2.1 Procedures**

2.1.1 For qualification approval, the procedures shall be in accordance with 3.4 of the sectional specification, IEC 60384-11.

2.1.2 For quality conformance inspection, the test schedule (Table 4) includes sampling, periodicity, severities and requirements. The formation of inspection lots is covered by 3.5.1 of IEC 60384-11.

Table 4 – Test schedule for quality conformance inspection

Subclause number and test ^a	D or ND ^c	Conditions of test ^a	Number of specimens and number of non-conforming items ^c			Performance requirements ^a
			<i>IL</i>	<i>n</i>	<i>c</i>	
Group A inspection (lot-by-lot) Sub-group A0 4.2.2 Capacitance 4.2.3 Tangent of loss angle ($\tan \delta$) 4.2.1 Voltage proof (Test A) 4.2.4 Insulation resistance (Test A)	ND	Frequency : 1 kHz for all capacitance values Method: ... Measuring point 1a Measuring point 1a	100% ^d			Within specified tolerance As in 4.2.3.2 No breakdown or flashover As in 4.2.4.2
Group A inspection (lot-by-lot) Sub-group A1 4.1 Visual examination	ND		S-3	b	0	As in 4.1 Legible marking and as specified in 1.5 of this specification
Sub-group A2 4.1 Dimensions (gauging) ^e	ND		S-3	b	0	As specified in Table 1 of this specification

Table 4 – Test schedule for quality conformance inspection (continued)

Subclause number and test ^a	D or ND ^c	Conditions of test ^a	Number of specimens and number of non-conforming items ^c			Performance requirements ^a
			<i>IL</i>	<i>n</i>	<i>c</i>	
Group B inspection (lot-by-lot)						
Sub-group B1	ND		S-3	b	0	
4.5 Solderability (if applicable)		Without ageing Method: ...				Good tinning as evidenced by free flowing of the solder with wetting of the terminations or solder shall flow within ... s, as applicable
4.14 Solvent resistance of the marking (if applicable)		Solvent: ... Solvent temperature: ... Method 1 Rubbing material: cotton wool Recovery: ...				Legible marking
<p>^a Subclause numbers of tests and performance requirements refer to the sectional specification, IEC 60384-11, and Clause 1 of this specification.</p> <p>^b Number to be tested: sample size as directly allotted to the code letter for <i>IL</i> in Table 2a of IEC 60410.</p> <p>^c In this table: <i>IL</i> = inspection level <i>p</i> = periodicity in months <i>n</i> = sample size <i>c</i> = acceptance criterion (permitted number of non-conforming items) D = destructive ND = non-destructive</p> <p>^d 100 % testing shall be followed by re-inspection by sampling in order to monitor outgoing quality level by non-conforming items per million ($\times 10^{-6}$). The sampling level shall be established by the manufacturer. For the calculation of $\times 10^{-6}$ values, any parametric failure shall be counted as a non-conforming item. If one or more non-conforming items occur in a sample, this lot shall be rejected.</p> <p>^e This test may be replaced by in-production testing if the manufacturer installs Statistical Process Control (SPC) on dimensional measurements or other mechanisms to avoid components exceeding the limits.</p>						

Table 4 – Test schedule for quality conformance inspection (continued)

Subclause number and test ^a	D or ND ^c	Conditions of test ^a	Number of specimens and number of non-conforming items ^c			Performance requirements ^a
			<i>p</i>	<i>n</i>	<i>c</i>	
Group C inspection (periodic)						
Sub-group C1A	D		6	5	0 ^f	
Part of sample of Sub-group C-1						See detail specification
4.1 Dimensions (detail)						
4.4.1 Initial measurements		Capacitance Tangent of loss angle ($\tan \delta$): For $C_R \leq 10 \mu\text{F}$: at 1 kHz $C_R > 10 \mu\text{F}$: at 50 Hz to 120 Hz				
4.3 Robustness of terminations		Visual examination				No visible damage
4.4. Resistance to soldering heat		Method: ...				
4.4.2 Final measurements		Visual examination				No visible damage $\Delta C/C \leq 2\%$ of the value measured initially
4.13 Component solvent resistance (if applicable)		Solvent: ... Solvent temperature: ... Method 2 Recovery: ...				See detail specification
Sub-group C1B	D		6	5	0 ^f	
Other part of sample of Subgroup C1						
4.6.1 Initial measurements		Capacitance Tangent of loss angle ($\tan \delta$): For $C_R \leq 10 \mu\text{F}$: at 1 kHz $C_R > 10 \mu\text{F}$: at 50 Hz to 120 Hz				
4.6 Rapid change of temperature		T_A = Lower category temperature T_B = Upper category temperature Five cycles Duration $t_1 = 30$ min Visual examination				No visible damage
4.7 Vibration		Method of mounting, see 1.1 of this specification Procedure B4 Frequency range: ... Hz to ... Hz Amplitude: 0,75 mm or acceleration 98 m/s^2 (whichever is the less severe) Total duration: 6 h				

Table 4 – Test schedule for quality conformance inspection (continued)

Subclause number and test ^a	D or ND ^c	Conditions of test ^a	Number of specimens and number of non-conforming items ^c			Performance requirements ^a
			<i>p</i>	<i>n</i>	<i>c</i>	
4.7.2 Final inspection		Visual examination				No visible damage
4.8 Bump (or shock, see 4.9)		Method of mounting, see 1.1 of this specification Number of bumps: ... Acceleration: ... m/s ² Duration of pulse: ... ms				
4.9 Shock (or bump, see 4.8)		Method of mounting: see 1.1 of this specification Acceleration: ... m/s ² Duration of pulse: ... ms				
4.8.3 Final measurements or 4.9.3		Visual examination Capacitance Tangent of loss angle (tan δ)				No visible damage $\Delta C/C \leq 5\%$ of value measured in 4.6.1 See detail specification
Sub-group C1 Combined sample of specimens of Subgroups C1A and C1B	D		6	10	0 ^f	
4.10 Climatic sequence						
4.10.2 Dry heat		Temperature: upper category temperature Duration: 16 h				
4.10.3 Damp heat, cyclic, Test Db, first cycle						
4.10.4 Cold		Temperature: lower category temperature Duration: 2 h				
4.10.5 Low air pressure (if required by the detail specification)		Air pressure: 8,5 kPa (85 mbar)				
4.10.5.3 Intermediate inspection		Visual examination				No permanent breakdown, flashover or harmful deformation of the case
4.10.6 Damp heat, cyclic, Test Db, remaining cycles		Recovery: 1 h to 2 h				
4.10.6.2 Final measurements		Visual examination Capacitance Tangent of loss angle (tan δ) Insulation resistance				No visible damage Legible marking $\Delta C/C \leq 5\%$ of value measured in 4.4.2, 4.8.3 or 4.9.3 as applicable Tan $\delta \leq 0,01$ or 1,2 times values measured in 4.3.1 or 4.6.1, as applicable, whichever is the greater $\geq 50\%$ of values in 4.2.4.2

Table 4 – Test schedule for quality conformance inspection (continued)

Subclause number and test ^a	D or ND ^c	Conditions of test ^a	Number of specimens and number of non-conforming items ^c			Performance requirements ^a
			<i>p</i>	<i>n</i>	<i>c</i>	
Sub-group C2 4.11 Damp heat, steady state 4.11.1 Initial measurements 4.11.3 Final measurements		Capacitance Tangent of loss angle ($\tan \delta$) For $C_R \leq 10 \mu\text{F}$: at 1 kHz $C_R > 10 \mu\text{F}$: at 50 Hz to 120 Hz Recovery: 1 to 2 h Visual examination Capacitance Tangent of loss angle ($\tan \delta$) Insulation resistance	6	10	0 ^f	No visible damage Legible marking $\Delta C/C \leq 5\%$ of value measured in 4.11.1 $\tan \delta \leq 0,01$ or 1,2 times values measured in 4.11.1, whichever is the greater $\geq 50\%$ of values in 4.2.4.2
Sub-group C3 4.12 Endurance 4.12.1 Initial measurements 4.12.5 Final measurements	D	Duration: 1 000 h Capacitance Tangent of loss angle ($\tan \delta$) For $C_R \leq 10 \mu\text{F}$: at 1 kHz $C_R > 10 \mu\text{F}$: at 50 Hz to 120 Hz Recovery: 1 h to 2 h Visual examination Capacitance Tangent of loss angle ($\tan \delta$) Insulation resistance	6	10	0 ^f	No visible damage Legible marking $\Delta C/C \leq 5\%$ of value measured in 4.12.1 $\tan \delta \leq 0,01$ or 1,2 times values measured in 4.12.1, whichever is the greater $\geq 50\%$ of values in 4.2.4.2
Sub-group C4 4.2.5 Characteristics depending on temperature	ND	Capacitance	6	10	0 ^f	As in 4.2.5

Table 4 – Test schedule for quality conformance inspection (*continued*)

a	Subclause numbers of tests and performance requirements refer to the sectional specification, IEC 60384-11, and Clause 1 of this specification.
b	Number to be tested: sample size as directly allotted to the code letter for <i>IL</i> in Table 2a of IEC 60410.
c	In this table: <i>IL</i> = inspection level <i>p</i> = periodicity in months <i>n</i> = sample size <i>c</i> = acceptance criterion (permitted number of non-conforming items) <i>D</i> = destructive <i>ND</i> = non-destructive
d	100 % testing shall be followed by re-inspection by sampling in order to monitor outgoing quality level by non-conforming items per million ($\times 10^{-6}$). The sampling level shall be established by the manufacturer. For the calculation of $\times 10^{-6}$ values, any parametric failure shall be counted as a non-conforming item. If one or more non-conforming items occur in a sample, this lot shall be rejected.
e	This test may be replaced by in-production testing if the manufacturer installs Statistical Process Control (SPC) on dimensional measurements or other mechanisms to avoid components exceeding the limits.
f	If one non-conforming item is obtained, all the tests of the subgroup shall be repeated on a new sample and then no further non-conforming items are permitted. Release of product may continue during repeat testing.

Bibliography

IEC 60384-1, *Fixed capacitors for use in electronic equipment – Part 1: Generic specification*

NOTE Harmonized as EN 60384-1:2001 (modified).

Annex ZA
(normative)

**Normative references to international publications
with their corresponding European publications**

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60384-11	- ¹⁾	Fixed capacitors for use in electronic equipment - Part 11: Sectional specification - Fixed polyethylene-terephthalate film dielectric metal foil d.c. capacitors	EN 60384-11	2008 ²⁾

¹⁾ Undated reference.

²⁾ Valid edition at date of issue.

British Standards Institution (BSI)

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover.
Tel: +44 (0)20 8996 9000 Fax: +44 (0)20 8996 7400

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services.

Tel: +44 (0)20 8996 9001 Fax: +44 (0)20 8996 7001

Email: orders@bsigroup.com

You may also buy directly using a debit/credit card from the BSI Shop on the Website <http://www.bsigroup.com/shop>.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre.

Tel: +44 (0)20 8996 7111 Fax: +44 (0)20 8996 7048

Email: info@bsigroup.com

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration.

Tel: +44 (0)20 8996 7002 Fax: +44 (0)20 8996 7001

Email: membership@bsigroup.com

Information regarding online access to British Standards via British Standards Online can be found at <http://www.bsigroup.com/BSOL>.

Further information about BSI is available on the BSI website at <http://www.bsigroup.com>.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright & Licensing Manager.

Tel: +44 (0)20 8996 7070 Email: copyright@bsigroup.com