

BS EN 60684-3-281:2010



BSI Standards Publication

Flexible insulating sleeving

Part 3: Specifications for individual types of sleeving — Sheet 281: Heat-shrinkable, polyolefin sleeving, semiconductive

bsi.

...making excellence a habit.™

National foreword

This British Standard is the UK implementation of EN 60684-3-281:2010. It is identical to IEC 60684-3-281:2010.

The UK participation in its preparation was entrusted by Technical Committee GEL/15, Solid electrical insulating materials, to Subcommittee GEL/15/5, Flexible insulating sleeving for electrical purposes.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© BSI 2011

ISBN 978 0 580 65790 0

ICS 29.035.20

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 28 February 2011.

Amendments issued since publication

Amd. No.	Date	Text affected
-----------------	-------------	----------------------

**Flexible insulating sleeving -
Part 3: Specifications for individual types of sleeving -
Sheet 281: Heat-shrinkable, polyolefin sleeving, semiconductive
(IEC 60684-3-281:2010)**

Gaines isolantes souples -
Partie 3: Spécifications pour types
particuliers de gaines -
Feuille 281: Gaines thermorétractables
en polyoléfine, semiconductrices
(CEI 60684-3-281:2010)

Isolierschläuche -
Teil 3: Anforderungen für einzelne
Schlauchtypen -
Blatt 281: Halbleitende Polyolefin-
Wärmeschrumpfschläuche
(IEC 60684-3-281:2010)

This European Standard was approved by CENELEC on 2010-09-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 15/563/FDIS, future edition 1 of IEC 60684-3-281, prepared by IEC TC 15, Solid electrical insulating materials, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 60684-3-281 on 2010-09-01.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN and CENELEC shall not be held responsible for identifying any or all such patent rights.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2011-06-01
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2013-09-01

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 60684-3-281:2010 was approved by CENELEC as a European Standard without any modification.

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
-	-	Test requirements on accessories for use on power cables of rated voltage from 3,6/6(7,2) kV up to 20,8/36(42) kV - Part 1: Cables with extruded insulation	HD 629.1 S2	2006
IEC 60296	2003	Fluids for electrotechnical applications - Unused mineral insulating oils for transformers and switchgear	EN 60296 + corr. September	2004 2004
IEC 60502	Series	Power cables with extruded insulation and their accessories for rated voltages from 1 kV (Um = 1,2 kV) up to 30 kV (Um = 36 kV)	-	-
IEC 60684-1	2003	Flexible insulating sleeving - Part 1: Definitions and general requirements	EN 60684-1	2003
IEC 60684-2 + A1 + A2	1997 2003 2005	Flexible insulating sleeving - Part 2: Methods of test	EN 60684-2 + A1 + A2	1997 2003 2005
IEC 60757	1983	Code for designation of colours	HD 457 S1	1985

CONTENTS

INTRODUCTION.....	5
1 Scope.....	6
2 Normative references	6
3 Designation	7
4 Conditions of test	7
5 Requirements	7
6 Sleeving conformance	7
Annex A (informative) Guidance to the available sizes and wall thicknesses	10
Table 1 – Property requirements	8
Table 2 – Resistance to selected fluids	9
Table A.1 – Type A, thin wall	10
Table A.2 – Type B, medium wall	10

INTRODUCTION

This International Standard is one of a series which deals with flexible insulating sleeving for electrical purposes.

The series consists of three parts:

Part 1: Definitions and general requirements (IEC 60684-1)

Part 2: Methods of test (IEC 60684-2)

Part 3: Specifications for individual types of sleeving (IEC 60684-3)

This standard comprises one of the sheets of Part 3 as follows:

Sheet 281: Heat-shrinkable, polyolefin sleeving, semiconductive

FLEXIBLE INSULATING SLEEVING –

Part 3: Specifications for individual types of sleeving – Sheet 281: Heat-shrinkable, polyolefin sleeving, semiconductive

1 Scope

This part of IEC 60684 gives the requirements for two types of heat-shrinkable, polyolefin sleeving, semiconductive, with a nominal shrink ratio of 3:1.

This sleeving has been found suitable up to temperatures of 100 °C.

- Type A: Thin wall Internal diameter up to 195,0 mm typically
- Type B: Medium wall Internal diameter up to 120,0 mm typically

These sleeveings are normally supplied in the colour black.

Since these types of sleeveings cover a significantly large range of sizes and wall thicknesses, Tables A.1 and A.2 in this standard provides guidance to the range of sizes available. The actual size shall be agreed between the user and the supplier.

Materials which conform to this specification meet established levels of performance. However, the selection of a material by a user for a specific application should be based on the actual requirements necessary for adequate performance in that application and not based on this specification alone.

This sleeving is designed to be used in MV cable accessories and as such electrical performance must be proven as part of the assembly. Examples of this are described in HD 629 and IEC 60502 series.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60296:2003, *Fluids for electrotechnical applications – Unused mineral insulating oils for transformers and switchgear*

IEC 60502 (all parts), *Power cables with extruded insulation and their accessories for rated voltages from 1 kV ($U_m = 1,2$ kV) up to 30 kV ($U_m = 36$ kV)*

IEC 60684-1:2003, *Flexible insulating sleeving – Part 1: Definitions and general requirements*

IEC 60684-2:1997, *Flexible insulating sleeving – Part 2: Methods of test*
Amendment 1 (2003)
Amendment 2 (2005)

IEC 60757:1983, *Code for designation of colours*

HD 629, *Test requirements on accessories for use on power cables of rated voltages from 3,6/6(7,2)kV up to 20,8/36 (42)kV – Part 1: Cables with extruded insulation*

3 Designation

The sleeving shall be identified by the following designation:

Description	IEC publication number	IEC part number	IEC sheet number	Type	Size (expanded and recovered internal diameter in millimetres)	Colour
↓	↓	↓	↓	↓	↓	↓
Sleeving	IEC 60684	- 3	-281	- A	- 50/20	Black

Any colour abbreviation shall comply with IEC 60757, where applicable. Non-standard colours shall be written out in full.

NOTE This information is for labelling only in accordance with IEC 60684-1.

4 Conditions of test

Unless otherwise specified, the sleeving shall be shrunk in a forced air circulation oven for (10 ± 1) min at $200 \text{ }^\circ\text{C} \pm 3 \text{ K}$ prior to testing.

5 Requirements

In addition to the general requirements given in IEC 60684-1, the sleeving shall comply with the requirements of Tables 1 and 2.

6 Sleeving conformance

Conformance to the requirements of this specification shall normally be based on the results from typical sizes:

- Type A, Thin wall: Recovered ID 20 mm - 30 mm
- Type B, Medium wall: Recovered ID 20 mm - 30 mm

Table 1 – Property requirements

Property	IEC 60684-2 clause or subclause	Units	Max. or min.	Requirements	Remarks
Dimensions – Internal diameter – Wall thickness – Concentricity – expanded – recovered	3 3.1.2 3.3.2 3.3.3	mm mm %	Min. Min.	To be agreed between the purchaser and the supplier 60 85	
Heat shock Tensile strength Elongation at break	6 19.1 and 19.2 19.1 and 19.2	MPa %	Min. Min.	8 175	Heat at 150 °C ± 5 K.
Longitudinal change	9	%	Max.	+5 –10	
Bending at low temperature	14	–	–	No cracking shall be visible.	Test at –40 °C For strips, the mandrel shall be between 20 and 22 times the wall thickness. Full section sleeving is tested unfilled and the mandrel shall be between 20 and 22 times the outer diameter.
Dimensional stability on storage	16	–	–	The dimensions shall remain as agreed.	See Clause 1 Scope.
Tensile strength Elongation at break	19.1 and 19.2 19.1 and 19.2	MPa %	Min. Min.	10 200	Use a jaw separation rate of 100 mm/min. Below 6,5 mm Ø as sleeving. At 6,5 mm Ø and above as dumbbells
Secant modulus at 2 % elongation	19.4	MPa	Max.	250	
Resistance to selected fluids Tensile strength Elongation at break	36 19.1 and 19.2 19.1 and 19.2	MPa %	Min. Min.	8 175	Use the fluids and test temperatures specified in Table 2. Immersion (24 ± 1) h
Heat ageing Tensile strength Elongation at break	39 19.1 and 19.2 19.1 and 19.2	MPa %	Min. Min.	8 175	Heat at 135 °C ± 3 K.
Volume resistivity at room temperature	23 23.4.2	Ω·m	Min.	10 ³	See note.
Long term ageing Elongation at break	50 19.2	%	Min.	100	The ageing temperature shall be 100 °C ± 3 K.

NOTE This value is set so as to define the tube as conductive. It does not indicate any guarantee of suitable performance in an accessory and further testing by the supplier will be needed to prove this. Note also that the value may change with applied voltage.

Table 2 – Resistance to selected fluids

Test fluid No.	Fluids	Type	Standard or symbol	Immersion temperature at °C ± 2 K
1	Insulating oil	Mineral based	IEC 60296	23
2			Isopropyl alcohol	23
3	–	Water	De-ionized	85

Other fluids and/or temperatures may be specified for customers with specific needs. These additional fluids and/or temperatures shall be applicable when incorporated into agreements between the supplier and the customer.

Annex A (informative)

Guidance on the available sizes and wall thicknesses

Table A.1 – Type A, thin wall

Internal diameter		Wall
Expanded Min. mm	Recovered Max. mm	Recovered wall thickness mm
20,0	8,0	2,0
25,0	10,0	2,0
30,0	12,0	2,0
38,0	16,0	2,0
40,0	15,0	2,0
50,0	20,0	2,0
65,0	24,0	2,0
75,0	28,0	2,0
80,0	24,0	2,0
95,0	35,0	2,0
110,0	45,0	2,0
120,0	55,0	2,0
155,0	65,0	2,0
180,0	70,0	2,0
195,0	90,0	2,5

Table A.2 – Type B, medium wall

Internal diameter		Wall
Expanded Min. mm	Recovered Max. mm	Recovered wall thickness mm
36,0	10,0	3,0
51,0	14,0	3,0
63,0	18,0	3,0
70,0	23,0	3,0
85,0	22,0	3,0
90,0	34,0	3,0
95,0	29,0	3,0
120,0	34,0	3,0

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com



...making excellence a habit.™