

BS EN 62087-4:2016



BSI Standards Publication

Audio, video and related equipment — Determination of power consumption

Part 4: Video recording equipment

National foreword

This British Standard is the UK implementation of EN 62087-4:2016. It is identical to IEC 62087-4:2015. Together with BS EN 62087-1:2016, BS EN 62087-2, BS EN 62087-3:2016, BS EN 62087-5:2016 and BS EN 62087-6:2015 it supersedes BS EN 62087:2012 which will be withdrawn on 19 February 2019.

The UK participation in its preparation was entrusted to Technical Committee EPL/100, Audio, video and multimedia systems and equipment.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2016.

Published by BSI Standards Limited 2016

ISBN 978 0 580 82956 7

ICS 33.160.10

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 April 2016.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

English Version

Audio, video and related equipment - Determination of power
consumption - Part 4: Video recording equipment
(IEC 62087-4:2015)

Appareils audio, vidéo et matériel connexe - Détermination
de la consommation de puissance - Partie 4: Matériel
d'enregistrement vidéo
(IEC 62087-4:2015)

Messverfahren für die Leistungsaufnahme von Audio,
Video- und verwandten Geräten -
Teil 4: Videoaufzeichnungsgeräte
(IEC 62087-4:2015)

This European Standard was approved by CENELEC on 2015-07-10. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

European foreword

The text of document 100/2469/FDIS, future edition 1 of IEC 62087-4, prepared by Technical Area 12 “AV energy efficiency and smart grid applications” of IEC/TC 100 “Audio, video and multimedia systems and equipment” was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62087-4:2016.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2016-08-19
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2019-02-19

This document supersedes EN 62087:2012 (partially).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 62087-4:2015 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61938:2013	NOTE	Harmonized as EN 61938:2013 (not modified).
IEC 62087 Series	NOTE	Harmonized as EN 62087 Series.
IEC 62087-2:2015	NOTE	Harmonized as EN 62087-2:2015 (not modified).
IEC 62301:2011	NOTE	Harmonized as EN 50564:2011 (modified).
IEC 62542:2013	NOTE	Harmonized as EN 62542:2013 (not modified).

Annex ZA
(normative)

**Normative references to international publications
with their corresponding European publications**

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60107-1	1997	Methods of measurement on receivers for television broadcast transmissions - Part 1: General considerations - Measurements at radio and video frequencies	EN 60107-1	1997
IEC 62087-1	2015	Audio, video, and related equipment - Determination of power consumption - Part 1: General	EN 62087-1	2016
IEC 62216	2009	Digital terrestrial television receivers for the DVB-T system	EN 62216	2011

CONTENTS

FOREWORD	3
INTRODUCTION	5
1 Scope	6
2 Normative references	6
3 Terms, definitions and abbreviations	6
3.1 Terms and definitions	6
3.2 Abbreviations	7
4 Specification of operating modes and functions	7
4.1 General	7
4.2 Auto power down function	8
5 Measuring conditions for video recorders	9
5.1 Input signal	9
5.1.1 General	9
5.1.2 RF test signal	9
5.1.3 Broadband input signal	9
5.2 Input terminals	9
5.2.1 Analogue terrestrial input terminal	9
5.2.2 Cable television input terminal	10
5.2.3 Digital terrestrial input terminal	10
5.2.4 Satellite input terminal	10
5.3 Measurement procedure	10
5.3.1 General measuring conditions	10
5.3.2 Stabilization	10
5.3.3 Environmental conditions	10
5.3.4 Setup	10
5.3.5 Power measurements	11
Bibliography	15
Figure 1 – Auto power down function	14
Table 1 – Operating modes and functions	8
Table 2 – Matrix for multituner VRs	12

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**AUDIO, VIDEO AND RELATED EQUIPMENT –
DETERMINATION OF POWER CONSUMPTION –****Part 4: Video recording equipment**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62087-4 has been prepared by technical area 12: AV energy efficiency and smart grid applications, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

This first edition of IEC 62087-4 cancels and replaces Clause 7 of IEC 62087:2011. This standard together with IEC 62087-1 to IEC 62087-3 and IEC 62087-5 to IEC 62087-6 cancels and replaces IEC 62087:2011. This International Standard constitutes a technical revision.

This edition includes significant technical changes with respect to Clause 7 of IEC 62087:2011. The changes include fundamental and extensive revisions to cover video recorders such as DVD and BD types as well as recorders with removable solid state memory. Clause 7 has been revised in its entirety.

The text of this standard is based on the following documents:

FDIS	Report on voting
100/2469/FDIS	100/2499/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

A list of all parts in the IEC 62087 series, published under the general title *Audio, video, and related equipment – Determination of power consumption*, can be found on the IEC website.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

This part of IEC 62087 specifies methods of measurement for the power consumption of video recording equipment for consumer use.

IEC 62087:2011 revises methods for measuring power consumption of set top boxes mainly in the modes of On mode and Standby-active, high mode. These modes correspond to the active modes which are defined in IEC 62542:2013.

This standard has been divided into multiple parts. At the time of publication of this part, the following parts are planned or published:

- Part 1: General
- Part 2: Signals and media
- Part 3: Television sets
- Part 4: Video recording equipment
- Part 5: Set-top boxes (STB)
- Part 6: Audio equipment

AUDIO, VIDEO AND RELATED EQUIPMENT – DETERMINATION OF POWER CONSUMPTION –

Part 4: Video recording equipment

1 Scope

This part of IEC 62087 specifies methods of measurement for the power consumption of video recording equipment with removable media. It specifies the different modes of operation which are relevant for measuring power consumption.

The methods of measurement are applicable only for equipment which can be connected to the mains.

The measuring conditions in this standard represent the normal use of the equipment and may differ from specific conditions, as specified, for example, in safety standards.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60107-1:1997, *Methods of measurement on receivers for television broadcast transmissions – Part 1: General considerations – Measurements at radio and video frequencies*

IEC 62087-1:2015, *Audio, video, and related equipment – Methods of measurement for power consumption – Part 1: General*

IEC 62216:2009, *Digital terrestrial television receivers for the DVB-T system*

3 Terms, definitions and abbreviations

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62087-1:2015, as well as the following apply.

3.1.1

additional functions

functions that are not required for the basic operation of the equipment

3.1.2

buffering

temporary storage of video and audio streams in some form of memory in order to perform time shifting functions

3.1.3

hard disk drive

non removable media with a spinning disk for recording video and audio

3.1.4

removable media

write-once or rewritable device to store audio, video or other data via a standardized read/write interface usable in all devices with the respective interface

Note 1 to entry: Examples include optical discs (DVD, BD), memory cards, video tape cassettes.

3.1.5

television set

TV

equipment for the reception and display of television broadcast and similar services for terrestrial, cable, satellite and broadband network transmission of analogue and/or digital signals

Note 1 to entry: A television set may include additional functions that are not required for its basic operation.

3.1.6

time shifting

capability of a device to allow playback type functions with real time broadcast

Note 1 to entry: Such functions may include fast forward, review (rewind), pause and slow motion.

3.1.7

video recording equipment

equipment for the recording and reproduction of video and audio signals on a recording medium

Note 1 to entry: Equipment with only playback function are included as well.

Note 2 to entry: Examples are video cassette recorder (VCR) or a digital versatile disc (DVD) player or recorder.

3.2 Abbreviations

'	Prime
BD	Blu-ray Disc™ ¹
DVD	Digital Versatile Disc
EPG	Electronic Program Guide
IP	Internet Protocol
HD	High Definition (720 p or better)
LNB	Low Noise Block converter
PF	Picture Failure point
RF	Radio Frequency
SD	Standard Definition
TV	TeleVision set
VCR	Video Cassette Recorder
VR	Video Recorder

4 Specification of operating modes and functions

4.1 General

Table 1 contains the operating modes and functions for video recorders.

¹ Blu-ray Disc™ is a trade mark of the Blue-ray Disc Association. This information is given for the convenience of users of this document and does not constitute an endorsement by IEC of the product named.

4.2 Auto power down function

An auto power down feature may be implemented on a VR to power down into a Partial On mode after a predetermined time and possibly predetermined conditions. Such a feature should be referred to as auto power down.

Table 1 – Operating modes and functions

Power	Mode	Sub-mode	Function(s)	Description
0 W	Disconnected	Disconnected	Disconnect	The equipment is disconnected from all external power sources.
≥0 W	Off	Off	Off	The equipment is connected to an external power source and provides no functions that depend on a power source. The equipment cannot be switched into any other mode with the remote control unit, or an external or internal signal. Note that some power may be consumed if an EMC filter or other components exist on the source side of the power switch.
>0 W	Partial On	Standby-passive	<ul style="list-style-type: none"> – Wake on – remote control – internal signal 	The equipment is connected to an external power source and does not provide its primary functions. The equipment can be switched into another mode with the remote control unit or an internal signal, but not with an external signal.
		Standby-active, low	<ul style="list-style-type: none"> – Wake on – remote control – internal signal – external signal 	The equipment is connected to an external power source and does not provide its primary functions. The equipment can be switched into another mode with the remote control unit, an internal signal, or an external signal.
		Standby-active, high	<ul style="list-style-type: none"> – Wake on – remote control – internal signal – external signal – Data communications 	The equipment is connected to an external power source and does not provide its primary functions. The equipment can be switched into another mode with the remote control unit, an internal signal, or an external signal. Additionally, the equipment is exchanging/receiving data with/from an external source.
	On	On-play	Playing a programme	Playing content from a build in storage device, from removable media or streamed via a device port.
		On-broadcast	Pictures and sound from a broadcast	The equipment is performing the function of providing a viewer with video and audio from a broadcast.
		On-record	Recording a programme from a broadcast	The equipment is connected to a power source and records a signal from an external or internal source.
		On-multifunction	Recording Playing back	The equipment is performing multifunction “On-play” and/or “On-record” simultaneously.

5 Measuring conditions for video recorders

5.1 Input signal

5.1.1 General

In general terms, input signals shall be of the strength and quality for the type of broadcast system on which the VR is intended to be used. Where a VR supports multiple broadcast systems, it shall be tested for each broadcast system in which it operates. Each measured result shall be described in the report.

5.1.2 RF test signal

5.1.2.1 General

For digital terrestrial, satellite and cable VRs, the test signal shall be a signal representative of those present in the typical environment in which the VR is intended to be used. The video and audio components of the transport stream shall be as described in 5.1.2.2 and 5.1.2.3. For analogue terrestrial, satellite and cable VRs, the signal should be typical of the type of signal the VR is designed to receive.

5.1.2.2 Video test signal

The VR shall be tested using an appropriate input signal. This signal should be at the highest resolution that the VR is capable of decoding using the most processing intensive advanced decoding standard of the intended broadcast system(s) that the VR will be used on. A description of the signal used for the test shall be included in the test report. This description shall include at a minimum, resolution, frame rate and bit rate.

If the VR under test is an HD decoder, additional testing may also be conducted with an SD input signal.

Where the VR is operating in a download or recording mode, the input signal should contain content that simulates material that would typically be downloaded or recorded.

Where a VR has a conditional access system, it should be tested whilst decoding encrypted content.

Where a VR can record other services than the one being watched, the test signal should contain sufficient services to enable this feature to be tested.

5.1.2.3 Audio test signal

The VR shall be tested using an appropriate input signal. The audio test signal should have the maximum data rate (bit/s).

The audio format used during the power measurement shall be described in the report.

5.1.3 Broadband input signal

An input signal that provides the equivalent multiplexed transport stream as an appropriate internet protocol (IP) broadband signal conforming to 5.1.2.2 and 5.1.2.3.

5.2 Input terminals

5.2.1 Analogue terrestrial input terminal

If the VR is being tested with an analogue terrestrial RF input signal, the signals used shall conform to IEC 60107-1:1997, 3.3, and shall have the input signal level set at –39 dB(mW)

when terminated with a 75Ω resistor or at a level to provide a perceptually noise free or error free picture.

NOTE 39 dB(mW) corresponds to 70 dB(μ V).

5.2.2 Cable television input terminal

If the VR is being tested with a cable television RF input signal, the signals used shall conform to the cable television specifications for the region, and shall have the input signal level set at -49 dB(mW) with a termination of 75Ω resistor or at a level to provide better than the picture failure point (PF) as defined in IEC 62216 for digital signals or a perceptually noise free picture or error free for analogue signals.

NOTE 49 dB(mW) corresponds to 60 dB(μ V).

5.2.3 Digital terrestrial input terminal

If the VR is being tested with a digital terrestrial RF input signal, the signals used shall conform to the broadcast specifications for the region, and shall have the input signal level set at -49 dB(mW) with a termination of 75Ω resistor or at a level to provide better than the picture failure point (PF) as defined in IEC 62216 or a perceptually noise free picture.

5.2.4 Satellite input terminal

If the television set is being tested with a satellite input signal, the input signal level shall be set at -49 dB(mW) with a termination of 75Ω resistor or at a level to provide better than the picture failure point (PF) as defined in IEC 62216 for digital signals or a perceptually noise free picture or error free for analogue signals.

5.3 Measurement procedure

5.3.1 General measuring conditions

The general measuring conditions including the type of power meters to be used is as per IEC 62087-1:2015 except where conditions are otherwise specified in this subclause.

5.3.2 Stabilization

The measurements shall be performed after the VR has achieved a stable condition with respect to power consumption. Refer also to IEC 62087-1:2015.

NOTE There are several ways to consider a VR stable. For example, a VR can be considered stable between 15 min and 30 min after entering into each operation mode. In this case, the time used to stabilize the VR shall be recorded in the test report. A VR can be also considered stable when any of the results of the same test repeated are within 2 %.

5.3.3 Environmental conditions

The ambient temperature shall be $23 \text{ }^\circ\text{C} \pm 5 \text{ }^\circ\text{C}$. Refer also to IEC 62087-1:2015.

5.3.4 Setup

The VR shall be set up in a manner to simulate a normal operating environment. In this condition, the measurement shall be made without optional peripheral devices attached to the device. The input signals to the VRs may be either live signals or generated test streams that simulate live signals that the VR is designed to receive and decode.

Where a VR can power an LNB of an antenna amplifier this power shall not be included in the measurement. Where possible this power supply should be disabled. Where it cannot be disabled isolation connectors should be used to isolate the power supply.

If required the LNB or antenna amplifier should be powered from an external power source to the VR.

If possible, any function which may work in background of any On mode function should be disabled (turned off). If possible, any function which may cause the interruption of any On mode function should also be disabled (turned off). If they cannot be disabled the measurement should be scheduled so as to avoid working such background functions during the measurement.

NOTE Examples of background and/or interrupt functions for any On mode function are:

- background software download/install;
- timer recording;
- automatic deletion of an old TV programme which was recorded.

5.3.5 Power measurements

5.3.5.1 General

The VR under test shall be measured in each applicable mode as specified below. In the case of HD VRs, testing shall be with an HD input signal. Testing with an SD input signal may also be conducted. Where the SD test is conducted on an HD VR, the result shall be recorded as $P_{AV_ON_SD}$. If possible disable the time shifting function.

Unless the power measurement is being made with removable media any other removable media not being used shall be removed.

5.3.5.2 On-broadcast

Measure the average power consumed for at least 2 min. Record this as P_{AV_ON} . Record the time used to measure the average power.

5.3.5.3 On-play

Start a playback of a previously recorded programme on the VR and measure the average power consumed for at least 2 min. Record this as P_{PL} . Record the time used to measure the average power.

Start a playback of a programme on the removable media inserted into the VR and measure the average power consumed for at least 2 min. Record this as P_{RPL} . Record the time used to measure the average power.

5.3.5.4 On-record

Start or schedule a recording. With the VR recording the programme, measure the average power consumed for at least 2 min. Record this as P_{REC_ON} . Record the time used to measure the average power.

Start or schedule a recording. With the VR recording the programme to the inserted removable media measure the average power consumed for at least 2 min. Record this as $P_{REC_RM_ON}$. Record the time used to measure the average power.

5.3.5.5 On-multifunction with a single tuner

Set the VR to record a programme while simultaneously playing back a previously recorded programme and measure the average power consumed for at least 2 min. Record this as P_{MF_ST} . Record the time used to measure the average power. Time shifting is covered in this measurement as this is the case when the VR is playing back the same program as it is recording.

NOTE The mechanism for multifunction with a single tuner is the same as for time shift or recording.

5.3.5.6 On-multifunction with a multituner

Table 2 shows the matrix that shall be used to characterize a multituner VR.

Table 2 – Matrix for multituner VRs

	Tuner	Viewing	Add 2 nd tuner recording HD or SD	Add 3 rd tuner recording HD or SD ^a	Add 4 th tuner recording HD or SD ^a	Add <i>n</i> th tuner recording HD or SD ^a
Sequence 1	$P_{MFA_SD_n}$	SD	$P_{MFA_SD_2}$	$P_{MFA_SD_3}$	$P_{MFA_SD_4}$	$P_{MFA_SD_n}$
Sequence 2	$P_{MFA_HD_n}$	HD	$P_{MFA_HD_2}$	$P_{MFA_HD_3}$	$P_{MFA_HD_4}$	$P_{MFA_HD_n}$
^a If fitted.						

Measure the average power for at least 2 min for each of the modes in the matrix. Record the time used to measure the average power.

For SD VRs, only sequence 1 shall be performed. For HD VRs, both sequence 1 and sequence 2 shall be performed.

5.3.5.7 Standby-active, high

If possible, activate a download mode from the primary service and measure the average power consumed for at least 2 min. This measurement may require information from the manufacturer and/or service provider to ensure the transport stream contains a suitable download and instructions on how to set the VR to receive the download. Record this value as P_{SAH} . Record the time used to measure the average power.

NOTE It may not be possible to place the VR into this mode. If this is the case and the value is still required, it may have to be provided by a manufacturer's declaration.

5.3.5.8 Standby-active, low

To ensure that the VR is in standby active and not performing any downloading or recording function, the following procedure should be used.

- Put the VR into its on mode.
- If the VR is capable of scheduling a recording then schedule a recording 2 or more hours in the future.
- After 5 min in this mode, press the standby or off button on the remote control.
- Leave the VR for a minimum of 30 min or until higher power mode maintenance activities within the UUT have been completed.

Measure the average power consumed for at least 2 min. Record this as P_{SAL} . Record the time used to measure the average power. Record the time taken to switch to standby active, low.

5.3.5.9 Standby-passive

To ensure that the VR is in standby passive, the following procedure should be used.

- a) Put the VR into its On mode.
- b) If the VR is capable of scheduling a recording then schedule a recording 2 or more hours in the future.
- c) After 5 min in this mode, press the standby or off button on the remote control.
- d) Leave the VR for a minimum of 30 min or until higher power mode maintenance activities within the UUT activities have been completed.

Measure the average power consumed for at least 2 min. Record this as P_{SP} . Record the time used to measure the average power. Record the time taken to switch to Standby- passive.

NOTE The method for determining standby-active, low and standby-passive are identical as the switching into either one of these modes is the same. Which mode the VR actually switches to is actually determined by the platform in which the VR is operating. A VR with a terrestrial tuner will be more likely to be in a passive mode and a VR with a cable or satellite tuner will be more likely to be in a standby-active, low mode. Both methods are specified here to be consistent with the definitions in Table 1.

5.3.5.10 Off

Turn the VR off using the power switch, if available, and measure the average power consumed for at least 2 min. Record this as P_{OFF} . Record the time used to measure the average power.

5.3.5.11 Auto power down

If the UUT includes an auto power down feature, use the following procedure to determine the auto power down interval and the power consumption after auto power down is completed. (See Figure 1.)

- a) Place the UUT in the On mode with the auto power down function enabled. The auto power down interval is specified by the manufacturer. The auto power down interval should be reported.
- b) Stop any main functions of the UUT and start a timer to determine the auto power down interval.
- c) Allow the UUT to automatically power down.
- d) Monitor the power consumption of the UUT until the power consumption stabilizes.
- e) Stop the timer and report the auto power down interval.
- f) Measure the average power consumed for a 2 min. Record this as P_{APD} .




Figure 1 – Auto power down function

Bibliography

IEC 61938:2013, *Multimedia systems – Guide to the recommended characteristics of analogue interfaces to achieve interoperability*

IEC 62087 (all parts), *Audio, video, and related equipment – Determination of power consumption*

IEC 62087-2:2015, *Audio, video, and related equipment – Methods of measurement for power consumption – Part 2: Signals and media*

IEC 62301:2011, *Household electrical appliances – Measurement of standby power*

IEC 62542:2013, *Environmental standardization for electrical and electronic products and systems – Glossary of terms*

EN 50049-1:1998, *Domestic and Similar Electronic Equipment Interconnection Requirements: Peritelevision Connector*

SMPTE EG 1-1990 (Archived 2004), *Alignment Color Bar Test Signal for Television Picture Monitors*

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK