

BS IEC 62899-402-1:2017



BSI Standards Publication

Printed electronics

Part 402-1: Printability — Measurement of qualities — Pattern width

National foreword

This British Standard is the UK implementation of IEC 62899-402-1:2017.

The UK participation in its preparation was entrusted to Technical Committee AMT/9, Printed Electronics.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2017.

Published by BSI Standards Limited 2017

ISBN 978 0 580 89201 1

ICS 31.180

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 March 2017.

Amendments/corrigenda issued since publication

Date	Text affected
-------------	----------------------



INTERNATIONAL STANDARD



**Printed electronics –
Part 402-1: Printability – Measurement of qualities – Pattern width**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.180

ISBN 978-2-8322-3998-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	3
INTRODUCTION.....	5
1 Scope.....	6
2 Normative references	6
3 Terms and definitions	6
4 Atmospheric conditions for evaluation and conditioning	7
5 Measuring methods and instruments	7
5.1 Measuring instrument.....	7
5.2 Preparation of imaging (specimen).....	7
5.3 Measuring method	7
5.4 Obtaining width and related attributes	8
6 Report of results	9
6.1 Measurement identification information	9
6.2 Instrument system and its specification	9
6.3 Measuring position.....	9
6.4 Results	9
Annex A (normative) Drawing method of inner edge lines and outer edge lines.....	11
Bibliography.....	12
Figure 1 – Captured image of two edges of pattern and inner/outer edge lines.....	8
Figure 2 – Obtained position difference as a function of y	8
Table 1 – Example of reporting items	10

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRINTED ELECTRONICS –

**Part 402-1: Printability – Measurement of qualities –
Pattern width**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62899-402-1 has been prepared by IEC technical committee 119: Printed electronics.

The text of this standard is based on the following documents:

FDIS	Report on voting
119/133/FDIS	119/143/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62899 series, published under the general title *Printed electronics*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This document contains fundamental information on the measurement of printed pattern width in printed electronics. This document includes measurement procedures as well as definitions of pattern width and related attributes such as variation properties of width, which are quite different from those in graphic art printing or the etching process. For example, in graphic art printing, the pattern width is generally more than several millimetres and the variation of width is relatively small and negligible. However, in printed electronics, the printed line patterns, through printing processes such as inkjet, gravure, flexography, etc., can have very narrow width of under several tens of micrometres, and the variation of pattern width can be large due to rough edges, which is hardly observed in the etching process. Therefore, it is difficult to define the line width exactly. The accurate information about pattern width can be very important for control and management of printability in the printing process and this can strongly affect the reliability and performance of printed electronics devices made of several sets of patterns.

This document excludes the standardization of the measurement system. It specifies the properties related to the width of the printed patterns obtained from the optical measurement system.

It is useful to use appropriate software that is capable of image processing, including image conversion, edge detection, calculation of the edge variation, etc., and should include information on the edge detection methods used.

PRINTED ELECTRONICS –

Part 402-1: Printability – Measurement of qualities – Pattern width

1 Scope

This part of IEC 62899 specifies the measurement methods of the widths of the printed patterns in printed electronics. These printed pattern widths are treated as two-dimensional on a substrate. When the patterns are definitely affected by three-dimensional configurations, these are specified in measurement methods for thickness in printed electronics.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 291, *Plastics – Standard atmospheres for conditioning and testing*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.1

stroke width

distance from edge to edge along a line normal to the vertical line of the captured image in the region of interest (ROI)

3.2

pattern width

distance from one edge to the other edge along a line normal to the pattern center line

3.3

pattern center line

approximate center line of two edges obtained from the centers of the stroke widths

3.4

mean pattern width

mean value of the pattern width

3.5

minimum pattern width

minimum value of the pattern width

3.6**maximum pattern width**

maximum value of the pattern width

3.7**inner pattern width**

distance between the inner edge lines which are drawn at the innermost points of the edges

3.8**outer pattern width**

distance between the outer edge lines which are drawn at the outermost points of the edges

3.9**region of interest****ROI**

area (inside defined boundaries) that the user wants to analyse

4 Atmospheric conditions for evaluation and conditioning

The standard atmosphere for evaluation (test and measurement) and storage of the specimen shall be a temperature of (23 ± 2) °C and relative humidity of (50 ± 10) %, conforming to standard atmosphere class 2 specified in ISO 291. For a test piece which is a substrate with printed patterns, the standard atmosphere for evaluation (test and measurement) and storage of the specimen shall be a temperature of (23 ± 1) °C and relative humidity of (50 ± 5) %, conforming to standard atmosphere class 1 specified in ISO 291.

If conditioning is necessary, the same standard atmosphere specified above shall apply.

5 Measuring methods and instruments**5.1 Measuring instrument**

The measurement of pattern width shall be carried out with an instrument that can obtain the image of patterns. The repeatability and accuracy of the measuring instrument should be less than 10 % of the tolerance specification of the width. From the measurement system, the image of the pattern should be converted to an image file. The image should include the information of pixel size when converted to an image file.

5.2 Preparation of imaging (specimen)

The specimen for measuring pattern width contains the whole image of the pattern in the width direction. The measurer should report the size of the ROI and the resolution of the measurement system.

5.3 Measuring method


For the measurement of the width of the patterns, proper software that can recognize the two edges from patterns of the captured image and calculate the distance between two edges is required. Information on the two edges which border the width of the pattern is required. The required information on edges includes the position difference between two edges. The measurement steps are as follows:

1) Find a region of interest (ROI)

The ROI shall contain the whole pattern in the width direction.

2) Locate the two edges by image capture

Using the proper software that can recognize the two edges in the ROI, edge images can be obtained.




IEC

Figure 1 – Captured image of two edges of pattern and inner/outer edge lines

3) Specification of width

Draw inner edge lines and outer edge lines at each edge (Figure 1) and define the inner pattern width as the distance between the inner edge lines and the outer pattern width as the distance between the outer edge lines.

Capture the position difference between the two edges versus the coordinate perpendicular to the width direction and set this value as $f_E(y)$ (Figure 2). Therefore, $f_E(y)$ is the pattern width as a function of y , which is the coordinate in the length direction.



IEC

Figure 2 – Obtained position difference as a function of y

5.4 Obtaining width and related attributes

With the information obtained above, the width and related attributes can be obtained as follows:

- W_0 (mean pattern width): mean value of $f_E(y)$
- W_S (minimum pattern width): minimum value of $f_E(y)$

- c) W_L (maximum pattern width): maximum value of $f_E(y)$
- d) W_I (inner pattern width): distance between the inner edges lines
- e) W_O (outer pattern width): distance between the outer edges lines

f) σ_W (variation of pattern width): $\sqrt{\frac{\sum [f_{E,i}(y_i) - W_O]^2}{n-1}}$

g) peak-to-peak to mean: $E_1 = \frac{W_L - W_S}{W_O}$

h) variation to mean: $E_2 = \frac{\sigma_W}{W_O}$

6 Report of results

6.1 Measurement identification information

The report shall include the date of the measurements, the identity of the operator, and the lot identifications.

6.2 Instrument system and its specification

The report shall include a description of the instrument system used with its specification, such as the type of instrumentation, resolution and ROI.

6.3 Measuring position

The report shall include the measuring position.

6.4 Results

The report shall include the items given in Table 1. The right side column of Table 1 is an example of the corresponding values of the items of the left side column of Table 1.

Table 1 – Example of reporting items

ORIGINATOR	XYZ Printing Company
Test description	Results of March 18, 2014 print set
Date of report	April 2, 2014
Test operator	CHK
Atmospheric conditions	
Temperature	
Relative humidity	
INSTRUMENTATION	XYZ Optical Company, Model XXX
Type	Confocal
Resolution	2 μ m
ROI	1 mm \times 1 mm
CONFORMANCE TESTS	
Width Attributes Measurements	Within the tolerance
SAMPLING POSITION	Indicate the position of the sample with the whole pattern design
PATTERN WIDTH ATTRIBUTES	
Mean pattern width	

Annex A

(normative)

Drawing method of inner edge lines and outer edge lines

The drawing method shall be as follows:

- a) Find a region of interest (ROI)

The image capturing method is according to 5.2 and 5.3.

- b) Draw a center line

The measurer shall set a pattern center line in a captured image. If the pattern center line is tilted in the captured image, the measurer shall find a region of interest (ROI) again so that the center line is perpendicular to the x axis (horizontal line) of the newly captured image.

- c) Find the innermost points and outermost points at the two edges of the image (see Figure 1)

The innermost point is the farthest point from one side of the ROI window to the edge of the pattern on the same side.

The outermost point is the nearest point from one side of the ROI window to the edge of the pattern on the same side.

- d) Draw inner edge lines and outer edge lines at the two edges of the image (see Figure 1)

The inner edge line is a line drawn parallel to the pattern center line and passing the innermost point of the edge.

The outer edge line is a line drawn parallel to the pattern center line and passing the outermost point of the edge.

Bibliography

ISO/IEC TS 24790:2012, *Information technology – Office equipment – Measurement of image quality attributes for hardcopy output – Monochrome text and graphic images*

Raman Maini and Himanshu Aggarwal, “*Study and Comparison of Various Image Edge Detection Techniques,*” International Journal of Image Processing(IJIP), Vol. 3 pp. 1-11, 2009

G. T. Shrivakshan and C. Chandrasekar, “*Comparison of various Edge Detection Techniques used in Image Processing,*” International Journal of Computer Science Issues(IJCSI), Vol. 9, pp. 269-276, 2012

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit, or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than 1 device provided that it is accessible by the sole named user only and that only 1 copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than 1 copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright & Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email subscriptions@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK