

BS ISO 1832:2017



BSI Standards Publication

Indexable inserts for cutting tools — Designation

National foreword

This British Standard is the UK implementation of ISO 1832:2017. It supersedes BS ISO 1832:2012 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee MTE/18, Tools tips and inserts for cutting applications.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2017.
Published by BSI Standards Limited 2017

ISBN 978 0 580 92410 1

ICS 25.100.01

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 March 2017.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

INTERNATIONAL
STANDARD

BS ISO 1832:2017

ISO
1832

Sixth edition
2017-02

**Indexable inserts for cutting tools —
Designation**

Plaquettes amovibles pour outils coupants — Désignation



Reference number
ISO 1832:2017(E)

© ISO 2017



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword.....	iv
1 Scope.....	1
2 Normative references.....	1
3 Terms and definitions.....	1
4 Explanation of designation code.....	1
5 Symbols.....	3
5.1 Symbol for insert shape — Reference ①.....	3
5.2 Symbol for normal clearance — Reference ②.....	4
5.3 Symbol for tolerance class — Reference ③.....	4
5.4 Symbol for fixing and/or chip breakers — Reference ④.....	7
5.5 Symbol for insert size — Reference ⑤.....	9
5.6 Symbol for insert thickness — Reference ⑥.....	9
5.7 Symbol for insert corner configuration — Reference ⑦.....	10
6 Optional symbols for indexable inserts.....	12
6.1 General.....	12
6.2 Symbol for cutting edge condition — Reference ⑧.....	12
6.3 Symbol for the corner type and the application of the insert (direction of feed motion) — Reference ⑨.....	13
7 Additional symbols for tipped inserts.....	13
7.1 General.....	13
7.2 Size of cutting edge condition — Reference ⑩.....	13
7.2.1 General.....	13
7.2.2 E = rounded.....	13
7.2.3 T = chamfered.....	14
7.2.4 S = chamfered and rounded.....	14
7.2.5 K = double chamfered.....	15
7.2.6 P = double chamfered and rounded.....	16
7.3 Style of tipped or solid cutting edge and number of tipped corners — Reference ⑪.....	16
7.4 Length of tipped cutting edge — Reference ⑫.....	18
Annex A (informative) Symbols for insert size (reference ⑤) according to standardized inscribed circles for equilateral and round inserts.....	20
Annex B (informative) Symbols for standardized insert thicknesses (reference ⑥).....	22
Annex C (informative) Relationship between designations in this document and the ISO 13399 series.....	23
Bibliography.....	24

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

This document was prepared by Technical Committee ISO/TC 29, *Small tools*, Subcommittee SC 9, *Tools with defined cutting edges, cutting items*.

This sixth edition cancels and replaces the fifth edition (ISO 1832:2012), which has been technically revised.

Indexable inserts for cutting tools — Designation

1 Scope

This document establishes a code for the designation of the usual types of indexable inserts for cutting tools in hard cutting materials or any other cutting materials, in order to simplify orders and specifications for such inserts.

It also specifies the designations for cubic boron nitride (BL, BH, BC) inserts, tipped and solid, as well as polycrystalline diamond (DP) inserts, tipped.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 513, *Classification and application of hard cutting materials for metal removal with defined cutting edges — Designation of the main groups and groups of application*

ISO 3002-1, *Basic quantities in cutting and grinding — Part 1: Geometry of the active part of cutting tools — General terms, reference systems, tool and working angles, chip breakers*

ISO 16462, *Cubic boron nitride inserts, tipped or solid — Dimensions, types*

ISO 16463, *Polycrystalline diamond inserts, tipped — Dimensions, types*

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

4 Explanation of designation code

For indexable inserts, the designation code comprises nine symbols for designating the dimensions and other characteristics; the first seven symbols (symbols ① to ⑦) shall be used in every designation. Symbols ⑧ and ⑨ may be used when necessary.

For tipped inserts in accordance with ISO 16462 and ISO 16463, the designation code comprises 12 symbols for designating the dimensions and other characteristics; symbols ① to ⑦ as well as ⑪ and ⑫ shall be used in every designation. Symbols ⑧, ⑨ and ⑩ may be used when necessary. Symbols ⑪ and ⑫ shall be separated by a dash as shown in [Clause 4](#), example 2.

In addition to the standardized designation for indexable inserts and tipped inserts, a supplementary symbol ⑬ consisting of one or two characters may be added by the manufacturer for a better description of his/her product (for example, different chip breakers), provided this symbol is separated from the standardized designation by a dash and that it does not contain letters specific to references ⑧, ⑨ and ⑩.

No addition to or extension of the designations specified in this document shall be made without consultation with ISO/TC 29 and without its agreement. Rather than adding symbols not provided for in this system, it is preferable to add all necessary explanations in the form of detailed sketches or specifications to the designation in accordance with this document.

However, if the letter symbol “X” is used in position 4 of the designation, it is allowed to use, in positions 5, 6 and 7, symbols representing values not appearing in this document, but which shall be described explicitly using the sketch or the detailed specifications given in [5.4](#).

The significance of the symbols constituting the designation code is as follows:

①	Letter symbol identifying	insert shape (see 5.1)	} Compulsory symbols for indexable inserts	} Compulsory symbols for tipped inserts according to ISO 16462 and ISO 16463, except as noted
②	Letter symbol identifying	normal clearance (see 5.2)		
③	Letter symbol identifying	tolerance class (see 5.3)		
④	Letter symbol indicating	fixing and/or chip breakers (see 5.4)		
⑤	Number symbol identifying	insert size (see 5.5)		
⑥	Number symbol identifying	insert thickness (see 5.6)		
⑦	Letter or number symbol identifying	insert corner configuration (see 5.7)		
⑧	Letter symbol indicating (optional symbol for indexable and tipped inserts)	cutting edge condition (see 6.2)		
⑨	Letter symbol identifying (optional symbol for indexable and tipped inserts)	cutting direction (see 6.3)		
⑩	Number symbol identifying (optional symbol for tipped inserts)	size of cutting edge condition (see 7.2)		
⑪	Letter symbol identifying	style of tipped or solid cutting edge and number of tipped corners (see 7.3)		
⑫	Letter or number symbol identifying	length of tipped cutting edge (see 7.4)		
⑬	Manufacturer’s symbol or cutting material designation according to ISO 513 (optional symbol for indexable and tipped inserts)			

EXAMPLE 1 General designation

	①	②	③	④	⑤	⑥	⑦	⑧	⑨		⑬
Metric dimensions:	T	P	G	N	16	03	08	E	N	—	...
Inch dimensions:	T	P	G	N	3	2	2	E	N	—	...

EXAMPLE 2 Designation of inserts according to ISO 16462 and ISO 16463

	①	②	③	④	⑤	⑥	⑦	⑧	⑩	⑨	⑪	⑫	⑬		
Designation of insert for turning	S	N	M	A	15	06	08	E		(N)	—	B	L	—	...
Designation of insert for milling	T	P	G	T	16	T3	AP	S	01520	R	—	M	028	—	...

The designations and symbols of the different angles allowing geometrical definition of the indexable inserts shall conform with ISO 3002-1, with the following conventions:

- the insert is considered in the tool-in-hand system;
- the reference plane, P_r , is parallel to the base of the insert;
- the assumed working plane, P_f , is perpendicular to the reference plane, P_r , and is parallel to the assumed direction of feed motion. This plane is defined only in the case of inserts having one or more wiper edges.

The assumed direction of feed motion is taken parallel to the considered wiper edge (see Note 1 to [Table 9](#)).

For the relationship between designations in this document and the ISO 13399 series, see [Annex C](#).

5 Symbols

5.1 Symbol for insert shape — Reference ①

See [Table 1](#).

Table 1











Type	Letter symbol	Description of shape	Included angle, ϵ_r	Illustration
I Equilateral and equian- gular inserts	H	Hexagonal inserts	120°	
	O	Octagonal inserts	135°	
	P	Pentagonal inserts	108°	
	S	Square inserts	90°	
	T	Triangular inserts	60°	
^a The smaller angle is always the included angle that is considered.				

Table 1 (continued)


Type		Letter symbol	Description of shape	Included angle, ε_r	Illustration
II	Equilateral but non-equiangular inserts	C	Rhombic inserts	80° ^a	
		D		55° ^a	
		E		75° ^a	
		M		86° ^a	
		V		35° ^a	
		W	Trigon inserts	80° ^a	
III	Non-equilateral but equiangular inserts	L	Rectangular inserts	90°	
IV	Non-equilateral and non-equiangular inserts	A	Parallelogram-shaped inserts	85° ^a	
		B		82° ^a	
		K		55° ^a	
V	Round inserts	R	Round inserts	—	

^a The smaller angle is always the included angle that is considered.

5.2 Symbol for normal clearance — Reference ②

See [Table 2](#).

Table 2

Letter symbol	
For normal clearance, choose, from the letter symbols listed below, the one that corresponds to the major cutting edge (see the figure below).	
If (in spite of different clearances) all cutting edges have to be used as major cutting edges, the symbol to be used for the designation of the normal clearance shall be the symbol applicable to the normal clearance of the longer cutting edge, which is also considered the major cutting edge for the indication of the insert size (see reference ⑤).	
	<p>A — 3° B — 5° C — 7° D — 15° E — 20° F — 25° G — 30° N — 0° P — 11° O — Other normal clearances requiring special specification</p>

5.3 Symbol for tolerance class — Reference ③

See [Table 3](#).

The dimensions concerned are d (nominal diameter of the inscribed circle of the insert), s (thickness of the insert) and m . For this last dimension, the three cases represented in [Figures 1](#) to [3](#) are distinguished.




Figure 1 — Case 1: inserts with odd numbers of sides and rounded corners




Figure 2 — Case 2: inserts with even numbers of sides and rounded corners




Figure 3 — Case 3: inserts with wiper edges (see Note 1 in [Table 9](#))

Table 3









Letter	Tolerance in millimetres			Tolerance in inches		
	d	m	s	d	m	s
A ^a	±0,025	±0,005	±0,025	±0,001	±0,000 2	±0,001
F ^a	±0,013	±0,005	±0,025	±0,000 5	±0,000 2	±0,001
C ^a	±0,025	±0,013	±0,025	±0,001	±0,000 5	±0,001
H	±0,013	±0,013	±0,025	±0,000 5	±0,000 5	±0,001
E	±0,025	±0,025	±0,025	±0,001	±0,001	±0,001
G	±0,025	±0,025	±0,13	±0,001	±0,001	±0,005
J ^a	from ±0,05 ^b to ±0,15 ^b	±0,005	±0,025	from ±0,002 ^b to ±0,006 ^b	±0,000 2	±0,001
K ^a	from ±0,05 ^b to ±0,15 ^b	±0,013	±0,025	from ±0,002 ^b to ±0,006 ^b	±0,000 5	±0,001
L ^a	from ±0,05 ^b to ±0,15 ^b	±0,025	±0,025	from ±0,002 ^b to ±0,006 ^b	±0,001	±0,001
M	from ±0,05 ^b to ±0,15 ^b	from ±0,08 ^b to ±0,2 ^b	±0,13	from ±0,002 ^b to ±0,006 ^b	from ±0,003 ^b to ±0,008 ^b	±0,005
N	from ±0,05 ^b to ±0,15 ^b	from ±0,08 ^b to ±0,2 ^b	±0,025	from ±0,002 ^b to ±0,006 ^b	from ±0,003 ^b to ±0,008 ^b	±0,001
U	from ±0,08 ^b to ±0,25 ^b	from ±0,13 ^b to ±0,38 ^b	±0,13	from ±0,003 ^b to ±0,01 ^b	from ±0,005 ^b to ±0,015 ^b	±0,005

a These tolerance classes normally apply to indexable inserts with wiper edges.

b The tolerance is dependent upon the insert size (see [Tables 4](#) and [5](#)) and should be indicated for insert according to the corresponding dimensional standards.

Tolerances on d for tolerance classes J, K, L, M, N and U for inserts of shapes H, O, P, S, T, C, E, M, W and R and tolerances on m for tolerance classes M, N and U for inserts with an included angle of 60° or more, of shapes H, O, P, S, T, C, E, M and W, are indicated in [Table 4](#).



Table 4

Diameter of inscribed circle d		Tolerance on d				Tolerance on m			
		Classes J, K, L, M, N		Class U		Classes M and N		Class U	
mm	in	mm	in	mm	in	mm	in	mm	in
4,76	3/16	±0,05	±0,002	±0,08	±0,003	±0,08	±0,003	±0,13	±0,005
5,56	7/32								
6 ^a	—								
6,35	1/4								
7,94	5/16								
8 ^a	—								
9,525	3/8	±0,08	±0,003	±0,13	±0,005	±0,13	±0,005	±0,2	±0,008
10 ^a	—								
12 ^a	—	±0,1	±0,004	±0,18	±0,007	±0,15	±0,006	±0,27	±0,011
12,7	1/2								
15,875	5/8								
16 ^a	—	±0,13	±0,005	±0,25	±0,01	±0,18	±0,007	±0,38	±0,015
19,05	3/4								
20 ^a	—	±0,15	±0,006	±0,25	±0,01	±0,2	±0,008	±0,38	±0,15
25 ^a	—								
25,4	1	±0,15	±0,006	±0,25	±0,01	±0,2	±0,008	±0,38	±0,15
31,75	1 1/4								
32 ^a	—								
		H	O	P	S	T	C, E, M	W	R (tolerance on d only)
Shape of the inserts concerned									

^a Applies only to round inserts.

In the case of rhombic inserts with an included angle of 55° (shape D) and of 35° (shape V), the values for tolerance classes M and N on d and m are indicated in [Table 5](#).









Table 5

Diameter of inscribed circle <i>d</i>		Tolerance on <i>d</i>		Tolerance on <i>m</i>		Shape of the inserts concerned
		Classes M and N		Classes M and N		
mm	in	mm	in	mm	in	
5,56	7/32	± 0,05	± 0,002	± 0,11	± 0,004	
6,35	1/4					
7,94	5/16					
9,525	3/8					
12,7	1/2	± 0,08	± 0,003	± 0,15	± 0,006	
15,875	5/8	± 0,1	± 0,004	± 0,18	± 0,007	
19,05	3/4					
6,35	1/4	± 0,05	± 0,002	± 0,16	± 0,006	
7,94	5/16					
9,525	3/8					
12,7	1/2					

5.4 Symbol for fixing and/or chip breakers — Reference ④

See [Table 6](#).

Table 6







Letter symbol	Fixing	Chip breakers ^a	Illustration
N	Without fixing hole	Without chip breakers	
R		Chip breakers on one face only	
F		Chip breakers on both faces	
A	With cylindrical fixing hole	Without chip breakers	
M		Chip breakers on one face only	
G		Chip breakers on both faces	
W	With partly cylindrical fixing hole, 40° to 60° countersink on one side only	Without chip breakers	
T		Chip breakers on one face only	

^a The definition of chip breakers is given in ISO 3002-1.

^b Non-equilateral inserts shall always be designated in reference ④ by X because the indication of width (measured perpendicularly on the major cutting edge or perpendicularly on the longer edge) and details concerning special features or construction are necessary.

The letter symbol X shall not be used for those insert shapes which are not defined under reference ①.

Table 6 (continued)

Letter symbol	Fixing	Chip breakers ^a	Illustration
Q	With partly cylindrical fixing hole, 40° to 60° countersinks on both sides	Without chip breakers	
U		Chip breakers on both faces	
B	With partly cylindrical fixing hole, 70° to 90° countersink on one side only	Without chip breakers	
H		Chip breakers on one face only	
C	With partly cylindrical fixing hole, 70° to 90° countersinks on both sides	Without chip breakers	
J		Chip breakers on both faces	
X ^b	With dimensions or details requiring detailed explanation, a sketch or additional specifications		—

^a The definition of chip breakers is given in ISO 3002-1.

^b Non-equilateral inserts shall always be designated in reference ④ by X because the indication of width (measured perpendicularly on the major cutting edge or perpendicularly on the longer edge) and details concerning special features or construction are necessary.

The letter symbol X shall not be used for those insert shapes which are not defined under reference ①.

5.5 Symbol for insert size — Reference ⑤

See [Table 7](#).

Table 7

Type	Number symbol
<p style="text-align: center;">I - II Equilateral inserts</p>	<p>— In countries using the metric system, choose the value of the side length as the symbol of designation and disregard any decimals. If the resulting symbol has only one digit, it shall be preceded by a zero.</p> <p>EXAMPLE Edge length: 15,5 mm Symbol of designation: 15</p> <p> Edge length: 9,525 mm Symbol of designation: 09</p> <p>— In countries using the inch system, choose the value of the inscribed circle as the symbol of designation.</p> <p>The symbol is the numerator of the fraction measured in $\frac{1}{8}$ in.</p> <p>a) It is a one-digit symbol when the numerator is a whole number.</p> <p>EXAMPLE Diameter of inscribed circle: $\frac{1}{2}$ in Symbol of designation: 4 ($\frac{1}{2} = \frac{4}{8}$)</p> <p>b) It is a two-digit symbol when the numerator is not a whole number.</p> <p>EXAMPLE Diameter of inscribed circle: $\frac{5}{16}$ in Symbol of designation: 2,5 ($\frac{5}{16} = 2,5/8$)</p> <p>NOTE Annex A gives the symbols for insert size for the usually standardized diameters of the inscribed circle of equilateral inserts.</p>
<p style="text-align: center;">III - IV Non-equilateral inserts</p>	<p>The symbol of designation for the insert size is always given for the major cutting edge or the longer cutting edge. The indication of other dimensions shall be made by means of a sketch or detailed explanation, indicated at position 4 by the symbol X.</p> <p>— In countries using the metric system, the symbol of designation is the length, disregarding any decimals.</p> <p>EXAMPLE Length of the main edge: 19,5 mm Symbol of designation: 19</p> <p>— In countries using the inch system, the symbol of designation is the numerator of the fraction for the value in $\frac{1}{4}$ in.</p> <p>EXAMPLE Length of the main edge: $\frac{3}{4}$ in Symbol of designation: 3</p>
<p style="text-align: center;">V Round inserts</p>	<p>— In countries using the metric system, choose the value of the diameter as the symbol of designation and disregarding any decimals.</p> <p>EXAMPLE Insert diameter: 15,875 mm Symbol of designation: 15</p> <p>For inserts having rounded metric diameters, the same rule is valid, combined with a special symbol at reference ⑦ (see 5.7).</p> <p>— In countries using the inch system, proceed as for equilateral inserts (type I - II).</p>

5.6 Symbol for insert thickness — Reference ⑥

See [Table 8](#).

The thickness, s , of an insert is defined as the distance between the cutting edge of the corner and the opposing supporting surface of the insert; see [Figures 4](#) a), b) and c).




Figure 4 — Thickness of an insert

Rounded or chamfered cutting edges are considered sharp cutting edges.

Table 8

Number symbol	
— In countries using the metric system, take the numerical value of the thickness as the symbol of designation for the insert thickness, disregarding any decimals. If the resulting symbol has only one digit, it shall be preceded by 0 (zero).	
EXAMPLE	Insert thickness: 3,18 mm Symbol of designation: 03
As an exception for inserts having thicknesses of 1,98 mm and 3,97 mm, in order to distinguish them from those having thicknesses of 1,59 mm (symbol 01) and 3,18 mm (symbol 03), precede the digit by the letter T.	
EXAMPLE	Insert thickness: 3,97 mm Symbol of designation: T3
— In countries using the inch system, the symbol of designation for the insert thickness is the numerator of the fraction measured in $\frac{1}{16}$ in.	
a) It is a one-digit symbol when the numerator is a whole number.	
EXAMPLE	Insert thickness: $\frac{1}{8}$ in Symbol of designation: 2 ($\frac{1}{8} = \frac{2}{16}$)
b) It is a two-digit symbol when the numerator is a whole number.	
EXAMPLE	Insert thickness: $\frac{3}{32}$ in Symbol of designation: 1,5 ($\frac{3}{32} = \frac{1,5}{16}$)
NOTE Annex B gives the symbols for standardized insert thicknesses.	

5.7 Symbol for insert corner configuration — Reference ⑦

See [Table 9](#).

Table 9

Number or letter symbol	
a) If the inserts have rounded corners, the symbol of designation is represented	
1) in countries using the metric system, by the value of the corner radius given in 0,1 mm; if the number is less than 10, it should be preceded by 0 (zero).	
EXAMPLE	Corner radius: 0,8 mm Designation symbol: 08
If the corner is not rounded, use the symbol of designation 00 (zero-zero).	
2) in countries using the inch system, by the following figures:	
<ul style="list-style-type: none"> 0 — Sharp corner (not rounded) 1 — Corner radius $\frac{1}{64}$ in 2 — Corner radius $\frac{1}{32}$ in 3 — Corner radius $\frac{3}{64}$ in 4 — Corner radius $\frac{1}{16}$ in 6 — Corner radius $\frac{3}{32}$ in 8 — Corner radius $\frac{1}{8}$ in X — Any other corner radius 	
b) If inserts have wiper edges, use, in the order given, the following symbols of designation:	
For cutting edge angel κ_r	For wiper edge normal clearance α'_n
A — 45°	A — 3°
D — 60°	B — 5°
E — 75°	C — 7°
F — 85°	D — 15°
P — 90°	E — 20°
Z — Any other cutting edge angle	F — 25°
	G — 30°
	N — 0°
	P — 11°
	Z — Any other wiper edge normal clearance
NOTE 1 The wiper edge is a part of the minor cutting edge.	
Key	
1 major cutting edge	
2 chamfered corner	
3 wiper edge	
4 minor cutting edge	
a Assumed direction of feed motion.	
NOTE 2 Inserts with wiper edge can or cannot have chamfered corners, depending on their type. The designation for indexable inserts gives no information as to whether the inserts have or do not have chamfered corners. For standardized inserts, this information is given in dimensional standards; for non-standardized inserts, it is given in suppliers' catalogues.	
c) To supplement the designation in position 7 for round inserts, countries using the metric system shall indicate	
— 00 (zero-zero) if the diameter is converted from an inch value;	
— M0 (M-zero) if the diameter is a metric one.	

6 Optional symbols for indexable inserts

6.1 General

The compulsory designation for indexable inserts other than those specified in ISO 16462 and ISO 16463 comprises the seven symbols given in 5.1 to 5.7. As stated in Clause 4, the symbols given in 6.2 and 6.3 may be used when necessary.







If only one symbol is needed (cutting edge condition or cutting direction), it shall occupy position 8. If both cutting edge condition and cutting direction are to be specified, the two symbols shall occupy positions 8 and 9, respectively.

Symbols given in 6.2 and 6.3 may also be used for designating tipped inserts in accordance with ISO 16462 and ISO 16463 where necessary.

6.2 Symbol for cutting edge condition — Reference ⑧

See Table 10.

Table 10

Letter symbol	Cutting edge condition	Illustration
F	Sharp cutting edges	
E	Rounded cutting edges	
T	Chamfered cutting edges	
S	Chamfered and rounded cutting edges	
K	Double chamfered cutting edge	
P	Double chamfered and rounded cutting edge	

6.3 Symbol for the corner type and the application of the insert (direction of feed motion) — Reference ⑨

See [Table 11](#).

Table 11

Letter symbol	Corner type	Application of the insert	Illustration
R	Right-hand insert	For non-equilateral and non-equiangular inserts and for all inserts with asymmetrical corners and/or asymmetrical chip breaker, permitting the use of the insert in only one direction of feed motion	<p>a Direction of feed motion.</p>
L	Left-hand insert		<p>a Direction of feed motion.</p>
N	Neutral insert		<p>a Direction of feed motion.</p>

7 Additional symbols for tipped inserts

7.1 General

Number symbols ⑪ and ⑫ given in [7.3](#) and [7.4](#) shall be used for designating tipped inserts in accordance with ISO 16462 and ISO 16463. Symbol ⑩ given in [7.2](#) may be used when necessary. Number symbols ⑪ and ⑫ shall be separated by a dash as shown in [Clause 4](#), example 2.

7.2 Size of cutting edge condition — Reference ⑩


7.2.1 General

The maximum allowable shall be a five-digit number symbol, depending on the cutting edge condition. For the different kinds of cutting edge conditions, see [Figures 5](#) to [9](#) and [Tables 12](#) to [15](#).

7.2.2 E = rounded

There is no coding of the size.

EXAMPLE SNMA150608E



Key

a Honing.

Figure 5 — Illustration of a rounded cutting edge

7.2.3 T = chamfered

Five-digit number symbol

— b_γ - T-land size in 1/100 mm: three-digit

— γ_b - T-land angle: two-digit




Figure 6 — Illustration of a chamfered cutting edge

Table 12

Number symbol	b_γ mm	Number symbol	γ_b
005	0,05	05	5°
010	0,10	10	10°
015	0,15	15	15°
020	0,20	20	20°
025	0,25	25	25°
030	0,30	30	30°
050	0,50		
070	0,70		
100	1,00		
150	1,50		
200	2,00		

EXAMPLE SNMA150608T05020


7.2.4 S = chamfered and rounded

Five-digit number symbol

— b_γ - T-land size in 1/100 mm: three-digit

— γ_b - T-land angle: two-digit

— rounding: no code



Key

a Honing.

Figure 7 — Illustration of a chamfered and rounded cutting edge

Table 13

Number symbol	b_γ mm	Number symbol	γ_b
005	0,05	05	5°
010	0,10	10	10°
015	0,15	15	15°
020	0,20	20	20°
025	0,25	25	25°
030	0,30	30	30°
050	0,50		
070	0,70		
100	1,00		
150	1,50		
200	2,00		

EXAMPLE SNMA150608S05020

7.2.5 K = double chamfered

Five-digit number symbol

- $b_{\gamma 1}$ – T-land size in 1/100 mm: three-digit
- γ_{b1} – T-land angle: two-digit
- $b_{\gamma 2} \times \gamma_{b2}$ dependent on $b_{\gamma 1} \times \gamma_{b1}$




Figure 8 — Illustration of a double chamfered cutting edge

Table 14


Number symbol	$b_{\gamma 1}$ mm	γ_{b1}	$b_{\gamma 2}$ mm	γ_{b2}
05015	0,50	15°	0,10	30°
07015	0,70	15°	0,15	30°
10015	1,00	15°	0,20	30°
15010	1,50	10°	0,25	30°
20010	2,00	10°	0,25	30°

EXAMPLE SNMA150608K15010

7.2.6 P = double chamfered and rounded

Five-digit number symbol

- $b_{\gamma 1}$ — T-land size in 1/100 mm: three-digit
- γ_{b1} — T-land angle: two-digit
- $b_{\gamma 2} \times \gamma_{b2}$ dependent on $b_{\gamma 1} \times \gamma_{b1}$
- rounding: no code



Key

a Honing.

Figure 9 — Illustration of a double chamfered and rounded cutting edge

Table 15

Number symbol	$b_{\gamma 1}$ mm	γ_{b1}	$b_{\gamma 2}$ mm	γ_{b2}
05015	0,50	15°	0,10	30°
07015	0,70	15°	0,15	30°
10015	1,00	15°	0,20	30°
15010	1,50	10°	0,25	30°
20010	2,00	10°	0,25	30°

EXAMPLE SNMA150608P15010

7.3 Style of tipped or solid cutting edge and number of tipped corners — Reference ⑪

The one-digit letter symbol is given in [Table 16](#).

Table 16

























Letter symbol	Illustration	Description
S		solid
F		full face — one-sided
E		full face — two-sided
A		tipped — one-sided — one corner
B		tipped — one sided — two corners
C		tipped — one sided — three corners
D		tipped — one sided — four corners
G		tipped — one sided — five corners
H		tipped — one sided — six corners
J		tipped — one sided — eight corners
K		tipped — two sided — one corner
L		tipped — two sided — two corners
M		tipped — two sided — three corners

Table 16 (continued)

Letter symbol	Illustration	Description
N		tipped — two sided — four corners
P		tipped — two sided — five corners
Q		tipped — two sided — six corners
R		tipped — two sided — eight corners
T		tipped — full thickness — one corner
U		tipped — full thickness — two corners
V		tipped — full thickness — three corners
W		tipped — full thickness — four corners
X		tipped — full thickness — five corners
Y		tipped — full thickness — six corners
Z		tipped — full thickness — eight corners

EXAMPLE SNMA150608S05020-B

7.4 Length of tipped cutting edge — Reference ⑫

For the one-digit letter symbol, see [Table 17](#).

Table 17

Letter symbol	Description	Cutting edge length l_{1min}
L	long	Given in ISO 16462 and ISO 16463
S	short	
F	full cutting edge length	

a) Letter symbols “L” and “S”

- this symbol may appear on letter symbols A, B, C, D, G, H, J, K, L, M, N, P, Q, R, T, U, V, W, X, Y, Z, contained in [Table 16](#);
- cutting edge length is according to standard length.

b) Letter symbol “F”

- this symbol may appear on letter symbols A, B, K, L, T, U, S, F, E, contained in [Table 16](#).

For three-digit number symbol, if the tip length is not full cutting edge length or in conformity with the standard length, the effective tip length shall be indicated as a three-digit number symbol which gives the length in 1/10 mm. If the tip length is less than 10,0 mm, the symbol shall be prefixed by zero(s) (0) (e.g. tipped cutting edge length 4,5 mm = 045 tipped cutting edge length 10,7 mm = 107).

EXAMPLE Insert with 90° included angle (S), normal clearance angle 0° (N), tolerance class (M), with cylindrical fixing hole and no chip breakers (A), cutting edge length 15,875 mm (15), insert thickness 6,35 mm (06), corner radius 0,8 mm (08), cutting edge condition chamfered and rounded (S), T-land size 0,5 mm (050), T-land angle 20° (20), tipped on one side with two corners (B), tip length $l_1 = 3,0$ mm (L)

SNMA150608S05020-BL

or

Insert with 90° included angle (S), normal clearance angle 0° (N), tolerance class (M), with cylindrical fixing hole and no chip breakers (A), cutting edge length 15,875 mm (15), insert thickness 6,35 mm (06), corner radius 0,8 mm (08), cutting edge condition chamfered and rounded (S), T-land size 0,5 mm (050), T-land angle 20° (20), tipped on one side with two corners (B), tip length $l_1 = 4,5$ mm (045)

SNMA150608S05020-B045

Annex A (informative)

Symbols for insert size (reference ⑤) according to standardized inscribed circles for equilateral and round inserts

A.1 Equilateral and round inserts: “non-metric”

See [Table A.1](#).

Table A.1

Diameter of inscribed circle <i>d</i>		Number symbol for insert size (reference ⑤) for insert shape											
		H	O	P	S	T	C	D	E	M	V	W	R ^a
3,97		—	—	—	03	06	—	04	—	—	06	02	—
	5/32	1,2											
4,76		—	—	—	04	08	04	05	04	04	08	L3	—
	3/16	1,5											
5,56		—	—	—	05	09	05	06	05	05	09	03	—
	7/32	1,8											
6,35		03	02	04	06	11	06	07	06	06	11	04	06
	1/4	2											
7,94		04	03	05	07	13	08	09	08	07	13	05	07
	5/16	2,5											
9,525		05	04	07	09	16	09	11	09	09	16	06	09
	3/8	3											
12,7		07	05	09	12	22	12	15	13	12	22	08	12
	1/2	4											
15,875		09	06	11	15	27	16	19	16	15	27	10	15
	5/8	5											
19,05		11	07	13	19	33	19	23	19	19	33	13	19
	3/4	6											
25,4		14	10	18	25	44	25	31	26	25	44	17	25
	1	8											

Table A.1 (continued)

31,75		18	13	23	31	54	32	38	32	31	54	21	31
	1 1/4	10											
<p>NOTE The edge length, l, can be calculated by means of the following formulae:</p> <ul style="list-style-type: none"> — for equiangular inserts (shape H, O, P, S, T): $l = d \cdot \tan \frac{180^\circ}{n}$ <p>where n is the number of sides of the polygon;</p> <ul style="list-style-type: none"> — for the rhombic inserts (shape C, D, E, M, V) and for inserts shape W: $l = \frac{d}{2} \left(\cot \frac{\varepsilon_{r1}}{2} + \cot \frac{\varepsilon_{r2}}{2} \right)$ <p>where ε_{r1} and ε_{r2} are the included angles at the sharp and obtuse corners.</p> <p>^a See list item c) of Table 9. For “metric” round inserts, see A.2.</p>													

If these symbols are used with significance other than that given in [Table A.1](#), the symbol at reference ④ shall be X.

A.2 Round inserts: “metric”

See [Table A.2](#).

Table A.2

Diameter of insert d		Number symbol for insert size for “metric” round insert (shape R) ^a
mm	in	
6		06
	0,236	—
8		08
	0,315	—
10		10
	0,394	—
12		12
	0,472	—
16		16
	0,63	—
20		20
	0,787	—
25		25
	0,984	—
32		32
	1,26	—

^a See list item c) of [Table 9](#).

Annex B (informative)

Symbols for standardized insert thicknesses (reference ⑥)

Table B.1

Insert thickness <i>s</i>		Number symbol for insert thickness	
mm	in	metric	Imperial (inch)
1,59	1/16	01	1
1,98	5/64	T1	1,2
2,38	3/32	02	1,5
3,18	1/8	03	2
3,97	5/32	T3	2,5
4,76	3/16	04	3
5,56	7/32	05	3,5
6,35	1/4	06	4
7,94	5/16	07	5
9,52	3/8	09	6
12,7	1/2	12	8

If these symbols are used with a meaning other than that given in [Table B.1](#), the symbol at reference ④ shall be X.

Annex C (informative)

Relationship between designations in this document and the ISO 13399 series

C.1 Relationship between designations

For the relationship between the designations in this document and preferred symbols according to the ISO 13399 series, see [Table C.1](#).

Table C.1 — Relationship between designations in this document and the ISO 13399 series

Symbol in this document	Reference in this document	Property name in the ISO 13399 series	Symbol in the ISO 13399 series	Reference in the ISO 13399 series
—	5.1 symbol 1	Insert shape code	SC	ISO/TS 13399-2, 71CE7A9F0C79F
α_n	5.2 symbol 2	Clearance angle major	AN	ISO/TS 13399-2, 71DD70308D3E3
—	5.3 symbol 3	Tolerance class insert	TCINS	ISO/TS 13399-2, 71CE7AA215888
d	5.3 , Tables 3, 4, 5	Diameter of inscribed circle	IC	—
—	5.4 symbol 4	Insert mounting style code	IFS	ISO/TS 13399-2, 71CE- 7A97711B8
—	5.5 symbol 5	Cutting edge length	L	ISO/TS 13399-2, 71DD6C95DA49B
S	5.6 symbol 6	Insert thickness	S	ISO/TS 13399-2, 71CE7A9F5308C
—	5.7 symbol 7	Rounded corner: corner radius wiper edge: wiper edge length	RE BS	ISO/TS 13399-2, 71DD6C8ACA503 71CE7AA249F88
—	6.2 symbol 8	Cutting edge condition code	CECC	ISO/TS 13399-2, 71DD6C90953D8
—	6.3 symbol 9	Insert hand	IH	ISO/TS 13399-2, 71CF- 29872F0AB
$b_\gamma + \gamma_b$	7.2 symbol 10	Face land size code	FLSC	ISO/TS 13399-2, 71DD6C9371B86
—	7.3 symbol 11	Tipped cutting edge code	TCE	ISO/TS 13399-2, 71CE7AA1E3D75
—	7.4 symbol 12	Coded letter symbol: N.N coded number symbol: cutting edge effective length	N.N LE	ISO/TS 13399-2 N.N 71DD6C958C615

Bibliography

- [1] ISO 13399 (all parts), *Cutting tool data representation and exchange*

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit, or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than 1 device provided that it is accessible by the sole named user only and that only 1 copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than 1 copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright & Licensing team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email subscriptions@bsigroup.com.

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Useful Contacts

Customer Services

Tel: +44 345 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 345 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK