

BS ISO 4164:2012



BSI Standards Publication

# Mopeds — Engine test code — Net power

**bsi.**

...making excellence a habit.™

**National foreword**

This British Standard is the UK implementation of ISO 4164:2012.

The UK participation in its preparation was entrusted to Technical Committee AUE/14, Motor cycles and mopeds.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2012.  
Published by BSI Standards Limited 2012.

ISBN 978 0 580 71423 8

ICS 43.140

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 October 2012.

**Amendments issued since publication**

Date	Text affected
------	---------------

---

INTERNATIONAL  
STANDARD

**ISO**  
**4164**

Second edition  
2012-09-15

---

---

**Mopeds — Engine test code — Net  
power**

*Cyclomoteurs — Code d'essai des moteurs — Puissance nette*



Reference number  
ISO 4164:2012(E)



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

<b>Foreword</b> .....	<b>iv</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Symbols</b> .....	<b>2</b>
<b>5 Standard reference conditions</b> .....	<b>2</b>
<b>6 Tests</b> .....	<b>3</b>
6.1 General.....	3
6.2 Measuring equipment and instrument accuracy.....	3
6.3 Setting and test conditions.....	3
6.4 Test procedure.....	10
<b>7 Torque, power and specific fuel consumption</b> .....	<b>10</b>
7.1 Calculation of measured torque, measured power and specific fuel consumption.....	10
7.2 Net torque and net power.....	11
7.3 Corrected net torque and corrected net power.....	12
<b>8 Test report</b> .....	<b>13</b>
8.1 General.....	13
8.2 The description of test report.....	13
8.3 Statement of results.....	16
<b>Bibliography</b> .....	<b>19</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 4164 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 23, *Mopeds*.

This second edition cancels and replaces the first edition (ISO 4164:1978), which has been technically revised.

# Mopeds — Engine test code — Net power

## 1 Scope

This International Standard specifies methods for evaluating the performance of engines designed for mopeds as defined in ISO 3833, in particular with a view to the presentation of power curves and specific fuel consumption at full load as a function of engine speed, for net power assessment. It is applicable to reciprocating internal combustion engines (spark-ignition), excluding free-piston engines, and rotary piston engines, either naturally aspirated or pressure-charged and equipped with either mechanical pressure-charger or turbocharger.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2710-1, *Reciprocating internal combustion engines — Vocabulary — Part 1: Terms for engine design and operation*

ISO 3833, *Road vehicles — Types — Terms and definitions*

ISO 15550, *Internal combustion engines — Determination and method for the measurement of engine power — General requirements*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 2710-1, ISO 15550 and the following apply.

### 3.1

#### **net power**

power obtained on a test bed at the end of the crankshaft or its equivalent at the corresponding engine speed with the equipment and auxiliaries listed in 6.3.1

### 3.2

#### **corrected net power**

net power corrected under the standard reference conditions

### 3.3

#### **net torque**

torque transmitted on a test bed at the end of the crankshaft or its equivalent at the corresponding engine speed with the equipment and auxiliaries listed in 6.3.1

### 3.4

#### **corrected net torque**

net torque corrected under the standard reference conditions

### 3.5

#### **specific fuel consumption**

amount of fuel consumed by an engine per unit of power and time

NOTE The amount of the lubricants for two-stroke cycle engines is excluded.

### 3.6 auxiliaries

equipment and devices necessary to make the engine acceptable for service in the intended application.

## 4 Symbols

The symbols used in this International Standard are given in Table 1.

**Table 1 — Symbols**

Symbols	Designation	Unit
$b_e$	Specific fuel consumption	g/(kW·h)
$p_d$	Ambient dry air barometric pressure during the test	kPa
$p_r$	Standard reference total barometric pressure	kPa
$p_{sr}$	Standard reference saturated water vapour pressure	kPa
$p_{sy}$	Ambient saturated water vapour pressure during the test	kPa
$p_y$	Ambient total barometric pressure during the test	kPa
$P$	Measured power	kW
$P_o$	Corrected net power	kW
$P_y$	Net power	kW
$T$	Measured torque	Nm
$T_o$	Corrected net torque	Nm
$T_y$	Net torque	Nm
$t_r$	Standard reference ambient air temperature	K
$t_y$	Engine inlet air temperature during the test	K
$\alpha_a$	Correction factor for ambient test conditions	-
$\alpha_m$	Correction factor for efficiency of the transmission	-
$\eta_i$	Efficiency of each element constituting the transmission	-
$\eta_t$	Efficiency of the transmission which is located between the crankshaft and the measurement point	-
$\phi_r$	Standard reference relative humidity	%
$\phi_y$	Ambient relative humidity during the test	%

## 5 Standard reference conditions

For the purpose of determining the power and fuel consumption of an engine, the following standard reference conditions shall be used:

- Standard reference total barometric pressure:  $p_r = 100$  kPa;
- Standard reference air temperature:  $t_r = 298$  K;
- Standard reference relative humidity:  $\phi_r = 30$  %;

NOTE A relative humidity of 30 % at a temperature of 298 K corresponds to a water pressure of 1 kPa. The corresponding dry barometric pressure is 99 kPa.



## 6 Tests

### 6.1 General

This test method is used for verifying the net power of an engine type with the declared values. It presents engine performance at full power/torque as a function of engine speed by generating curves of corrected net torque, corrected net power and specific fuel consumption.

### 6.2 Measuring equipment and instrument accuracy

#### 6.2.1 Torque

The dynamometer torque-measuring system shall have an accuracy of  $\pm 1\%$  in the range of scale values required for the test. The torque-measuring system shall be calibrated to take into account friction losses. The accuracy may be  $\pm 2\%$  for measurements carried out at a power less than 50 % of maximum power.

#### 6.2.2 Engine speed

The engine speed measuring system shall have an accuracy of  $\pm 0,5\%$ .

#### 6.2.3 Fuel flow

The fuel flow measuring system shall have an accuracy of  $\pm 2\%$ .

#### 6.2.4 Fuel temperature

The fuel temperature measuring system shall have an accuracy of  $\pm 1\text{ K}$ .

#### 6.2.5 Engine inlet air temperature

The air temperature measuring system shall have an accuracy of  $\pm 1\text{ K}$ .

#### 6.2.6 Barometric pressure

The barometric pressure measuring system shall have an accuracy of  $\pm 70\text{ Pa}$ .

#### 6.2.7 Back pressure in exhaust system

The system used to measure the back pressure (differential pressure) in the exhaust system shall have an accuracy of  $\pm 25\text{ Pa}$ .

#### 6.2.8 Test-room humidity

The test-room-humidity measuring system shall have an accuracy of  $\pm 5\%$  in relative humidity.

NOTE In the specified test atmospheric conditions in 6.3.3, the worst relative humidity measurement accuracy of  $\pm 5\%$  corresponds to a wet and dry bulb thermometer measurement accuracy of  $\pm 0,5\text{ K}$ . In the worst case, it is estimated that accuracy of  $\pm 0,5\text{ K}$  in a wet and dry bulb thermometer measurement would give the influence of approximately  $\pm 0,3\%$  on the net power measuring result.

### 6.3 Setting and test conditions

#### 6.3.1 Equipment and auxiliaries

During the test, if the equipment and auxiliaries specified in Table 2 are the standard productions, they shall be installed on the test bench as far as possible in the same position and as the same condition as in the intended application.

**Table 2 — Equipment and auxiliaries to be installed for the test to determine engine power**

No.	Equipment and auxiliaries
1	Inlet system:
	Inlet manifold
	Crankcase emission control system
	Control devices for dual induction
	Electronic control system
	Air flow meter
	<p>Air inlet ductwork            Except in the case where there is a risk of the system having a noticeable influence upon engine power, where the equivalents may be used. In this case, a check shall be made to ascertain that inlet depression does not differ by more than 100 Pa from the limit specified by the manufacturer for a clean air filter.</p>
<p>Air filter            Except in the case where there is a risk of the system having a noticeable influence upon engine power, where the equivalents may be used. In this case, a check shall be made to ascertain that inlet depression does not differ by more than 100 Pa from the limit specified by the manufacturer for a clean air filter.</p>	
<p>Inlet silencer            Except in the case where there is a risk of the system having a noticeable influence upon engine power, where the equivalents may be used. In this case, a check shall be made to ascertain that inlet depression does not differ by more than 100 Pa from the limit specified by the manufacturer for a clean air filter.</p>	
<p>Speed-limiting device            Except in the case where there is a risk of the system having a noticeable influence upon engine power, where the equivalents may be used. In this case, a check shall be made to ascertain that inlet depression does not differ by more than 100 Pa from the limit specified by the manufacturer for a clean air filter.</p>	
2	Induction-heating device of inlet manifold

Table 2 (continued)

No.	Equipment and auxiliaries
3	Exhaust system:
	Exhaust purifier
	Exhaust manifold
	Pressure-charging device
	<p>Connecting pipes</p> <p>If it is impracticable to fit the standard exhaust system, a system permitting the normal engine running characteristics in accordance with the manufacturer's specification shall be fitted for the test. In particular, in the test laboratory, the exhaust extraction system at the point where the test bench exhaust system is connected shall not create a pressure differing from the atmospheric pressure by more than <math>\pm 740</math> Pa at the exhaust extraction duct, with the engine in operation, unless the manufacturer has specifically prescribed the back pressure prior to the test, in which case the lower of the two pressures shall be used.</p>
	<p>Silencer</p> <p>If it is impracticable to fit the standard exhaust system, a system permitting the normal engine running characteristics in accordance with the manufacturer's specification shall be fitted for the test. In particular, in the test laboratory, the exhaust extraction system at the point where the test bench exhaust system is connected shall not create a pressure differing from the atmospheric pressure by more than <math>\pm 740</math> Pa at the exhaust extraction duct, with the engine in operation, unless the manufacturer has specifically prescribed the back pressure prior to the test, in which case the lower of the two pressures shall be used.</p>
	<p>Tail pipe</p> <p>If it is impracticable to fit the standard exhaust system, a system permitting the normal engine running characteristics in accordance with the manufacturer's specification shall be fitted for the test. In particular, in the test laboratory, the exhaust extraction system at the point where the test bench exhaust system is connected shall not create a pressure differing from the atmospheric pressure by more than <math>\pm 740</math> Pa at the exhaust extraction duct, with the engine in operation, unless the manufacturer has specifically prescribed the back pressure prior to the test, in which case the lower of the two pressures shall be used.</p>
4	Electronic control system
	Fuel supply system
	<p>Fuel supply pump</p> <p>If necessary, the fuel feed pressure may be adjusted to reproduce the fuel pressures existing in the particular engine application (particularly when a "fuel return" system, for example to tank or filter, is used).</p>
	Carburettor
	Electronic control system
	Gaseous fuel pressure reducer
	Gaseous fuel evaporator
Gaseous fuel mixer	

**Table 2** (continued)

No.	Equipment and auxiliaries
5	Fuel injection equipment Prefilter Filter Fuel injection pump High-pressure pipes Injector Air inlet valve Electronic control system
6	Liquid-cooling equipment Radiator Fan Fan cowl Water pump Thermostat
	<p>The radiator, fan, fan cowl, water pump, thermostat and cowl shall be located on the test bed in the same relative positions that they are to occupy on the vehicle or machine. The cooling liquid circulation shall only be operated by the engine water pump.</p> <p>Cooling of the liquid may be provided either by the engine radiator or by an external circuit, provided that the pressure loss of this circuit and the pressure at the pump inlet remains substantially the same as those of the engine cooling system. The radiator shutter, if incorporated, shall be set in the open position.</p> <p>Where the fan, radiator and cowl system cannot conveniently be fitted to the engine, the power absorbed by the fan when separately mounted in its correct position in relation to the radiator and cowl (if used), shall be determined at the speeds corresponding to the engine speeds used for measurement of the engine power either by calculation from standard characteristics or by practical tests. This power, corrected to the standard atmospheric conditions defined in Clause 5, shall be deducted from the corrected power.</p> <p>Where a disconnectable or progressive fan or blower is incorporated, the test shall be performed with the fan or blower disconnected or with the progressive fan running at maximum slip.</p> <p>The thermostat may be fixed in the fully open position.</p>

Table 2 (continued)

No.	Equipment and auxiliaries
7	<p data-bbox="284 327 571 360">Air cooling equipment</p> <p data-bbox="284 371 368 405">Cowl</p> <p data-bbox="284 416 480 450">Fan or blower</p> <p data-bbox="284 461 703 495">Temperature-regulating device</p> <p data-bbox="284 506 1485 607">The radiator, fan, fan cowl, water pump, thermostat and cowl shall be located on the test bed in the same relative positions that they are to occupy on the vehicle or machine. The cooling liquid circulation shall only be operated by the engine water pump.</p> <p data-bbox="284 607 1485 730">Cooling of the liquid may be provided either by the engine radiator or by an external circuit, provided that the pressure loss of this circuit and the pressure at the pump inlet remains substantially the same as those of the engine cooling system. The radiator shutter, if incorporated, shall be set in the open position.</p> <p data-bbox="284 730 1485 920">Where the fan, radiator and cowl system cannot conveniently be fitted to the engine, the power absorbed by the fan when separately mounted in its correct position in relation to the radiator and cowl (if used), shall be determined at the speeds corresponding to the engine speeds used for measurement of the engine power either by calculation from standard characteristics or by practical tests. This power, corrected to the standard atmospheric conditions defined in Clause 5, shall be deducted from the corrected power.</p> <p data-bbox="284 920 1485 1021">Where a disconnectable or progressive fan or blower is incorporated, the test shall be performed with the fan or blower disconnected or with the progressive fan running at maximum slip.</p>
8	<p data-bbox="284 1037 555 1070">Electrical equipment</p> <p data-bbox="284 1081 432 1115">Generator</p> <p data-bbox="284 1115 1453 1182">The electrical power of the generator shall be the minimum. It shall be limited to that necessary for operation of accessories which are indispensable for engine operation.</p> <p data-bbox="284 1193 400 1227">Battery</p> <p data-bbox="284 1227 1453 1294">If the connection of a battery is necessary, a fully charged battery in good condition shall be used.</p> <p data-bbox="284 1305 639 1339">Spark distribution system</p> <p data-bbox="284 1350 448 1384">Coil or coils</p> <p data-bbox="284 1395 384 1429">Wiring</p> <p data-bbox="284 1440 448 1473">Spark-plugs</p> <p data-bbox="284 1485 624 1518">Electronic control system</p> <p data-bbox="284 1518 1485 1585">The spark advance shall be representative of in-use conditions established with the minimum octane fuel recommended by the manufacturer.</p>

**Table 2** (continued)

No.	Equipment and auxiliaries
9	Pressure-charging equipment
	Compressor driven either directly by the engine and/or by the exhaust gases
	Boost control For engines equipped with variable boost as a function of charge or inlet air temperature, octane rating and/or engine speed, the boost pressure shall be representative of in-vehicle conditions established with the minimum octane fuel as recommended by the manufacturer.
	Charge air cooler Charge air-cooled engines shall be tested with the charge air-cooling system operating, whether this system is liquid- or air-cooled. If the engine manufacturer prefers, a test bed system may replace an air-cooled cooler. In either case the measurement of power at each speed shall be made with the pressure drop and temperature drop of the engine air across the charge air cooler in the test bed the same as those specified by the manufacturer for the system on the complete vehicle.
	Coolant pump or fan (engine-driven)
10	Anti-pollution device These may include, e.g. Exhaust Gas Recirculation (EGR) system, catalytic converter, secondary air-supply, fuel evaporation protection systems and crankcase emission control system.
11	Lubricating oil pump
12	Oil cooler

### 6.3.2 Test conditions

The test conditions shall be as follows:

- a) The power test shall consist of a run at full throttle, the engine being equipped with equipment and auxiliaries as specified in 6.3.1.
- b) The engine speed during a test run shall not deviate from the selected speed by more than  $\pm 1\%$ .
- c) Performance data shall be obtained under stabilized operating conditions in accordance with the manufacturer's specifications, with an adequate fresh-air supply to the engine.

Before the test, the engine shall have been run-in in accordance with the manufacturer's recommendations. Test conditions such as inlet air temperature shall be selected to be as near to the standard reference conditions (see Clause 5) as possible in order to minimize the magnitude of the correction factor.

- d) No data shall be taken until torque, engine speed and temperatures have been maintained substantially constant as specified by the manufacturer.
- e) If the constant operating conditions (torque, engine speed and temperatures) are not specified by the manufacturer, no data shall be taken until the engine speed has been maintained within the limits specified in 6.3.2 b). Each measurement period shall be equal for every measurement.
- f) Data on the observed brake load, the fuel consumption and the engine inlet air temperature shall be taken virtually simultaneously and shall, in each case, be the average of two consecutive stabilized readings for which the brake load and fuel consumption do not vary by more than 2 %.

No adjustment shall be made to the engine between these readings.

- g) A measurement time of not less than 10 s shall be used when measuring engine speed and fuel consumption with an automatically synchronized counter-timer combination.

- h) For liquid-cooled engines, the temperature of the coolant at the outlet from the engine shall be kept within  $\pm 5$  K from the upper thermostatically controlled temperature specified by the manufacturer. If no temperature is specified by the manufacturer, the temperature shall be  $353 \text{ K} \pm 5 \text{ K}$ .

For air-cooled engines, the temperature at a point indicated by the manufacturer shall be kept within  $0/-20$  K of the maximum value specified by the manufacturer for the reference conditions.

If no temperature is specified by the manufacturer, the temperature of the ignition spark-plug washer shall be  $523 \text{ K}$  or less. For multi-cylinder engines, it is permissible to measure the ignition spark-plug washer temperature at only one representative cylinder.

- i) The fuel temperature shall be measured as near as possible to the inlet of the carburettor or fuel injector manifold assembly. Fuel temperature shall be maintained within  $\pm 5$  K of the temperature specified by the manufacturer. However, the minimum test fuel temperature allowed shall be the ambient air temperature. If the test fuel temperature is not specified by the manufacturer, it shall be  $298 \text{ K} \pm 20 \text{ K}$ .
- j) The lubricating oil temperature measured in the oil sump or at the oil cooler outlet, if fitted, shall be maintained within the limits established by the engine manufacturer.
- k) Engine inlet air temperature shall be measured within  $0,15$  m of the point of entry to the air cleaner, or, if no air cleaner is used, within  $0,15$  m of the air inlet horn. The inlet depression measurement shall be made at the same point.

The thermometer or thermocouple shall be shielded from fuel spray-back and radiant heat and located directly in the air stream. A sufficient number of locations shall be used to give a representative average of the inlet temperature.

- l) The exhaust temperature shall be measured at a point in the exhaust pipe(s) adjacent to the outlet flange(s) of the exhaust manifold(s) or ports.
- m) In cases of type approval (certification) or acceptance test, the selection of fuel for power test shall be agreed by the parties involved and be selected in accordance with the requirements of Table 3. In the case of other tests, an appropriate fuel for the test can be used.
- n) Unleaded gasoline shall be used for the engine equipped with the catalyst. Specifications for test fuels in 8.2.2 e) shall be reported in cases of type approval (certification) or acceptance test. For other types of test, at least the following fuel information shall be reported.
- 1) make and name;
  - 2) octane number RON or MON;
  - 3) relative density at  $288 \text{ K}$ , in  $\text{g}/\text{cm}^3$ ;
  - 4) lower calorific value, in  $\text{kJ}/\text{kg}$ ;
  - 5) applicable fuel standard(s).
- o) In case of using commercial fuels, it is permitted to only report the following information:
- 1) make and name;
  - 2) grade;
  - 3) applicable fuel standard(s).
- p) Data to be recorded shall be those indicated in 8.3.

**Table 3 — Test fuels**

Test purpose	Interested parties	Fuel selection
Type approval (certification)	Certification body, manufacturer or supplier	Reference fuel, if one is defined Commercial fuel if no reference fuel is defined
Acceptance test	Manufacturer or supplier Customer or inspector	Commercial fuel as specified by the manufacturer

### 6.3.3 Test atmospheric conditions

The atmospheric conditions during the test shall be within the range given below.

- a) Engine inlet air temperature, in kelvin,  $288 \leq t_y \leq 308$
- b) Dry pressure, in kilo pascal,  $90 \leq p_d \leq 110$

NOTE  $p_d = p_y - \phi_y p_{sy}$

### 6.4 Test procedure

Measurements shall be taken at a sufficient number of engine speeds to completely define the torque and power curve between the lowest and the highest engine speeds recommended by the manufacturer. The speed range shall include the point at which the engine produces its maximum torque and power. Data shall be taken incrementally from the lowest to the highest engine speeds recommended by the manufacturer. When the temperature exceeds the value specified in 6.3.2 g), the measurements shall be made intermittently.

## 7 Torque, power and specific fuel consumption

### 7.1 Calculation of measured torque, measured power and specific fuel consumption

The measured torque and measured power shall be calculated by Formulae (1) and (2), respectively,

$$T = WL \tag{1}$$

$$P = \frac{2\pi WLN}{60k} = cWN \tag{2}$$

where

$c$  is the coefficient of dynamometer  $\left( c = \frac{2\pi L}{60k} \right)$ ;

$k$  is the conversion factor ( $k = 1000$ );

$L$  is the arm length of dynamometer, in meters;

$N$  is the dynamometer rotation speed, in  $\text{min}^{-1}$ ;

$W$  is the dynamometer braking load, in newtons.



When the power take-off shaft rotation speed is different from the crankshaft rotation speed, the measured torque shall be defined as the quotient of the torque,  $T$ , divided by the reduction gear ratio defined in Formula (3),

$$r_g = \frac{n_c}{n_p} \quad (3)$$

where

- $n_c$  is the crankshaft rotation speed, in  $\text{min}^{-1}$ ;
- $n_p$  is the power take-off shaft rotation speed, in  $\text{min}^{-1}$ ;
- $r_g$  is the reduction gear ratio.

The specific fuel consumption shall be calculated by Formula (4):

$$b_e = \frac{B}{P} \quad (4)$$

where

- $B$  is the amount of fuel consumed by an engine per unit of time, in grams per hour.

## 7.2 Net torque and net power

The net torque and net power shall be determined by multiplying the measured torque and measured power by the correction factor ( $\alpha_m$  factor), which is defined by the efficiency of the transmission used during the test.

### 7.2.1 Determination of correction factor $\alpha_m$

Where the measurement point is at the crankshaft, this factor is equal to 1.

Where the measurement point is not at the crankshaft, this factor is calculated using Formula (5):

$$\alpha_m = \frac{1}{\eta_t} \quad (5)$$

where  $\eta_t$  is the efficiency of the transmission which is located between the crankshaft and the measurement point.

This efficiency of the transmission,  $\eta_t$ , is determined from the product of efficiency  $\eta_i$  of each element constituting the transmission and calculated by Formula (6):

$$\eta_t = \eta_1 \times \eta_2 \times \dots \times \eta_i \quad (6)$$

The efficiency  $\eta_i$  of each element constituting the transmission shall be in accordance with Table 4.

**Table 4 — Transmission component efficiencies**

Component	Type	
Gear	Spur gear	0,98
	Helical gear	0,98
	Bevel gear	0,98
Chain	Roller	0,95
	Silent	0,98
Belt	Toothed	0,95
	V-belt	0,94
Hydraulic coupler or converter	Hydraulic coupler	0,92
	Non-locked hydraulic converter	0,92

### 7.2.2 Calculation of net torque and net power

The net torque and net power shall be calculated by Formulae (7) and (8), respectively,

$$T_y = \alpha_m T \quad (7)$$

$$P_y = \alpha_m P \quad (8)$$

### 7.3 Corrected net torque and corrected net power

The corrected net torque and corrected net power shall be determined by multiplying the net torque and net power by the correction factor ( $\alpha_a$  factor). This factor is to determine the corrected net torque and power, taking into account the standard reference conditions given in Clause 5.

#### 7.3.1 Determination of correction factor $\alpha_a$

The correction factor  $\alpha_a$  for naturally aspirated and pressure-charged spark-ignition engines, with or without charge air cooling, shall be calculated by Formula (9);

$$\alpha_a = \left( \frac{p_r - \varphi_r p_{sr}}{p_y - \varphi_y p_{sy}} \right)^{1,2} \left( \frac{t_y}{t_r} \right)^{0,6} \quad (9)$$

Formula (9) is only applicable if:

$$0,96 \leq \alpha_a \leq 1,06$$

If these limits are exceeded, the corrected power value obtained shall be given and the test conditions (temperature and pressure) precisely stated in the test report.

#### 7.3.2 Calculation of corrected net torque and corrected net power

The corrected net torque and corrected net power shall be calculated by Formulae (10) and (11), respectively,

$$T_0 = \alpha_a T_y = \alpha_a \alpha_m T \quad (10)$$

$$P_0 = \alpha_a P_y = \alpha_a \alpha_m P \quad (11)$$

## **8 Test report**

### **8.1 General**

The requirements for the test report shall be as follows:

### **8.2 The description of test report**

The test report shall include the following engine identification and test information.

#### **8.2.1 Essential characteristics of spark-ignition engines**

##### **8.2.1.1 Engine description**

- a) Reciprocating engines
  - 1) Make
  - 2) Type
  - 3) Identification number
  - 4) Cycle
  - 5) Engine swept volume (total displacement volume)
  - 6) Bore and stroke
  - 7) Number and layout of cylinders
  - 8) Firing order
  - 9) Compression ratio
  - 10) Cooling system
- b) Rotary piston engines
  - 1) Make
  - 2) Type
  - 3) Identification number
  - 4) Engine swept volume (total displacement volume)
  - 5) Eccentricity (ratio)
  - 6) Operating width
  - 7) Number of rotors
  - 8) Compression ratio
  - 9) Cooling system

#### **8.2.2 Equipment and auxiliaries**

For the following equipment and auxiliaries, the make, type, specifications, setting conditions, etc. shall be described when the standard production equipment is not used.

- a) Cooling system;

EXAMPLE Nature of liquid, radiator, fan, blower, etc.

b) Pressure charger;

EXAMPLE Compressor system, charge air cooling system, etc.

c) Inlet system;

EXAMPLE Inlet manifold, air filter, inlet silencer, etc.

d) Emission control devices;

EXAMPLE Exhaust Gas Recirculation (EGR) system, catalytic converter, secondary air-supply, fuel evaporation protection systems and crankcase emission control system, etc.

e) Fuel feed system;

EXAMPLE Carburetor, fuel feed pump, fuel injection system, etc.

f) Ignition systems;

EXAMPLE Ignition timing control system, spark-plug, ignition coil, ignition condenser, radio interference suppression equipment, etc.

g) Exhaust system;

EXAMPLE Exhaust pipe, silencer (muffler), etc.

h) Lubrication system;

EXAMPLE Feed system, oil cooler, etc.

i) Electric equipment;

EXAMPLE Generator/alternator, etc.

j) Transmission;

k) Auxiliaries which are driven by engine and not be able to removed from engine during the test.

### 8.2.3 Test conditions during net power measurement

The following test conditions shall be reported in the test report.

a) Pressure measurements;

- 1) Total barometric pressure, kPa
- 2) Ambient relative humidity, %
- 3) Ambient saturated water vapour pressure, kPa
- 4) Back pressure in exhaust system, kPa
- 5) Back pressure measurement point
- 6) Inlet depression, Pa
- 7) Absolute pressure in inlet manifold, Pa

b) Temperature measurements;

- 1) Engine inlet air temperature, K
- 2) Temperature of air at the outlet from the charge air cooling system, K

- 3) Engine coolant temperature, K
- 4) Temperature at specific point of air-cooled engines, K
- 5) Lubricating oil temperature, K
- 6) Fuel temperatures, K
  - i) Fuel temperature measured at the inlet of the carburettor or fuel injector manifold assembly, K
  - ii) Fuel temperature measured inside the fuel flow meter, K
- c) Characteristics of dynamometer;
  - 1) Make
  - 2) Type
  - 3) Constant
- d) Type of fuel flow measurement system;
- e) Specifications of test fuel [see 6.3.2 l) for the items to be reported];
  - 1) Liquid fuel;
    - i) Make and name
    - ii) Research octane number (RON) or motor octane number (MON)
    - iii) Relative density at 288 K, g/cm<sup>3</sup>
    - iv) Reid vapour pressure, kPa
    - v) Distillation;
      - I) Initial boiling point, K
      - II) 10 % (volume), K
      - III) 50 % (volume), K
      - IV) 90 % (volume), K
      - V) Final boiling point, K
      - VI) Residue, volume %
    - vi) Hydrocarbon analysis;
      - I) Olefins, volume %
      - II) Aromatics, volume %
      - III) Saturates, volume %
    - vii) Oxidation stability, minute
    - viii) Existent gum, mg/100mL
    - ix) Sulfur content, weight %
    - x) Lead content, mg/L
    - xi) Carbon/hydrogen mole ratio or carbon/hydrogen weight ratio

- xii) Benzene, volume %
  - xiii) ETBE, volume %
  - xiv) Ethanol, volume %
  - xv) MTBE, volume %
  - xvi) Methanol, volume %
  - xvii) Phosphorus content, mg/L
  - xviii) Mixture-ratio of fuels to lubricants, volume %
  - xix) Lower calorific value (measured or calculated value), kJ/kg
  - xx) Others
- 2) Gaseous fuel;
- i) Make and name
  - ii) Storage pressure, kPa
  - iii) Utilization pressure and measurement point, kPa
  - iv) Lower calorific value (measured or calculated value), kJ/kg
  - v) Others
- f) Lubrication oil;
- 1) Make and name
  - 2) Grade
  - 3) SAE viscosity

### 8.3 Statement of results

The following items shall be included in the test results report and the characteristic curves of the corrected net torque, corrected net power and the specific fuel consumption shall be drawn as a function of the engine speed. The example of test results report is given in Table 5. The results shall be reported by Table 6.

- a) Maximum corrected net torque, Nm
- b) Engine speed at maximum corrected net torque,  $\text{min}^{-1}$
- c) Specific fuel consumption at maximum corrected net torque,  $\text{g/kW}\cdot\text{h}$
- d) Maximum corrected net power, kW
- e) Engine speed at corrected maximum net power,  $\text{min}^{-1}$
- f) Specific fuel consumption at maximum corrected net power,  $\text{g/kW}\cdot\text{h}$

Table 5 — Example of test results for the characteristic curves

No.	Engine speed		Dynamo- meter rotation speed	Dynamo- meter braking force	Meas- ured torque	Meas- ured power	Temperatures					Test room rela- tive humid- ity	Total baro- metric pres- sure	Cor- rec- tion factor $\alpha_a$	Cor- rec- ted net torque	Correc- ted net power	Meas- ured fuel con- sump- tion	Specific fuel con- sump- tion <sup>c</sup>		
	min <sup>-1</sup>	Meas- ured					Inlet air	Cool- ing <sup>a</sup>	Oil	Exhaust gas	Fuel								Ambi- ent air	K
1	1																			
	2																			
	Mean																			
2	1																			
	2																			
	Mean																			
	1																			
	2																			
	Mean																			
	1																			
	2																			
	Mean																			

Date ..... Time of test start: ..... test end: .....

<sup>a</sup> Specify the measurement point (delete where inapplicable):  
 — at the cooling liquid outlet;  
 — at the spark-plug gasket;  
 — at other points (specify these).

<sup>b</sup> Delete as applicable.

<sup>c</sup> Without correction of power.

**Table 6 — Test results**

<b>Items</b>	<b>Value</b>	<b>Engine speed at measurement</b>	<b>Specific fuel consumption at measurement</b>
Maximum corrected net torque	Nm	min <sup>-1</sup>	g/(kW·h)
Maximum corrected net power	kW	min <sup>-1</sup>	g/(kW·h)



## Bibliography

- [1] ISO 1585, *Road vehicles — Engine test code — Net power*
- [2] ISO 3007, *Petroleum products and crude petroleum — Determination of vapour pressure — Reid method*
- [3] ISO 3405, *Petroleum products — Determination of distillation characteristics at atmospheric pressure*
- [4] ISO 3675, *Crude petroleum and liquid petroleum products — Laboratory determination of density — Hydrometer method*
- [5] ISO 3830, *Petroleum products — Determination of lead content of gasoline — Iodine monochloride method*
- [6] ISO 3837, *Liquid petroleum products — Determination of hydrocarbon types — Fluorescent indicator adsorption method*
- [7] ISO 4106, *Motorcycles — Engine test code — Net power*
- [8] ISO 4260, *Petroleum products and hydrocarbons — Determination of sulfur content — Wickbold combustion method*
- [9] ISO 5164, *Motor fuels — Determination of knock characteristics — Research method*
- [10] ISO 6246, *Petroleum products — Gum content of light and middle distillate fuels — Jet evaporation method*
- [11] ISO 7536, *Petroleum products — Determination of oxidation stability of gasoline — Induction period method*
- [12] ISO 8754, *Petroleum products — Determination of sulfur content — Energy-dispersive X-ray fluorescence spectrometry*





# British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

## About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

## Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at [bsigroup.com/standards](http://bsigroup.com/standards) or contacting our Customer Services team or Knowledge Centre.

## Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at [bsigroup.com/shop](http://bsigroup.com/shop), where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

## Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to [bsigroup.com/subscriptions](http://bsigroup.com/subscriptions).

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

**PLUS** is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit [bsigroup.com/shop](http://bsigroup.com/shop).

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email [bsmusales@bsigroup.com](mailto:bsmusales@bsigroup.com).

## BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

## Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

## Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

## Useful Contacts:

### Customer Services

**Tel:** +44 845 086 9001

**Email (orders):** [orders@bsigroup.com](mailto:orders@bsigroup.com)

**Email (enquiries):** [cservices@bsigroup.com](mailto:cservices@bsigroup.com)

### Subscriptions

**Tel:** +44 845 086 9001

**Email:** [subscriptions@bsigroup.com](mailto:subscriptions@bsigroup.com)

### Knowledge Centre

**Tel:** +44 20 8996 7004

**Email:** [knowledgecentre@bsigroup.com](mailto:knowledgecentre@bsigroup.com)

### Copyright & Licensing

**Tel:** +44 20 8996 7070

**Email:** [copyright@bsigroup.com](mailto:copyright@bsigroup.com)



...making excellence a habit.™