BS ISO 7216:2015



BSI Standards Publication

Agricultural and forestry tractors — Measurement of noise emitted when in motion



BS ISO 7216:2015 BRITISH STANDARD

National foreword

This British Standard is the UK implementation of ISO 7216:2015.

The UK participation in its preparation was entrusted to Technical Committee AGE/6, Agricultural tractors and forestry machinery.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2015. Published by BSI Standards Limited 2015

ISBN 978 0 580 87267 9

ICS 17.140.20; 65.060.01

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 October 2015.

Amendments issued since publication

Date Text affected

INTERNATIONAL STANDARD

ISO 7216:2015 ISO 7216

Second edition 2015-10-01

Agricultural and forestry tractors — Measurement of noise emitted when in motion

Tracteurs agricoles et forestiers — Mesurage du bruit émis en mouvement



BS ISO 7216:2015 **ISO 7216:2015(E)**



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Co	ontents	Page
Fore	reword	iv
Intr	roduction	
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Measurement units and tolerances	2
5	Instrumentation	2
6	Circumstances for testing 6.1 Acoustical environment 6.2 Ambient conditions	2
7	Layout of the test area	
8	Condition of tractor	
9	Test procedure	
10	Interpretation of results	4
11	Test report	4
Ann	nex A (informative) Designation of Maintenance Agency	5
Rihl	liogranhy	6

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 23, *Tractors and machinery for agriculture and forestry*, Subcommittee SC 2, *Common tests*.

This second edition cancels and replaces the first edition (ISO 7216:1992), of which has been technically revised for the technical harmonization with OECD Code 2, 4.8: July 2014.

Introduction

Technical harmonization with OECD is ensured by the Maintenance Agency operating as specified in $\underline{\text{Annex } A}$.

Agricultural and forestry tractors — Measurement of noise emitted when in motion

1 Scope

This International Standard specifies a method for measuring the A-weighted sound pressure level of the noise emitted by agricultural and forestry tractors while the vehicle is in motion.

The conditions specified for the operation of the agricultural and forestry tractors during the measurements are defined to provide a realistic and repeatable assessment of the maximum noise emitted when it is in motion.

This International Standard is applicable to agricultural and forestry tractors, fitted with elastic tyres or rubber tracks.

It is not applicable to special forestry machinery, for example, forwarders, skidders, etc., as defined in ISO 6814 and agricultural and forestry tractors, fitted with steel tracks.

NOTE The test method calls for an acoustical environment which can only be obtained in an extensive open space.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61672-1, Electroacoustics — Sound level meters

IEC 60942, Electroacoustics — Sound calibrators

ISO 6814:2009, Machinery for forestry — Mobile and self-propelled machinery — Terms, definitions and classification

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

agricultural tractor

self-propelled agricultural vehicle having at least two axles and wheels, or endless tracks, particularly designed to pull agricultural trailers and pull, push, carry and operate implements used for agricultural work (including forestry work), which may be provided with a detachable loading platform

Note 1 to entry: The agricultural vehicle has a maximum design speed of not less than 6 km/h and may be equipped with one or more seats.

[SOURCE: ISO 12934:2013, 3.1]

BS ISO 7216:2015 ISO 7216:2015(E)

3.2

unballasted tractor mass

mass in the tractor in working order with tanks and radiators full, roll-over protective structure with cladding, and any track equipment or additional front-wheel drive components required for normal use

Note 1 to entry: Not included are the operator, optional ballast weights, additional wheel equipment, special equipment and loads.

[SOURCE: ISO 5700:2013, 3.2]

4 Measurement units and tolerances

The following units and tolerances apply to the maximum value measured:

_	rotational frequency (r/min)	± 0,5 %;
_	time (s)	± 0,2 s;
_	distance (m or mm)	± 0,5 %;
_	force (N)	± 1,0 %;
_	mass (kg)	± 0,5 %;
_	atmospheric pressure (kPa)	± 0,2 kPa;
_	tyre pressure (Pa)	±5%.

5 Instrumentation

- **5.1** A precision quality sound level meter shall be used meeting or exceeding the requirements of IEC 61672-1 for a class 1 instrument. If alternative measuring equipment is used, the tolerances shall not exceed those given in the relevant clauses of IEC 61672-1 for a class 1 instrument. Measurement shall be carried out with a frequency weighting network in conformity with curve A and set to give fast response as is described in the IEC publication.
- **5.2** The calibration of the equipment at the time of measurement shall be in accordance in all respects with the specifications of IEC 61672-1 for a class 1 instrument. Checking of the calibration shall be carried out at appropriate intervals and at least before and after each measurement session, using an acoustical calibrator in accordance with the specifications of IEC 60942 for a class 1 instrument. The calibrator shall be checked annually to verify its output and its calibration shall be traceable to a national standards laboratory.

6 Circumstances for testing

6.1 Acoustical environment

- **6.1.1** Measurements shall be made in a sufficiently silent, flat, and open zone. This area shall be an open space of 50 m radius, of which the central part of at least 20 m radius shall be practically level and made concrete, asphalt, or similar material and shall not be covered with powdery snow, high grass, friable soil or cinders.
- **6.1.2** The surface of the test track shall be of such a kind that pneumatic tyres or rubber tracks do not cause excessive noise. The surface shall be as clean and dry as possible (e.g. free of gravel, leaves, snow, etc.).


6.2 Ambient conditions

- **6.2.1** Measurements shall be made in fine weather with little or no wind. The level of background noise and the level of wind noise at the microphone location shall be at least 10 dB(A) below the noise level measured during the test. Any extraneous noise occurring during the reading, which is not connected to general sound level measurement, shall not be taken into consideration.
- **6.2.2** No correction shall be made to the test results for the atmospheric conditions or other factors. Atmospheric pressure shall not be less than 96,6 kPa. If this is not possible because of conditions of altitude, a modified injection pump setting may have to be used, details of which will be included in the report.

7 Layout of the test area

- **7.1** The centreline of the track (CC), a line (PP) perpendicular to it and passing through the centre of the test area and two lines (AA and BB) parallel to line PP and 10 m from it shall be marked on the track (see Figure 1).
- **7.2** The microphone shall be placed 1,2 m above ground and a distance of 7,5 m from the axis of forward movement of the tractor, measured along the perpendicular PP to the axis (see <u>Figure 1</u>).

The microphone shall be oriented in a direction normal to the centreline of the path of travel on the track.



^a One microphone position may be eliminated, in which case an additional test run from BB to AA is required.

Figure 1 — Layout of the test area — Microphone position

8 Condition of tractor

- **8.1** Measurement will be made on the unballasted tractor with no load and without trailer or semitrailer.
- **8.2** Immediately before the test, the engine shall be brought to its normal operating temperature.
- **8.3** The stabilized ground speed to be used will be equal to three-quarters of the attainable maximum in the transmission gear or setting giving the highest speed used for roadwork.

9 Test procedure

- **9.1** At least two measurements shall be carried out on each side of the tractor. Preliminary measurements to establish governor control setting may be made but shall not be taken into consideration.
- **9.2** Tractors shall be driven at stabilized ground speed, under the conditions specified in <u>Clause 8</u>, as far as line AA. At this moment, the governor control lever shall quickly be fully opened. The lever shall be held in this position until the tractor has passed line BB and then brought to the minimum position as quickly as possible.

10 Interpretation of results

- 10.1 Measurements shall be considered valid if the difference between two consecutive measurements on the same side of the tractor does not exceed 2 dB(A).
- **10.2** The highest sound level measured shall constitute the test result.

11 Test report

The test report shall include the following details:

- a) reference to this International Standard
- b) name and address of the manufacturer
- c) the tractor type, model serial number and transmission type
- d) the type and rated speed of the engine
- e) a brief description of the silencing system (if provide)
- f) whether the tractor is two- or four-wheel drive
- g) details of the test site, the testing ground conditions and meteorological conditions
- h) sound level meter, make, model, type
- i) the number of measurements and the sound pressure levels recorded
- j) overall test results
- k) date and place of test and signature of the tester.

Annex A (informative)

Designation of Maintenance Agency

- **A.1** A Maintenance Agency has been established by the ISO Technical Management Board (TMB) to ensure that technical harmonization can be maintained between ISO/TC 23/SC 2 Standards and OECD Tractor Test Codes. It operates through guidelines approved by the TMB, accessible at http://standards.iso.org/iso/7216 that entrust it to the following functions:
- a) to receive the requests for changes from recognized ISO/TC 23/SC 2 P-members;
- b) to evaluate and resolve the requests for changes;
- c) to publish the approved changes.
- **A.2** Changes to this International Standard will be announced by the MA Secretariat to ISO/TC 23/SC 2 and will be made publicly available at http://standards.iso.org/iso/7216. They constitute authoritative amendments to Clauses 1 to 11 of this International Standard.

Bibliography

- [1] ISO 12934:2013, Tractors and machinery for agriculture and forestry Basic types Vocabulary
- [2] ISO 5700:2013, Tractors for agriculture and forestry Roll-over protective structures Static test method and acceptance conditions
- [3] OECD Code 2: July 2014, OECD Standard Code for the official testing of agricultural and forestry tractor performance





British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards -based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com
Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070 Email: copyright@bsigroup.com

