# Oil of bitter orange (Citrus aurantium L.)

ICS 71.100.60



#### National foreword

This British Standard reproduces verbatim ISO 9844:2006 and implements it as the UK national standard.

The UK participation in its preparation was entrusted to Technical Committee AW/54, Essential oils, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep UK interests informed:
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

#### **Cross-references**

The British Standards which implement international publications referred to in this document may be found in the BSI Catalogue under the section entitled "International Standards Correspondence Index", or by using the "Search" facility of the BSI Electronic Catalogue or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

#### Summary of pages

This document comprises a front cover, an inside front cover, the ISO title page, pages ii to iv, pages 1 to 11 and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 28 April 2006

 $\bigcirc$  BSI 2006

ISBN 0 580 48206 5

#### Amendments issued since publication

Amd. No.	Date	Comments

## INTERNATIONAL STANDARD

ISO 9844

Second edition 2006-03-01

### Oil of bitter orange (Citrus aurantium L.)

Huile essentielle d'orange amère (Citrus aurantium L.)



Cont	<b>ents</b> Pag	јe
Forewo	ord	iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4 4.1 4.2 4.3	Requirements Appearance Colour Odour	1 1 1
4.4	Relative density at 20 °C, $d_{20}^{20}$	2
4.5 4.6 4.7 4.8 4.9 4.10	Refractive index at 20 °C	2 2 2 2
5	Sampling	3
6 6.1 6.2 6.3 6.4	Test methods	3 3 3
6.5 6.6	Residue on evaporation	3
7	Packaging, labelling, marking and storage	3
Annex	A (informative) Typical chromatograms of the analysis by gas chromatography of the essential oil of bitter orange (Citrus aurantium L.)	4
Annex	B (informative) Flashpoint	0
Bibliog	jraphy 1	1

#### **Foreword**

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 9844 was prepared by Technical Committee ISO/TC 54, Essential oils.

This second edition cancels and replaces the first edition (ISO 9844:1991), which has been technically revised.

#### Oil of bitter orange (Citrus aurantium L.)

#### 1 Scope

This International Standard specifies certain characteristics of the oil of bitter orange (*Citrus aurantium* L.), in order to facilitate assessment of its quality.

#### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/TR 210, Essential oils — General rules for packaging, conditioning and storage

ISO/TR 211, Essential oils — General rules for labelling and marking of containers

ISO 212, Essential oils — Sampling

ISO 279, Essential oils — Determination of relative density at 20 °C — Reference method

ISO 280, Essential oils — Determination of refractive index

ISO 592, Essential oils — Determination of optical rotation

ISO 875, Essential oils — Evaluation of miscibility in ethanol

ISO 4715, Essential oils — Quantitative evaluation of residue on evaporation

ISO 11024-1, Essential oils — General guidance on chromatographic profiles — Part 1: Preparation of chromatographic profiles for presentation in standards

ISO 11024-2, Essential oils — General guidance on chromatographic profiles — Part 2: Utilization of chromatographic profiles of samples of essential oils

#### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

#### 3 1

#### oil of bitter orange

essential oil obtained by expression, without heating, by mechanical treatment, from the pericarp of the fruit of *Citrus aurantium* L., of the Rutaceae family

NOTE For information on the CAS number, see ISO/TR 21092.

#### 4 Requirements

#### 4.1 Appearance

Liquid.

#### 4.2 Colour

Pale yellow to brownish green.

#### 4.3 Odour

Characteristic of the outer part of bitter orange peel.

#### 4.4 Relative density at 20 °C, $d_{20}^{20}$

American type		Equator	rial type	Mediterranean type		
min.	max.	min.	max.	min.	max.	
0,840	0,860	0,845	0,860	0,840	0,860	

#### 4.5 Refractive index at 20 °C

American type		Equator	rial type	Mediterranean type		
min.	max.	min.	max.	min.	max.	
1,472	1,476	1,473	1,478	1,472	1,476	

#### 4.6 Optical rotation at 20 °C

American type	Equatorial type	Mediterranean type	
+ 88° to + 98°	+ 88° to + 95°	+ 88° to + 98°	

#### 4.7 Miscibility in ethanol, 90 % (volume fraction), at 20 °C

It shall not be necessary to use more than 8 volumes of ethanol, 90 % (volume fraction), to obtain a clear solution with 1 volume of essential oil.

#### 4.8 Residue on evaporation

American type		Equator	rial type	Mediterranean type		
min.	max.	min.	max.	min.	max.	
3,5 %	6,0 %	3,0 %	6,0 %	3,5 %	6,0 %	

#### 4.9 Chromatographic profile

Analysis of the essential oil shall be carried out by gas chromatography. In the chromatogram obtained, the representative and characteristic components shown in Table 1 shall be identified. The proportions of these components, indicated by the integrator, shall be as shown in Table 1. This constitutes the chromatographic profile of the essential oil.

#### 4.10 Flashpoint

Information on the flashpoint is given in Annex B.

Table 1 — Chromatographic profile

	American type		Equato	Equatorial type		Mediterranean type	
Components	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum	
	%	%	%	%	%	%	
α-Pinene	0,3	0,7	0,3	0,6	0,2	0,7	
β-Pinene	0,3	1,2	0,3	0,8	0,2	1,2	
Myrcene	1,6	2,0	1,6	2,0	1,5	3,0	
Limonene	93,0	95,0	92,0	95,0	93,0	95,0	
Linalool	0,1	0,4	0,1	0,4	0,1	0,4	
Linalyl acetate	0,6	1,0	traces	0,5	0,5	1,0	
Geranyl acetate	0,1	0,3	nd <sup>a</sup>	0,3	0,1	0,3	
β-Caryophyllene	traces	0,2	traces	0,1	traces	0,2	
Germacrene D	0,1	0,2	traces	0,1	traces	0,2	
<i>trans</i> -β-Nerolidol	traces	0,2	nd <sup>a</sup>	0,3	traces	0,2	
Octanal	traces	0,2	nd <sup>a</sup>	0,3	traces	0,1	
Decanal	0,1	0,2	nd <sup>a</sup>	0,2	traces	0,3	
a Undetected.		•	•	•		•	
NOTE The chromatographic profile is normative, contrary to the typical chromatograms given for information in Annex A.							

#### 5 Sampling

See ISO 212.

Minimum volume of test sample: 50 ml

NOTE This volume allows each of the tests specified in this International Standard to be carried out at least once.

#### 6 Test methods

6.1 Relative density at 20 °C,  $d_{20}^{20}$ 

See ISO 279.

6.2 Refractive index at 20 °C

See ISO 280.

6.3 Optical rotation at 20 °C

See ISO 592.

## 6.4 Miscibility in ethanol, 90 % (volume fraction), at 20 °C

See ISO 875.

#### 6.5 Residue on evaporation

See ISO 4715.

#### 6.6 Chromatographic profile

See ISO 11024-1 and ISO 11024-2.


## 7 Packaging, labelling, marking and storage

See ISO/TR 210 and ISO/TR 211.

## Annex A (informative)


Typical chromatograms of the analysis by gas chromatography of the essential oil of bitter orange (*Citrus aurantium* L.)

A.1 Typical chromatograms of the analysis by gas chromatography of the essential oil of bitter orange (*Citrus aurantium* L.), American type



Peak	didentification	Operating conditions
1	α-Pinene	Column: methyl silicone; length 50 m; internal diameter 0,2 mm
2	β-Pinene	Stationary phase: poly(dimethyl siloxane) (SP5®)
3	Octanal	Film thickness: 0,33 µm
4	Myrcene	Oven temperature: temperature programming from 60 °C to 240 °C at a rate of 3 °C/min, then
5	Limonene	isothermal at 240 °C for 30 min
6	Linalool	Injector temperature: 270 °C
7	Decanal	Detector temperature: 280 °C
8	Linalyl acetate	Detector: flame ionization type
9	Geranyl acetate	Carrier gas: helium
10	β-Caryophyllene	Volume injected: 0,2 µl
11	Germacrene D	Carrier gas flow rate: 1 ml/min
12	<i>trans</i> -β-Nerolidol	Split ratio: 1/50


Figure A.1 — Typical chromatogram taken on an apolar column



real	k identification	Operating conditions
1	$\alpha$ -Pinene	Column: Carbowax; length 50 m; internal diameter 0,2 mm
2	$\beta$ -Pinene	Stationary phase: poly(ethylene glycol) (Suplecowax-10®)
3	Myrcene	Film thickness: 0,4 μm
4	Limonene	Oven temperature: temperature programming from 60 °C to 240 °C at a rate of 3 °C/min, then
5	Octanal	isothermal at 240 °C for 30 min
6	Decanal	Injector temperature: 270 °C
7	Linalool	Detector temperature: 280 °C
8	Linalyl acetate	Detector: flame ionization type
9	β-Caryophyllene	Carrier gas: helium
10	Germacrene D	Volume injected: 0,2 µl
11	Geranyl acetate	Carrier gas flow rate: 1 ml/min
12	trans-β-Nerolidol	Split ratio: 1/50


Figure A.2 — Typical chromatogram taken on a polar column

## A.2 Typical chromatograms of the analysis by gas chromatography of the essential oil of bitter orange (*Citrus aurantium* L.), Equatorial type



Peak identification		Operating conditions
1	$\alpha$ -Pinene	Column: silica capillary; length 60 m; internal diameter 0,25 mm
2	$\beta$ -Pinene	Stationary phase: poly(dimethyl siloxane) (SolGel-1ms)
3	Octanal	Film thickness: 0,25 μm
4	Myrcene	Oven temperature: isothermal at 60 °C for 10 min, then temperature programming from 60 °C
5	Limonene	to 300 °C at a rate of 2 °C/min, then isothermal at 300 °C for 20 min
6	Linalool	Injector temperature: 250 °C
7	Decanal	Detector temperature: 250 °C
8	Linalyl acetate	Detector: mass spectrometer
9	Geranyl acetate	Carrier gas: helium
10	β-Caryophyllene	Volume injected: 0,2 μl
11	Germacrene D	Carrier gas flow rate: 1 ml/min
12	trans-β-Nerolidol	Split ratio: 1/60


Figure A.3 — Typical chromatogram taken on an apolar column



rea	k identification	Operating conditions
1	$\alpha$ -Pinene	Column: silica capillary; length 20 m; internal diameter 0,10 mm
2	β-Pinene	Stationary phase: poly(ethylene glycol) (Suplecowax-10®)
3	Sabinene	Film thickness: 0,20 μm
4	Myrcene	Oven temperature: isothermal at 50 °C for 1 min, then temperature programming from 50 °C
5	Limonene	to 200 °C at a rate of 10 °C/min, then isothermal for 13 min
6	$\beta$ -Phellandrene	Injector temperature: 250 °C
7	Octanal	Detector temperature: 250 °C
8	Nonanal	Detector: flame ionization type
9	Decanal	Carrier gas: helium
10	Linalool	Volume injected: 0,2 µl
11	Linalyl acetate	Carrier gas flow rate: 30 ml/min
12	β-Carvophyllene	Split ratio: 1/650


Figure A.4 — Typical chromatogram taken on a polar column

## A.3 Typical chromatograms of the analysis by gas chromatography of the essential oil of bitter orange (*Citrus aurantium* L.), Mediterranean type



Peal	k identification	Operating conditions
1	$\alpha$ -Pinene	Column: silica capillary; length 60 m; internal diameter 0,25 mm
2	β-Pinene	Stationary phase: poly(5 % diphenyl/95 % dimethyl siloxane) (DB5 MS®)
3	Myrcene	Film thickness: 0,25 µm
4	Octanal	Oven temperature: isothermal at 40 °C for 5 min, then temperature programming from 40 °C
5	Limonene	to 220 °C at a rate of 4 °C/min, then isothermal at 220 °C for 5 min
6	Linalool	Injector temperature: 260 °C
7	Decanal	Detector temperature: 280 °C
8	Linalyl acetate	Detector: MS type, Full Scan (50-200)
9	Geranyl acetate	Carrier gas: helium
10	β-Caryophyllene	Volume injected: 0,3 μl
11	Germacrene D	Carrier gas flow rate: 1 ml/min
12	<i>trans</i> -β-Nerolidol	Split ratio: 1/150

Figure A.5 — Typical chromatogram taken on an apolar column



Peak identification		Operating conditions
1	$\alpha$ -Pinene	Column: silica capillary; length 60 m, internal diameter 0,32 mm
2	β-Pinene	Stationary phase: poly(ethylene glycol) (Suplecowax-10®)
3	Myrcene	Film thickness: 0,25 μm
4	Limonene	Oven temperature: isothermal at 75 °C for 4 min, then temperature programming from 75 °C
5	Octanal	to 150 °C at a rate of 2 °C/min, then from 150 °C to 240 °C at a rate of 5 °C/min, then
6	Decanal	isothermal at 240 °C for 20 min
7	Linalool	Injector temperature: 225 °C
8	Linalyl acetate	Detector temperature: 225 °C
9	$\beta$ -Caryophyllene	Detector: MS type, Full Scan (50-200)
10	Germacrene D	Carrier gas: helium
11	Geranyl acetate	Volume injected: 0,03 μl
12	<i>trans</i> -β-Nerolidol	Carrier gas flow rate: 1,5 ml/min
		Split ratio: 1/100

Figure A.6 — Typical chromatogram taken on a polar column

#### Annex B

(informative)

#### **Flashpoint**

#### **B.1 General information**

For safety reasons, transport companies, insurance companies, and people in charge of safety services require information on the flashpoints of essential oils, which in most cases are flammable products.

A comparative study on the relevant methods of analysis (see ISO/TR 11018) concluded that it was difficult to recommend a single apparatus for standardization purposes, given that

- there is a wide variation in the chemical composition of essential oils;
- the volume of the sample needed in certain test methods would be too costly for high-priced essential oils;
- as there are several different types of equipment which can be used for the determination, users cannot be expected to use one specified type only.

Consequently, it was decided to give a mean value for the flashpoint in an informative annex to each International Standard in order to meet the requirements of the interested parties.

The equipment with which this value was obtained should be specified.

For further information see ISO/TR 11018.

## B.2 Flashpoint of the essential oil of bitter orange

## B.2.1 Flashpoint of the essential oil of bitter orange, American type

The mean value is +47 °C.

NOTE Obtained with "Pensky Martens" equipment.

## **B.2.2** Flashpoint of the essential oil of bitter orange, Equatorial type

The mean value is +50 °C.

NOTE Obtained with "miniflash-petrotest France" equipment.

## **B.2.3 Flashpoint of the essential oil of bitter orange, Mediterranean type**

The mean value is +47 °C.

NOTE Obtained with "Pensky Martens" equipment.

#### **Bibliography**

- [1] ISO/TR 11018, Essential oils General guidance on the determination of flashpoint
- [2] ISO/TR 21092, Essential oils Characterization

#### **BSI** — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

#### Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

#### **Buying standards**

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001. Fax: +44 (0)20 8996 7001. Email: orders@bsi-global.com. Standards are also available from the BSI website at <a href="http://www.bsi-global.com">http://www.bsi-global.com</a>.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

#### Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre. Tel: +44 (0)20 8996 7111. Fax: +44 (0)20 8996 7048. Email: info@bsi-global.com.

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration.

Tel: +44 (0)20 8996 7002. Fax: +44 (0)20 8996 7001.

Email: membership@bsi-global.com.

Information regarding online access to British Standards via British Standards Online can be found at <a href="http://www.bsi-global.com/bsonline">http://www.bsi-global.com/bsonline</a>.

Further information about BSI is available on the BSI website at <a href="http://www.bsi-global.com">http://www.bsi-global.com</a>.

#### Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means — electronic, photocopying, recording or otherwise — without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright & Licensing Manager. Tel: +44 (0)20 8996 7070. Fax: +44 (0)20 8996 7553. Email: copyright@bsi-global.com.

BSI 389 Chiswick High Road London W4 4AL