

Optics and photonics — Preparation of drawings for optical elements and systems —

Part 17: Laser irradiation damage threshold

ICS 01.100.20; 31.260; 37.020

National foreword

This British Standard reproduces verbatim ISO 10110-17:2004 and implements it as the UK national standard.

The UK participation in its preparation was entrusted to Technical Committee CPW/172, Optics and optical instruments, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international publications referred to in this document may be found in the *BSI Catalogue* under the section entitled “International Standards Correspondence Index”, or by using the “Search” facility of the *BSI Electronic Catalogue* or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the ISO title page, pages ii and iii, a blank page, pages 1 to 4, an inside back cover and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 1 June 2004

Amendments issued since publication

Amd. No.	Date	Comments

© BSI 1 June 2004

ISBN 0 580 43828 7

INTERNATIONAL
STANDARD

ISO
10110-17

First edition
2004-03-01

**Optics and photonics — Preparation of
drawings for optical elements and
systems —**

Part 17:
Laser irradiation damage threshold

*Optique et photonique — Préparation des dessins pour éléments et
systèmes optiques —*

Partie 17: Seuil de dommage au rayonnement laser



Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 10110-17 was prepared by Technical Committee ISO/TC 172, *Optics and photonics*, Subcommittee SC 1, *Fundamental standards*.

ISO 10110 consists of the following parts, under the general title *Optics and photonics — Preparation of drawings for optical elements and systems*:

- *Part 1: General*
- *Part 2: Material imperfections — Stress birefringence*
- *Part 3: Material imperfections — Bubbles and inclusions*
- *Part 4: Material imperfections — Inhomogeneity and striae*
- *Part 5: Surface form tolerances*
- *Part 6: Centring tolerances*
- *Part 7: Surface imperfection tolerances*
- *Part 8: Surface texture*
- *Part 9: Surface treatment and coating*
- *Part 10: Table representing data of optical elements and cemented assemblies*
- *Part 11: Non-toleranced data*
- *Part 12: Aspheric surfaces*
- *Part 14: Wavefront deformation tolerance*
- *Part 17: Laser irradiation damage threshold*

Optics and photonics — Preparation of drawings for optical elements and systems —

Part 17: Laser irradiation damage threshold

1 Scope

ISO 10110 specifies the presentation of design and functional requirements for optical elements in technical drawings used for manufacturing and inspection.

This part of ISO 10110 specifies rules for the indication of the damage threshold from laser irradiation up to which optical surfaces shall not exhibit any damage as defined in ISO 11254-1.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 10110-5, *Optics and optical instruments — Preparation of drawings for optical elements and systems — Part 5: Surface form tolerances*

ISO 10110-6, *Optics and optical instruments — Preparation of drawings for optical elements and systems — Part 6: Centring tolerances*

ISO 10110-7, *Optics and optical instruments — Preparation of drawings for optical elements and systems — Part 7: Surface imperfection tolerances*

ISO 10110-10:2003, *Optics and photonics — Preparation of drawings for optical elements and systems — Part 10: Table representing data of optical elements and cemented assemblies*

ISO 11145, *Optics and optical instruments — Lasers and laser-related equipment — Vocabulary and symbols*

ISO 11254-1:2000, *Lasers and laser-related equipment — Determination of laser-induced damage threshold of optical surfaces — Part 1: 1-on-1 test*

ISO 11254-2, *Lasers and laser-related equipment — Determination of laser-induced damage threshold of optical surfaces — Part 2: S-on-1 test*

3 Terms and definitions

For the purposes of this document the terms and definitions given in ISO 11145, ISO 11254-1 and the following apply.

**3.1
wavelength**

λ
wavelength of the laser radiation

**3.2
threshold**

highest quantity of laser radiation incident upon the optical surface for which the extrapolated probability of damage is zero

NOTE The quantity of laser radiation may be expressed in energy density H_{\max} or power density E_{\max} .

[ISO 11254-1:2000]

**3.3
effective pulse duration**

τ_{eff}
(laser pulse) ratio of the total pulse energy to maximum pulse power

[ISO 11254-1:2000]

**3.4
threshold energy density**

H_{th}
(pulsed laser irradiation) energy density threshold, expressed in joules per square centimetre, above which damage may occur

**3.5
threshold power density**

E_{th}
(pulsed laser irradiation) power density threshold, expressed in watts per square centimetre, above which damage may occur

**3.6
threshold linear power density**

F_{th}
(continuous wave and long pulse laser irradiation) linear power density threshold, expressed in watts per centimetre, above which damage may occur

NOTE For laser damage considerations a long pulse is when the thermal transit distance, $(2 D \tau_{\text{eff}})^{1/2}$, where D is the thermal diffusivity, is in the order of the size of the test spot $d_{\text{T,eff}}$.

4 Other test parameters

Any other test parameters shall be in accordance with the relevant parts of ISO 11254. For certain optical elements it may be necessary to specify the state and plane of polarization as well as the angle of incidence.

5 Specifications

5.1 General

Specifications of laser irradiation damage threshold apply to the finished surfaces, particularly surface treatments and coatings.

5.2 Damage threshold for pulsed laser irradiation

The specification of a laser irradiation damage threshold, H_{th} or E_{th} , for an optical surface shall include the laser wavelength, λ , and the effective pulse duration, τ_{eff} .

5.3 Damage threshold for long pulse and continuous wave (cw) laser irradiation

The specification of a laser irradiation damage threshold, F_{th} , for an optical surface shall include the laser wavelength, λ , and the effective pulse duration, τ_{eff} . In case of cw-irradiation specify the irradiation time.

NOTE In case of cw-lasers (i.e. irradiation time longer than 0,25 s according to ISO 11145) the effective pulse duration is not defined and the term "irradiation time" is used.

6 Indication

The laser irradiation damage threshold shall be indicated on the technical drawing by a code number and the parameters specified in Clause 5. Additional requirements shall be covered by notes.

The code number for the laser radiation threshold is **6**.

The indication shall have the following form:

a) for pulsed laser irradiation:

$$\mathbf{6}/H_{th}; \lambda; \tau_{eff} \text{ or } \mathbf{6}/E_{th}; \lambda; \tau_{eff}$$

b) for long pulse and cw laser irradiation:

$$\mathbf{6}/F_{th}; \lambda; \tau_{eff}$$

The units of H_{th} , E_{th} , F_{th} , λ and τ_{eff} shall be given in the indication.

7 Location

The indication on the technical drawing shall be shown in connection with a leader line to the surface to which it relates and will be associated with other surface codes (3/, 4/, 5/) as specified in ISO 10110-5, ISO 10110-6 and ISO 10110-7. An example of such an indication is shown in Figure A.1 of ISO 10110-1:1996.

Alternatively, the indication may be listed in a table according to Figure 3 of ISO 10110-10:2003.

8 Examples of indication

EXAMPLE 1: **6/25 J·cm⁻²; 1 064 nm; 20 ns**

This means that the damage threshold is above an energy density of 25 J·cm⁻², for a laser wavelength of 1 064 nm (Nd:YAG) and an effective pulse duration of 20 ns.

EXAMPLE 2: **6/10 kW·cm⁻¹; 10,6 μm; 1 s**

This means that the damage threshold is above a linear power density of 10 kW·cm⁻¹ for a cw laser emitting at 10,6 μm wavelength (CO₂) and an irradiation time of 1 s.

Bibliography

- [1] ISO 10110-1:1996, *Optics and optical instruments — Preparation of drawings for optical elements and systems — Part 1: General*

BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001. Fax: +44 (0)20 8996 7001. Email: orders@bsi-global.com. Standards are also available from the BSI website at <http://www.bsi-global.com>.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre. Tel: +44 (0)20 8996 7111. Fax: +44 (0)20 8996 7048. Email: info@bsi-global.com.

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration. Tel: +44 (0)20 8996 7002. Fax: +44 (0)20 8996 7001. Email: membership@bsi-global.com.

Information regarding online access to British Standards via British Standards Online can be found at <http://www.bsi-global.com/bsonline>.

Further information about BSI is available on the BSI website at <http://www.bsi-global.com>.

Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright & Licensing Manager. Tel: +44 (0)20 8996 7070. Fax: +44 (0)20 8996 7553. Email: copyright@bsi-global.com.