

BS ISO 10880:2017



BSI Standards Publication

# Non-destructive testing — Infrared thermographic testing — General principles

**National foreword**

This British Standard is the UK implementation of ISO 10880:2017.

The UK participation in its preparation was entrusted to Technical Committee WEE/46, Non-destructive testing.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2017.  
Published by BSI Standards Limited 2017

ISBN 978 0 580 82615 3

ICS 19.100

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 January 2017.

**Amendments/corrigenda issued since publication**

Date	Text affected
------	---------------

---

INTERNATIONAL  
STANDARD

BS ISO 10880:2017

**ISO**  
**10880**

First edition  
2017-02

---

---

**Non-destructive testing — Infrared  
thermographic testing — General  
principles**

*Essais non destructifs — Essais thermographiques infrarouge —  
Principes généraux*



Reference number  
ISO 10880:2017(E)

© ISO 2017



## **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Ch. de Blandonnet 8 • CP 401  
CH-1214 Vernier, Geneva, Switzerland  
Tel. +41 22 749 01 11  
Fax +41 22 749 09 47  
copyright@iso.org  
www.iso.org

# Contents

Page

<b>Foreword</b> .....	<b>iv</b>
<b>Introduction</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Infrared thermographic testing personnel</b> .....	<b>1</b>
<b>5 Infrared thermographic testing equipment</b> .....	<b>1</b>
5.1 Infrared camera.....	1
5.2 Equipment used for active thermography.....	2
<b>6 Test environment</b> .....	<b>2</b>
6.1 Installation environment for the test equipment.....	2
6.2 Avoidance of disturbance.....	2
<b>7 Test method</b> .....	<b>2</b>
7.1 Emissivity of test object.....	2
7.2 Passive thermography and active thermography.....	3
7.3 Imaging method.....	3
7.3.1 General.....	3
7.3.2 Non-uniformity and infrared intensity value correction.....	3
7.3.3 Field of view and spatial resolution.....	3
7.3.4 Angle.....	3
7.3.5 Temperature range and temperature resolution.....	4
7.3.6 Display of thermal images.....	4
7.3.7 Frame time and exposure time.....	4
7.3.8 Testing by using the infrared-reflecting mirror.....	4
7.3.9 Adjustment of focus.....	4
7.3.10 Confirmation of settings.....	4
7.4 Signal processing and image processing.....	4
<b>8 Implementation and reporting of tests</b> .....	<b>5</b>
8.1 Items described in the NDT procedures.....	5
8.2 Items described in the NDT instructions.....	5
8.3 Record of test conditions.....	5
8.4 Report.....	6
<b>Bibliography</b> .....	<b>7</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 135, *Non-destructive testing*, Subcommittee SC 8, *Thermographic testing*.

## Introduction

The industrial applications of infrared thermographic testing in non-destructive testing (NDT) are growing, along with a remarkable improvement in thermographic technologies. The effectiveness of any application of infrared thermographic testing depends upon proper and correct usage of the method. The purpose of this document is to provide general principles for infrared thermographic testing in order to promote the correct and effective application of a variety of industrial NDT, such as in power plants, buildings and structures, electronic instruments and industrial materials.





# Non-destructive testing — Infrared thermographic testing — General principles

## 1 Scope

This document provides general principles for infrared thermographic testing in the field of industrial non-destructive testing (NDT).

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 9712, *Non-destructive testing — Qualification and certification of NDT personnel*

ISO 10878, *Non-destructive testing — Infrared thermography — Vocabulary*

## 3 Terms and definitions

For the purposes of this document the terms and definitions given in ISO 10878 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

## 4 Infrared thermographic testing personnel

Personnel who are responsible for conducting infrared thermographic testing (TT) shall meet the following criteria.

- a) TT personnel shall have an adequate knowledge of the basics of infrared measurement and heat-transfer engineering as required by ISO 9712.
- b) The TT personnel's visual acuity and colour vision shall meet the requirements of ISO 9712.

## 5 Infrared thermographic testing equipment

### 5.1 Infrared camera

Each infrared camera has different properties and functions, such as the type of infrared detecting device, the spatial resolution (instantaneous field of view, effective pixels), temperature range, temperature resolution, temperature accuracy, frame time, exposure time, detection wavelength range, cooling method, scanning method, and the visible image display and recording function. It is necessary to ensure that an infrared camera with appropriate properties and functions with appropriate temperature calibration to meet the purpose of the testing is used.

If necessary, various devices that can be attached to the infrared camera such as wavelength filters, attenuation filters, replacement lenses, monitors, computers and software for data collection and processing, and infrared-reflecting mirrors may be used.

## 5.2 Equipment used for active thermography

Select the appropriate heating or cooling system, taking into account the properties and functions of the infrared camera, the test environment, and the status of the test object (dimensions, shape, emissivity, material, temperature before thermal loading, and so on.)

NOTE For the heating system, a heating lamp, a flash lamp, an electric radiation heater, an induction coil, a contact-type heater, a hot-air device, a reflection board, a power-distribution device, or a vibrational apparatus can be used. For the cooling system, a sprinkler, an atomizer, or an air blower can be used.

## 6 Test environment

### 6.1 Installation environment for the test equipment

Conduct the test in an environment where the temperature, humidity, and atmosphere are appropriate for the test equipment, including the infrared camera.

### 6.2 Avoidance of disturbance

In order to avoid reflections from objects other than the test object or background (temperature of the ambient environment), increasing the object's emissivity may be necessary. This can be achieved with paint or any other type of adequate surface preparation and/or treatment as described in [7.1](#). Moreover, during the installation of the infrared camera, several positions may be tested in order to determine which one minimizes the effect of reflections.

If the temperature of the test object is low, note that the proportion of the reflected apparent temperature to the total infrared radiation energy arriving at the infrared camera can be high.

Take care of absorption, scattering, and reflection of infrared radiation energy by any substances that are present between the infrared camera and the test object (for example, water vapour, carbon dioxide, or window materials).

## 7 Test method

### 7.1 Emissivity of test object

For temperature measurements, the emissivity of the test object shall be taken into account. Set the emissivity value within the radiometric software or within the camera as correctly as possible in order to match the apparent temperature with the true temperature [\[3\]](#) [\[4\]](#).

NOTE 1 If the emissivity of the surface of the test object is not uniform, the infrared radiation energy will not be uniform, even if the temperature of the surface of the test object is uniform. If the emissivity is low, the effects of reflections and/or transmission become proportionately larger.

NOTE 2 The emissivity of test object may vary with the material, the temperature, the roughness of the surface, the thickness of any oxidized membrane on the surface, the presence of impurities on the surface, the angle, and wavelength range of the infrared camera.

NOTE 3 If the emissivity of the test object is low or not uniform, a coating of matte black material can be applied thinly and uniformly until the surface of the base material is covered. Alternatively, a thin membrane of a material with a high emissivity can be attached to the surface to ensure that the emissivity is as uniform as possible during the test.

NOTE 4 Other methods can also be used, such as roughening the surface of plastics (for example, with sandpaper) or oxidizing the surface of metals and so on.

In the radiometric software, the ambient temperature shall also be considered.

## 7.2 Passive thermography and active thermography

Passive thermography is a thermographic technique for inspecting objects or installations by measuring their emitted thermal radiation, without using any additional energy source for thermal stimulation. It is not necessary to induce an additional temperature change within the objects or installations for the purpose of the test.

**EXAMPLE** Passive thermography can be used, for instance, for inspecting electrical installations and mechanical components, in process. It can also be used, for instance, when natural thermal loading by solar radiation exists, such as for buildings and structures<sup>[1]</sup> <sup>[2]</sup> <sup>[9]</sup>, or when the presence of an anomaly or a defect results in the generation or absorption of heat, such as a defect in transmission or distribution equipment.

Detecting anomalies by passive thermography has some physical limitations, which are often overcome by active thermography.

Active thermography is a thermographic examination of materials and objects which requires additional thermal stimulation.

**NOTE** The thermal stimulation can be optical, sonic (ultrasonic), inductive, microwave, or using any other form of energy.

In active thermography, if a test is meant to detect conductive anomalies, then a uniform thermal loading is preferred. The intensity of the thermal load shall be properly adjusted in relation to

- the performance of the infrared camera,
- the thermal properties of the test object, such as the thermal diffusivity, and
- the position, shape, dimensions, and depth of an anomaly or defect.

Care shall be taken not to damage the object under test, as a result of excessive thermal loading.

## 7.3 Imaging method

### 7.3.1 General

Steps shall be taken to ensure that the apparatus to be used for the test is operating correctly, i.e. in accordance with the technical specifications, and its settings are appropriate to the object under test.

### 7.3.2 Non-uniformity and infrared intensity value correction

Before imaging is performed, it is necessary to enable the non-uniformity correction function of the infrared camera to correct for variations in the sensitivity of individual infrared detection elements. If any equipment, such as a wavelength filter, replacement lens, or infrared-reflecting mirror, is attached to the optical system, it is necessary to apply an appropriate correction to the infrared intensity value.

### 7.3.3 Field of view and spatial resolution

One of the limitations in the detection of anomalies is the spatial resolution on the object. The distance between the camera and the object shall be adapted so that the spatial resolution is at least equal to the size of the anomalies. Changing the lens, for one offering a better resolution, might be necessary.

### 7.3.4 Angle

An angle of 45° or less between a line normal to the surface to be tested and the optical axis of the infrared camera is preferred. If this is not possible, an angle of 60° maximum is acceptable.

**NOTE** If the angle exceeds 60°, or for tests on the rear face of the object, a method involving an infrared-reflecting mirror can be used as described in [7.3.8](#).

### 7.3.5 Temperature range and temperature resolution

Set the optimum measurement range of the infrared camera according to the expected signal dynamics to obtain with the test object.

NOTE 1 Sufficient signal-to-noise is needed for a proper analysis.

NOTE 2 The temperature resolution of the infrared camera decreases as the temperature range is increased.

### 7.3.6 Display of thermal images

The level and span of the image display should be properly adjusted not to miss the indications from the image.

### 7.3.7 Frame time and exposure time

Appropriate frame rate and integration time shall be selected to detect any anomaly and defect of the test object.

When imaging an unsteady or high-speed phenomenon, the frame time of the infrared camera should be set to be sufficiently short to permit capture of the transient phenomenon. For imaging high-speed phenomena, a short exposure time is therefore desirable; however, note that the sensitivity of the camera is low for short exposure times.

### 7.3.8 Testing by using the infrared-reflecting mirror

A test object that cannot be imaged directly can be imaged indirectly by means of an infrared-reflecting mirror. Note that right and left directions on the shot image will be reversed and that the reflectivity of the mirror affects the accuracy of the test.

### 7.3.9 Adjustment of focus

The infrared camera shall be focused on the test object during imaging.

NOTE For test objects with a low intrinsic contrast, the focus can be set accurately by attaching a thin metallic scale or similar object at the surface of the test object, which can be recognized in thermal images.

### 7.3.10 Confirmation of settings

Before the test, check the settings under the test conditions, as described in [7.3.2](#) to [7.3.9](#).

NOTE The settings of the temperature range and the focus cannot be adjusted after recording.

## 7.4 Signal processing and image processing

To reduce test errors and/or to extract and emphasize anomalies, carry out the appropriate signal-processing and image-processing operations when necessary. Methods such as threshold-value processing, averaging, smoothing, background elimination, difference processing, frequency analysis, lock-in processing, or motion compensation are available for signal and image processing, and these should be used when necessary.

## 8 Implementation and reporting of tests

### 8.1 Items described in the NDT procedures

Procedures giving information on the test and the object to test shall be prepared and written. They shall contain details such as (but not limited to)

- a) the purpose of the test,
- b) applicable scope,
- c) applicable standards,
- d) testing personnel,
- e) the test object and area to be tested,
- f) test equipment,
- g) test environment,
- h) the test method and test conditions,
- i) the evaluation method, and
- j) the record and report.

### 8.2 Items described in the NDT instructions

NDT instructions shall be prepared and written. They shall contain items such as (but not limited to)

- a) the test date, time, and location,
- b) the test area,
- c) test equipment (model, type number, and lens of the infrared camera, optical systems used, such as the infrared-reflecting mirrors, etc.),
- d) the test method and test condition (passive or active thermography, thermal loading method and conditions, values of settings for the infrared camera, method of surface preparation for pseudo black body, ambient disturbance factors that require attention, etc.), and
- e) the method for recording.

### 8.3 Record of test conditions

The results of infrared thermographic testing are different depending on the test environment, the test equipment, and the test method. Any conditions that could affect the result shall be recorded such as

- a) test date, time, and location,
- b) test personnel,
- c) test object and area to be tested (shape, dimensions, material, and surface texture of the test object; distance between the infrared camera and the test object, a visual image of the test object and so on),
- d) test equipment [models and type numbers of infrared camera (detection element, effective number of pixels), optical system such as lens, filter and infrared-reflecting mirror, temperature range, exposure time, frame rate and so on],

- e) test environment [temperature, humidity, weather (in the case of outdoor testing), positional relationships between the infrared camera, test object, and any ambient factors that could affect the results],
- f) test method and test conditions
  - method of surface preparation for pseudo black body to improve emissivity,
  - selection of passive or active thermography; in the case of active thermography, the thermal loading method and conditions such as the thermal source, distance, heating method, and heating time,
  - signal processing and image processing methods used, and
- g) the evaluation method (reasons why relevant data are evaluated as pertaining to abnormal heat-generation points or flaws, based on the indications obtained).

#### **8.4 Report**

Report items that are described in the NDT procedures and items described in the NDT instructions as the occasion demands.

## Bibliography

- [1] ISO 6781:1983, *Thermal insulation — Qualitative detection of thermal irregularities in building envelopes — Infrared method*
- [2] ISO 18251-1, *Non-destructive testing — Infrared thermography — System and equipment — Part 1: Description of characteristics*
- [3] ISO 18434-1:2008, *Condition monitoring and diagnostics of machines — Thermography — Part 1: General procedures*
- [4] ASTM E1933-14, *Standard Practice for Measuring and Compensating for Emissivity Using Infrared Imaging Radiometers*
- [5] ASTM E1934-99a (2010), *Standard Guide for Examining Electrical and Mechanical Equipment with Infrared Thermography*
- [6] ASTM E 2582-07, *Standard Practice for Infrared Flash Thermography of Composite Panels and Repair Patches Used in Aerospace Applications*
- [7] DIN 54190-1:2004, *Non-destructive testing — Thermographic testing — Part 1: General principles*
- [8] DIN 54190-3:2006, *Non-destructive testing — Thermographic testing — Part 3: Terms and definitions*
- [9] NDIS 3427:2009, *General principles of infrared thermographic testing method*







# British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

## About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

## Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at [bsigroup.com/standards](http://bsigroup.com/standards) or contacting our Customer Services team or Knowledge Centre.

## Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at [bsigroup.com/shop](http://bsigroup.com/shop), where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

## Copyright in BSI publications

All the content in BSI publications, including British Standards, is the property of and copyrighted by BSI or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use.

Save for the provisions below, you may not transfer, share or disseminate any portion of the standard to any other person. You may not adapt, distribute, commercially exploit, or publicly display the standard or any portion thereof in any manner whatsoever without BSI's prior written consent.

## Storing and using standards

Standards purchased in soft copy format:

- A British Standard purchased in soft copy format is licensed to a sole named user for personal or internal company use only.
- The standard may be stored on more than 1 device provided that it is accessible by the sole named user only and that only 1 copy is accessed at any one time.
- A single paper copy may be printed for personal or internal company use only.

Standards purchased in hard copy format:

- A British Standard purchased in hard copy format is for personal or internal company use only.
- It may not be further reproduced – in any format – to create an additional copy. This includes scanning of the document.

If you need more than 1 copy of the document, or if you wish to share the document on an internal network, you can save money by choosing a subscription product (see 'Subscriptions').

## Reproducing extracts

For permission to reproduce content from BSI publications contact the BSI Copyright & Licensing team.

## Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to [bsigroup.com/subscriptions](http://bsigroup.com/subscriptions).

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

**PLUS** is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit [bsigroup.com/shop](http://bsigroup.com/shop).

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email [subscriptions@bsigroup.com](mailto:subscriptions@bsigroup.com).

## Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

## Useful Contacts

### Customer Services

**Tel:** +44 345 086 9001

**Email (orders):** [orders@bsigroup.com](mailto:orders@bsigroup.com)

**Email (enquiries):** [cservices@bsigroup.com](mailto:cservices@bsigroup.com)

### Subscriptions

**Tel:** +44 345 086 9001

**Email:** [subscriptions@bsigroup.com](mailto:subscriptions@bsigroup.com)

### Knowledge Centre

**Tel:** +44 20 8996 7004

**Email:** [knowledgecentre@bsigroup.com](mailto:knowledgecentre@bsigroup.com)

### Copyright & Licensing

**Tel:** +44 20 8996 7070

**Email:** [copyright@bsigroup.com](mailto:copyright@bsigroup.com)

### BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK