

BS ISO 12614-6:2014



BSI Standards Publication

Road vehicles — Liquefied natural gas (LNG) fuel system components

Part 6: Pressure regulator

bsi.

...making excellence a habit.™

National foreword

This British Standard is the UK implementation of ISO 12614-6:2014.

The UK participation in its preparation was entrusted to Technical Committee GSE/40, Gas supply equipment for natural gas vehicles.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014. Published by BSI Standards Limited 2014

ISBN 978 0 580 77152 1

ICS 43.060.40

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 July 2014.

Amendments issued since publication

Date	Text affected
------	---------------

**Road vehicles — Liquefied natural gas
(LNG) fuel system components —**

**Part 6:
Pressure regulator**

*Véhicules routiers — Équipements pour véhicules utilisant le gaz
naturel liquéfié (GNL) comme combustible —*

Partie 6: Régulateur de pression





COPYRIGHT PROTECTED DOCUMENT

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Marking	2
5 Construction and assembly	2
6 Test	2
6.1 Applicability.....	2
6.2 Hydrostatic strength.....	3
6.3 External leakage.....	3
6.4 Continued operation.....	3
Bibliography	4

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 22, *Road vehicles*, Subcommittee SC 25, *Vehicles using gaseous fuels*.

ISO 12614 consists of the following parts, under the general title *Road vehicles — Liquefied natural gas (LNG) fuel system components*:

- *Part 1: General requirements and definitions*
- *Part 2: Performance and general test methods*
- *Part 3: Check valve*
- *Part 4: Manual valve*
- *Part 5: Tank pressure gauge*
- *Part 6: Pressure regulator*
- *Part 7: Pressure relief valve*
- *Part 8: Excess flow valve*
- *Part 9: Gas-tight housing and ventilation hose*
- *Part 10: Rigid fuel line in stainless steel*
- *Part 11: Fittings*
- *Part 12: Rigid fuel line in copper and its alloys*
- *Part 13: Pressure control regulator*
- *Part 14: Differential pressure fuel content gauge*
- *Part 15: Capacitance fuel content gauge*

- *Part 16: Heat exchanger – vaporizer*
- *Part 17: Natural gas detector*
- *Part 18: Gas temperature sensor*

Road vehicles — Liquefied natural gas (LNG) fuel system components —

Part 6: Pressure regulator

1 Scope

This part of ISO 12614 specifies tests and requirements for the pressure regulator, a liquefied natural gas fuel system component intended for use on the types of motor vehicles defined in ISO 3833. This part of ISO 12614 is applicable to vehicles using natural gas in accordance with ISO 15403 (mono-fuel, bi-fuel, or dual-fuel applications). It is not applicable to the following:

- 1) fuel containers;
- 2) stationary gas engines;
- 3) container mounting hardware;
- 4) electronic fuel management;
- 5) refueling receptacles.

NOTE 1 It is recognized that miscellaneous components not specifically covered herein can be examined to meet the criteria of this part of ISO 12614 and tested according to the appropriate functional tests.

NOTE 2 All references to pressure in this part of ISO 12614 are to be considered gauge pressures unless otherwise specified.

NOTE 3 This part of ISO 12614 is based upon a working pressure for natural gas as a fuel of 1,6 MPa (16 bar). (1 bar = 0,1 MPa = 105 Pa; 1 MPa = 1 N/mm².) Other working pressures can be accommodated by adjusting the pressure by the appropriate factor (ratio). For example, a 2 MPa (20 bar) working pressure system will require pressures to be multiplied by 1,25.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 12614-1, *Road vehicles — Liquefied natural gas (LNG) fuel system components — Part 1: General requirements and definitions*

ISO 12614-2, *Road vehicles — Liquefied natural gas (LNG) fuel system components — Part 2: Performance and general test methods*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12614-1 and the following apply.

3.1

lock-up pressure

stabilized outlet pressure of the regulator at 0 (zero) flow

4 Marking

Marking of the component shall provide sufficient information to allow the following to be traced:

- a) the manufacturer's or agent's name, trademark, or symbol;
- b) the model designation (part number);
- c) the working pressure or pressure and temperature range.

The following additional markings are recommended:

- a) the direction of flow (when necessary for correct installation);
- b) the type of fuel;
- c) electrical ratings (if applicable);
- d) the symbol of the certification agency;
- e) the type approval number;
- f) the serial number or date code;
- g) a reference to this part of ISO 12614 (i.e. ISO 12614-6:2014).

NOTE This information can be provided by a suitable identification code on at least one part of the component when it consists of more than one part.

5 Construction and assembly

5.1 The pressure regulator shall comply with the applicable provisions of ISO 12614-1 and ISO 12614-2, and with the tests specified in [Clause 6](#).

5.2 The pressure regulator shall have a factory-set maximum outlet pressure. The maximum outlet pressure rating and the inlet pressure rating shall be marked on the regulator.

6 Test

6.1 Applicability

The tests required to be carried out are indicated in [Table 1](#).

Table 1 — Tests applicable

Test	Applicable	Test procedure as required by ISO 12614-2	Specific test requirements of this part of ISO 12614
Hydrostatic strength	X	X	X (see 6.2)
Leakage	X	X	X (see 6.3)
Excess torque resistance	X	X	
Bending moment	X	X	
Continued operation	X	X	X (see 6.4)
Corrosion resistance	X	X	
Oxygen ageing	X	X	

^a The vibration resistance test in ISO 12614-2 is not applicable if the pressure regulator is engine-mounted.

Table 1 (continued)

Test	Applicable	Test procedure as required by ISO 12614-2	Specific test requirements of this part of ISO 12614
Electrical overvoltages	X	X	
Non-metallic synthetic immersion	X	X	
Vibration resistance	X	X ^a	
Brass material compatibility	X	X	
Insulation resistance			
Minimum opening voltage			
^a The vibration resistance test in ISO 12614-2 is not applicable if the pressure regulator is engine-mounted.			

6.2 Hydrostatic strength

6.2.1 Test the pressure regulator according to the procedure for testing hydrostatic strength specified in ISO 12614-2.

6.2.2 Test the inlet at a pressure of $2,5 \times$ the working pressure.

6.2.3 Test the outlet chamber, port, and all outlet fittings at 2 times the working pressure or 0,4 MPa (4 bar), whichever is the greater.

6.3 External leakage

Test the pressure regulator at the temperatures and pressures given in [Table 2](#).

Table 2 — Test temperatures and pressures

Temperature °C	Pressure (factor \times working pressure)	
	First	Second
-40	$1,0 \times$ WP	$0,25 \times$ WP
20	$0,25 \times$ WP	$1,5 \times$ WP
85 or 120	$0,25 \times$ WP	

6.4 Continued operation

The pressure regulator shall be able to withstand 50 000 cycles without any failure when tested according to the following procedure. Where the stages of pressure regulation are separate, the working pressure in a) to c) is considered to be the working pressure of the upstream stage.

- Recycle the regulator for 50 % of the total number of cycles at room temperature and at the working pressure. Each cycle shall consist of flow until stable outlet pressure has been obtained, after which the gas flow shall be shut off by a downstream valve within 1 s, until the downstream lock-up pressure has stabilized. Stabilized outlet pressures are defined as set pressure ± 15 % for at least 5 s. The regulator shall comply with [6.3](#) at room temperature at intervals of 20 %, 40 %, 60 %, 80 %, and 100 % of room temperature cycles.
- Repeat the cycling procedure of a) at -40 °C and 100 % of working pressure for 50 % of the total number of cycles.
- At the completion of the cycles, the lock-up pressure downstream of the regulator shall not exceed the lock-up pressure specified by the manufacturer.

Bibliography

- [1] ISO 3833, *Road vehicles — Types — Terms and definitions*

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com



...making excellence a habit.™