

BS ISO 12619-1:2014



BSI Standards Publication

# Road vehicles — Compressed gaseous hydrogen (CGH<sub>2</sub>) and hydrogen/natural gas blend fuel system components

Part 1: General requirements and definitions

**bsi.**

...making excellence a habit.™

**National foreword**

This British Standard is the UK implementation of ISO 12619-1:2014.

The UK participation in its preparation was entrusted to Technical Committee GSE/40, Gas supply equipment for natural gas vehicles.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014.  
Published by BSI Standards Limited 2014

ISBN 978 0 580 66557 8  
ICS 43.060.40

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 June 2014.

**Amendments/corrigenda issued since publication**

Date	Text affected
------	---------------

---

INTERNATIONAL  
STANDARD

**ISO**  
**12619-1**

First edition  
2014-06-15

---

---

**Road vehicles — Compressed gaseous  
hydrogen (CGH<sub>2</sub>) and hydrogen/  
natural gas blend fuel system  
components —**

Part 1:  
**General requirements and definitions**

*Véhicules routiers — Composants des circuits d'alimentation pour  
hydrogène gazeux comprimé (CGH<sub>2</sub>) et mélanges de gaz naturel et  
hydrogène —*

*Partie 1: Exigences générales et définitions*



Reference number  
ISO 12619-1:2014(E)

© ISO 2014



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

	Page
Foreword .....	iv
<b>1 Scope .....</b>	<b>1</b>
<b>2 Normative references .....</b>	<b>1</b>
<b>3 Terms and definitions .....</b>	<b>2</b>
<b>4 Construction and assembly .....</b>	<b>4</b>
<b>5 Electrical equipment and wiring .....</b>	<b>5</b>
<b>6 Instructions .....</b>	<b>5</b>
<b>7 Marking .....</b>	<b>6</b>
<b>Bibliography .....</b>	<b>8</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 22, *Road vehicles*, Subcommittee SC 25, *Vehicles using gaseous fuels*.

ISO 12619 consists of the following parts, under the general title *Road vehicles — Compressed gaseous hydrogen (CGH<sub>2</sub>) and hydrogen/natural gas blends fuel system components*:

- *Part 1: General requirements and definitions*
- *Part 2: Performance and general test methods*
- *Part 3: Pressure regulator*

# Road vehicles — Compressed gaseous hydrogen (CGH<sub>2</sub>) and hydrogen/natural gas blend fuel system components —

## Part 1: General requirements and definitions

### 1 Scope

This part of ISO 12619 specifies general requirements and definitions of compressed gaseous hydrogen (CGH<sub>2</sub>) and hydrogen/natural gas blends fuel system components, intended for use on the types of motor vehicles defined in ISO 3833. It also provides general design principles and specifies requirements for instructions and markings.

This part of ISO 12619 is applicable to vehicles using CGH<sub>2</sub> in accordance with ISO 14687-1 or ISO 14687-2 and hydrogen/natural gas blends using natural gas in accordance with ISO 15403-1 and ISO/TR 15403-2. It is not applicable to the following:

- liquefied hydrogen (LH<sub>2</sub>) fuel system components;
- fuel containers;
- stationary gas engines;
- container mounting hardware;
- electronic fuel management;
- refuelling receptacles.

NOTE 1 It is recognized that miscellaneous components not specifically covered herein can be examined to meet the criteria of this part of ISO 12619 and tested according to the appropriate functional tests.

NOTE 2 All references to pressure in this part of ISO 12619 are to be considered gauge pressures unless otherwise specified.

NOTE 3 This part of ISO 12619 may not apply to fuel cell vehicles in compliance with international regulations.

### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6722-1, *Road vehicles — 60 V and 600 V single-core cables — Part 1: Dimensions, test methods and requirements for copper conductor cables*

ISO 6722-2, *Road vehicles — 60 V and 600 V single-core cables — Part 2: Dimensions, test methods and requirements for aluminium conductor cables*

ISO 12619-2, *Road vehicles — Compressed gaseous hydrogen (CGH<sub>2</sub>) and hydrogen/natural gas blend fuel system components — Part 2: Performance and general test methods*

ISO 14687-1, *Hydrogen fuel — Product specification — Part 1: All applications except proton exchange membrane (PEM) fuel cell for road vehicles*

ISO 14687-2, *Hydrogen fuel — Product specification — Part 2: Proton exchange membrane (PEM) fuel cell applications for road vehicles*

ISO 15403-1, *Natural gas — Natural gas for use as a compressed fuel for vehicles — Part 1: Designation of the quality*

ISO/TR 15403-2, *Natural gas — Natural gas for use as a compressed fuel for vehicles — Part 2: Specification of the quality*

ISO 16380<sup>1)</sup>, *Road vehicles — Blended fuels refuelling connector*

ISO 17268, *Gaseous hydrogen land vehicle refuelling connection devices*

### 3 Terms and definitions

#### 3.1

##### **agent**

person or organization responsible for holding the compliance certificate

#### 3.2

##### **burst pressure**

pressure which causes structural failure of the component and consequential inability of the component to retain hydrogen or hydrogen/natural gas blends

#### 3.3

##### **compressed gaseous hydrogen**

##### **CGH2**

gaseous hydrogen which has been compressed and stored for use as a vehicle fuel

#### 3.4

##### **filter**

component that is intended to remove contaminants from the gas stream

#### 3.5

##### **flexible fuel line**

flexible tubing or hose through which gaseous hydrogen or hydrogen/natural gas blend flows

#### 3.6

##### **fitting**

connector used in joining a piping, tubing, or hose system

#### 3.7

##### **fuel cell gas injector**

device used for introducing gas into the fuel cell

#### 3.8

##### **gas air mixer**

device for mixing the gaseous fuel and intake air for the engine

#### 3.9

##### **gas flow adjuster**

gas flow restricting device that is installed downstream of a pressure regulator for controlling gas

#### 3.10

##### **gas injector**

device for introducing gaseous fuel into the engine or associated intake system

---

1) To be published.



**3.11**

**gas tight housing**

device which vents gas leakage to outside the vehicle including the gas ventilation hose, the clear opening of which is at least 450 mm<sup>2</sup>

**3.12**

**hydrogen/natural gas blend**

mixture of natural gas and more than 2 % by volume of hydrogen and not pure hydrogen as per ISO 14687-1 or ISO 14687-2

**3.13**

**pressure indicator**

pressurized device which indicates the gas pressure

**3.14**

**pressure regulator**

device used to control the delivery pressure of gaseous fuel to the engine

**3.15**

**pressure relief device**

**PRD**

one-time use device that when activated under specified performance conditions, is used to vent the container contents

**3.16**

**rigid fuel line**

tubing which has been designed not to flex in normal operation and through which either gaseous hydrogen or hydrogen/natural gas blend flow

**3.17**

**service pressure**

settled pressure at a uniform gas temperature of 15 °C

**3.18**

**test pressure**

pressure to which a component is taken during acceptance testing

**3.19**

**valve**

device by which the flow of a fluid may be controlled

**3.20**

**manual valve**

valve which is operated manually

**3.21**

**automatic valve**

valve which is not operated manually

**3.22**

**automatic cylinder valve**

automatic valve rigidly fixed to the cylinder which controls the flow of gas to the fuel system

**3.23**

**check valve**

automatic valve which allows gas to flow in only one direction

**3.24**

**excess flow valve**

valve which automatically shuts off, or limits, the gas flow when the flow exceeds a set design value

**3.25**

**manual cylinder valve**

manual valve rigidly fixed to the cylinder

**3.26**

**pressure relief valve**

**PRV**

self closing device which opens to prevent a pre-determined upstream pressure being exceeded

**3.27**

**service valve**

manual valve which is closed only when servicing the vehicle

**3.28**

**working pressure**

maximum pressure to which a component is designed to be subjected to and which is the basis for determining the strength of the component under consideration

**4 Construction and assembly**

**4.1** Materials normally in contact with hydrogen shall be determined to be acceptable in hydrogen service, with particular attention to hydrogen embrittlement and hydrogen accelerated fatigue. Materials and design shall be such that there will be no significant change in the functioning of the device, deformation or mechanical change in the device, and no harmful corrosion, deformation, or deterioration of the materials.

Resistance to chloride stress corrosion cracking shall be taken under consideration if selecting stainless steel materials. Resistance to sustained load cracking shall be taken under consideration if selecting aluminium materials.

**NOTE 1** Material performance data in hydrogen environments may be found in the Sandia National Laboratory Technical Reference for Hydrogen Compatibility of Materials or the ANSI/AIAA G-095 Guide to Safety of Hydrogen and Hydrogen Systems and ASME B31.12 Hydrogen Piping and Pipelines.

**NOTE 2** Guidance to account for the degradation effects of hydrogen on the mechanical performance of a material can be found in ISO/TR 15916.

**4.2** Jointing components shall provide gas tight sealing performance. Where joints are required to be disassembled, it is recommended that any tapered thread fittings be replaced

**4.3** Components on board shall be suitable for service within the following temperature ranges:

**Table 1 — Temperature ranges for on board components**

	Location on board	
	Location a	Location b
<b>Cold</b>	- 40°C to 120°C	- 40°C to 85°C
<b>Moderate</b>	- 20°C to 120°C	- 20°C to 85°C
Location a: Inside the engine compartment in case of internal combustion engine vehicle. Location b: Elsewhere in case of internal combustion engine vehicle. In case of fuel cell vehicle, only location b is considered.		

**4.4** Components on board shall be suitable for service in accordance with the following service pressures (as specified for the refuelling connectors in ISO 16380 and ISO 17268):

**Table 2 — Hydrogen/natural gas blend fuel system components**

Service Pressure	Working Pressure
20 MPa	25 MPa
25 MPa	31,25 MPa
35 MPa	43,75 MPa

**Table 3 — Hydrogen fuel system components**

Service Pressure	Working Pressure
25 MPa	31,25 MPa
35 MPa	43,75 MPa
70 MPa	87,50 MPa

**4.5** All non-metallic materials used in seals and diaphragms shall comply with the oxygen ageing test specified in ISO 12619-2.

**4.6** All non-metallic materials in contact with gaseous hydrogen and hydrogen/natural gas blends shall comply with the non-metallic material immersion test, hydrogen compatibility test specified in ISO 12619-2.

**4.7** All components subject to weather exposure and other corrosive conditions shall be made of corrosion resistant material or otherwise protected.

**4.8** It is recognized that multifunctional components may be made up of several components as defined in ISO 12619-3 and subsequent parts. Such components shall be examined for conformance to this part of ISO 12619 and tested according to the appropriate functional tests.

**4.9** Fuel flow shut-off shall be normally closed.

## **5 Electrical equipment and wiring**

**5.1** Any openings through which electrical wiring components pass shall be equipped with means to prevent chafing and abrasion of the wire insulation.

**5.2** Electrical equipment and circuit wiring in a component shall be of automotive quality with respect to mechanical strength, insulation and current carrying capacity, in accordance with either ISO 6722-1 or ISO 6722-2.

**5.3** Materials used for electrical construction shall be suitable for their particular application. When determining the acceptability of an electrical insulating material, consideration shall be given to its mechanical strength, dielectric strength, heat-resistant properties, the degree to which it is enclosed or protected, and any other features influencing fire and accident hazards

## **6 Instructions**

**6.1** Clear, concise instructions and diagrams, stated in terms clearly understandable and adequate for proper assembly, installation, maintenance and safe operation, shall be provided by the manufacturer of the component and component package. The information shall also require that intermediate assemblers transmit the component warnings and information to the final installer. The manufacturer shall provide

copies of the instructions in response to requests, including service parts. Critical parts of the component information shall be worded in the imperative.

**6.2** Instructions for periodic maintenance of components, as required, shall be provided. Parts which require periodic replacement shall be identified.

**6.3** This information shall be in the predominant language(s) of the country of destination.

**6.4** Instructions shall at least include:

- working pressure (MPa);
- temperature range;
- rated for use with pre-cooled hydrogen;
- installation torques;
- orientation requirements;
- venting requirements with consideration for water ingress;
- type of fuel (i.e. “hydrogen and hydrogen/natural gas blends” or “pure hydrogen”);
- type of vehicle (e.g. fuel cell vehicle, internal combustion engine vehicle);
- flow ratings of connections if required for safety, such as flow requirements into and out of relief;
- valves;
- requirements for warning labels that might be required as part of the installation.

Instructions shall also include, as appropriate:

- installation instructions, including torques;
- installation orientation requirements;
- service procedures;
- recommendations for service access.

## **7 Marking**

The components shall include the following information as required:

- a) the manufacturer's or agent's name, trademark or symbol;
- b) the model designation (part number);
- c) the working pressure or working pressure and temperature range;
- d) the direction of flow (when necessary for correct installation);
- e) the type of fuel;
- f) electrical ratings (if applicable);
- g) the symbol of the certification agency (if applicable);
- h) the type approval number;

- i) the serial number or date code;
- j) reference to this part of ISO 12619, i.e. ISO 12619-1:2014.

Marking shall remain legible for the life of the component and shall not be removable without destroying or defacing the marking. Permanent adhesive labels are permissible, or markings may be etched, stamped, or moulded into the component.

NOTE 1 Specific information required for each component can be found in ISO 12619-3 and subsequent parts of the ISO 12619 series.

NOTE 2 This information can be provided by a suitable identification code on at least one part of the component when it consists of more than one part.

## Bibliography

- [1] ISO 2782, *Rubber, vulcanized or thermoplastic – Determination of permeability to gases*
- [2] ISO 3833, *Road vehicles — Types — Terms and definitions*
- [3] ISO 11114-4, *Transportable gas cylinders — Compatibility of cylinder and valve materials with gas contents — Part 4: Test methods for selecting metallic materials resistant to hydrogen embrittlement*
- [4] ISO 12619-3, *Road vehicles — Compressed gaseous hydrogen (CGH<sub>2</sub>) and hydrogen/natural gas blend fuel system components — Part 3: Pressure regulator*
- [5] ISO 13686, *Natural gas — Quality designation*
- [6] ISO/TS 15869, *Gaseous hydrogen and hydrogen blends — Land vehicle fuel tanks*
- [7] ISO/TR 15916, *Basic considerations for the safety of hydrogen systems*
- [8] ISO 23273, *Fuel cell road vehicles — Safety specifications — Protection against hydrogen hazards for vehicles fuelled with compressed hydrogen*









# British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

## About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

## Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at [bsigroup.com/standards](http://bsigroup.com/standards) or contacting our Customer Services team or Knowledge Centre.

## Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at [bsigroup.com/shop](http://bsigroup.com/shop), where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

## Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to [bsigroup.com/subscriptions](http://bsigroup.com/subscriptions).

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

**PLUS** is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit [bsigroup.com/shop](http://bsigroup.com/shop).

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email [bsmusales@bsigroup.com](mailto:bsmusales@bsigroup.com).

## BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

## Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

## Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

## Useful Contacts:

### Customer Services

**Tel:** +44 845 086 9001

**Email (orders):** [orders@bsigroup.com](mailto:orders@bsigroup.com)

**Email (enquiries):** [cservices@bsigroup.com](mailto:cservices@bsigroup.com)

### Subscriptions

**Tel:** +44 845 086 9001

**Email:** [subscriptions@bsigroup.com](mailto:subscriptions@bsigroup.com)

### Knowledge Centre

**Tel:** +44 20 8996 7004

**Email:** [knowledgecentre@bsigroup.com](mailto:knowledgecentre@bsigroup.com)

### Copyright & Licensing

**Tel:** +44 20 8996 7070

**Email:** [copyright@bsigroup.com](mailto:copyright@bsigroup.com)



...making excellence a habit.™