

BS ISO 12647-5:2015



BSI Standards Publication

Graphic technology — Process control for the manufacture of half-tone colour separations, proof and production prints
Part 5: Screen printing

bsi.

...making excellence a habit.™

National foreword

This British Standard is the UK implementation of ISO 12647-5:2015. It supersedes BS ISO 12647-5:2001 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee PAI/43, Graphic technology.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2015. Published by BSI Standards Limited 2015

ISBN 978 0 580 76727 2

ICS 37.100.01

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 January 2015.

Amendments issued since publication

Date	Text affected
------	---------------

INTERNATIONAL
STANDARD

ISO
12647-5

Second edition
2015-01-15

**Graphic technology — Process
control for the manufacture of half-
tone colour separations, proof and
production prints —**

Part 5:
Screen printing

*Technologie graphique — Contrôle du processus de confection de
sélections couleurs tramées, d'épreuves et de tirages —*

Partie 5: Sérigraphie



Reference number
ISO 12647-5:2015(E)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Requirements	2
4.1 Data requirements for screen printing systems.....	2
4.1.1 Data delivery.....	2
4.1.2 Data resolution.....	2
4.2 Printing forme requirements.....	2
4.2.1 Resolution.....	2
4.2.2 Stencil production.....	3
4.2.3 Printing forme orientation.....	3
4.2.4 Image size tolerance.....	3
4.3 Print production requirements.....	3
4.3.1 Visual characteristics of image components.....	3
4.3.2 Tolerance for image positioning.....	4
4.3.3 Image reproduction.....	4
5 Test method and reporting: Control strip	5
Annex A (informative) Process control strip example	6
Annex B (normative) Correction of colorimetric data for variation in substrate colour	7
Annex C (informative) Solid patch aims for various gamut options	8
Bibliography	9

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 130, *Graphic technology*.

This second edition cancels and replaces the first edition (ISO 12647-5:2001), which has been technically revised.

ISO 12647 consists of the following parts, under the general title *Graphic technology — Process control for the manufacture of half-tone colour separations, proof and production prints*:

- *Part 1: Parameters and measurement methods*
- *Part 2: Offset lithographic processes*
- *Part 3: Coldset offset lithography on newsprint*
- *Part 4: Publication gravure printing*
- *Part 5: Screen printing*
- *Part 6: Flexographic printing*
- *Part 7: Proofing processes working directly from digital data*
- *Part 8: Validation print processes working directly from digital data*

Introduction

Historically, this International Standard established the process control parameters and their aim values and tolerances for the most important professional printing processes of the graphic arts industry. The initial concept was that the groundwork for the series was laid down in ISO 12647-1. This part of the ISO 12647- series differs from that concept because screen printing has changed significantly since this International Standard was initially conceived.

This edition of this part of ISO 12647 differs from the earlier edition by not defining specific printing condition aims but instead requiring that a specific reference printing condition (characterization data set) be specified. This part of ISO 12647 requires that the colour of the printed product match a characterization data set or a printing condition agreed upon by the provider and the receiver and specifies minimum requirements and tolerances to be communicated and produced. Where specific physical parameters can impact the final result (screen angles, resolution, screen mesh, etc.), specifications and tolerances are provided for these parameters.

Because material produced by screen printing varies widely in both size and nominal viewing distance, a viewing distance metric is introduced as part of all screening and resolution requirements.

Graphic technology — Process control for the manufacture of half-tone colour separations, proof and production prints —

Part 5: Screen printing

1 Scope

This part of ISO 12647 specifies the requirements for the screen printing of four-colour process-colour material used for display, signage, and graphics using flat bed or cylinder printing equipment. Both the size and resolution of the finished product are unrestricted. The process stages included are

- data preparation and delivery,
- proof production,
- printing forme preparation, and
- production printing.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 12639, *Graphic technology — Prepress digital data exchange — Tag image file format for image technology (TIFF/IT)*

ISO 12647-1, *Graphic technology — Process control for the production of half-tone colour separations, proof and production prints — Part 1: Parameters and measurement methods*

ISO 12647-7, *Graphic technology — Process control for the production of half-tone colour separations, proof and production prints — Part 7: Proofing processes working directly from digital data*

ISO 12647-8, *Graphic technology — Process control for the production of half-tone colour separations, proof and production prints — Part 8: Validation print processes working directly from digital data*

ISO 13655:2009, *Graphic technology — Spectral measurement and colorimetric computation for graphic arts images*

ISO 15930-1, *Graphic technology — Prepress digital data exchange — Use of PDF — Part 1: Complete exchange using CMYK data (PDF/X-1 and PDF/X-1a)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 12647-1 apply.

4 Requirements

4.1 Data requirements for screen printing systems

4.1.1 Data delivery

Screen print systems shall accept digital data delivered as PDF/X data files as defined in ISO 15930-1 or TIFF/IT files as defined in ISO 12639.

The intended printing condition shall be either

- 1) a published Characterized Reference Printing Condition (CRPC) as listed in the ICC registry at www.color.org, or
- 2) a custom data set where none of the available reference colour characterization data sets are considered appropriate for the intended printing because of the inks, paper, or other factors.

Where the characterization data to be used have a substrate colour (CIELAB values) that does not match the substrate to be used, the data should be adjusted using the tristimulus correction method defined in [Annex B](#).

Prior agreement as to the characterization data and substrate adjustment to be used shall be obtained between all parties involved before copy preparation work is started.

Characterization data sets are the only method recognized by this part of ISO 12647 for the proper identification of the printing condition to be used. Film and/or directly exposed screens shall be generated from digital data and legacy film should be assumed to have been prepared to some agreed upon reference characterization.

4.1.2 Data resolution

Input data should be provided at a data spacing of twice the screen ruling to be used as determined by the scaling criteria, e.g.: 140 cm⁻¹ pixels for a 70 cm⁻¹ screen ruling.

4.2 Printing forme requirements

4.2.1 Resolution

Printed material produced by screen printing varies widely in both size and nominal viewing distance. For screen printing the reference acceptable image quality criteria shall be based on a 70 cm⁻¹ screen ruling viewed at a distance of 42 cm (175 lpi at 16,5 inches). This relationship of distance and screen ruling defines when rosettes are no longer visible to a viewer with 20/20 vision (dot fusion).

This relationship should be scaled for other viewing distances or other screen rulings. For the same viewing quality at different distances, maintain the relationship of resolution to distance.

NOTE For a convenient approximation, divide either the desired distance in meters or the desired resolution in dots per centimetre into 30 to compute the other for that specific pair. This is sometimes referred to as the rule of 30.

The target resolution shall be based on an agreement between the printer and their customer. It should be in accordance with the following three criteria:

- 1) a minimum screen ruling with dots large enough to reproduce a tonal range from 1 % to 98 % using the mesh as configured, the imaging technique, the emulsion and the ink;
- 2) a minimum printed dot size that is not less than 1,5x the width of the thread diameter of the mesh;
- 3) a maximum screen ruling as recommended by the “rule of 30” for the intended viewing condition.

4.2.2 Stencil production

The silver, thermal, or inkjet film used for imaging screens shall have sufficient UV density ($>4,0$) in printing areas and sufficient UV transparency ($<0,1$) in the non-printing areas to produce all dots required in 4.2.1. Direct to screen and computer to screen systems (CTS) shall have sufficient resolution to be able to produce all dots required in 4.2.1.

NOTE Computer to screen systems (CTS) directly image the stencil and direct to screen systems (DTS) apply an image which is used to create the stencil.

4.2.3 Printing forme orientation

4.2.3.1 Printing forme preparation

The angle of the screen mesh attached to the screen frame shall be at 0° and $90^\circ \pm 1^\circ$ with respect to the frame. The angles of the image shall also be 0° and $90^\circ \pm 1^\circ$ with respect to the frame.

4.2.3.2 Screen angles

For half-tone dots without a principal axis, the nominal difference between the screen angles for cyan, magenta, and black shall be 30° , with the screen angle of yellow separated at 15° from another colour.

For half-tone dots with a principal axis, the nominal difference between screen angles for cyan, magenta, and black shall be 60° , with the screen angle of yellow separated by 15° from another colour.

In all cases, no colour should align within $7,5^\circ$ of the mesh (frame). If flesh tones are present, the yellow should not be referenced to magenta.

NOTE 1 This is to prevent moiré in flesh tones and to ensure that no row of dots lines up with the mesh, which would destabilize the small dot structure. It is poor practice to use and rotate offset films to produce the forme.

NOTE 2 It is common practice to use frequency modulated screening for the yellow separation with approximately the same size as the dots in the 10 % area of the conventional separations and a different tonal compensation curve.

4.2.4 Image size tolerance

For film based systems, the set of supplied films under common environmental equilibrium shall not differ by more than 0,02 % in the lengths of their diagonals.

4.3 Print production requirements

4.3.1 Visual characteristics of image components

4.3.1.1 Visual appearance of the supplied proof

Supplied proofs shall be prepared in accordance with either ISO 12647-7 or ISO 12647-8 except where indicated below and shall use the same characterization data set chosen for production. The tristimulus correction factor shall be used to adjust for the substrate colour when the production stock is not available. Proofs shall have the proper colour but may have a different size than the intended product. Proof resolution may be finer than the intended product. In this case the rule of 30 shall be followed within the constraints of the proofing equipment assuming the proof to be viewed at 42 cm.

4.3.1.2 Print substrate colour

For the best colour reproduction, the print substrate colour should be restricted as shown in [Table 1](#). All colour measurement shall be made in accordance with ISO 13655:2009, white backing, M1.

NOTE Surface finish, if applied, can severely affect the substrate colour.

Table 1 — Print substrate colour restrictions

$90 \leq L^* \leq 100$
$-3 \leq a^* \leq 3$
$-5 \leq b^* \leq 5$

4.3.1.3 Ink set colours

The screen printing production shall use process inks which best match the solid objective in the referenced characteristic data set.

NOTE If these inks are being used to produce the required reference characterization data set for screen print only applications, use [Annex C](#) for suggested values for the solids of different gamut classes. If these inks are being used to match an offset characterization data, it has been demonstrated that the same inks can comply with ISO 12647-2 goals.

4.3.1.4 Ink set gloss

If it is deemed necessary to specify the gloss of solid tone colours, then the specular gloss of the ink set single print solid areas should be measured and recorded at an agreed angle of incidence.

4.3.2 Tolerance for image positioning

The maximum deviation between the image centres of any two printed colours shall not be more than a distance equal to the pitch of the screen ruling used and should not be more than a distance equal to one-half of the pitch of the screen ruling used.

NOTE This tolerance includes any forme generation deviations.

4.3.3 Image reproduction

For the production print, the target colour coordinates of the solids and two colour overprints shall be as given in the selected characterization data set. The deviation from these targets values for an OK sheet or for the average of the production run shall be as specified in [Table 2](#). The variability of the process colour solids throughout the run in production is restricted by the following condition. For at least 68 % of the prints, the colour differences from the OK sheet shall not exceed the appropriate variation tolerance specified in [Table 2](#) and should not exceed one-half of that value. All colour measurement shall be made in accordance with ISO 13655:2009, white backing, M1.

NOTE 1 The secondary colours red, green, and blue are dependent on the print sequence and can vary depending on conditions that include the mechanics of the press, the surface characteristics of the substrate, and the rheological and transparency properties of the inks. Thus, conformance of the primaries to specifications is not sufficient for the conformance of the secondaries.

The production print should exhibit a predictable middle tone weight and colour balance (neutral grey) and should exhibit a predictable tone value transition and balance throughout the colour space.

NOTE 2 There are several methods to achieve this objective. See ISO/TS 10128:2009[2], 4.3, for an assessment of the three optional methods and an example of colour balance.

Table 2 — CIELAB ΔE_{ab} tolerances for the solids of the process colours¹

Type of tolerance	Black		Cyan		Magenta		Yellow	
	ΔE_{ab}	ΔE_{00}^b	ΔE_{ab}	ΔE_{00}^b	ΔE_{ab}	ΔE_{00}^b	ΔE_{ab}	ΔE_{00}^b
Deviation tolerance	4,0	2,8	5,0	3,5	6,0	4,2	6,0	4,2
Variation tolerance ^a	1,5	1,1	2,0	1,4	3,0	2,1	3,0	2,1

^a The distribution of CIELAB colour differences is not Gaussian but skewed. For reasons of consistency, the variation tolerance is defined here as the upper limit for 68 % of the production copies. This is analogous to a Gaussian distribution where 68 % are within plus or minus one standard deviation of the mean.

^b Tolerance values for DE2000 are given for information only.

¹ Measured in accordance with ISO 13655:2009, M1 with white backing.

5 Test method and reporting: Control strip

For process control a multi-colour control strip shall be used. This control strip shall be printed along with the subject on all proofs and should be printed on all production jobs. It shall contain well-defined control patches with accurate tone value designations and meet the quality and resolution requirements of the accompanying image. The screen print colour bar shall include Solid; C, M, Y, K patches; Tonal percentages of C, M, Y, K of 5 %, 10 %, 25 %, 50 %, 75 %, and 90 %; RGB overprints a white patch; and neutral grey C,M,Y patches for 10 %, 25 %, 50 %, 75 %, and 90 % (see [Annex A](#)).

The control patches on the stencil, together with the subject matter, should be inspected to ensure that the intended tone values have been achieved. In addition, for information purposes, or the checking of stencil and flooding problems, half-tone control patches may be printed along with the control strip that contain the same half-tone screen values as used in the image area of the print.

NOTE The effective measurement aperture diameters of the densitometers on the print need to be large enough to accommodate and include the required quantity of half-tone dots in each measurement as specified in the documentation of the densitometers' manufacturer. In addition, for measurement with apertures of less than 5 mm diameters the typical practice is to average five readings of every control patch.

For line screens 18 dots per centimeter or less it is recommended that an average of five or more readings in every control patch and the measurement should then be averaged.

Annex A (informative)

Process control strip example



Figure A.1 — Example IDEAlliance Screen control strip

Annex B (normative)

Correction of colorimetric data for variation in substrate colour

Although there are a number of computational techniques used or proposed for the correction of colorimetric data for variation in substrate colour, the consistent use of a single method enhances the ability of different users to achieve similar results.

One conversion method that produces reasonable results for half-tone type images is based on the observation that when the differences in CIE X , CIE Y , and CIE Z between measurements made of identical patches on two substrates having different colours are plotted versus the CIE X , CIE Y , and CIE Z respectively, for measurements on substrate 1 versus substrate 2, the result is approximately a straight line. This leads to a model for predicting the colour of a print on substrate 2 in the form of a linear conversion. Formulae (B.1) and (B.2) show the predictive conversion for CIE tristimulus X for predicting the colour change between substrate 1 and substrate 2.

NOTE 1 The approximate linear relationship fits best when the absorbance of the two substrates are similar.

For CIE X :

$$X_2 = X_1 \times (1 + C) - X_{\min} \times C \quad (\text{B.1})$$

with

$$C = \frac{X_{s2} - X_{s1}}{X_{s1} - X_{\min}} \quad (\text{B.2})$$

where

X_1 is the measured value of X of the specimen on substrate 1;

X_2 is the converted value of X of the specimen on substrate 2;

C is a constant;

X_{s1} is the measured value of X of substrate 1;

X_{s2} is the measured value of X of substrate 2;

X_{\min} is the minimum value of X of the specimen on substrate 1.

NOTE 2 In practice, the X , Y , and Z values of the four-colour solid are often used as an approximation of the minimum values.

Conversion of CIE Y and CIE Z is accomplished in an analogous manner and new CIE L^* , a^* , and b^* CIELAB values are computed.

This colorimetric conversion method is referred to as the tristimulus correction method.

NOTE 3 This is similar to, but not necessarily identical to the International Color Consortium method referred to as substrate relative colorimetric transforms.

Annex C (informative)

Solid patch aims for various gamut options

Table C.1 — CIELAB colour values for solid tones of the primary and secondary colours for screen printing

	Small gamut option			Medium gamut option ^b			Large gamut option		
	<i>L*</i>	<i>a*</i>	<i>b*</i>	<i>L*</i>	<i>a*</i>	<i>b*</i>	<i>L*</i>	<i>a*</i>	<i>b*</i>
Black (K)	24	0	0	18	0	0	8	0	0
Cyan (C)	59	-35	-43	52	-33	-51	46	-32	-54
Magenta (M)	51	70	-15	47	74	-5	42	79	10
Yellow (Y)	90	-11	66	89	-9	83	88	-7	100
Red ^a (M + Y)	50	59	42	47	67	50	44	66	47
Green ^a (C + Y)	55	-68	32	49	-65	30	43	-62	28
Blue ^a (C + M)	28	27	-41	21	26	-40	16	29	-39

^a Colour sequence Yellow, Cyan, Magenta.
^b According approximately to offset PC1.

Bibliography

- [1] ISO 5-3:2009, *Photography and graphic technology — Density measurements — Part 3: Spectral conditions*
- [2] ISO/TS 10128:2009, *Graphic technology — Methods of adjustment of the colour reproduction of a printing system to match a set of characterization data*
- [3] ISO 12637-3:2009, *Graphic technology — Vocabulary — Part 3: Printing terms*
- [4] ISO 12647-2, *Graphic technology — Process control for the production of half-tone colour separations, proof and production prints — Part 2: Offset lithographic processes*

British Standards Institution (BSI)

BSI is the national body responsible for preparing British Standards and other standards-related publications, information and services.

BSI is incorporated by Royal Charter. British Standards and other standardization products are published by BSI Standards Limited.

About us

We bring together business, industry, government, consumers, innovators and others to shape their combined experience and expertise into standards-based solutions.

The knowledge embodied in our standards has been carefully assembled in a dependable format and refined through our open consultation process. Organizations of all sizes and across all sectors choose standards to help them achieve their goals.

Information on standards

We can provide you with the knowledge that your organization needs to succeed. Find out more about British Standards by visiting our website at bsigroup.com/standards or contacting our Customer Services team or Knowledge Centre.

Buying standards

You can buy and download PDF versions of BSI publications, including British and adopted European and international standards, through our website at bsigroup.com/shop, where hard copies can also be purchased.

If you need international and foreign standards from other Standards Development Organizations, hard copies can be ordered from our Customer Services team.

Subscriptions

Our range of subscription services are designed to make using standards easier for you. For further information on our subscription products go to bsigroup.com/subscriptions.

With **British Standards Online (BSOL)** you'll have instant access to over 55,000 British and adopted European and international standards from your desktop. It's available 24/7 and is refreshed daily so you'll always be up to date.

You can keep in touch with standards developments and receive substantial discounts on the purchase price of standards, both in single copy and subscription format, by becoming a **BSI Subscribing Member**.

PLUS is an updating service exclusive to BSI Subscribing Members. You will automatically receive the latest hard copy of your standards when they're revised or replaced.

To find out more about becoming a BSI Subscribing Member and the benefits of membership, please visit bsigroup.com/shop.

With a **Multi-User Network Licence (MUNL)** you are able to host standards publications on your intranet. Licences can cover as few or as many users as you wish. With updates supplied as soon as they're available, you can be sure your documentation is current. For further information, email bsmusales@bsigroup.com.

BSI Group Headquarters

389 Chiswick High Road London W4 4AL UK

Revisions

Our British Standards and other publications are updated by amendment or revision.

We continually improve the quality of our products and services to benefit your business. If you find an inaccuracy or ambiguity within a British Standard or other BSI publication please inform the Knowledge Centre.

Copyright

All the data, software and documentation set out in all British Standards and other BSI publications are the property of and copyrighted by BSI, or some person or entity that owns copyright in the information used (such as the international standardization bodies) and has formally licensed such information to BSI for commercial publication and use. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI. Details and advice can be obtained from the Copyright & Licensing Department.

Useful Contacts:

Customer Services

Tel: +44 845 086 9001

Email (orders): orders@bsigroup.com

Email (enquiries): cservices@bsigroup.com

Subscriptions

Tel: +44 845 086 9001

Email: subscriptions@bsigroup.com

Knowledge Centre

Tel: +44 20 8996 7004

Email: knowledgecentre@bsigroup.com

Copyright & Licensing

Tel: +44 20 8996 7070

Email: copyright@bsigroup.com



...making excellence a habit.™